
- Standard Library

- `<stdio.h>`
- `<ctype.h>`
- `<stdlib.h>`
- `<assert.h>`
- `<stdarg.h>`
- `<time.h>`

<stdio.h>: Opening, closing files

`FILE* fopen(const char* filename, const char* mode)`

- mode can be "r"(read), "w"(write), "a"(append).
- "b" can be appended for binary input/output (unnecessary in *nx)
- returns NULL on error.

`FILE* freopen(const char* filename, const char* mode, FILE* stream)`

- redirects the stream to the file.
- returns NULL on error.
- Where can this be used? (redirecting stdin, stdout, stderr)

`int fflush(FILE* stream)`

- flushes any unwritten data.
- if stream is NULL flushes all outputs streams.
- returns EOF on error.

<stdio.h>: File operations

int remove(**const char*** filename)

- removes the file from the file system.
- retrn non-zero on error.

int rename(**const char*** oldname,**const char*** newname)

- renames file
- returns non-zero on error (reasons?: permission, existence)

<stdio.h>:Temporary files

`FILE* tmpfile(void)`

- creates a temporary file with mode "wb+".
- the file is removed **automatically** when program terminates.

`char* tmpnam(char s[L_tmpnam])`

- creates a string that is not the name of an existing file.
- return reference to internal static array if `s` is NULL. Populate `s` otherwise.
- generates a new name every call.

<stdio.h>: Raw I/O

`size_t fread(void* ptr, size_t size, size_t nobj, FILE* stream)`

- reads at most `nobj` items of size `size` from stream into `ptr`.
- returns the number of items read.
- `fEOF` and `ferror` must be used to test end of file.

`size_t fwrite(const void* ptr, size_t size, size_t nobj, FILE* stream)`

- write at most `nobj` items of size `size` from `ptr` onto `stream`.
- returns number of objects written.

<stdio.h>: File position

int fseek(FILE* stream, **long** offset, **int** origin)

- sets file position in the stream. Subsequent read/write begins at this location
- origin can be SEEK_SET, SEEK_CUR, SEEK_END.
- returns non-zero on error.

long ftell (FILE* stream)

- returns the current position within the file. (limitation? long data type).
- returns -1L on error.

int rewind(FILE* stream)

- sets the file pointer at the beginning.
- equivalent to fseek(stream,0L,SEEK_SET);

<stdio.h>: File errors

void clearerr(FILE* stream)

- clears EOF and other error indicators on stream.

int feof(FILE* stream)

- return non-zero (TRUE) if end of file indicator is set for stream.
- only way to test end of file for functions such as `fwrite()`, `fread()`

int ferror(FILE* stream)

- returns non-zero (TRUE) if **any** error indicator is set for stream.

<ctype.h>: Testing characters

| | |
|-------------|--------------------------------------|
| isalnum(c) | isalpha(c) isdigit (c) |
| iscntrl (c) | control characters |
| isdigit (c) | 0-9 |
| islower(c) | 'a'-'z' |
| isprint (c) | printable character (includes space) |
| ispunct(c) | punctuation |
| isspace(c) | space, tab or new line |
| isupper(c) | 'A'-'Z' |

<string.h>: Memory functions

void* memcpy(**void*** dst,**const void*** src,size_t n)

- copies `n` bytes from `src` to location `dst`
- returns a pointer to `dst`.
- `src` and `dst` **cannot overlap**.

void* memmove(**void*** dst,**const void*** src,size_t n)

- behaves same as `memcpy()` function.
- `src` and `dst` **can overlap**.

int memcmp(**const void*** cs,**const void*** ct,int n)

- compares first `n` bytes between `cs` and `ct`.

void* memset(**void*** dst,int c,int n)

- fills the first `n` bytes of `dst` with the value `c`.
- returns a pointer to `dst`

<stdlib.h>:Utility

double atof(**const char*** s)

int atoi(**const char*** s)

long atol(**const char*** s)

- converts character to float, integer and long respectively.

int rand()

- returns a pseudo-random numbers between 0 and RAND_MAX

void srand(**unsigned int** seed)

- sets the seed for the pseudo-random generator!

<stdlib.h>: Exiting

void abort(**void**)

- causes the program to terminate abnormally.

void exit(**int** status)

- causes normal program termination. The value `status` is returned to the operating system.
- `0` `EXIT_SUCCESS` indicates successful termination. Any other value indicates failure (`EXIT_FAILURE`)

<stdlib.h>:Exiting

void atexit (**void** (*fcn) (**void**))

- *registers* a function `fcn` to be called when the program terminates normally;
- returns non zero when registration cannot be made.
- After `exit()` is called, the functions are called in reverse order of registration.

int system(**const char*** cmd)

- executes the command in string `cmd`.
- if `cmd` is not null, the program executes the command and returns exit status returned by the command.

<stdlib.h>: Search and sorting

```
void* bsearch(const void* key,const void* base,  
             size_t n,size_t size,  
             int (*cmp)(const void* keyval,const void* datum));
```

- searches `base[0]` through `base[n-1]` for `*key`.
- function `cmp()` is used to perform comparison.
- returns a pointer to the matching item if it exists and `NULL` otherwise.

```
void qsort(void* base,size_t n,  
           size_t sz,  
           int (*cmp)(const void*,const void*))!
```

- sorts `base[0]` through `base[n-1]` in ascending/descending order.
- function `cmp()` is used to perform comparison.

<assert.h>:Diagnostics

void assert(**int** expression)

- used to check for invariants/code consistency during debugging.
- does nothing when expression is true.
- prints an error message indicating, expression, filename and line number.

Alternative ways to print filename and line number during execution is to use: `__FILE__`, `__LINE__` macros.

<stdarg.h>: Variable argument lists

Variable argument lists:

- functions can variable number of arguments.
- the data type of the argument can be different for each argument.
- atleast one mandatory argument is required.
- Declaration:

```
int printf (char* fmt ,...); /*fmt is last named argument*/
```

va_list ap

- `ap` defines an iterator that will point to the variable argument.
- before using, it has to be initialized using `va_start`.

<stdarg.h>: Variable argument list

`va_start(va_list ap, lastarg)`

- `ap` `lastarg` refers to the **name** of the last named argument.
- `va_start` is a macro.

`va_arg(va_list ap, type)`

- each call of `va_arg` points `ap` to the next argument.
- `type` has to be inferred from the fixed argument (e.g. `printf`) or determined based on previous argument(s).

`va_end(va_list ap)`

- must be called before the function is exited.

<stdarg.h>:Variable argument list(cont.)

```
int sum(int num,...)
{
    va_list ap; int total=0;
    va_start(ap,num);
    while(num>0)
    {
        total+=va_arg(ap,int);
        num--;
    }
    va_end(ap);
    return total;
}

int suma=sum(4,1,2,3,4); /*called with five args*/
int sumb=sum(2,1,2); /*called with three args*/
```

time_t, clock_t, **struct** tm data types associated with time.

| | | |
|------------|---------------------|----------------------------|
| struct tm: | int tm_sec | seconds |
| | int tm_min | minutes |
| | int tm_hour | hour since midnight (0,23) |
| | int tm_mday | day of the month (1,31) |
| | int tm_mon | month |
| | int tm_year | years since 1900 |
| | int tm_wday | day since sunday (0,6) |
| | int tm_yday | day since Jan 1 (0,365) |
| | int tm_isdst | DST flag |

<time.h>

`clock_t clock()`

- returns processor time used since beginning of program.
- divide by `CLOCKS_PER_SEC` to get time in seconds.

`time_t time(time_t * tp)`

- returns current time (seconds since Jan 1 1970).
- if `tp` is not `NULL`, also populates `tp`.

`double difftime(time_t t1, time_t t2)`

- returns difference in seconds.

`time_t mktime(struct tm* tp)`

- converts the structure to a `time_t` object.
- returns -1 if conversion is not possible.

`char* asctime(const struct tm* tp)`

- returns string representation of the form "Sun Jan 3 15:14:13 1988".
- returns static reference (can be overwritten by other calls).

`struct tm* localtime(const time_t * tp)`

- converts **calendar time** to local time".

`char* ctime(const time_t * tp)`

- converts **calendar time** to string representation of local time".
- equivalent to `sctime(localtime(tp))!`

```
size_t strftime (char* s, size_t smax, const char* fmt, const struct tm* tp)
```

- returns time in the desired format.
- does not write more than `smax` characters into the string `s`.

| | |
|----|--------------------------|
| %a | abbreviated weekday name |
| %A | full weekday name |
| %b | abbreviated month name |
| %B | full month name |
| %d | day of the month |
| %H | hour (0-23) |
| %I | hour (0-12) |
| %m | month |
| %M | minute |
| %p | AM/PM |
| %S | second |