HIGH-SPEED PASSENGER ELEVATORS & VERTICAL TRANSPORTATION SPECIFICATIONS:
1. ELEVATOR MACHINES: Permanent Magnet Synchronous Motor (PMSM) gearless machine with regenerative VVVF drives.
2. CAR SPEED & CAPACITY:
   ? VVIP Dignitary Elevators: Speed 2.5 m/s, capacity 20 passengers (1360 kg), center-opening stainless steel doors.
   ? Service & Stretcher Elevators: Speed 1.75 m/s, capacity 26 passengers (1768 kg), door clear opening 1200mm.
3. DESTINATION CONTROL SYSTEM (DCS):
   ? Intelligent hall touch-screens assigning passengers to the optimal elevator car, minimizing travel time by 35%.
4. SAFETY & EMERGENCY LIFE SUPPORT:
   ? Automatic Rescue Device (ARD) powered by maintenance-free sealed gel batteries bringing car to nearest landing during blackout.
   ? Firefighters lift compliance conforming to EN 81-72 with trap door, ladder, and waterproof electrical equipment.

| Elevator Tag | Service Purpose | Capacity | Speed | Stops / Openings | Car Dimensions (W x D |
|---|---|---|---|---|---|
| LIFT-VVIP-01 | Hon'ble Speaker & CM Lift | 20 Pass (1360 kg) | 2.5 m/s | 6 Stops / 6 Openings | 2000 x 1750 mm |
| LIFT-VVIP-02 | Ministers & Cabinet Lift | 20 Pass (1360 kg) | 2.5 m/s | 6 Stops / 6 Openings | 2000 x 1750 mm |
| LIFT-PASS-01 to 04 | Members of Assembly (MLAs) | 20 Pass (1360 kg) | 2.0 m/s | 6 Stops / 6 Openings | 1900 x 1700 mm |
| LIFT-SRV-01/02 | Service & Medical Stretcher | 26 Pass (1768 kg) | 1.75 m/s | 6 Stops / 6 Openings | 1600 x 2400 mm |
| ESC-01 to 04 | Public Gallery Heavy Escalator | 9,000 Persons/hr | 0.5 m/s | Rise: 6.5 Metres | Step Width: 1000 mm |

| | | |
|---|---|---|
| AMARAVATI GOVERNMENT COMPLEX · LEGISLATIVE ASSEMBLY | | |
| DWG TITLE: VERTICAL TRANSPORTATION (LIFTS & ESCALATORS) | | |
| DRAWING NO: Lift_D2E_VT Specification_Ara | REV: R1 | SCALE: 1:100 |
| CLIENT: AP CRDA / GOVT OF ANDHRA PRADESH | DATED: 28-09-2026 | |