ENERGY RECOVERY WHEEL (ERV) PERFORMANCE SPECIFICATIONS:

1. Conforming to ASHRAE 84 and Eurovent certified for sensible and latent energy exchange between exhaust and fresh air.
2. Aluminum honeycomb wheel rotor with polymer coating impregnated with 3A molecular sieve desiccant.
3. Desiccant pore diameter of 3 Angstroms selectively captures water vapor while repelling organic pollutants and smells.
4. Built-in purge angle sector preventing cross-contamination: Cross-leakage strictly < 0.04% of total air volume.
5. Stepper motor variable speed drive with microprocessor controller for automatic freeze protection in winter conditions.

Wheel Tag	Fresh Air m3/h	Exhaust Air m3/h	Sensible Eff %	Latent Eff %	Power kW Saved
HRW-01 (Chamber)	15,000 m3/h	15,000 m3/h	77.5%	72.0%	54.2 kW
HRW-02 (Secretariat)	10,000 m3/h	10,000 m3/h	76.0%	70.5%	35.8 kW
HRW-03 (Ministers Block)	12,000 m3/h	12,000 m3/h	78.0%	73.0%	44.0 kW
HRW-04 (Press & Media)	8,000 m3/h	8,000 m3/h	75.5%	71.0%	28.5 kW

AMARAVATI GOVERNMENT COMPLEX · LEGISLATIVE ASSEMBLY		
DWG TITLE: ROTARY ENERGY RECOVERY ENTHALPY WHEEL TECHNIC		
DRAWING NO: SL-288 - Heat Recovery Data Sh	REV: R1	SCALE: 1:100
CLIENT: AP CRDA / GOVT OF ANDHRA PRADESH	DATED: 28-09-2026	