KITCHEN FRESH AIR MAKE-UP AXIAL FAN SPECIFICATIONS:

1. Tube axial flow supply fan with aerofoil adjustable pitch die-cast aluminum blades.
2. Heavy gauge hot-dip galvanized casing with flanged connections to SMACNA rectangular supply air ductwork.
3. Totally Enclosed Fan Cooled (TEFC) Class H insulated motor rated for continuous operation at 55°C ambient.
4. Washable aluminum synthetic pre-filter MERV 8 integrated at weather louvre intake.
5. Sound attenuator section reducing fan breakout sound to <= 62 dBA at 1.5m perimeter distance.

Fan Tag	Location Served	Air Flow CFM	Static Pressure	Fan RPM	Motor kW
FAF-KIT-01	Main Assembly Kitchen (Cooking Area)	8,500 CFM	350 Pa	1440 RPM	7.5 kW
FAF-KIT-02	Dignitary Dining Pantry Prep	4,200 CFM	280 Pa	1440 RPM	3.7 kW
FAF-KIT-03	Staff Cafeteria Kitchen	6,000 CFM	320 Pa	1440 RPM	5.5 kW

AMARAVATI GOVERNMENT COMPLEX · LEGISLATIVE ASSEMBLY		
DWG TITLE: KITCHEN FRESH AIR SUPPLY AXIAL FAN TECHNICAL		
DRAWING NO: SL-288 - VENTILATION-FRESH A	REV: E1	SCALE: 1:100
CLIENT: AP CRDA / GOVT OF ANDHRA PRADESH	DATED: 28-09-2026	