COMMERCIAL KITCHEN EXHAUST SCRUBBER & CENTRIFUGAL FAN DATA:

1. Two-stage Electrostatic Precipitator (ESP) ionizing cell with certified grease extraction efficiency >= 95%.
2. Integrated high-output UV-C ozone sterilization lamps destroying residual volatile grease vapors and odors.
3. Fire-rated high-temperature backward curved centrifugal exhaust fan rated for 400°C / 2 hours continuous run per EN 12101-3.
4. Automated wash cycle with hot water and eco-detergent sprays purging collected grease to grease interceptor trap.
5. Fire suppression interlock with Ansul R-102 wet chemical kitchen hood system.

Scrubber Tag	Exhaust CFM	ESP Cell Qty	UV-C Lamps	Exhaust Fan Motor	Fire Rating
ESP-SCR-01	9,000 CFM	6 Dual Cells	12x 150W UV-C	11.0 kW Centrifugal	400°C / 2 Hrs
ESP-SCR-02	4,500 CFM	3 Dual Cells	6x 150W UV-C	5.5 kW Centrifugal	400°C / 2 Hrs
ESP-SCR-03	6,500 CFM	4 Dual Cells	8x 150W UV-C	7.5 kW Centrifugal	400°C / 2 Hrs