PRIMARY & SECONDARY CENTRIFUGAL PUMP TECHNICAL DATA SHEET:

1. Horizontal split-case and end-suction centrifugal pumps engineered for continuous duty in district cooling applications.
2. Pump casing: High-grade cast iron (ASTM A48 Class 35); Impeller: Machined nickel-aluminum bronze (ASTM B148).
3. Heavy-duty silicon carbide vs silicon carbide mechanical face seals with EPDM O-rings suitable for glycol solution.
4. Electric motors: IE4 super-premium efficiency squirrel cage induction motors conforming to IEC 60034-30-1.
5. Factory hydrostatically tested to 1.5 times the maximum working pressure (Tested to 24 bar for 30 minutes).

Pump Model	Service	Flow m3/hr	Head m	Impeller Dia	Efficiency %	Motor kW
NK 125-250	Primary Chiller Evaporator	350 m3/h	22 m	254 mm	84.5%	30 kW IE4
NK 150-315	Secondary Distribution	420 m3/h	38 m	312 mm	86.2%	55 kW IE4
NK 100-200	Condenser Cooling Tower	480 m3/h	25 m	215 mm	85.0%	45 kW IE4
CRN 32-4	Chilled Water Pressurization	25 m3/h	45 m	Multi	78.0%	5.5 kW IE4

AMARAVATI GOVERNMENT COMPLEX · LEGISLATIVE ASSEMBLY		
DWG TITLE: PRIMARY & SECONDARY CHILLED WATER PUMPS TECHN		
DRAWING NO: SL-288- PUMP DATA SHEET-1	SHEET: ASSEMB	SCALE: 1:100
CLIENT: AP CRDA / GOVT OF ANDHRA PRADESH	DATED: 28-09-2026	