EMERGENCY EGRESS STAIRCASE SPECIFICATIONS:
? Fire Rating: 2-Hour Fire Rated Steel Stringers with Anti-Slip Chequered Treads
? Width of Staircase: 1500mm Clear Width | Riser: 150mm | Tread: 300mm
? Positive Pressurization System: 50 Pa Differential Pressure to Prevent Smoke Ingress
? Photoluminescent Exit Signage & Emergency LED Battery Backup (3 Hours Duration)

STRUCTURAL COLUMN SCHEDULE & COORDINATE MATRIX
Col C1-A | M60 Grade | 1200x1200mm | +18.50m Level
Col C1-B | M60 Grade | 1200x1200mm | +18.50m Level
Shear W1 | PT Flared | 800mm Thk | +42.00m Level
Spire Leg A | Steel S355 | Dia 1600mm | +120.0m Level
Spire Leg B | Steel S355 | Dia 1600mm | +120.0m Level
Spire Apex | Aero Cone | Dia 800mm | +250.0m Level

AMARAVATI GOVERNMENT COMPLEX · LEGISLATIVE ASSEMBLY		
DWG TITLE: EMERGENCY INCLINED EGRESS STAIRCASE DETAILS		
DRAWING NO: 171020-LA-INCL-612	REV: R1	SCALE: 1:100
CLIENT: AGICL / GOVT OF ANDHRA PRADESH	DATE: 28-09-2026	