

# AUGMENTED SELF-ASSEMBLY

Solving the Intrinsic System Augmentation problem  
for a self-assembly task

---

## Midterm Presentation

Loïc Matthey



Supervisors:

Vijay Kumar  
Grégory Mermoud  
Alcherio Martinoli

Special contributions:

Spring Berman



# CONTENTS

1. Introduction
2. Goals
3. Stochastic assembly task
4. Intrinsic System Augmentation problem
5. Puzzle test case
6. Webots implementation
7. Models and parameters fitting
8. Conclusion
9. Further work



# 1. INTRODUCTION

## Context

- Joint work with the GRASP Lab from University of Pennsylvania (Penn), Prof. Vijay Kumar.
- Combine interests in assembly and multi-robots teams.
- Strong theoretical foundations needed.
- Considered problem:
  - ▶ Stochastic assembly of products



# 1. INTRODUCTION

## Augmented assembly

- Problem of stochastic: poor yield
- Idea: add agents to the initial system to improve performance.

▶ Augmented system.

- Questions:
  - How to formulate ?
  - How to augment the system ?



## 2. GOALS

- Propose a theoretical framework for the Augmented System problem.
- Validation using a higher-level assembly task (biological scale).
  - Use Webots as physics simulator.
- Develop mathematical models and simulations fitting the tasks.
  - Use Chemical Reactions formalism.
- Optimize the Augmented System using mathematical foundations.



# 3. STOCHASTIC ASSEMBLY

## Definition


- Let  $M_i$  pieces of different types, assembling with bi-directional connections.
- Let those pieces move and assemble randomly in an arena of size  $A$ .
- Let the final assembled products be known as  $S_j$ .
- Let a system of reactions  $R$  showing the assembling of pieces via their connections. These reactions can contain disassembling reactions too.
- Then this system will create a certain amount  $|S_j|$  after a time  $T_f$ .

► Goal: obtain the bigger  $|S_j|$  after the smaller  $T_f$ .



# 4. INTRINSIC SYSTEM AUGMENTATION

- Define two systems:
  - Intrinsic (initial) system.
  - Augmented system.
- Define a common metric (systems should be measurable).
- Model the intrinsic system behavior.
- Optimize the model of the intrinsic system.
- Link the Augmented system to the optimized model.






# 5. PUZZLE TEST CASE

## Description

- Simplification of an assembly task.
- Specific pieces to assemble.
- Robot to carry the pieces.
  - still self-assembly? Yes.
- Measure scalability and efficiency of assembly.
  - Stochastic controllers
  - “Designed” controllers





# 5. PUZZLE TEST CASE


## Relation to Augmented System

- Intrinsic and Augmented system ?
- Stochastic controllers:
  - Like self-assembly of pieces, assuming they move and assemble randomly.
- “Designed” controllers:
  - “Augment” virtually the system by changing the stochastic behavior for something better.
  - This is similar to adding extra robots to conduct this new behavior.



# 6. WEBOTS IMPLEMENTATION

## Basic components




- Khepera III modified.
  - Protruding arm to carry the pieces.
- Arm with rotating connector.
- Pieces with several connectors.
  - Top connector for the robots.
  - Side connectors to assemble to other pieces.



# 6. WEBOTS IMPLEMENTATION

## Capabilities




- Rotating connector:
  - Allows full access to every side connectors
- Pieces and robots communicate with emitter / receiver.
  - Offers relative positioning for alignment



# 6. WEBOTS IMPLEMENTATION

## Capabilities



- Rotating connector:
  - Allows full access to every side connectors
- Pieces and robots communicate with emitter / receiver.
  - Offers relative positioning for alignment



# 6. WEBOTS IMPLEMENTATION

## Systematic experiments


- Webots World Generator  
written in Python, to generate  
specific number of robots and  
pieces.
- Random initial positioning for  
every robot and piece in the  
arena.
- Supervisor handling the  
experiments and writing to  
files.



# 6. WEBOTS IMPLEMENTATION

## Systematic experiments

- Webots World Generator written in Python, to generate specific number of robots and pieces.
- Random initial positioning for every robot and piece in the arena.
- Supervisor handling the experiments and writing to files.






# 6. WEBOTS IMPLEMENTATION

## Behavior

- Spring's work, adapted.
- All local radio communications (0.4m radius).
- Robot search for lying pieces and carry them.
- When encounter a robot, check if the assembly is possible.
- Alignment and assembling of pieces.
- Answer to a given plan, written in forms of reactions.






# 6. WEBOTS IMPLEMENTATION

## Behavior

- Spring's work, adapted.
- All local radio communications (0.4m radius).
- Robot search for lying pieces and carry them.
- When encounter a robot, check if the assembly is possible.
- Alignment and assembling of pieces.
- Answer to a given plan, written in forms of reactions.






# 6. WEBOTS IMPLEMENTATION

## Results

- 1 Puzzle (5 pieces), 4 robots
- 100 experiments, 20 min maximum.
- Initial positions and rotations between each of them.
- 96% assembly success in 20 min.
- 75% of all experiments assembled after 6 min.






# 6. WEBOTS IMPLEMENTATION

## Results

- 1 Puzzle (5 pieces), 4 robots
  - 100 experiments, 20 min maximum.
  - Initial positions and rotations between each of them.
- 96% assembly success in 20 min.
- 75% of all experiments assembled after 6 min.






# 6. WEBOTS IMPLEMENTATION

## Results

- 3 Puzzle (15 pieces), 15 robots
- 100 experiments, 20 min maximum.
- Initial positions and rotations between each of them.
- 80% assembly success.
- 75% of all assemblies done after 11 min.






# 6. WEBOTS IMPLEMENTATION

## Results

- 3 Puzzle (15 pieces), 15 robots
  - 100 experiments, 20 min maximum.
  - Initial positions and rotations between each of them.
- 80% assembly success.
- 75% of all assemblies done after 11 min.








# 7. MODELS

## Description

- Chemical Reactions Networks.
- Used for chemical and biological processes.
- Well adapted because of flexibility and versatility.



~

$$\dot{R} = -k_1 R P_i^f$$

$$\dot{P}_i^f = -k_1 R P_i^f$$

$$\dot{P}_1^c = k_1 R P_1^f - k_2 P_1^c P_2^c$$

$$\dot{P}_2^c = k_1 R P_2^f - k_2 P_1^c P_2^c$$

$$\dot{P}_5^c = k_2 P_1^c P_2^c$$

$$\dot{P}_3^c = k_1 R P_3^f - k_3 P_3^c P_4^c + k'_3 P_6^c$$

$$\dot{P}_4^c = k_1 R P_4^f - k_3 P_3^c P_4^c + k'_3 P_6^c$$

$$\dot{P}_6^c = k_3 P_3^c P_4^c - k'_3 P_6^c$$



# 7. MODELS

## Simulations


- Lots of literature available.
- Exact simulation: Stochastic Simulation Algorithm (SSA) by Gillespie, 1976.
- Approximate solutions: ODE Models or Hybrid Models (Stochastic + Deterministic).
- Simulation tools chosen:
  - StochKit for SSA. L. Petzold, UCSB.
  - Matlab for ODE Models.



# 7. MODELS

## Parameters estimation

- Hypothesis:
  - System should be well-mixed.
- Enforced by chemotaxis-like movement of robots.
- We can make non-spatiality assumption then.






# 7. MODELS

## Parameters estimation

- Reaction rates depends on encountering probabilities.
  - Measure them in Webots
  - A-priori guess using theoretical informations
- Chose to use the geometric probabilities, like N. Correll did.
  - Actually is the exact application of a chemical simulation formula to large-scale robots.

$$p_e \sim \frac{1}{A_{total}} v_r T w_d$$






# 7. MODELS

## Parameters estimation

- Reaction rates depends on encountering probabilities.
  - Measure them in Webots
  - A-priori guess using theoretical informations
- Chose to use the geometric probabilities, like N. Correll did.
  - Actually is the exact application of a chemical simulation formula to large-scale robots.

$$p_e \sim \frac{1}{A_{total}} v_r T w_d$$






# 7. MODELS

## Parameters estimation

- Rates verifications
- Webots experiments
  - Sample the times to event.
  - 100 experiments.
  - Fit an exponential distribution in Matlab.
- Verify effect of adding “dummy” robots.






# 7. MODELS

## Parameters estimation

- Rates verifications
- Webots experiments
  - Sample the times to event.
  - 100 experiments.
  - Fit an exponential distribution in Matlab.
- Verify effect of adding “dummy” robots.






# 7. MODELS

## Results - 1 puzzle

- 1 Puzzle (5 pieces), 4 robots
- Same rates for both models, from previous theoretical.
- ODE is too low, due to low numbers effects.
- Stochastic is good. Too high because no failures.






# 7. MODELS

## Results - 1 puzzle

- 1 Puzzle (5 pieces), 4 robots
- Same rates for both models, from previous theoretical.
- ODE is too low, due to low numbers effects.
- Stochastic is good. Too high because no failures.






# 7. MODELS

## Results - 3 puzzles

- 3 Puzzle (15 pieces), 15 robots
- ODE better but still low. Stochastic still better.

► Accurate models.

- Even with other robots and the possible well-mixed problem.






# 7. MODELS

## Results - 3 puzzles

- 3 Puzzle (15 pieces), 15 robots
- ODE better but still low. Stochastic still better.

► Accurate models.

- Even with other robots and the possible well-mixed problem.





# 8. CONCLUSION

- Created a Webots platform to simulate realistic assemblies.
- Further tests possible, with more interesting plans (multiple targets).
- Chemical Reactions Networks seems like a good model for this kind of problem.
- Simulations shows that Stochastic is indeed better at representing small populations dynamics.



# 9. FURTHER WORK

- Optimize the system !
  - Represent it as a Markov Chain.
  - This is a Multi-affine system that we have to optimize.
- Map the optimized system onto new robot behaviors or added agents.
  - “Augmentation” step.
- Assess the generalizability of this methodology and the possibles applications to other fields.



THANK YOU


ANY QUESTIONS ?




# 7. MODELS

## Stochastic Model

- Finishing times



Webots



Stochastic model



# OPTIMIZATION

- Chemical Reaction Networks are linear in  $\{1, x_1, \dots, x_n, x_1x_2, \dots, x_nx_m\}$ :

$$\dot{x} = E \cdot A \cdot y$$

With  $x$  vector of  $x_i$ ,  $E$  is the effector matrix,  $A$  the tunable parameters and  $y$  a vector of  $\{x_i, x_ix_j\}$ .

- Multi-affine system.
- We need to tune  $A$ , so that we converge to a desired equilibrium.
- Problem: non-linear.
  - Ideas: calculate several  $A$  for small regions (linearization assumption).