

More SQL Data Definition

Database Systems Lecture 6

Munawar, PhD

In this Lecture

- More SQL
 - DROP TABLE
 - ALTER TABLE
 - INSERT, UPDATE, and DELETE
 - Data dictionary
 - Sequences
- For more information
 - Connolly and Begg chapters 5 and 6

Creating Tables

- From last lecture...

- CREATE TABLE
- Columns
 - Data types
 - [NOT] NULL, DEFAULT values
- Constraints
 - Primary keys
 - Unique columns
 - Foreign keys

CREATE TABLE

```
<name> (  
    <col-def-1>,  
    <col-def-2>,  
        :  
    <col-def-n>,  
    <constraint-1>,  
        :  
    <constraint-k>)
```

Deleting Tables

- To delete a table use
 - **DROP TABLE**
 - **[IF EXISTS]**
 - **<name>**
- Example:
 - **DROP TABLE Module**
- **BE CAREFUL** with any SQL statement with DROP in it
 - You will delete any information in the table as well
 - You won't normally be asked to confirm
 - There is no easy way to undo the changes

Changing Tables

- Sometimes you want to change the structure of an existing table
 - One way is to DROP it then rebuild it
 - This is dangerous, so there is the ALTER TABLE command instead
- ALTER TABLE can
 - Add a new column
 - Remove an existing column
 - Add a new constraint
 - Remove an existing constraint

ALTERing Columns

To add or remove columns use

```
ALTER TABLE <table>  
  ADD COLUMN <col>
```

```
ALTER TABLE <table>  
  DROP COLUMN <name>
```

Examples

```
ALTER TABLE Student  
  ADD COLUMN  
    Degree VARCHAR(50)
```

```
ALTER TABLE Student  
  DROP COLUMN Degree
```

ALTERing Constraints

To add or remove
columns use

```
ALTER TABLE <table>  
    ADD CONSTRAINT  
        <definition>
```

```
ALTER TABLE <table>  
    DROP CONSTRAINT  
        <name>
```

Examples

```
ALTER TABLE Module  
    ADD CONSTRAINT  
        ck UNIQUE (title)
```

```
ALTER TABLE Module  
    DROP CONSTRAINT ck
```

INSERT, UPDATE, DELETE


- **INSERT** - add a row to a table
- **UPDATE** - change row(s) in a table
- **DELETE** - remove row(s) from a table
- **UPDATE** and **DELETE** use '**WHERE** clauses' to specify which rows to change or remove
- **BE CAREFUL** with these - an incorrect **WHERE** clause can destroy lots of data

INSERT

```
INSERT INTO  
  <table>  
  (col1, col2, ...)  
VALUES  
  (val1, val2, ...)
```

- The number of columns and values must be the same
- If you are adding a value to every column, you don't have to list them
- SQL doesn't require that all rows are different (unless a constraint says so)

INSERT



UPDATE

```
UPDATE <table>
SET col1 = val1
    [,col2 = val2...]
[WHERE
    <condition>]
```

- All rows where the condition is true have the columns set to the given values
- If no condition is given all rows are changed so BE CAREFUL
- Values are constants or can be computed from columns

UPDATE

Student

| ID | Name | Year |
|----|------|------|
| 1 | John | 1 |
| 2 | Mark | 3 |
| 3 | Anne | 2 |
| 4 | Mary | 2 |

```
UPDATE Student
SET Year = 1,
    Name = 'Jane'
WHERE ID = 4
```

Student

| ID | Name | Year |
|----|------|------|
| 1 | John | 1 |
| 2 | Mark | 3 |
| 3 | Anne | 2 |
| 4 | Jane | 1 |

```
UPDATE Student
SET Year = Year + 1
```

Student

| ID | Name | Year |
|----|------|------|
| 1 | John | 2 |
| 2 | Mark | 4 |
| 3 | Anne | 3 |
| 4 | Mary | 3 |

DELETE

- Removes all rows which satisfy the condition

DELETE FROM


<table>

[WHERE

<condition>]

- If no condition is given then ALL rows are deleted - BE CAREFUL
- Some versions of SQL also have **TRUNCATE TABLE <T>** which is like **DELETE FROM <T>** but it is quicker as it doesn't record its actions

DELETE



SELECT

- The SQL command you will use most often
 - Queries a set of tables and returns results as a table
 - Lots of options, we will look at many of them
 - Usually more than one way to do any given query
- SQL's SELECT is different from the relational algebra's selection σ
 - SELECT in SQL does all of the relational algebra
 - But it is a bit different because SQL differs from the relational model

SQL SELECT Overview

SELECT

[DISTINCT | ALL] <column-list>

FROM <table-names>

[WHERE <condition>]

[ORDER BY <column-list>]

[GROUP BY <column-list>]

[HAVING <condition>]

- (*[] - optional, | - or*)

Simple SELECT

```
SELECT <columns>  
FROM <table>
```

<columns> can be

- A single column
- A comma-separated list of columns
- * for 'all columns'

- Given a table Student with columns

- stuID
- stuName
- stuAddress
- stuYear

Sample SELECTs

SELECT * FROM Student

| <i>stuID</i> | <i>stuName</i> | <i>stuAddress</i> | <i>stuYear</i> |
|--------------|----------------|-------------------|----------------|
| 1 | Anderson | 15 High St | 1 |
| 2 | Brooks | 27 Queen's Rd | 3 |
| 3 | Chen | Lenton Hall | 1 |
| 4 | D'Angelo | Derby Hall | 1 |
| 5 | Evans | Lenton Hall | 2 |
| 6 | Franklin | 13 Elm St | 3 |
| 7 | Gandhi | Lenton Hall | 1 |
| 8 | Harrison | Derby Hall | 1 |

Sample SELECTs

```
SELECT stuName FROM Student
```

| <i>stuName</i> |
|----------------|
| Anderson |
| Brooks |
| Chen |
| D' Angelo |
| Evans |
| Franklin |
| Gandhi |
| Harrison |

Sample SELECTs

```
SELECT stuName, stuAddress  
FROM Student
```

| <i>stuName</i> | <i>stuAddress</i> |
|----------------|-------------------|
| Anderson | 15 High St |
| Brooks | 27 Queen's Rd |
| Chen | Lenton Hall |
| D'Angelo | Derby Hall |
| Evans | Lenton Hall |
| Franklin | 13 Elm St |
| Gandhi | Lenton Hall |
| Harrison | Derby Hall |

Being Careful

- When using DELETE and UPDATE
 - You need to be careful to have the right WHERE clause
 - You can check it by running a SELECT statement with the same WHERE clause first

Before running

```
DELETE FROM Student  
WHERE Year = 3
```

run

```
SELECT * FROM Student  
WHERE Year = 3
```

Sequences

- Often we want to assign each row a unique number
 - These are useful as primary keys
 - Using integers to reference rows is more efficient
 - We would like the DBMS to do this
- In most versions of SQL we can use autoincrementing fields to do this
 - Details differ between versions
 - Usually the first entry is assigned 1, the next 2, and so on, but Oracle lets you change this

Sequences

- In Oracle we use a *Sequence*
 - A sequence is a source of numbers
 - We can declare several sequences, giving each a name, a start point, and a step size
 - We can then generate unique numbers by asking for the next element from a sequence

Sequences in Oracle

- To declare a sequence:
`CREATE SEQUENCE <name>`
`[START WITH <value>]`
`[INCREMENT BY <value>]`
 - If no `START WITH` or `INCREMENT BY` values are given they default to 1
- To get the next value from a sequence
`<sequence name>.nextVal`

Sequence Example

- Creating a sequence

```
CREATE SEQUENCE mySeq START WITH 1
```

- Using a sequence

```
SELECT mySeq.nextVal FROM DUAL;
```

```
INSERT INTO Student
```

```
    (stuID, stuName, stuAddress)
```

```
VALUES
```

```
    (mySeq.nextVal, 'Steve Mills',
```

```
        '13 Elm Street')
```

SQL and the Data Dictionary

- The *data dictionary* or *catalogue* stores
 - Information about database tables
 - Information about the columns of tables
 - Other information - users, locks, indexes, and more
 - This is 'metadata'
- Some DBMSs let you query the catalogue
 - In Oracle you can access the metadata in several ways
 - There are 'system tables' with metadata in them
 - You can also **DESCRIBE** tables

Oracle Data Dictionary

- To find out what tables and sequences you have defined use

```
SELECT table_name  
FROM user_tables
```

- The user_tables table is maintained by Oracle
- It has *lots* of columns, so don't use

```
SELECT * FROM user_tables
```

Oracle Data Dictionary

- To find the details of a table use
`DESCRIBE <table name>`

- Example:

```
SQL> DESCRIBE Student;
```

| Name | Null? | Type |
|------------|----------|---------------|
| ----- | ----- | ----- |
| STUID | NOT NULL | NUMBER (38) |
| STUNAME | NOT NULL | VARCHAR2 (50) |
| STUADDRESS | | VARCHAR2 (50) |
| STUYEAR | | NUMBER (38) |

This Lecture in Exams

Track

| cID | Num | Title | Time | aID |
|-----|-----|------------|------|-----|
| 1 | 1 | Violent | 239 | 1 |
| 1 | 2 | Every Girl | 410 | 1 |
| 1 | 3 | Breather | 217 | 1 |
| 1 | 4 | Part of Me | 279 | 1 |
| 2 | 1 | Star | 362 | 1 |
| 2 | 2 | Teaboy | 417 | 2 |

CD

| cID | Title | Price |
|-----|-------------|-------|
| 1 | Mix | 9.99 |
| 2 | Compilation | 12.99 |

Artist

| aID | Name |
|-----|----------|
| 1 | Stellar |
| 2 | Cloudboy |

This Lecture in Exams

Add \$2.50 to the price of all CDs that cost more than \$10.00.

(2 marks)

Add a new column, Genre, to the CD table. This column should hold a string of up to 100 characters, and if no genre is provided then it should default to the value "Unknown".

(3 marks)

Add a track titled "Runnin" by the artist "Fat Freddy's Drop" which is 12 minutes and 27 second long to the CD titled "Compilation". For this part only, you may assume that the tables contain exactly the information shown above.

(3 marks)

Next Lecture

- SQL SELECT
 - WHERE clauses
 - SELECT from multiple tables
 - JOINS
- For more information
 - Connolly and Begg Chapter 5
 - Ullman and Widom, Chapter 6.5,6.1.