

Объектно-ориентированное программирование в F#

Юрий Литвинов

15.12.2016г

"За" и "против" ООП в функциональных языках

За:

- ▶ Портирование существующего кода
- ▶ Интеграция с другими языками
- ▶ Использование в основном для ООП с возможностью писать красивый код

Против:

- ▶ Не очень дружит с системой вывода типов
- ▶ Нет встроенной поддержки печати, сравнения и т.д.

Методы у типов

F#

```
type Vector = {x : float; y : float} with  
    member v.Length = sqrt(v.x * v.x + v.y * v.y)
```

```
let vector = {x = 1.0; y = 1.0}  
let length = vector.Length
```

```
type Vector with  
    member v.Scale k = {x = v.x * k; y = v.y * k}
```

```
let scaled = vector.Scale 2.0
```

Методы у Discriminated Union-ов

F#

```
type Tree<'a> =  
    | Tree of 'a * Tree<'a> * Tree<'a>  
    | Tip of 'a  
with  
    member t.Size =  
        match t with  
        | Tree(_, l, r) -> 1 + l.Size + r.Size  
        | Tip _ -> 1
```

Расширения

F#

```
type System.Int32 with
    member i.IsPrime =
        let limit = i |> float |> sqrt |> int
        let rec check j =
            j > limit or (i % j <> 0 && check (j + 1))
        check 2

printfn "%b" (5).IsPrime
printfn "%b" (8).IsPrime
```

Статические методы

F#

```
type Vector = {x : float; y : float} with  
    static member Create x y = {x = x; y = y}
```

```
let vector = Vector.Create 1.0 1.0
```

```
type System.Int32 with  
    static member IsEven x = x % 2 = 0
```

```
printfn "%b" <| System.Int32.IsEven 10
```

Методы и существующие функции

F#

```
type Vector = {x : float; y : float} with
    static member Create x y = {x = x; y = y}

let length (v : Vector) = sqrt(v.x * v.x + v.y * v.y)

type Vector with
    member v.Length = length v

printfn "%f" <| (Vector.Create 1.0 1.0).Length
printfn "%f" <| (length (Vector.Create 1.0 1.0))
```

Методы и каррирование

F#

```
open Operators
```

```
type Vector = {x : float; y : float} with  
    static member Create x y = {x = x; y = y}
```

```
let transform v rotate scale =  
    let r = System.Math.PI * rotate / 180.0  
    { x = scale * v.x * cos r - scale * v.y * sin r;  
      y = scale * v.x * sin r + scale * v.y * cos r }
```

```
type Vector with  
    member v.Transform = transform v
```

```
printfn "%A" <| (Vector.Create 1.0 1.0).Transform 45.0 2.0
```


Каррирование против кортежей

F#

```
type Vector with
    member v.TupledTransform (r, s) = transform v r s
    member v.CurriedTransform r s = transform v r s

let v = Vector.Create 1.0 1.0
printfn "%A" <| v.TupledTransform (45.0, 2.0)
printfn "%A" <| v.CurriedTransform 45.0 2.0
```

Кортежи: именованные аргументы

F#

```
type Vector with
    member v.TupledTransform (r, s) =
        transform v r s

let v = Vector.Create 1.0 1.0
printfn "%A" <| v.TupledTransform (r = 45.0, s = 2.0)
printfn "%A" <| v.TupledTransform (s = 2.0, r = 45.0)
```

Кортежи: опциональные параметры

F#

```
type Vector with
    member v.TupledTransform (r, ?s) =
        match s with
        | Some scale -> transform v r scale
        | None -> transform v r 1.0

let v = Vector.Create 1.0 1.0
printfn "%A" <| v.TupledTransform (45.0, 2.0)
printfn "%A" <| v.TupledTransform (90.0)
```

defaultArg

F#

```
type Vector with
    member v.TupledTransform (r, ?s) =
        transform v r <| defaultArg s 1.0

let v = Vector.Create 1.0 1.0
printfn "%A" <| v.TupledTransform (45.0, 2.0)
printfn "%A" <| v.TupledTransform (90.0)
```

Кортежи: перегрузка

F#

```
type Vector with
    member v.TupledTransform (r, s) =
        transform v r s
    member v.TupledTransform r =
        transform v r 1.0

let v = Vector.Create 1.0 1.0
printfn "%A" <| v.TupledTransform (45.0, 2.0)
printfn "%A" <| v.TupledTransform (90.0)
```

Кортежи против каррирования

За:

- ▶ Можно вызывать из .NET-кода
- ▶ Опциональные и именованные аргументы, перегрузки

Против:

- ▶ Не поддерживают частичное применение
- ▶ Не дружат с функциями высших порядков

Методы против свободных функций

Вывод типов

F#

```
type Vector = {x : float; y : float} with  
    member v.Length = v.x * v.x + v.y * v.y |> sqrt
```

```
let length v = v.x * v.x + v.y * v.y |> sqrt
```

```
let compareWrong v1 v2 =  
    v1.Length < v2.Length
```

```
let compareRight v1 v2 =  
    length v1 < length v2
```

Методы против свободных функций

Функции высших порядков

F#

```
type Vector = {x : float; y : float} with
    member v.Length = v.x * v.x + v.y * v.y |> sqrt

let length v = v.x * v.x + v.y * v.y |> sqrt

let lengths1 = [{x = 1.0; y = 1.0}; {x = 2.0; y = 2.0}]
               |> List.map (fun x -> x.Length)

let lengths2 = [{x = 1.0; y = 1.0}; {x = 2.0; y = 2.0}]
               |> List.map length
```


Классы, основной конструктор

F#

```
type Vector(x, y) =
    member v.Length = x * x + y * y |> sqrt

printfn "%A" <| Vector (1.0, 1.0)
```

F# Interactive

```
FSI_0003+Vector
type Vector =
    class
        new : x:float * y:float -> Vector
        member Length : float
    end
val it : unit = ()
```

Методы и свойства

F#

```
type Vector(x : float , y : float) =  
    member v.Scale s = Vector(x * s, y * s)  
    member v.X = x  
    member v.Y = y
```

F# Interactive

```
type Vector =  
    class  
        new : x:float * y:float -> Vector  
        member Scale : s:float -> Vector  
        member X : float  
        member Y : float  
    end
```

Private-поля и private-методы

F#

```
type Vector(x : float, y : float) =  
    let mutable mX = x  
    let mutable mY = y  
    let lengthSqr = mX * mX + mY * mY  
    member v.Length = sqrt lengthSqr  
    member v.X = mX  
    member v.Y = mY  
    member v.SetX x = mX <- x  
    member v.SetY y = mY <- y
```

Мутабельные свойства

F#

```
type Vector(x, y) =  
    let mutable mX = x  
    let mutable mY = y  
    member v.X  
        with get () = mX  
        and set x = mX <- x  
    member v.Y  
        with get () = mY  
        and set y = mY <- y
```

Автоматические свойства

F#

```
type Vector(x, y) =  
    member val X = x with get, set  
    member val Y = y with get, set  
  
let v = Vector(1.0, 1.0)  
v.X <- 2.0
```

Индексеры

F#

```
open System.Collections.Generic
```

```
type SparseVector(items : seq<int * float>) =  
    let elems = new SortedDictionary<_, _>()  
    do items |> Seq.iter (fun (k, v) -> elems.Add(k, v))  
  
    member t.Item  
        with get(idx) =  
            if elems.ContainsKey(idx) then elems.[idx]  
            else 0.0
```

```
let v = SparseVector [(3, 547.0)]  
printfn "%f" v.[4]
```

Операторы

F#

```
type Vector(x : float , y : float) =  
    member v.X = x  
    member v.Y = y  
  
    static member (+) (v1 : Vector , v2 : Vector) =  
        Vector(v1.X + v2.X, v1.Y + v2.Y)  
  
    static member (-) (v1 : Vector , v2 : Vector) =  
        Vector (v1.X - v2.X, v1.Y - v2.Y)  
  
    static member (~-) (v : Vector) =  
        Vector(-1.0 * v.x, -1.0 * v.y)  
  
let v = Vector (1.0 , 1.0) + Vector (2.0 , 2.0)
```

Вернёмся к конструкторам

Дополнительное поведение

F#

```
type Vector(x : float, y : float) =  
    let length () = x * x + y * y |> sqrt  
    do  
        printfn "Vector (%f, %f), length = %f"  
            x y <| length ()  
        printfn "Have a nice day"  
    let mutable x = x  
    let mutable y = y  
  
let v = Vector(1.0, 1.0)
```


let-функции и методы

F#

```
type Vector(x : float, y : float) =  
    let length () = x * x + y * y |> sqrt  
    let normalize () = Vector(x / length(), y / length())  
    member this.Normalize = normalize  
    member this.X = x  
    member this.Y = y  
  
let v = Vector(2.0, 2.0)  
let v' = v.Normalize ()
```

Рекурсивные методы

F#

```
type Math() =  
    member this.Fibonacci x =  
        match x with  
        | 0 | 1 -> 1  
        | _ -> this.Fibonacci (x - 1)  
                + this.Fibonacci (x - 2)  
  
let math = new Math()  
printfn "%i" <| math.Fibonacci 10
```

Много конструкторов

F#

```
type Vector(x : float, y : float) =  
    member this.X = x  
    member this.Y = y  
    new () =  
        printfn "Constructor with no parameters"  
        Vector(0.0, 0.0)  
  
let v = Vector(2.0, 2.0)  
let v' = Vector()
```

Модификаторы видимости

F#

```
type Example() =  
    let mutable privateValue = 42  
  
    member this.PublicValue = 1  
    member private this.PrivateValue = 2  
    member internal this.InternalValue = 3  
  
    member this.PrivateSetProperty  
        with get () =  
            privateValue  
        and private set(value) =  
            privateValue <- value
```

Наследование

F#

```
type Shape() =  
    class  
    end
```

```
type Circle(r) =  
    inherit Shape()  
    member this.R = r
```

Абстрактные классы

F#

```
[<AbstractClass >]
type Shape() =
    abstract member Draw : unit -> unit
    abstract member Name : string

type Circle(r) =
    inherit Shape()
    member this.R = r
    override this.Draw () =
        printfn "Drawing circle"
    override this.Name = "Circle"
```

Реализация по умолчанию

F#

```
type Shape() =  
    abstract member Draw : unit -> unit  
    abstract member Name : string  
    default this.Draw () =  
        printfn "Drawing shape"  
    default this.Name =  
        "Shape"
```

Вызов метода родителя

F#

```
type Shape() =  
    abstract member Draw : unit -> unit  
    abstract member Name : string  
    default this.Draw () = printfn "Drawing shape"  
    default this.Name = "Shape"
```

```
type Circle(r) =  
    inherit Shape()  
    member this.R = r  
    override this.Draw () =  
        base.Draw ()  
        printfn "Drawing circle"  
    override this.Name = "Circle"
```


Интерфейсы

F#

```
type Shape =  
    abstract member Draw : unit -> unit  
    abstract member Name : string  
  
type Circle(r) =  
    member this.R = r  
    interface Shape with  
        member this.Draw () =  
            printfn "Drawing circle"  
        member this.Name = "Circle"
```

Явное приведение типов

F#

```
let c = Circle 10
c.Draw ()    // Ошибка
(c :> Shape).Draw ()    // Ok

let draw (s : Shape) = s.Draw ()

draw c    // Ok
```

Наследование интерфейсов

F#

```
type IEnumerable <'a> =  
    abstract GetEnumerator : unit -> IEnumerator <'a>  
  
type ICollection <'a> =  
    inherit IEnumerable <'a>  
    abstract Count : int  
    abstract IsReadOnly : bool  
    abstract Add : 'a -> unit  
    abstract Clear : unit -> unit  
    abstract Contains : 'a -> bool  
    abstract CopyTo : 'a[] * int -> unit  
    abstract Remove : 'a -> unit
```

Объектные выражения

Реализация интерфейсов на лету

F#

```
type Shape =  
    abstract member Draw : unit -> unit  
    abstract member Name : string  
  
let rect w h =  
    { new Shape with  
        member this.Draw () =  
            printfn "Drawing rect , w = %d, h = %d" w h  
        member this.Name = "Rectangle"  
    }  
  
(rect 10 10).Draw ()
```

Частичная реализация интерфейса

F#

```
type Shape =  
    abstract member Draw : unit -> unit  
    abstract member Name : string  
  
let simpleShape nameFunc =  
    { new Shape with  
        member this.Draw () =  
            printfn "Drawing %s" this.Name  
        member this.Name = nameFunc ()  
    }  
  
(simpleShape (fun () -> "Star")).Draw ()
```

Делегация вложенному классу

F#

```
type Printer =  
    abstract member WriteString : string -> unit  
  
type HtmlWriter() =  
    let mutable count = 0  
    let printer =  
        { new Printer with  
            member this.WriteString s =  
                count <- count + s.Length  
                System.Console.Write(s) }  
    member x.CharCount = count  
    member x.Header () = printer.WriteString "<html>"  
    member x.Footer () = printer.WriteString "</html>"  
    member x.WriteString s = printer.WriteString s
```

Модули

F#

```
type Vector =  
    { x : float; y : float }  
  
module VectorOps =  
    let length v = sqrt(v.x * v.x + v.y * v.y)  
    let scale k v = { x = k * v.x; y = k * v.y }  
    let shiftX x v = { v with x = v.x + x }  
    let shiftY y v = { v with y = v.y + y }  
    let shiftXY (x, y) v = { x = v.x + x; y = v.y + y }  
    let zero = { x = 0.0; y = 0.0 }  
    let constX dx = { x = dx; y = 0.0 }  
    let constY dy = { x = 0.0; y = dy }
```

Расширения модулей

F#

```
module List =  
    let rec pairwise l =  
        match l with  
        | [] | [_] -> []  
        | h1 :: (h2 :: _ as t) -> (h1, h2) :: pairwise t  
  
let x = List.pairwise [1; 2; 3; 4]
```


Дотнетовские структуры

F#

```
[<Struct>]
type VectorStruct =
    val x : float
    val y : float
    new (x, y) = {x = x; y = y}
    member v.X = v.x
    member v.Y = v.y
    member v.Length = v.x * v.x + v.y * v.y |> sqrt

type VectorStruct' =
    struct
        val x: float
        val y: float
    end
```

Пространства имён

F#

```
namespace Vectors
```

```
type Vector =  
    { x : float; y : float }
```

```
module VectorOps =  
    let length v = sqrt(v.x * v.x + v.y * v.y)
```