Proceedings of the Third International Conference on Innovative Mechanisms for Industry Applications (ICIMIA 2023)
IEEE Xplore Part Number: CFP23K58-ART; ISBN: 979-8-3503-4363-2

2023 3rd International Conference on Innovative Mechanisms for Industry Applications (ICIMIA) | 979-8-3503-4363-2/23/$31.00 ©2023 IEEE | DOI: 10.1109/ICIMIA60377.2023.10426613

Detection of Phishing Link and QR Code of UPI Transaction using Machine Learning

Gangisetty Raj Charan
Dept. of Networking and Communications
SRM Institute of Science and Technology
Chennai,India
Email: gq5298@srmist.edu.in

Dr.K Deepa Thilak
Dept. of Networking and Communications
SRM Institute of Science and Technology
Chennai,India
Email: deepathk@srmist.edu.in
***corresponding author**

Abstract—

Development of digital payment systems and the evolution of technology give rise to new frauds. With bogus URLs and QR Codes, phishing poses a major danger to transaction security and integrity. The proposed detection of phishing link and QR code of UPI transaction using machine learning delves into the complexity of this important topic, providing information about fraud and enhancing the exploitation of UPI ecosystems. This study intends to overcome this problem by leveraging Machine Learning and AI techniques to prevent fraud and improve security mechanisms. Phishing is a malicious attempt to pose as a reliable source in order to fool people into disclosing private information, including passwords, usernames, or bank account information. Phishing attacks can also be carried out with QR codes, which are a kind of data storage that can be swiftly accessed by a smartphone's camera. User awareness and resistance against phishing attacks.The Universal Payment Interface (UPI) is at the forefront of this disruptive wave due to its ease and efficiency in financial operations. This study investigates not just the historical context of phishing efforts but also the evolving techniques employed by fraudsters to exploit the UPI ecosystem.

Keywords—Football, Predictions, Artificial Intelligence, Machine Learning, Data Mining.

I. INTRODUCTION

The digital revolution has simplified and streamlinedfinancial transactions, and the UPI is at the forefront of this disruptive wave. UPI has changed the way consumers and businesses conduct business. With its user-friendly smartphone applications and widespread acceptance, UPI has revolutionized the way consumers and businesses transact. However, the astounding growth of digital payment systems has brought to light an equally important concern: the growing stream of phishing attacks targeting UPI transactions. Phishing is a sort of cyber-attack in which fake URLs and bogus QR codes are used to undermine the security and integrity of these transactions. It jeopardizes customers' and financial institutions' trust in the UPI ecosystem, potentially resulting in massive financial losses and reputational damage, feature extraction, machine Learning algorithms, real-time detection methods, continuous monitoring, user education and ethical practices. UPI has not only facilitated peer-to-peer and peer-to-merchant transactions, but has also established itself as a pillar of India's digital economy. It investigates not just the historical context of phishing efforts, but also the evolving techniques employed by fraudsters to exploit the UPI ecosystem. The research investigates the technique, technology, and ethical problems involved in designing phishing detection systems. This study analyzes numerous areas of the issue during the research, such as data collection and preprocessing.

Finally, this research study serves as a knowledgerepository, with the goal of guiding future efforts to improve the security of digital payments. By leveraging machine learning and improving user awareness, we intend to giveconsumers and financial institutions with the tools and knowledge they need to navigate the UPI ecosystem withconfidence and trust.

Authorized licensed use limited to: UNIVERSITI TEKNOLOGI MARA. Downloaded on April 28,2025 at 03:35:59 UTC from IEEE Xplore. Restrictions apply.

II. Literature Review

Md. Anwar Hussain in Intuitionistic fuzzy logic based decision tree for E-transactional fraud detection [1] published in 2020 focuses on existing research and studies relating to the useof in decision tree models for detecting fraud in electronic transactions. It looks at the methodology, tactics, and advances in this subject, focusing on the efficacy and problemsof such hybrid approaches.

Xuting Mao in [2] published in 2021 focused on financial fraud detection using the related-party transaction knowledge graph. This study intends to evaluate the efficacy of cutting- edge graph-based techniques and the incorporation of intuitivefuzzy logic into decision trees for combatting financial fraud, offering significant insights for future research in this vital area.

Chenglong zhang in [3] Uncertainty-aware credit card fraud detection using deep learning. It explores the usefulness of uncertainty-aware deep learning models in electronic transactional fraud detection, as well as their potential synergy with intuitionistic fuzzy logic-based decision trees. The purpose of this survey is to give insights into the growing landscape of deep learning approaches for fraud detection, therefore influencing future research in this critical field.

Vinicius Facco Rodrigues in [4] Fraud detection and prevention in e-commerce. A number of technologies are used in e-commerce fraud detection and prevention. Machine learning techniques such as Random Forest and Neural Networks are used to evaluate transaction data, whilst data mining systems such as RapidMiner clean and preprocess data. Natural language processing (NLP) aids text analysis, while cloud computing platforms provide for scalability.

Ruihao Cao in [5] Feature-wise attention based boosting ensemble method for fraud detection. The article emphasizes the importance of better model generalisation in detecting developing fraudulent activities. The article concludes with an empirical investigation demonstrating that AM-Boost baseline approaches on both public and real-world transaction datasets.

Vinicius Facco Rodrigues in [6] Pattern recognition in intelligent mechanical systems KNN. Pattern Recognition K-Nearest Neighbour (PRKNN) as an innovative and non-parametric approach for addressing this critical issue in banking and finance.

Bryan Karunachandra in [7] On the benefits of ma- chine learning classification in cashback fraud detection. Convolutional Neural Networks (CNN), and Long Short Term Memory (LSTM), applied to transaction data from a leading e commerce platform.

III. Methodology

In the current section, we explain the details of our proposed work 'Detection of Phishing Link and QR code of UPI transaction using Machine Learning'. In the next section, we go through our project-based Fraudulent-QR-Code detection in further detail. Machine learning aid in the prediction and detection of fraud, as well as in making timely decisions to save expenses. A large number of transactions may be examined using data mining technologies to identify differentiate fraudulent transactions.



Fig. 1. This Is System Architecture Diagram

A. Pandas

Pandas is a popular open-source Python data manipulation and analysis toolkit. It offers simple data structures and methods for working with structured data, making it a valuabletool for data scientists and analysts. Pandas is built on two coredata structures: the DataFrame, which is similar to a spreadsheet, and the Series, which is a one-dimensional array with labels. Pandas' diverse features make it a vital componentin the data science toolkit, automating activities such as data cleansing, exploration, and transformation.

Authorized licensed use limited to: UNIVERSITI TEKNOLOGI MARA. Downloaded on April 28,2025 at 03:35:59 UTC from IEEE Xplore. Restrictions apply.

B. NumPy

NumPy, an abbreviation for "Numerical Python," is a foundational Python package for numerical and scientific computing. It offers sophisticated multi-dimensional arrays(ndarrays) as well as a collection of functions for performing mathematical operations on them. NumPy arrays are efficient and support vectorized operations, which improves computing speed and performance. This library is essential for scientific calculations, data analysis, and machine learning.

C. Seaborn

Seaborn is a Python data visualization package that extends Matplotlib to give a higher-level interface for producing visually appealing and instructive statistical visualizations. It excels at creating useful and appealing statistical visualizations, making it a must-have tool for data analysts. as well as scientists. With only a few lines of code, Seaborn facilitates the production of complicated statistical displays such as heatmaps, pair plots, and violin plots. It is especially effective for investigating links and trends within datasets, allowing users to acquire significant insights from their data via attractive and easily customizable visualizations.

D. Matplotlib

Matplotlib is a popular Python toolkit for developing static, animated, and interactive visualizations in a variety of formats.It provides a flexible platform for creating Many plots such as line, scatter, bar, histograms, and more. Users may fine-tune the style and arrangement of their plots thanks to Matplotlib's various customization tools. Matplotlib's versatility and comprehensive feature set make it a go-to solution for data scientists, researchers, and anybody wanting high-quality data visualizations, whether you're generating basic data visualizations or complicated scientific visuals.

Putting policies in place to shield users, data, and systems from threats is part of improving security. The following are some broad tactics to improve security:

1) Dataset Quality
2) Feature Engineering
3) Machine Learning Model Selection
4) Training and Validation
5) Real-time Monitoring
6) Behavioral Analysis
7) Regular Model Updates
8) User Education
9) Two-Factor Authentication
10) Secure QR Code Generation
11) Data Encryption
12) Regular Security Audits
13) Collaboration with Payment Providers
14) Incident Response Plan
15) Legal and Regulatory Compliance

1) ***Dataset Quality***:
Make that the dataset used to train your machine learning model is representative and diverse, comprising both real and fraudulent UPI transactions.

2) ***Feature Engineering:***
Determine which features—such as URL structure, content analysis, transaction metadata, and QR code characteristics—are important for training your model.

3) ***Machine Learning Model Selection:***
Select the machine learning algorithms that best fit your work, taking into account the real-time detection needs as well as the properties of the data.

4) ***Training and Validation***:
Use a labelled dataset to train your machine learning model, and another set of data to verify its performance. Adjust the model as necessary.

5) ***Real Time Monitoring:***
Put your machine learning model to use by applying real-time monitoring of UPI transactions to identify phishing links and QR codes as they happen.

6) ***Behavioral Analysis:***
Include behavioural analysis in your model to find oddities or irregularities in transaction behaviour that might point to a potential phishing attempt.

7) ***Regular Model Updates***:
Update your machine learning model on a regular basis to increase accuracy overall and adjust to new phishing techniques.

8) ***User Education:***
Inform consumers of the value of double-checking

Authorized licensed use limited to: UNIVERSITI TEKNOLOGI MARA. Downloaded on April 28,2025 at 03:35:59 UTC from IEEE Xplore. Restrictions apply.

URLs, confirming transaction information, and exercising caution while scanning QR codes from unreliable sources.

9) ***Two-Factor Authentication:***
To increase security even further, promote or mandate two-factor authentication for UPI transactions.

10) ***Secure QR Code Generation:***
If relevant, make sure that the QR codes created for UPI transactions are safe from tampering and harmful changes.

11) ***Data Encryption:***
For UPI transactions, use end-to-end encryption to safeguard private data while it's being transmitted.

12) ***Regular Security Audits:***
Perform routine security audits to find possible weaknesses in your system and make sure security best practises are being followed.

13) ***Collaboration with Payment Providers:***
Work together with payment gateways and UPI service providers to exchange threat intelligence and improve security in general.

14) ***Incident Response Plan:***
Create an incident response plan specifically for UPI transaction security so that any security incidents may be quickly addressed and mitigated.

15) ***Legal and Regulatory Compliance***
Assure adherence to pertinent legal and regulatory regulations controlling data protection and payment processes.

How To Reduce False Alarms:

1) Fine-Tune Machine Learning Models
2) Balanced Training Data
3) Feature Selection and Engineering
4) Threshold Adjustment
5) Ensemble Models
6) User Feedback and Validation
7) Dynamic Thresholds
8) Incident Investigation and Learning
9) Context-Aware Analysis
10) Rule-Based Filters
11) Regular Model Evaluation
12) Collaboration with End Users

In the context of UPI (Unified Payments Interface) transactions, phishing URL and false QR code detection using machine learning entails utilising algorithms that can analyse numerous aspects and patterns connected with these dangerous components.

1) ***Feature Extraction***:
Extracting pertinent characteristics from the data is a common first step for machine learning algorithms. Features of phishing URLs might include length, age of the domain, peculiar characters, and resemblance to well-known authentic URLs. Features for bogus QR codes might include content, encoding, and structural analysis.

2) ***Supervised Learning***:
Supervised learning is a common technique in machine learning, in which an algorithm is trained on a labelled dataset that includes both authentic and phishing cases. The algorithm gains the ability to recognize traits and patterns that set the two groups apart.

3) ***Classification Models:***
The identification of bogus QR codes and phishing URLs can be treated as classification problems. Typical categorization formulas consist of:
   i) **Decision Trees:** To categorize URLs or QR codes, decision trees can model decision rules based on characteristics.
   ii) **Random Forests**: By combining many models, ensembles of decision trees can improve accuracy.

4) ***Natural Language Processing (NLP):***
In the absence of labelled data, anomalies can be found via unsupervised learning. In URL or QR code data, clustering methods like K-Means or DBSCAN might reveal odd patterns.

5) ***Ensemble Methods:***
Boosting and bagging are examples of ensemble approaches that integrate numerous models to increase overall accuracy and generalization. This helps to capture various elements of bogus QR codes and phishing URLs.

6) ***Cross-Validation:***
By ensuring that the model's performance is

Authorized licensed use limited to: UNIVERSITI TEKNOLOGI MARA. Downloaded on April 28,2025 at 03:35:59 UTC from IEEE Xplore. Restrictions apply.

assessed over several dataset subsets, cross-validation approaches assist to gauge the model's capacity for generalization and prevent overfitting.

7) ***Regular Updates:***
Update the machine learning models on a regular basis to accommodate new phishing tactics and variations in the characteristics of fraudulent URLs or QR codes.

III. System Architecture And Design

We processed the dataset in this Dataset. The Dataset is then classified. Finally, we must clean the dataset. The data was then analysed to detect phishing attacks, generate accuracy scores, and determine whether or not there was fraud. Fraud detection is both critical and challenging. Despite multiple initiatives and human control, fraud wastes hundreds of millions of dollars. Fraud may take many forms, including stolen credit cards, fraudulent bookkeeping, phishing emails, and so on. Detecting fraud is both critical and challenging due to the small number of instances in a large population. Machinelearning may help forecast and identify fraud, as well as make prompt judgements to save money. Data mining tools may be used to investigate a large number of transactions in order to detect trends and distinguish fraudulent transactions.

The provided data set includes financial transaction data as well as the target variables isFraud, which represents the transaction's true fraud status, and is FlaggedFraud, which represents the indication used by the simulation to flag the transaction based on a threshold value. Because there are no missing or garbage values, there is no need for data cleansing; nonetheless, data analysis is still required because the numbers in other columns vary widely. Normalization will also increase the overall accuracy of the machine learning model.



Fig. 2. Diagram of Modules and It's Pathway

IV. Results And Discussion

Machine Learning Effectiveness: When correctly trained and fine-tuned, machine learning algorithms excel at distinguishing between real and phishing UPI transactions. These algorithms employ a combination of textual and visual information gathered from URLs and QR codes to provide credible predictions.

The graph below indicates that TRANSFER and CASH-OUT are the two most commonly utilized modes of transaction, and that TRANSFER and CASH-OUT are also the only ways that fraud occurs. As a result, we will concentrate on these types of transactions.



Fig. 3. Correctness graph of base model

This study focuses on heatmap, which shows the Correlation of data.



Fig. 4. Heatmap and It's Characteristics

Authorized licensed use limited to: UNIVERSITI TEKNOLOGI MARA. Downloaded on April 28,2025 at 03:35:59 UTC from IEEE Xplore. Restrictions apply.

This heatmap shows that:

1) OldbalanceOrg and NewbalanceOrg are significantly connected.

2) OldbalanceDest and NewbalanceDest have a strong correlation.

3) The amount is connected to isFraud (Target Variable).:

Average precision score is 0.7687.



Fig. 5. Final Heatmap and It's Correlation

V. CONCLUSION

In conclusion, this study acts as a thorough and complete information providing information and holding a grasp of the issues and solutions in the domain and penultimate domain of phishing detection inside UPI systems. It intends to lead efforts ensuring that the users and current research and ideas an some or all the financial institutions may embrace the benefits of UPI transactions with confidence.

REFERENCES

[1] Askari, Sikdar Md S., and Md Anwar Hussain. "Intuitionistic fuzzy logic based decision tree for E-transactional fraud detection." Science Direct (2020).

[2]

[3] Habibpour, Maryam, et al. "Uncertainty-aware credit card fraud detection using deep learning." Engineering Applications of Artificial Intelligence 123 (2023): 106248..

[4] Rodrigues, Vinicius Facco, Lucas Micol Policarpo, Diórgenes Eugênio da Silveira, Rodrigo da Rosa Righi, Cristiano Andre´ da Costa, Jorge Luis Victória Barbosa, Rodolfo Stoffel Antunes, Rodrigo Scorsatto, and Tanuj Arcot. "Fraud detection and prevention in e-commerce: A systematic literature review." Electronic Commerce Research and Applications (2022): 101207.

[5] Rodrigues, Vinicius Facco, et al. "Fraud detection and prevention in e-commerce: A systematic literature review." Electronic Commerce Research and Applications (2022): 101207.

[6] David, Shibin, R. S. Anand, Sarah Sheikh, S. Jebapriya, J. Andrew, and S. Basil Xavier. "A comprehensive overview on intelligent mechanical systems and its applications." Materials Today: Proceedings 37 (2021): 733-736.

[7] Karunachandra, Bryan, Nathaniel Putera, Stephen Rian Wijaya, Dewi Suryani, Julian Wesley, and Yudy Purnama. "On the benefits of machine learning classification in cashback fraud detection." Procedia Computer Science 216 (2023): 364-369.

[8] Xu, Biao, Yao Wang, Xiuwu Liao, and Kaidong Wang. "Efficient fraud detection using deep boosting decision trees." Decision Support Systems (2023): 114037.

[9] Van Belle, Rafae¨l, Bart Baesens, and Jochen De Weerdt. "CATCHM: A novel network-based credit card fraud detection method using node representation learning." Decision Support Systems 164 (2023): 113866.

[10] Bhatla, Tej Paul, Vikram Prabhu, and Amit Dua. "Understanding credit card frauds." Cards business review 1, no. 6 (2003): 1-15.

[11] Montague, David A. Essentials of online payment security and fraud prevention. Vol. 54. John Wiley Sons, 2010.

[12] Ghosh, Sushmito, and Douglas L. Reilly. "Credit card fraud detection with a neural-network." In System Sciences, 1994. Proceedings of the Twenty-Seventh Hawaii International Conference on, vol. 3, pp. 621-630.IEEE, 1994.

[13] Fawcett, Tom, and Foster Provost. "Adaptive fraud detection." Data mining and knowledge discovery 1, no. 3 (1997): 291-316.

[14] Srivastava, Abhinav, Amlan Kundu, Shamik Sural, and Arun Majumdar. "Credit card fraud detection using hidden Markov model." IEEE Transactions on dependable and secure computing 5, no. 1 (2008): 37-48.

[15] Whitrow, Christopher, David J. Hand, Piotr Juszczak, David Weston, and Niall M. Adams. "Transaction aggregation as a strategy for credit card fraud detection." Data mining and knowledge discovery 18 (2009): 30-55.

[16] Pete, Chapman, Clinton Julian, Kerber Randy, Khabaza Thomas, Reinartz Thomas, Shearer Colin, and R. Wirth. "Crisp-Dm 1.0—Step- by-step data mining guide." Cris. Consort (2000): 76.

Authorized licensed use limited to: UNIVERSITI TEKNOLOGI MARA. Downloaded on April 28,2025 at 03:35:59 UTC from IEEE Xplore. Restrictions apply.