# Billing Data Audit Report

Google Sheets billing data checked against the ArchiMate model

25 October 2026, 23:49

| 3 | 3 | 2 | 1 | 1 |
|---|---|---|---|---|
| Customer rows | Billing rows | Issues found | Need human review | Proposed corrections |

2 issue(s) detected. Source data was **not modified**; every correction needs approval.

## Issues by type

| Issue type | Source | Count |
|---|---|---|
| Customer Name Mismatch | Billing | 1 |
| Missing Customer Reference | Billing | 1 |

# AI Analysis

Generated by the local Ollama model from the audit results and the ArchiMate MCP context. Treat it as an explanation to verify, not as ground truth.

The code is a JSON object that represents a data model for a software system. It contains several sections:

1. `find_facturation`: This section contains a list of objects that represent business processes, application components, and application services related to facturation (billing).
2. `find_client`: This section contains a list of objects that represent business processes and data objects related to clients.
3. `find_donnée`: This section contains a list of objects that represent data objects related to client data.
4. `elements`: This section contains a list of objects that represent graphical elements, such as rectangles and lines, that are used to visualize the data model.
5. `connections`: This section contains a list of objects that represent relationships between the graphical elements.

The objects in each section have the following properties:

- `id`: a unique identifier for the object
- `type`: the type of object (e.g. business process, application component, data object)
- `name`: the name of the object
- `documentation`: a brief description of the object
- `properties`: an object that contains additional properties specific to the object
- `layer`: the layer of the object in the data model (e.g. business, application, technology)

The `connections` section contains objects that represent relationships between the graphical elements. Each connection object has the following properties:

- `id`: a unique identifier for the connection
- `relationship_ref`: a reference to the relationship between the two elements
- `source_node`: the ID of the source element
- `target_node`: the ID of the target element

Overall, this data model appears to be a representation of a software system that handles facturation and client data. The graphical elements and connections represent the structure and relationships between the different components of the system.

# Detailed Findings

| # | Issue | Location | References | Details | Action |
|---|---|---|---|---|---|
| 1 | **Customer Name Mismatch**<br>Billing | Row 2 | Invoice: INV001<br>Customer: C102 | Customer ID matches exactly, but the names differ.<br>Billing: 'Ahmed Benaly' vs Customers: 'Ahmed Ben Ali'<br>Proposal: Use 'Ahmed Ben Ali' in the billing record if Customers is the approved source of truth. | **Propose correction** |
| 2 | **Missing Customer Reference**<br>Billing | Row 4 | Invoice: INV003<br>Customer: C999 | Billing record references a customer_id absent from Customers. | **Review required** |

## Appendix: ArchiMate MCP session

**Tools available:** archimate_find_elements, archimate_get_element, archimate_get_view, archimate_list_elements, archimate_list_relationships, archimate_list_views, archimate_neighbors, archimate_relationships_of

**Queries run:** views, find_facturation, find_client, find_donnée

**MCP errors:** none

Full raw results are saved in archimate_audit_context.json.