Can Decision Models Replace Tool Calling for Coding Agents?

Aziz Muminov Alexandra Ilina

Preprint draft — 5 November 2026

Abstract

A coding agent connected to many MCP servers must either load every tool definition into its context (about 180k tokens for the 613 tools of twelve popular servers) or find tools through search, and harnesses ship different mechanisms: name lists with keyword search (Claude Code), BM25 (Codex, Anthropic's tool search, Hermes Agent), tool groups (GitHub Copilot), and embeddings or an LLM router (Goose). We ask whether a *decision model* (DM), here Microsoft Decision 1 (`microsoft/microsoft-decision-1` on OpenRouter's Decisions API), which returns calibrated probabilities over up to 255 options without generating text, is a better tool selector. We built a test suite from the real tool definitions of 30 MCP servers (613 and 1,076 tools) with simulated back ends, 71 coding tasks graded by hidden tests and required writes, and two agent harnesses (opencode and Hermes Agent). Our main experiment swaps the ranker inside Hermes Agent's tool-search bridge (BM25, two DM variants, embeddings, a Claude Code-style ranker, random) on 38 tasks over 1,076 tools, pinned and paired (684 runs). Every ranker, even random, passed 96–100% of runs, but tokens differed: random used 1.57× the tokens of BM25, and Microsoft Decision 1 with a calibrated "none" option (DM v3) was the only ranker significantly below BM25, at 0.88× [95% CI 0.78, 0.98]. Offline, a server-then-tool DM hierarchy ranks best (hit@1 0.93 at 613 tools against 0.48–0.54 for name, BM25 and embedding search and 0.86 for an LLM router), and on the agents' own queries its results contained the needed tool more often than BM25's (0.29 against 0.24). A projection suggests the DM's per-search fee pays off for agent models costing more than about $0.02 per run.

1 Introduction

Through the Model Context Protocol (MCP) [17], coding agents read CI logs, error trackers, tickets, chat, dashboards, clusters and databases, and the LLM must see each tool's definition (name, description, parameter schema) before calling it. Twelve widely used servers (GitHub, Grafana, Sentry, Atlassian, Linear, Slack, Notion, Kubernetes, MongoDB, Postgres, Git, Playwright) expose 613 tools whose definitions take about 180k tokens per request.

Harnesses therefore use *tool search*: definitions stay out of the prompt and the agent finds tools on demand (§2). Claude Code defers MCP tools, lists only their names, and loads them through a ToolSearch tool [3]; Anthropic's API and OpenAI's Codex CLI offer BM25 search [2, 20]; GitHub Copilot groups tools into "virtual tools" that the agent activates [14]; Goose has offered embedding-based and LLM-based tool routers (documented as a preview in 2025) [6]; Hermes Agent defers MCP tools behind a BM25 bridge [18]. These ranking functions have not been compared on the same tools and tasks.

Decision models (DMs) suit this ranking: a DM reads a state and a question with named options and returns a probability per option in one forward pass, without generating tokens. We

use Microsoft Decision 1 (MSD1; `microsoft/microsoft-decision-1`) [15] through OpenRouter's Decisions API [22]. But a DM accepts at most 255 options, fewer than a realistic catalog, and cannot write arguments.

We ask: *can a DM serve as a coding agent's tool selector, and is it better than the mechanisms harnesses ship?* Our test suite (§4) uses the real `tools/list` output of 30 MCP servers (613 tools, 1,076 with decoys such as GitLab beside GitHub), simulated back ends, 71 graded tasks, eight selection conditions and two harnesses. In brief (caveats in §6):

- **Main experiment (§5.1).** Six rankers in Hermes Agent's shipped search bridge, including two Microsoft Decision 1 variants; 38 tasks, 1,076 tools, DeepSeek V4.1 Flash on a pinned endpoint, 684 paired runs. Every ranker passed 96–100% of runs; random used 1.57× the tokens of BM25, and DM v3 (Microsoft Decision 1 with a "none" option) was the only ranker significantly below it (0.88×, 95% CI 0.78–0.98).
- **Offline (§5.3).** The DM hierarchy put the right tool first for 93% of 120 hand-written queries at 613 tools (88% at 1,076), against 45–54% for name, BM25 and embedding search and 82–86% for an LLM router, at a third of the router's cost; on agent-written queries the gap is smaller.
- **Live, eight mechanisms (§5.4).** With opencode every catalog condition passed 96–100% of runs, and search cut the largest prompt from about 182k tokens to 12–53k, so pass rate cannot separate rankers; tokens must be compared, paired.

Contributions. (i) A test suite for tool selection in coding agents on real MCP tool definitions, with simulated back ends, graded tasks and an isolated sandbox. (ii) A Microsoft Decision 1 tool ranker that passes the 255-option limit by choosing the server first, integrated into a shipped harness's search bridge. (iii) A comparison of shipped mechanisms and the DM, offline and in two agents. (iv) A paired protocol for measuring token differences between agent configurations.

2 How harnesses select tools

Table 1 lists the mechanisms we compare. All but native loading give the agent a search tool and a way to call what it finds, usually with a short server overview, so it pays for definitions only on retrieval.

Hermes's bridge. Hermes Agent 0.19.0 defers MCP tools once their definitions exceed 10% of the context window, as 613 tools do. `tool_search` returns compact hits (name and one line), `tool_describe` one full definition, and found tools are called directly with typed arguments. Our main experiment swaps only the ranker behind `tool_search` (Figure 1).

Skills and progressive disclosure. Agent skills [1] apply the same idea to instructions: a one-line summary stays in context and the body loads on demand. Our service overviews and the v2 "where things live" handbook (§4) play this role for the catalog.

3 Decision models as tool selectors

The interface. A Decisions API request carries a *state* (here the agent's search query) and named questions; a `choice` question lists options, each with a free-text description, and returns

Table 1: Tool-selection mechanisms in current harnesses and the conditions that reproduce them.

Condition	Shipped in	What the agent sees and does
native	Cursor, Cline, opencode; Claude Code with search off	every tool definition in every request
cc	Claude Code ToolSearch [3]	names of all deferred tools; `select:a,b` by exact name, or keyword search with name matches weighted highest (our approximation; the exact scoring is undocumented)
bm25	Anthropic tool search [2], Codex CLI [20], Hermes [18]	Okapi BM25 [24] over names, descriptions and parameters
groups	GitHub Copilot virtual tools [14]	one `activate_<group>` tool per server (servers over 40 tools split); activating loads the group's definitions
embed	Goose vector router [6], RAG-MCP [10]	cosine similarity of `text-embedding-3-small` vectors of query and tool
llm	Goose LLM router [6]	an LLM (DeepSeek V4.1 Flash) reads one line per tool and names the best ones
dm	this paper	Microsoft Decision 1 (`microsoft/microsoft-decision-1`) ranks servers, then tools; DM v3 adds a "none option (§3)
random	control	five random tools

a probability per option [22]. We describe each tool by its name, the first 300 characters of its description and its parameter names. The DM in all our experiments is Microsoft Decision 1 (MSD1), called as `microsoft/microsoft-decision-1` on OpenRouter's Decisions API and post-trained from Qwen3.5-9B [15]; it answers in about half a second and costs about $0.04 per million input tokens.

The 255-option limit. A `choice` question accepts at most 255 options, and MSD1 rejects requests beyond about 32k tokens. We compared four ways around the limit:

- **Hierarchy** (default): ask which server has the needed tool (12 or 30 options, each described by the server's purpose), take the most likely servers until they cover 90% of the probability mass (at most three), ask which of their tools fits (Linear, the largest server, has 198), and score each tool by $P(\text{server}) \cdot P(\text{tool} \mid \text{server})$.
- **Tournament**: split the catalog into chunks of at most 250, keep the top five of each, and decide among the survivors.
- **BM25→DM** and **embed→DM**: shortlist 100 tools with BM25 or embeddings, then let the DM choose among them.

Figure 1 shows the hierarchy inside Hermes's bridge.

Why the DM selects and does not call. A DM cannot write arguments, and most tool choices in a coding session are easy. On 395 tool decisions of one real session (the one in which this project was built), MSD1 predicted the next tool among 38 with accuracy 0.49 (TypeSafe Jev [26]: 0.60), below "always the shell" at 0.75, although the DMs' top five contained it 94–96% of the time. In that session 51 always-loaded tool definitions took about 59k tokens, 93% of the first request and 16% of all context tokens read. The DM belongs in the catalog: choosing which of hundreds of rarely used tools to show, while the LLM keeps the core tools and writes every call.




Figure 1: Tool selection with a decision model inside Hermes Agent's search bridge. The agent's query goes to the ranker slot, where the DM first chooses among servers and then among the tools of the most likely servers (at most 250 options per call). The agent receives compact hits, reads one full definition with `tool_describe`, and calls the tool directly with typed arguments. In the default harness BM25 fills the same slot; everything outside the dashed box is identical across conditions.

Table 2: The real tool catalog: tools per MCP server, from each server's own `tools/list`.

Catalog	Servers (tools)	Tools
main	Linear (198), Atlassian (98), GitHub (91), Grafana (81), Git (28), MongoDB (27), Playwright (25), Notion (24), Kubernetes (23), Sentry (9), Slack (8), Postgres (1)	613
extra	GitLab (127), monday (84), Salesforce (74), Heroku (33), HubSpot (21), AWS CloudWatch (19), AWS EKS (16), Airtable (16), Filesystem (14), CircleCI (13), Browserbase (9), Memory (9), Netlify (9), Terraform (9), Elasticsearch (4), ClickHouse (3), Figma (2), Docker (1)	+463
all	30 servers	1,076

4 Test suite

Real tool catalog. We started twelve MCP servers as an unprivileged user with dummy credentials and saved their `tools/list` responses: names, descriptions and input schemas exactly as published (Table 2). No tool was ever executed against a real service. This 613-tool catalog is our main setting. Eighteen further servers add 463 tools (1,076 in all), including natural decoys: GitLab beside GitHub, AWS CloudWatch beside Grafana Loki, AWS EKS beside Kubernetes.

Simulated back ends. Each task has a world: rules (tool, argument values to match, response), then organization-wide facts shared by all tasks; the first matching rule answers. Unmatched reads return what a real service would for something that does not exist (empty list or not found); unmatched writes succeed and are recorded for grading. Optionally, arguments are validated against the tool's schema.

Tasks. Each task is a small Python repository whose fix needs information that lives only in the services (a failing CI check, a Sentry stack trace, Loki logs, an alert threshold, a crash-looping pod, a Slack decision, a ticket, a wiki page, a document shape, a schema), reachable only through the catalog since the sandbox has no network or credentials. Many tasks also require a write (comment on the pull request, resolve the Sentry issue, move the ticket, reply in the thread, open a pull request).

- **v1** (33 tasks): 22 single-service, 3 multi-service, 4 *absent* (the information does not exist; the right outcome is to stop and leave a `TODO`), and 4 controls that need no catalog tool. Prompts often name the service ("check the logs in Loki").

- **v2** (38 tasks, Table 7): the same worlds with *symptom-first* prompts that do not name the service ("customers stopped getting shipping e-mails"), a shared "where things live" handbook in every README (like an `AGENTS.md`, naming the company's tools, including legacy GitLab, CloudWatch and EKS), and five new tasks, four multi-service and three on the extra servers, so that the decoy servers are sometimes the right answer.

Every prompt ends with the same escape clause: if the information is not available, do not guess; leave the code unchanged and add a `TODO: info not found` comment. In the final run (§5.1) every prompt also starts, identically in all conditions, with a note standing in for what real harnesses say in the system prompt about connected MCP servers: "Note: the company's internal services (code hosting, CI, error tracking, metrics and logs, incidents and on-call, tickets, docs and runbooks, chat, clusters, databases) are connected to you as tools. Some tools are loaded on demand: if a tool you need is not listed, use tool search to find it."

Grading and validation. A run passes when the hidden tests pass, every required write was made with the right arguments, and no destructive call was made (merge, delete, rollout restart, `kubectl apply`, ...). Before use, we checked that each task's hidden tests fail on the original repository and pass with the reference solution, that every tool it names exists, and that the reference calls get non-empty answers (empty for absent tasks) and satisfy the required writes.

Harnesses. *opencode* [21] (v1.19.4) runs headless with a shell limited to `pytest` and file tools limited to the project; our MCP server implements every condition of Table 1, returning the top five tools with full definitions and a service overview, with calls through `call_tool(name, arguments)`. *Hermes Agent* [18] 0.19.0 uses its own bridge over our server's full tool list; we patched the bridge's search function to ask our server's `/rank` endpoint when an environment variable is set, so rankers differ while packaging stays identical (Figure 1).

Isolation. Runs execute as an unprivileged user without credentials, reaching only the LLM proxy (which holds the API key) and the MCP server. Each Hermes run has its own mount namespace (work directory, home, private `/tmp`); the MCP server requires a per-run token hidden from the agent's shell; and Hermes's `approvals.deny` list blocks probing commands (`curl`, `ps`, `netstat`, `/proc`, `localhost`, ...). App. A lists how we arrived at this setup.

5 Experiments

We report the main experiment first, then supporting experiments on why the DM ranks well and why pass rate alone cannot separate rankers.

5.1 Main experiment: rankers inside Hermes's search bridge

Design. Everything is fixed except the ranker in Hermes's bridge (Figure 1):

- Hermes Agent 0.19.0 with the isolation of §4 and its `approvals.deny` list;
- task set v2 (38 tasks), 1,076 tools, schema validation, and the connected-services note (§4);
- one LLM, DeepSeek V4.1 Flash [8], pinned to DeepInfra's fp8 endpoint, temperature 0.6, seed 7;

Table 3: Main experiment: Hermes Agent, DeepSeek V4.1 Flash (pinned), task set v2 (38 tasks), 1,076 tools, three repeats, 114 runs per ranker (684 in all, re-graded). pass^3: tasks passed in all three repeats. Tokens: median per run. Ratio: geometric mean of per-slot token ratios against BM25 with a task-level bootstrap 95% CI. Fewer: slots (of 114) on which the ranker used fewer tokens than BM25. Bold: best value per column (highest accuracy, fewest tokens); random's perfect pass rate is one run more than the others.

Ranker	pass@1	pass^3	Tokens	Ratio vs. BM25 [95% CI]	Fewer	Searches/run
BM25 (Hermes, Codex)	0.991	37/38	558k	–	–	11.4
DM v3 ("none" option)	0.991	37/38	**459k**	**0.88** [0.78, 0.98]	**69/114**	10.1
DM v1	0.991	37/38	480k	0.93 [0.82, 1.03]	66/114	9.7
embeddings	0.965	35/38	562k	0.91 [0.81, 1.03]	63/114	11.1
Claude Code style	0.991	37/38	576k	1.02 [0.89, 1.16]	43/114	6.0
random	**1.000**	**38/38**	1,051k	1.57 [1.39, 1.79]	27/114	12.8

- six rankers in the same bridge: *Hermes BM25* (Hermes as shipped; Codex CLI also uses BM25); *DM v1* (Microsoft Decision 1, service then tool; top five); *DM v3* (the same with a calibrated "none" option: nothing when $P(\text{none}) \geq 0.4$, otherwise at most five tools); *embeddings* (`text-embedding-3-small`, as in Goose and RAG-MCP); *Claude Code style* (all deferred tool names in the prompt, keyword ranking and `select:<name>`); and *random* (five random tools, a lower bound);
- three repeats, $6 \times 38 \times 3 = 684$ runs; BM25, DM v1 and random were queued repeat by repeat with each slot's conditions back to back, DM v3, Claude Code style and embeddings later in parallel batches;
- analysis paired by slot: geometric mean of per-slot token ratios with a task-level bootstrap CI; pass@1 and pass^3 (the task passes in all three repeats).

Native loading is covered by the opencode runs (§5.4); an oracle ranker only labels searches offline.

Why paired, and why pinned. In pilot runs the paired log ratio of tokens between two conditions had a standard deviation of about 0.44, so detecting a 10% token difference with 80% power at $\alpha = 0.05$ needs about 136 pairs; the design gives 114 per comparison. Unpinned, OpenRouter routed DeepSeek requests to dozens of endpoints with different quantizations, and the harness sets no temperature, hence both fixes. A second LLM, Kimi K3.1 Pro, was piloted and dropped for cost and speed.

Grading. We corrected two rules during the run (the destructive-call rule matched any tool name containing "merge", blocking a required merge-request comment; one hidden test in `cw_reports` rejected a valid fix) and re-graded all runs from saved artefacts (33 of 684 verdicts changed).

Accuracy is at ceiling for every ranker, including random. All six rankers passed 96.5–100% of runs and abstained correctly on all 12 absent-task runs (Table 3); given five useless tools, an agent simply searches again. The remaining failures are real: a command run in a production pod in `k8s_crashloop` (`kubectl exec`, destructive; once each under BM25, DM v1 and Claude Code style, twice under embeddings), a wrong fix in `cw_reports` (DM v3, embeddings), and unchanged code in `prom_threshold` (embeddings, once).

Ranking shows up in tokens. Random ranking cost 1.57× the tokens of BM25 [1.39, 1.79] and used fewer tokens on only 27 of 114 slots, so the ranker matters. DM v3, Microsoft Decision 1




Figure 2: Main experiment: tokens per run relative to Hermes BM25 in the same (task, repeat) slot (114 slots per ranker). Grey: individual slots; blue: geometric mean with task-level bootstrap 95% CI.

with the "none" option, was the only ranker significantly below BM25: 0.88× [0.78, 0.98], about 12% fewer tokens (median 459k against 558k), fewer on 69 of 114 slots, with fewer searches (10.1 against 11.4). DM v1 (0.93× [0.82, 1.03]) and embeddings (0.91× [0.81, 1.03]) leaned 7–9% lower with intervals including 1; embeddings also had the lowest pass rate. The Claude Code-style ranker searched least (6.0 per run), as agents selected tools by name from the deferred list, but tied with BM25 in tokens (1.02×): listing 1,076 names costs context on every request.

Search accuracy in the live runs. We labelled every search in the BM25, DM v1, DM v3 and embeddings runs (4,785 searches from 408 runs) with the needed tool the agent was working towards; 2,862 were made while a needed tool was still missing and 879 on tasks that need no tool. Replaying the 2,862 queries through each ranker (hit: the five results contain a tool for the current step), the DM was right more often: DM v1 0.29, DM v3 0.28, BM25 0.24, embeddings 0.24, whichever ranker's agent wrote the queries (BM25 0.21–0.25, DM v1 0.27–0.30). DM v1 was right and BM25 wrong on 228 queries, the reverse on 84 (about 2.7:1). The results agents actually received follow the same order (BM25 0.23, embeddings 0.25, DM v1 0.27, DM v3 0.28). Rates are low because many searches are exploratory ("list all available services", guesses at services the company does not use): every ranker missed 1,890 queries. DM v3 answered "none" on 5.6% of its live searches (64 of 1,147); those we sampled asked for services absent from the catalog (AWS ECS, Google Drive, a Datadog-like APM). In the replay it answered "none" on 4.1% of queries for which a needed tool existed (117 of 2,862) and on 9% of searches from tasks that need no tool, where agents still search for plausible things ("find the Jira ticket").

Pilot. An earlier pilot on 12 v1 tasks with two repeats and 613 tools (24 paired slots) pointed the same way: DM v1 used 0.88× the tokens of BM25 (95% CI 0.77–1.02).

5.2 Projected savings for frontier models

This subsection is a projection, not a measurement. For more expensive agent models, we take the per-run token mix on the 71 slots that both Hermes BM25 and the DM had finished at the interim count (means per run): BM25 used 34k uncached input, 747k cached input and 11k output tokens (output includes reasoning), the DM 35k, 657k and 10k. The DM's own fee was $0.0020 per run

Table 4: *Projected* LLM cost per run with Hermes BM25 and with the DM in the bridge (including the DM fee of $0.0020 per run), if each model used the token mix measured with DeepSeek V4.1 Flash in the main run (interim, 71 slots). Prices: OpenRouter list prices on 5 November 2026, $ per million tokens (input / cached input / output). Saving per 1,000 runs is BM25 minus DM; negative means the DM costs more. [a]Gemini 4 Argon has the same list prices as Claude Sonnet 5.5 and GPT-6.1 Sol, and hence the same projection.

Agent model	Price (in / cached / out)	BM25 $/run	DM $/run	Change	Saving/1k runs
DeepSeek V4.1 Flash (measured)	0.15 / 0.003 / 0.60	0.0142	0.0152	+7%	−$1.0
Claude Haiku 5.5	0.10 / 0.01 / 0.50	0.0166	0.0171	+3%	−$0.5
Claude Sonnet 5.5[a]	2.00 / 0.10 / 10.00	0.257	0.238	−7%	$19
Kimi K3.1 Pro	2.00 / 0.20 / 10.00	0.332	0.304	−8%	$28
GPT-6.1 Sol[a]	2.00 / 0.10 / 10.00	0.257	0.238	−7%	$19
Claude Fable 5.1	10.00 / 0.25 / 50.00	1.099	1.020	−7%	$80

Table 5: Offline retrieval on 120 hand-written queries. Hit@k: a right tool is among the top k. Cost per 1,000 queries and median latency of the selecting call at 613 tools; name, BM25 and embedding search run locally (embedding cost is negligible). Bold: best value per accuracy column.

	613 tools			1,076 tools			
Mechanism	hit@1	hit@5	MRR	hit@1	hit@5	$/1k queries	latency (s)
Claude Code-style (cc)	0.48	0.71	0.56	0.45	0.65	0	0.01
BM25	0.54	0.75	0.62	0.49	0.76	0	<0.01
embeddings	0.51	0.80	0.61	0.47	0.75	≈0	0.67
LLM router	0.86	**0.98**	0.92	0.82	**0.98**	0.44	1.31
DM hierarchy	**0.93**	0.97	**0.95**	**0.88**	0.97	0.15	0.54
DM tournament	0.90	**0.98**	0.94	0.86	**0.98**	1.13	1.60
BM25→DM	0.87	**0.98**	0.91	0.80	0.96	0.18	0.33
embed→DM	0.88	**0.98**	0.93	0.80	**0.98**	0.18	0.99

(about ten searches at about $0.0002 each). We price both mixes at each model's OpenRouter list price on 5 November 2026 and add the fee to the DM column (Table 4).

Assumptions. A frontier agent would produce a similar token mix and reduction; stronger models may instead search less or write better BM25 queries. The projection uses the interim ratio (DM v1, 71 slots: 0.90× [0.76, 1.05]); the final DM v3 ratio, 0.88× [0.78, 0.98] (Table 3), supports a reduction of this size for one model, not yet for frontier models.

The fee is fixed; the saving scales with the agent's price. The DM's fee depends on the number of searches, while the tokens it saves are billed at the agent's price. Break-even lies at about $0.02 of agent-LLM cost per run. Below it, as with the model we measured, the DM makes a run about 3–7% more expensive; with the mid-range and frontier models in the table, about 7–8% cheaper ($19–80 per thousand runs). The fee could be lowered by returning exact tool names found in the query without a DM call, caching repeated queries, or answering from the server step alone when the DM is confident.

5.3 Why the DM ranks well: offline retrieval

We wrote two queries for each needed step of the v1 tasks, one in natural language and one as keywords (120 in all), and counted a hit when the top k contained any acceptable tool for that step (Table 5, Figure 3).




Figure 3: Offline retrieval, hit@1 (labelled) and hit@5, on the main and the extended catalog.

The DM ranks best; shipped lexical and embedding searches rank worst. At 613 tools the Microsoft Decision 1 hierarchy put a right tool first for 93% of queries, the Claude Code, Codex and Goose-vector mechanisms 48–54%, the LLM router 86%; learned rankers reached hit@5 of 0.97–0.98, the others 0.71–0.80. The DM hierarchy cost $0.15 per thousand queries, a third of the router's cost, at under half its latency.

Choosing the server first is the right way past 255 options. The hierarchy was the most accurate strategy at hit@1 and the cheapest. The tournament matched its hit@5 at seven times the cost, since it queries the DM for every chunk; BM25 or embedding shortlists were as cheap but lost 5–6 points at hit@1 when the shortlist dropped the right tool. Most needs also lie within one server.

Decoy servers cost every mechanism a little. Adding 463 tools, including GitLab, CloudWatch and EKS beside GitHub, Loki and Kubernetes, lowered hit@1 by 3–6 points for every mechanism and left the order unchanged (DM 0.875, LLM router 0.82, BM25 0.49).

On queries written by agents the gap narrows. On 183 agent-written queries from our live runs, mostly keyword lists and tool-name fragments, the DM still led at hit@1 (0.60 against 0.45 for BM25) but barely at hit@5 (0.70 against 0.66). Keyword-style queries suit lexical search, and agents compensate for a weak first query by searching again, so offline ranking quality translates only partly into agent behaviour.

5.4 Eight mechanisms in a live agent: opencode

Each of the 33 v1 tasks ran under eight conditions with two LLMs, DeepSeek V4.1 Flash and Tencent hy4, twice per task and model (528 runs, 613-tool catalog; Table 6, Figure 4).

The tasks need the catalog, and every mechanism provides it. Without a catalog no tool task passed (0 of 50); with one, every condition passed 96–100% (native, cc, bm25, llm, dm 50 of 50; groups 49; embed 48). All conditions abstained on the four absent tasks (8 of 8 runs each), and no control run made a catalog call. The three failures were hy4 runs: twice (groups, embed) the agent also restarted a production Kubernetes deployment unasked (destructive), and once (embed) it stopped searching before finding the ticket's specification.

Table 6: opencode on task set v1, 613 tools (two repeats per task). Pass: runs passed on the 25 tasks that need a catalog tool. Largest prompt: median over those runs. Cost: mean LLM cost per run over all 33 tasks, excluding the selector (LLM router: \$0.0011/\$0.0031 per run; DM: \$0.0003/\$0.0010). Bold: best pass rate and smallest largest prompt among conditions with catalog access (*none* has no catalog and passes no tool task).

	DeepSeek V4.1 Flash			Tencent hy4		
Condition	Pass	Largest prompt	\$/run	Pass	Largest prompt	\$/run
none	0/25	9.6k	0.0110	0/25	15.4k	0.0154
native	**25/25**	181.9k	0.0722	**25/25**	188.5k	0.1039
cc	**25/25**	16.2k	0.0089	**25/25**	**32.0k**	0.0375
bm25	**25/25**	13.4k	0.0093	**25/25**	33.6k	0.0417
groups	**25/25**	29.0k	0.0179	24/25	52.7k	0.0562
embed	**25/25**	13.3k	0.0090	23/25	49.0k	0.0514
llm	**25/25**	**11.7k**	0.0076	**25/25**	32.6k	0.0419
dm	**25/25**	14.0k	0.0082	**25/25**	34.6k	0.0470




Figure 4: opencode, task set v1, 613 tools: median largest prompt on the 25 tool tasks and mean cost per run, by condition and LLM.

Search removes most of the context. Loading every definition made the largest prompt about 182–189k tokens; with ranked search it was 12–16k (DeepSeek) and 32–35k (hy4), and 29–53k with groups, whose activation loads a whole server: 5–16× less. The cost per run fell from \$0.072 to \$0.008–0.009 for DeepSeek and from \$0.104 to \$0.038–0.047 for hy4. Differences among ranked searches are within run-to-run noise.

Runs use few tools. The median catalog run used 4 distinct catalog tools in about 10 calls, almost always from one server; 23 of the 25 v1 tool tasks need only one server. Choosing the server is most of the problem, which suits the DM hierarchy but is also easy for any mechanism with a service overview; hence task set v2 and the larger catalog in the main experiment.

6 Threats to validity and lessons

Ceiling. Pass rates were at ceiling on v1 and, despite the harder v2 tasks, in the main experiment (96–100% for every ranker, including random), so we rank by tokens, which are noisy.

Simulated answers. Real services return longer, messier results, which would raise token counts and could change how agents search; empty results for unmatched reads may make absent tasks easier to recognize.

The connected-services note. Every prompt of the final run starts with the same note on connected services (§4), in all conditions. Real harnesses put a comparable statement in the system prompt, and agents not told what exists may never search (App. B). The note names categories, not brands, but may still raise search rates above those of an unprompted agent.

Approximated mechanisms. We reimplemented Claude Code's ToolSearch, Copilot's virtual tools and Goose's routers from their documentation; only Hermes's bridge is shipped code. Our cc scoring in particular is an approximation.

Query distribution and scale. Hand-written retrieval queries overstate the DM's advantage; agent-written queries are shorter and more lexical (§5.3). The live results rest on two inexpensive LLMs and one DM, and the main experiment uses a single LLM.

Packaging. opencode conditions return full definitions and route calls through `call_tool`; Hermes returns compact hits and typed calls. We therefore compare rankers only within one harness.

Power. With 114 pairs per comparison the main experiment is slightly short of the roughly 136 pairs needed to detect a 10% token difference; differences of that size may remain inconclusive.

7 Related work

Tool retrieval for large catalogs. Retrieving tools before generation is the standard answer to large catalogs [7, 23]. RAG-MCP [10] retrieves MCP tool descriptions with embeddings to reduce prompt bloat, and MCP-Zero [9] lets the agent request tools by describing what it needs, server first and tool second, the hierarchy our DM uses. Lee [12] find that selecting a tool is largely retrieval. We compare such ideas with shipped mechanisms inside unmodified agents.

MCP benchmarks. LiveMCPBench [16] evaluates agents navigating many real MCP servers, MCPMark [27] stress-tests realistic MCP use with verifiable tasks, and MCP-Atlas [5] and Toolathlon [13] score task completion with real tools. They measure end-to-end success; we fix the agent, vary only the selection mechanism, and simulate back ends so runs are reproducible and writes can be graded safely.

Vendor reports. Stacklok compared its MCP Optimizer with Anthropic's tool search tool on 2,792 tools and reported much higher selection accuracy for its hybrid retrieval [25]; Arcade tested Anthropic's tool search on about 4,000 tools [11]. Both measure selection accuracy, not task completion, and neither reports token costs per task.

Decision models. The Artificial Analysis Decision Index [4] and an analysis of it [19] compare DMs with LLMs on standalone decisions, including tool calling; we place a DM inside agents as the tool-search ranker.

8 Conclusion

A decision model can serve as a coding agent's tool selector. On real MCP tool definitions, Microsoft Decision 1 ranks tools more accurately than the lexical and embedding searches current harnesses ship and more cheaply than an LLM router, and asking for the server first takes it past its 255-option limit. In live agents, however, every search mechanism reaches ceiling pass rates, and agents' own queries narrow the ranking advantage. Inside Hermes Agent's shipped bridge, on harder tasks and a catalog with decoys, random ranking cost 57% more tokens than BM25, and Microsoft Decision 1 with a calibrated "none" option was the only ranker significantly cheaper, at about 12% fewer tokens (0.88×, 95% CI 0.78–0.98). If a similar reduction holds for other agent models, the DM would make runs 7–8% cheaper for mid-range and frontier models and slightly more expensive for the inexpensive model we measured (§5.2).

Reproducibility. We will release the tool harvester, catalog snapshots, simulator, the 71 tasks with hidden tests and reference solutions, the MCP server with all conditions, the Hermes patch, the sandbox setup, all run records, and the analysis and figure scripts.

Use of AI assistance. Claude Code, Anthropic's coding agent, helped throughout this work: it wrote the harness, catalog harvester, tasks and analysis scripts, ran the experiments, and drafted the paper, under the authors' direction. The authors chose the research questions, reviewed the code, results and text, and are responsible for the content. The session analysed in §3 is this assistant's own session. [TODO: authors: confirm or revise the AI-use statement.]

References

[1] Anthropic. Agent skills overview (Claude platform documentation). https://platform.claude.com/docs/en/agents-and-tools/agent-skills/overview, 2025. Accessed 5 November 2026.

[2] Anthropic. Tool search tool (Claude platform documentation; regex and BM25 variants). https://platform.claude.com/docs/en/agents-and-tools/tool-use/tool-search-tool, 2025. Accessed 5 November 2026.

[3] Anthropic. Claude code documentation: Scale with MCP tool search. https://code.claude.com/docs/en/mcp, 2026. Accessed 5 November 2026.

[4] Artificial Analysis. Artificial analysis decision index v1.0. https://artificialanalysis.ai/evaluations/artificial-analysis-decision-index, 2026.

[5] Chaithanya Bandi et al. MCP-Atlas: A large-scale benchmark for tool-use competency with real MCP servers. *arXiv preprint arXiv:2602.00933*, 2026.

[6] Block. goose: Tool router (vector-based) and LLM-based tool selection strategy. https://web.archive.org/web/20251031035432/https://block.github.io/goose/docs/guides/managing-tools/tool-router/, 2025. Archived 31 October 2025 (preview feature); not listed in the current documentation at goose-docs.ai. Source: https://github.com/block/goose.

[7] Huamin Chen, Xunzhuo Liu, Junchen Jiang, Bowei He, and Xue Liu. Outcome-aware tool selection for semantic routers: Latency-constrained learning without LLM inference. *arXiv preprint arXiv:2603.13426*, 2026.

[8] DeepSeek. DeepSeek V4.1 Flash. Model card, via OpenRouter as `deepseek/deepseek-v4.1-flash-1017`: https://openrouter.ai/deepseek/deepseek-v4.1-flash-1017, 2026.

[9] Xiang Fei, Xiawu Zheng, and Hao Feng. MCP-Zero: Active tool discovery for autonomous LLM agents. *arXiv preprint arXiv:2506.01056*, 2025.

[10] Tiantian Gan and Qiyao Sun. RAG-MCP: Mitigating prompt bloat in LLM tool selection via retrieval-augmented generation. *arXiv preprint arXiv:2505.03275*, 2025.

[11] Eric Gustin. Anthropic tool search test: 4,000 tools, 60% success. https://www.arcade.dev/blog/anthropic-tool-search-4000-tools-test/, December 2025. Arcade.dev blog, 3 December 2025.

[12] Janghoon Lee. Selection is retrieval, abstention is not: On-device tool routing over 70 Korean-English actions. *arXiv preprint arXiv:2609.18672*, 2026.

[13] Junlong Li et al. The tool decathlon: Benchmarking language agents for diverse, realistic, and long-horizon task execution. *arXiv preprint arXiv:2510.25726*, 2025.

[14] Microsoft. Use tools with agents (Visual Studio Code documentation: 128-tool limit and virtual tools). https://code.visualstudio.com/docs/copilot/agents/agent-tools, 2026. Accessed 5 November 2026; see also the GitHub blog post "How we're making GitHub Copilot smarter with fewer tools".

[15] Microsoft. Not every decision needs an LLM: Getting started with Microsoft-Decision-1. https://techcommunity.microsoft.com/blog/educatordeveloperblog/not-every-decision-needs-an-llm-getting-started-with-microsoft-decision-1/4563468, October 2026. Microsoft Community Hub, Educator Developer Blog.

[16] Guozhao Mo, Wenliang Zhong, Jiawei Chen, Qianhao Yuan, Xuanang Chen, Yaojie Lu, et al. LiveMCPBench: Can agents navigate an ocean of MCP tools? *arXiv preprint arXiv:2508.01780*, 2025.

[17] Model Context Protocol. Model context protocol specification. https://modelcontextprotocol.io/specification/2025-06-18, 2025.

[18] Nous Research. Hermes agent. https://github.com/NousResearch/hermes-agent, version 0.19.0 (PyPI), 2026.

[19] Randal S. Olson. When to use a decision model instead of an LLM. Blog post, 15 October 2026, https://www.randalolson.com/2026/10/14/when-to-use-a-decision-model-instead-of-an-llm/, 2026.

[20] OpenAI. Codex CLI: open-source coding agent; MCP tool search with BM25 in `codex-rs/core/src/tools/handlers/tool_search.rs`. https://github.com/openai/codex, 2026. Source checked 5 November 2026.

[21] opencode contributors. opencode: an open-source coding agent. https://opencode.ai, version 1.19.4, 2026.

[22] OpenRouter. Decisions API reference. https://openrouter.ai/docs/api/api-reference/alphadecisions/submit-a-decisions-request, 2026.

[23] Yujia Qin et al. ToolLLM: Facilitating large language models to master 16000+ real-world APIs. *arXiv preprint arXiv:2307.16789*, 2023.

[24] Stephen Robertson and Hugo Zaragoza. The probabilistic relevance framework: BM25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4):333–389, 2009.

[25] Stacklok. Stacklok's MCP optimizer vs Anthropic's tool search tool: A head-to-head comparison. https://stacklok.com/blog/stackloks-mcp-optimizer-vs-anthropics-tool-search-tool-a-head-to-head-comparison/, 2025.

[26] TypeSafe AI. Jev 1.14 decision model. https://typesafe.ai; served via OpenRouter as `typesafe/jev-1.14`, 2026.

[27] Zijian Wu, Xiangyan Liu, Xinyuan Zhang, Lingjun Chen, Fanqing Meng, Lingxiao Du, et al. MCPMark: A benchmark for stress-testing realistic and comprehensive MCP use. *arXiv preprint arXiv:2509.24002*, 2025.

A Harness hardening

The setup of §4 is the result of fixes made during development; runs made before them are not reported. In order:

- Agents run as an unprivileged user with an empty environment and no credentials; experiment files are readable only by root and the API key is held by a local proxy that admits only the experiment models (harness-level permissions alone let an agent read hidden tests through absolute paths).
- Each Hermes run gets its own mount namespace: a private work directory, home directory and `/tmp`, so runs cannot see each other's files or leftovers.
- The MCP server accepts only requests carrying a per-run token that the agent's shell cannot read, so the shell cannot list the catalog or query the ranker directly.
- Hermes's `approvals.deny` list blocks probing commands (`curl`, `wget`, `ps`, `ss`, `netstat`, `nmap`, `lsof`, `/proc`, `localhost`, `find /`).
- Rankers are compared inside Hermes's own bridge (compact hits, `tool_describe`, typed calls) rather than through a separate MCP-side search with a generic `call_tool`, so that only the ranking differs.
- The provider and sampling are pinned (DeepInfra fp8, temperature 0.6, seed 7) and the conditions of each (task, repeat) slot are queued back to back.

B The earlier synthetic pilot

An earlier version of this study used a fictional company's catalog of 100 and 300 synthetic tools (about 610 tokens each) with opencode, and compared loading all tools, a DM-backed `find_tool`/`call_tool` pair with and without a service list, and tools preselected from the task prompt. It showed the same pattern as the real-catalog runs: search matched native loading at a fraction of the context, and an agent without a list of the services sometimes never searched. We replaced it because its templated descriptions were more uniform and easier to rank than real ones, its tasks

were at ceiling, and its tools resembled no real server, so it could not compare the mechanisms that harnesses ship. Its code and results remain in the repository.

C Task set v2

Table 7: Task set v2 (38 tasks). Prompts are shortened to their first sentence and shown without the escape clause. Services: the servers of the needed tools, in order; $+w$: number of required writes; $\star$: new in v2.

Category	Task	Prompt (first sentence)	Services
control	`c_chunk`	chunk in batching/chunk.py drops the last partial chunk.	–
control	`c_dedupe`	dedupe in collections_util/dedupe.py loses the original order.	–
control	`c_duration`	parse_duration in timeutil/duration.py only understands hours.	–
control	`c_leap`	is_leap in calendar_util/leap.py is wrong for some years.	–
single	`confluence_limits`	Our public API rate limits changed.	atlassian
single	`eks_importer` $\star$	The data team's nightly batch-importer job has failed three nights in a row.	aws_eks
single	`gh_ci_fail`	Pull request #214 in acme/payments can't be merged because a check is red.	github $+1w$
single	`gh_codesearch`	SUPPORTED_CURRENCIES in shop/currencies.py has drifted from the company-wide canonical list, which lives in another repository.	github
single	`gh_dependabot`	Security says acme/payments has dependencies with known vulnerabilities.	github
single	`gh_issue`	Please implement acme/payments#301.	github
single	`gh_open_pr`	Pagination in acme/catalog is broken (see #57).	github $+2w$
single	`gh_release`	We are behind on the ledger API.	github
single	`gh_review`	There is reviewer feedback waiting on pull request #88 in acme/ledger.	github $+1w$
single	`grafana_incident`	We are in the middle of an incident about checkout timeouts and the responders agreed on a mitigation.	grafana $+1w$
single	`jira_impl`	Pick up PAY-412: implement it, then move it to review.	atlassian $+1w$
single	`k8s_crashloop`	ledger-worker keeps restarting in production (namespace ledger) since the last config change.	kubernetes
single	`k8s_oom`	report-builder (namespace reports) keeps dying in production.	kubernetes
single	`linear_bug`	Fix ENG-77 and move it to In Review.	linear $+1w$
single	`loki_errors`	Customers stopped getting shipping e-mails at around 06:00 UTC today; the notifier service is the suspect.	grafana
single	`mongo_shape`	The nightly export has started crashing on recent orders.	mongodb
single	`notion_runbook`	We are rotating the webhook signing keys.	notion
single	`oncall_contact`	Set ESCALATION_CONTACT in ops/escalation.py to the e-mail address of whoever is on call for the payments team right now.	grafana

Category	Task	Prompt (first sentence)	Services
single	`pg_migration`	Add migrations/0042_payments_merchant_idx.sql with an index named payments_merchant_created_idx for looking up a merchant's payments by creation time.	postgres
single	`prom_threshold`	Set SLOW_REQUEST_MS in alerts/config.py to twice the checkout service's current p99 request latency, in milliseconds.	grafana
single	`sentry_events`	Since this morning's deploy some clients get HTTP 500 from POST /refunds.	sentry
single	`sentry_fix`	The noisiest production error of payments-api right now needs to go.	sentry +1w
single	`slack_decision`	The payments team agreed on a new webhook retry policy in a chat discussion.	slack +1w
multi	`cw_reports` ⋆	The legacy reports API has been answering 502 since yesterday evening.	aws_cloudwatch, slack +1w
multi	`gl_pipeline` ⋆	The main-branch pipeline of billing-legacy is red.	gitlab +1w
multi	`linear_notion_pr` ⋆	Do ENG-91 the way our API guidelines say, and open a pull request for it from a branch named eng-91 against main in acme/public-api.	linear, notion, github +1w
multi	`multi_alert`	Something is paging for the checkout service.	grafana, slack +1w
multi	`multi_jira_conf`	Implement PAY-530 as its design document specifies, then leave a one-line summary on the ticket.	atlassian +1w
multi	`multi_sentry_gh`	A recent change to ledger-worker introduced a reconciliation bug that shows up as a production error.	sentry, github +1w
multi	`promo_sentry_jira` ⋆	Android users report they can't apply promo codes.	sentry, atlassian +1w
absent	`absent_jira`	Implement PAY-999 in payments/limits.py.	–
absent	`absent_release`	Pin SDK_VERSION in sdk/version.py to the newest release of acme/ghost-sdk (without the leading v).	–
absent	`absent_sentry`	The billing-cron error someone mentioned in standup needs fixing in billing/cron.py.	–
absent	`absent_slack`	Set CACHE_TTL_S in cache/config.py to the value the platform team agreed on.	–