

Project Title:

Network Port Scanning & Security Analysis using Nmap

PROJECT OVERVIEW

Objective

Identify open ports and services on a target system and analyze potential security risks.


Tools

- Kali Linux
- Nmap
- VirtualBox
- Target: Metasploitable2 **OR** Your own test VM

STEP 1: Setup Environment

Set **both machines** to:


Network → Host-Only Adapter



STEP 2: Find Target IP

Command ifconfig:

On Kali Linux



```
(kali@kali)~$ ifconfig
br-6d7c97741749: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
    inet 172.18.0.1 netmask 255.255.0.0 broadcast 172.18.255.255
    ether 02:42:12:be:57:1a txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0


docker0: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
    inet 172.17.0.1 netmask 255.255.0.0 broadcast 172.17.255.255
    ether 02:42:33:4e:02:3b txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

eth0: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
    ether 00:0c:29:e7:70:55 txqueuelen 1000 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0-10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 8 bytes 480 (480.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 8 bytes 480 (480.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

(kali@kali)~$
```

On Metasploitable2:



```
Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.


To access official Ubuntu documentation, please visit:
http://help.ubuntu.com/
No mail.
msfadmin@metasploitable:~$ ifconfig
eth0      Link encap:Ethernet HWaddr 00:0c:29:64:29:a7
          UP BROADCAST MULTICAST MTU:1500 Metric:1
          RX packets:0 errors:0 dropped:0 overruns:0 frame:0
          TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:0 (0.0 B) TX bytes:0 (0.0 B)
          Interrupt:17 Base address:0x2000

lo        Link encap:Local Loopback
          inet addr:127.0.0.1 Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING MTU:16436 Metric:1
          RX packets:136 errors:0 dropped:0 overruns:0 frame:0
          TX packets:136 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:40201 (39.2 KB) TX bytes:40201 (39.2 KB)

msfadmin@metasploitable:~$
```

STEP 3: Basic Nmap Scan

On Kali:



```
(kali@kali)~$ nmap 127.0.0.1
Starting Nmap 7.94SVN ( https://nmap.org ) at 2026-01-13 08:39 EST
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00034s latency).
All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.
Not shown: 1000 closed tcp ports (conn-refused)

Nmap done: 1 IP address (1 host up) scanned in 0.17 seconds
```

On Metasploitable2:

```
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
953/tcp   open  rndc
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
3632/tcp  open  distccd
5432/tcp  open  postgres
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
8009/tcp  open  ajp13

Nmap done: 1 IP address (1 host up) scanned in 0.153 seconds
msfadmin@metasploitable:~$
```

STEP 4: Service Detection Scan

nmap -sV 127.0.0.1

On Kali:

```
(kali㉿kali)-[~]
$ nmap -sV 127.0.0.1
Starting Nmap 7.94SVN ( https://nmap.org ) at 2026-01-13 08:39 EST
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00031s latency).
All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.
Not shown: 1000 closed tcp ports (conn-refused)

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 0.56 seconds
```

On Metasploitable2:

```
Nmap done: 1 IP address (1 host up) scanned in 0.153 seconds
msfadmin@metasploitable:~$ nmap -sU 127.0.0.1

Starting Nmap 4.53 ( http://insecure.org ) at 2026-01-13 08:41 EST
Stats: 0:00:06 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 21.74% done; ETC: 08:41 (0:00:21 remaining)
Stats: 0:00:06 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 60.87% done; ETC: 08:41 (0:00:03 remaining)
Stats: 0:00:07 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 65.22% done; ETC: 08:41 (0:00:03 remaining)
Stats: 0:00:08 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 65.22% done; ETC: 08:41 (0:00:04 remaining)

[!]+ Stopped nmap -sU 127.0.0.1
msfadmin@metasploitable:~$ _
```

STEP 5: Save Scan Results

nmap -sV 127.0.0.1 -oN nmap_results.txt

```
(kali㉿kali)-[~]
└─$ nmap -sV 127.0.0.1 -oN nmap_results.txt
Starting Nmap 7.94SVN ( https://nmap.org ) at 2026-01-13 08:42 EST
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00076s latency).
All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.
Not shown: 1000 closed tcp ports (conn-refused)

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 0.51 seconds
```