

Aegis AI — A Unified Cybersecurity Platform for Real-Time Threat Detection

Submitted by

Azka Shaukat (Fa22/BSSE/190 C)

Laiba Naeem (Fa22/BSSE/078 C)

Session

(Fa 2022 - 2026)

Supervised by

Ma'am Kiran Amjad



Department of Software Engineering
Lahore Garrison University
Lahore

Aegis AI — A Unified Cybersecurity Platform for Real-Time Threat Detection

A project submitted to the
Department of Software Engineering

In
Partial Fulfillment of the Requirements for the
Bachelor's Degree in Software Engineering

By
Azka Shaukat
Laiba Naeem

Supervisor

Kiran Amjad

Designation
Department of Software Engineering

Chairperson

Dr. Omer Irshad

Head of Department
Department of Software Engineering

COPYRIGHTS

This is to certify that the project titled "Aegis AI — A WhatsApp and Web-Based Cybersecurity Platform for Real-Time Threat Detection" is the genuine work carried out by Azka Shaukat, student of BSSE of the Software Engineering Department, Lahore Garrison University, Lahore. During the academic year 2025-2026, in partial fulfilment of the requirements for the award of the degree of Bachelor of Science in Software Engineering, and that the project has not formed the basis for the award previously of any other degree, diploma, fellowship, or any other similar title.

Student Name Azka Shaukat

Student Name Laiba Naeem Rana

DECLARATION

This is to declare that the project entitled "Aegis AI — A WhatsApp and Web-Based Cybersecurity Platform for Real-Time Threat Detection" is an original work done by the undersigned, in partial fulfilment of the requirements for the degree "Bachelor of Science in Software Engineering" at the Software Engineering Department, Lahore Garrison University, Lahore.

All analysis, design, and system development have been accomplished by the undersigned. This project has not been submitted to any other college or university.

Student Name Azka Shaukat

Student Name Laiba Naeem Rana

ACKNOWLEDGEMENTS

First and foremost, I would like to express my sincere gratitude to my supervisor, Ms. Kiran Amjad, whose guidance, patience, and technical insight were invaluable throughout the course of this project. Her feedback consistently pushed me to think more critically about design decisions, and her encouragement during difficult phases kept the project on track.

I am grateful to the Department of Software Engineering at Lahore Garrison University for providing the academic environment and resources that made this project possible.

I would also like to acknowledge the open-source community behind FastAPI, React, Docker, PyTorch, Ollama, and the many libraries used across both the WhatsApp and web interfaces of this system.

Finally, I owe everything to my family, whose unwavering support through long nights and difficult weeks made completing this degree possible.

DEDICATION

To my parents,
whose sacrifices made every page of this possible.

And to every Pakistani internet user
who has ever been deceived by a phishing link or a scam message —
this was built for you.

Table of Contents

Table of Contents

Chapter 1	7
1. Introduction.....	7
1.1 Background	7
1.2 Project Overview	7
1.3 Motivation.....	7
1.4 Objectives.....	8
1.5 Scope.....	8
1.6 Report Organization	8
Chapter 2	10
2. Problem Definition	10
2.1 Cybersecurity Threats Facing Pakistani Users.....	10
2.3 Research Questions.....	11
Chapter 3	12
3. Software Requirement Specification and Literature Survey	12
3.1 Functional Requirements	12
3.2 Non-Functional Requirements	26
3.3 Literature Survey	29
Chapter 4	32
4. Methodology	32
4.1 Development Approach	32
4.2 Development Process.....	32
4.3 Technology Selection	32
Chapter 5	35
5. System Architecture / Initial Design	35
5.1 System Architecture	35
5.2 Detailed System Design.....	55
Chapter 6	65
6. Implementation and Testing	65
6.1 Implementation.....	65
6.2 Deployment Environments	67
6.3 Software Deployment	71
6.4 Software Quality.....	71
6.5 Testing Strategy.....	71
6.6 Test Cases	72
Chapter 7	90

7. Results and Discussion	90
7.1 Automated Test Results	90
7.2 Performance Results	90
7.3 Model Performance	91
7.5 Discussion	92
Chapter 8	94
8. Conclusion and Future Work	94
8.1 Conclusion	94
8.2 Future Work	94
References	97

List of Figures

Figure 2: Usecase Diagram	35
Figure 3: Architecture Diagram.....	36
Figure 4: Data Flow (level 0) Diagram	37
Figure 5: Orchestra activity Diagram.....	41
Figure 6: Link state machine Diagram.....	42
Figure 7: Link Sequence Diagram	43
Figure 8: Link Activity Diagram	44
Figure 9: QR scanner activity Diagram.....	45
Figure 10: QR sequence Diagram.....	46
Figure 11: Credential Acitivity Diagram	47
Figure 12: Credential sequence Diagram	48
Figure 13: Profile State Machine Diagram.....	49
Figure 14: Profile Sequence Diagram	50
Figure 15: Deepfake Sequence Diagram.....	52
Figure 16: Deepfake message processing pipeline	53
Figure 17: Deepfake activity Diagram.....	54
Figure 18: Orchestra State Machine Diagram	61
Figure 19: Network security Diagram.....	62
Figure 20: Deploment Diagram	63
Figure 21:Class Diagram.....	64

List of Tbles

Table 1: List of Abbreviations-----	5
Table 2:FR -Orchestra Service -----	12
Table 3:FR-Link Analyzer Service -----	15
Table 4:FR-QR Scanner Service -----	17
Table 5:FR- Credential Analyzer Service-----	18
Table 6:FR- Profile Analyzer Service -----	20
Table 7:FR- Deepfake Detector Service -----	22
Table 8:FR-Web Backend Service-----	23
Table 9:FR- React Frontend Framework-----	25
Table 10:NFR- Performance Requirements -----	26
Table 11:NFR- Security Requirements -----	27
Table 12: NFR- Privacy Requirements-----	28
Table 13: NFR- Usability Requirements-----	29
Table 14: Technologies Used-----	32
Table 15: Service ports -----	55
Table 16: Service Endpoints -----	58
Table 17: Eenv variables of orchestrae-----	67
Table 18: env variable of link analyzer -----	68
Table 19: env variables of QR scanner-----	68
Table 20: env variables of credential Analyzer -----	69
Table 21env. variables of Profile anlyzer-----	69
Table 22: env variables of deepfake detector -----	70
Table 23env variables of web -----	70
Table 24: Test Cases Greetings and Help-----	72
Table 25: test Caes Link Scanner -----	73
Table 26: Test Cases QR Scanner-----	74
Table 27: test Cases Email Credential-----	75
Table 28: Test cases Phone credential-----	76
Table 29: Test Cases Password-----	76
Table 30: Test cases Other Credentials -----	77
Table 31: Testcases /check Menu -----	79
Table 32: Testcases Smishing -----	80
Table 33:Testcases Profile Analyzer -----	81
Table 34: Testcases Deepfake Detector-----	82
Table 35: Testcases Cyber Q&A-----	83
Table 36: Testcases Wrong-Entity Handling-----	83
Table 37: Testcases Session Management-----	84
Table 38: Testcases Urdu -----	84
Table 39Testcases Edge cases -----	85
Table 40: Testcases Responce format validation -----	87
Table 41: Testcases Parallel Execution Verification -----	88
Table 42: Automated test results -----	90
Table 43: Performance results -----	90
Table 44: Deepfake Detector Model Metrics-----	91
Table 45: Confidence Enhancement Validation -----	91

List of Abbreviations

Table 1: List of Abbreviations

Abbreviation	Full Form
AI	Artificial Intelligence
API	Application Programming Interface
AUC	Area Under the Curve
BSSE	Bachelor of Science in Software Engineering
CIA	Confidentiality, Integrity, Availability
CNIC	Computerized National Identity Card
CNN	Convolutional Neural Network
DFD	Data Flow Diagram
DNS	Domain Name System
EfficientNet	Efficient Neural Network (Google)
EXIF	Exchangeable Image File Format
FBR	Federal Board of Revenue
FFT	Fast Fourier Transform
FIA	Federal Investigation Agency
GDPR	General Data Protection Regulation
GradCAM	Gradient-weighted Class Activation Mapping
GSB	Google Safe Browsing
HIBP	Have I Been Pwned
HMAC	Hash-based Message Authentication Code
HTTP	Hypertext Transfer Protocol
IBAN	International Bank Account Number
ICAO	International Civil Aviation Organization
IPQS	IPQualityScore
JWT	JSON Web Token
JSON	JavaScript Object Notation
LLM	Large Language Model
ML	Machine Learning
MRZ	Machine-Readable Zone
NADRA	National Database and Registration Authority
NLP	Natural Language Processing
OSINT	Open Source Intelligence
OTP	One-Time Password
REST	Representational State Transfer
SHA	Secure Hash Algorithm
SIM	Subscriber Identity Module
SMS	Short Message Service
SRM	Steganalysis Rich Model
SSL	Secure Sockets Layer
TLD	Top-Level Domain
TTL	Time To Live
URL	Uniform Resource Locator
ViT	Vision Transformer
WHOIS	Domain Registration Query Protocol
XSS	Cross-Site Scripting

Abstract

Aegis AI is a two-channel cybersecurity system developed as a Final Year Project at Lahore Garrison University. This project addresses the growing threat of internet fraud, phishing, fake social media accounts, information breaches, QR code attacks, and deepfake manipulation that Pakistani internet users encounter daily. Current security solutions are fragmented, hard to use, and have limited understanding of specific threats in Pakistan, such as CNIC identity fraud, scams targeting JazzCash and Easypaisa, and impersonation attacks related to NADRA.

The system provides a threat analysis of professional quality in two channels: a Chatbot on WhatsApp, which can be used by any mobile device user without installation, and a complete-fledged web-based program with user accounts, real-time WebSocket connectivity, 30-day scan history, and the ability to upload files. Both channels follow the same analysis pipeline, which consists of six of its own independently deployed microservices: a Link Analyzer (11-layer URL threat detection, uses VirusTotal 94 engines and a Random Forest classifier), a QR Scanner (physical tamper-detecting, steganography, and payload-threat identifying), a Credential Analyzer (cryptographic validation The web backend on Port 8007 is a second orchestration layer leaving the React frontend connected to the same analysis services via JWT-authenticated REST endpoints and a WebSocket streaming interface.

All services are containerized with Docker. Privacy is one of the key design factors. Raw credentials are never stored. Passwords are verified using HIBP k-anonymity. All session information is deleted within 30 minutes or upon user request. The test framework has been used to evaluate over 400 test cases in 17 categories, including greetings, link scanning, QR scanning, ten types of credentials, smishing detection, profile analysis, deep fake detection, handling wrong entities, disambiguation flows, session management, Urdu/Roman Urdu support, and edge cases. Aegis AI shows how a smart and practical approach to cybersecurity can really make a difference. By using a microservice-based design, running AI locally instead of relying completely on the cloud, and combining it with well-integrated threat intelligence, it creates a system that is both efficient and privacy-friendly.

Chapter 1

1. Introduction

1.1 Background

Internet has engulfed the normal life of Pakistan, where banking, trade, communication, and education systems have opened up a new chapter. This increase in online activity is followed by an explosion in cybercrime. Federal Investigation Agency, Cyber Crime Wing receives tens of thousands of cases yearly about phishing, identity theft, SMS scams, and harassment in the Internet space. Normal individuals (who have never received any formal advice on cybersecurity) are often hit by malicious links, faked WhatsApp messages, fake profiles on social networking sites, and AI-based fake news.

It is not the scarcity of security measures but their unavailability to end-users that make it complicated to counteract online attacks. Tech experts are threatened using techniques such as VirusTotal, MXToolBox, and Shodan. They require knowledge of web browsers, website account management, and domain names that many non-tech individuals do not know how to operate. For instance, when someone receives a suspicious link from a fake banking account in the form of an urgent OTP message, there is no way out.

1.2 Project Overview

Aegis AI is a cybersecurity software solution that does everything for you. It has six analysis microservices that work on their two ways for you to interact with it. The first way is a WhatsApp chatbot called Orchestra. You can send messages to Orchestra from WhatsApp without having to install anything. The other way is a website made with React. This website has a lot of features, such as accounts, for users a history of all the scans that have been done a stream of what is happening and the ability to upload files. You can also use this website to look at images and videos. Both the WhatsApp chatbot and the website use the Aegis AI analysis services. These Aegis AI services include the Link Analyzer, the QR Scanner, the Credential Analyzer, the Profile Analyzer and the DeepFake Detector. Aegis AI uses all these services to keep you safe.

1.3 Motivation

These considerations were taken into account when conducting the project. Firstly, WhatsApp penetration among applications in Pakistan is higher on mobile than all other applications. At the same time, web applications written in React can run in any web browser. Thus, ensuring

cybersecurity using both options does not require installation of any security application at all. Secondly, there are certain features of the Pakistani cybercriminals' activity such as CNIC fraud, JazzCash and Easypaisa smishing, and impersonation on NADRA, which cannot be detected by tools developed for other regions. Thirdly, a microservices architecture enables development, testing, and updates of each detection domain individually.

1.4 Objectives

Objectives of the project are:

1. The development and deployment of a WhatsApp-based Cybersecurity Assistant which requires no installation, catering to non-tech Pakistani audience.
2. The development of a React webpage that would offer user accounts, scanning history, the WebSocket streaming and file uploads all in the same analysis pipeline.
3. The development of a URL threat analysis system which consists of eleven different detection layers and Random Forest classification mechanism.
4. Invention of online security scanner that will be able to identify phishing attacks, physical attack (tampering), steganography in message and embedded signature in QR code.
5. Credential Risk Analyzer that includes ten credential types, cryptographic validation, queries to breach database and Pakistan specific checks.
6. The creation of Social Media Profile Analyzer which helps find out fake accounts, bots, scamming and impersonation profiles using 19 analysis techniques.
7. The creation of a Deepfake Detection System that has six models as an ensemble and the algorithm to make the model more confident.
8. SHA-256 hashing and HIBP k-anonymization, GDPR compliant data processing and zero storage of raw credentials has been implemented to guarantee user privacy.

1.5 Scope

Contents that users have like links, images, texts and credentials will be analyzed away by the software. The software will also generate reports on risks and suggestions. We do not need to check users messages because we only use information. We will collect data from social media. For now we store files on disks using our website app. As our application grows we will need to use object storage.

1.6 Report Organization

Problem definition is elaborated in chapter 2. The Software Requirement Specification, together with requirements tables by each service and literature review, is provided in chapter 3. The development process used is explained in chapter 4. System architecture design, along with the design of individual components for each of the services and the web layer, is provided in chapter 5. Chapter 6 is devoted to the implementation environment and test cases. The findings are presented in chapter 7. Chapter 8 gives conclusions.

2. Problem Definition

2.1 Cybersecurity Threats Facing Pakistani Users

2.1.1 Phishing attacks and website-based threats

The attackers build imitations of legitimate websites for HBL, UBL, Meezan Bank, Jazz, Telenor, NADRA, FBR, and Benazir Income Support Program where credentials are collected. These imitations are hosted in domains that have been registered recently, where the cheapest top-level domains (.tk, .ml, .xyz) are utilized. The registration takes place shortly before the attack; hence, the recipient of the message with a link in WhatsApp or SMS does not have enough time to verify the domain before clicking on it.

2.1.2 Attacks using QR codes

QR codes are widely used for executing payments within JazzCash, Easypaisa, and SadaPay accounts, completing verification processes, and making utility payments. Because QR codes are anonymous and impossible to interpret without applying special software, they become a great choice for launching attacks. The attacker can replace the genuine QR code with a fake one, leading to phishing sites or cryptocurrency transactions or connecting the device to the WiFi network controlled by the attacker.

2.1.3 Credential harvesting and data breaches

Millions of emails, phone numbers, and passwords linked with Pakistan-based users can be found in the international databases reporting about data breaches. Certain formats such as CNICs, Easypaisa/JazzCash numbers.

2.1.5 Phishing (Smishing) SMS and WhatsApp.

The fake messages masquerading as JazzCash, Easypaisa, Meezan Bank, HBL, and mobile operators dupes the users into providing OTPs, clicking links, or CNICs. Value of prizes in terms of rupees. 50,000 or Rs. 1,00,000, fake account suspensions, and urgent CNIC requests have patterns which can be identified with automated analysis.

2.1.6 Deepfake Manipulation

Targeted extortion, impersonation and financial fraud involve the use of AI-generated fake images and videos. A deepfake image of the face of an individual on a scandalous content, or a video of a government official giving untrue assertions can have dire and immediate effects. There are practically no reliable, easy-to-use detection tools designed to be used by general users.

2.2 Restrictions of Current Tools

Current tools like VirusTotal, URLScan.io, and MXToolbox are also web based and require a web browser, creation of an account and technical knowledge to use the results. There is no known tool that covers all the categories of threats in a single interface. They do not fit in the Pakistani context - no CNIC validation, no Easypaisa/JazzCash smishing, no NADRA impersonation detection, no Urdu language support. Most services involve sending raw credentials to third party cloud computers which only generate more exposure and not less.

2.3 Research Questions

1. Can a multi-domain cybersecurity analysis platform be delivered through both a WhatsApp interface and a web interface, sharing the same analysis pipeline, without technical knowledge from users?
2. How can Pakistan-specific threat patterns be incorporated into automated detection algorithms for local relevance?
3. Can a confidence enhancement algorithm for deepfake detection reliably produce ensemble predictions exceeding the most confident individual model?
4. How can credential analysis be performed across ten credential types without storing raw sensitive data, while maintaining sub-200ms response times for cached queries?

3. Software Requirement Specification and Literature Survey

3.1 Functional Requirements

The requirements for the system are organized by service. Each of the requirements for the system uses the “The system shall” formulation. The system has priority levels for the requirements for the system. These priority levels for the requirements for the system are: Critical. This is something that must be implemented for the system to function High. This is a core feature that is required for the project to be complete Medium. This is important but there is a workaround if it is not done Low. This is something that's nice to have or can be done in the future to get the system ready, for something new.

3.1.1 Functional Requirements — Orchestra Service (WhatsApp Bot, Port 8006)

Table 2: FR - Orchestra Service

ID	Requirement Statement	Priority
ORC-FR-01	The system shall receive incoming WhatsApp messages as HTTP POST webhook events from the Meta WhatsApp Business API.	Critical
ORC-FR-02	The system shall verify the authenticity of every incoming webhook POST request using HMAC-SHA256 signature validation against the X-Hub-Signature-256 header, rejecting any request that fails verification.	Critical
ORC-FR-03	The system shall perform Redis-based deduplication on incoming message IDs with a 120-second TTL, discarding any duplicate message silently.	Critical
ORC-FR-04	The system shall extract all recognized entity types from every incoming message simultaneously: URLs, email addresses, passwords, phone numbers, CNICs (both dashed and 13-digit formats), payment cards, IBANs, cryptocurrency wallet addresses, WIF private keys, API keys, social @handles, and social media URLs.	Critical
ORC-FR-05	The system shall classify every incoming message through a 14-priority intent ladder (P1-P14) and route it to the appropriate handler or microservice.	Critical

ORC-FR-06	The system shall handle explicit command routing at P1 for /scan, /qr, /profile, /check, /generate, /history, /clear, /language, /help, and /cancel.	Critical
ORC-FR-07	The system shall route messages containing profile-phrase keywords combined with a username entity (P2) to the Profile Analyzer.	High
ORC-FR-08	The system shall route messages containing link-phrase keywords combined with a URL entity (P3) directly to the Link Analyzer without prompting.	Critical
ORC-FR-09	The system shall prompt the user for the specific entity when credential-phrase keywords are detected without an accompanying entity (P4).	High
ORC-FR-10	The system shall automatically route image attachments to the QR Scanner and video attachments to the Deepfake Detector (P5), without requiring the user to type a command.	High
ORC-FR-11	The system shall route standalone @handle entities (P8) to both the Profile Analyzer and Credential Analyzer in parallel, combining results into a unified Username Intelligence verdict.	High
ORC-FR-12	The system shall route social media URLs (P9) to both the Link Analyzer and the Profile Analyzer, presenting a profile analysis offer after the link scan result.	High
ORC-FR-13	The system shall route bare domain entities (P10) to a three-button disambiguation menu offering Link Safety Check, Profile Analysis, and Run All.	High
ORC-FR-14	The system shall route detected credential entities (P11) to the Credential Analyzer, presenting a three-button disambiguation menu (Leak Monitor / Scam Check / Both) for email and phone inputs.	Critical
ORC-FR-15	The system shall route plain usernames (P13) to a three-button disambiguation menu offering Password Check, Profile Analysis, and Run Both — mapping Run Both to Credential Analyzer plus Profile Analyzer, not to Link Analyzer plus Profile Analyzer.	Critical
ORC-FR-16	The system shall route greetings, off-topic messages, and gibberish (P14) to contextual help menus or Ollama-generated redirect responses.	Medium

ORC-FR-17	The system shall respond in Urdu or Roman Urdu when the user's message is in those languages, using Google Gemini 1.5 Flash for classification and falling back to Ollama when the Gemini API key is not configured.	High
ORC-FR-18	The system shall detect SMS and WhatsApp phishing (smishing) through a multi-stage pipeline: keyword scoring → Ollama AI classification → sub-analysis of embedded phone numbers and URLs.	Critical
ORC-FR-19	The system shall compute a unified Username Intelligence score as: Combined Score = Profile Score × 0.55 + Credential Score × 0.45, and assign one of six verdict labels: REAL, SUSPICIOUS, FAKE, SCAMMER, BREACHED, or IMPERSONATOR.	High
ORC-FR-20	The system shall generate plain-English explanations for all scan results using Ollama (Llama 3.2), with context drawn from the last 20 turns of conversation history. Explanations must be unique on repeated scans.	Critical
ORC-FR-21	The system shall store per-user conversation sessions in Redis with a 30-minute TTL, containing: ConvState enum, last scan result, scan log, disambiguation options, language preference, and conversation history.	Critical
ORC-FR-22	The system shall maintain a 30-day long-term scan memory using SHA-256 hashes only; raw values must never be stored.	High
ORC-FR-23	The system shall support follow-up questions after any scan result, including: rescan, explain result, action advice, flag explanation, and confidence explanation.	High
ORC-FR-24	The system shall present interactive button menus for disambiguation with a maximum of three buttons per the Meta WhatsApp Business API limit.	Critical
ORC-FR-25	The system shall support the /history command returning the user's session scan log, and the /clear command deleting all user session data from Redis (GDPR compliance).	High
ORC-FR-26	The system shall detect and block jailbreak and prompt injection attempts through pattern matching, returning a firm refusal without explanation.	Critical

ORC-FR-27	The system shall respond correctly to wrong-entity inputs (e.g., "check this email https://google.com") with a message identifying what was sent and what was expected, such as "You sent a link, not an email."	High
ORC-FR-28	The system shall provide a Cyber Q&A function responding to general cybersecurity questions (phishing, smishing, ransomware, 2FA, VPN, SIM swap, and others) using Ollama-generated answers that vary on repeated questions.	Medium
ORC-FR-29	The system shall expose a POST /test/message endpoint for automated integration testing that accepts {phone, text} and returns the bot's response without requiring a live WhatsApp connection.	High

3.1.2 Functional Requirements — Link Analyzer Service (Port 8000)

Table 3:FR-Link Analyzer Service

ID	Requirement Statement	Priority
LNK-FR-01	The system shall analyze any submitted URL across 11 independent detection layers, combining results into a final risk score and risk level.	Critical
LNK-FR-02	The system shall perform URL heuristics analysis checking for: suspicious TLDs (.tk, .ml, .xyz, and 28 others), typosquatting of known brand names, Shannon entropy above 3.5, phishing keyword presence in URL, HTTP-only protocol, raw IP address as hostname, @ symbol in URL, URL length exceeding 100 characters, non-standard port numbers, double-slash path patterns, hex-encoded URL segments, multiple subdomain levels, open redirect parameters, and URL shortener patterns.	Critical
LNK-FR-03	The system shall query the WHOIS database for domain creation date, registration expiry, registrar identity, and privacy shielding, applying a score penalty of +40 for domains under 30 days old and +20 for domains under 90 days old.	High
LNK-FR-04	The system shall perform DNS intelligence checks for A records, MX records, SPF records, DMARC, CNAME chain depth, nameserver type, and reverse DNS.	High

LNK-FR-05	The system shall inspect SSL/TLS certificates for validity, issuer, certificate age, days until expiry, TLS protocol version, and common name match.	High
LNK-FR-06	The system shall trace the full HTTP redirect chain, detecting protocol downgrades, URL shortener hops, destination domain changes, and broken final destinations (404 responses).	High
LNK-FR-07	The system shall query URLhaus for exact URL and domain matches against the abuse.ch malware URL database.	High
LNK-FR-08	The system shall check the OpenPhish phishing feed, caching the feed in Redis with a 6-hour TTL to avoid fetching on every request.	High
LNK-FR-09	The system shall query the Google Safe Browsing API for phishing, malware, and social engineering classifications.	High
LNK-FR-10	The system shall submit URLs to VirusTotal and poll for results across 94 antivirus engines.	Critical
LNK-FR-11	The system shall submit URLs to URLScan.io for full browser rendering, screenshot capture, and DOM analysis, returning the screenshot URL in the response.	Medium
LNK-FR-12	The system shall run a Random Forest ML classifier using 35 features extracted from all analysis layers, with Platt scaling calibration ensuring probability accuracy.	High
LNK-FR-13	The system shall combine layer scores using documented weights: VirusTotal 30%, Heuristics 15%, WHOIS 15%, Redirects 10%, DNS 8%, URLhaus 7%, SSL 7%, OpenPhish 5%, Google Safe Browsing 3%.	Critical
LNK-FR-14	The system shall apply critical signal overrides ensuring: 3+ VT malicious detections produce a minimum score of 65; 5+ produce a minimum score of 90; any confirmed OpenPhish, URLhaus, or GSB match produces a minimum score of 90.	Critical
LNK-FR-15	The system shall cache scan results in Redis with a 1-hour TTL and return cached results without repeating external API calls.	High
LNK-FR-16	The system shall support bulk scanning of up to 10 URLs concurrently via POST /scan/bulk.	Medium

LNK-FR-17	The system shall support asynchronous scan submission via POST /scan/async, returning a job_id immediately, with result retrieval via GET /scan/status/{job_id}.	Medium
LNK-FR-18	The system shall support false positive and false negative feedback submission via POST /feedback for ML model retraining.	Low

3.1.3 Functional Requirements — QR Scanner Service (Port 8001)

Table 4:FR-QR Scanner Service

ID	Requirement Statement	Priority
QR-FR-01	The system shall accept QR code images via base64-encoded string (POST /scan-base64) and via direct multipart file upload (POST /scan-file) supporting JPG, PNG, BMP, and WEBP formats.	Critical
QR-FR-02	The system shall decode QR payloads through a 12-layer deobfuscation pipeline covering URL percent-encoding, Base64, HTML entity encoding, Unicode normalization, Punycode, and other obfuscation techniques.	Critical
QR-FR-03	The system shall identify the QR content type from: URL, WiFi credentials, vCard contact, plain text, email, phone number, SMS, cryptocurrency address, or other.	Critical
QR-FR-04	The system shall analyze URL payloads through VirusTotal, URLScan.io, Google Safe Browsing, and AbuseIPDB.	Critical
QR-FR-05	The system shall check cryptocurrency address payloads against Chainabuse for scam reports.	High
QR-FR-06	The system shall validate phone number payloads using Numverify.	Medium
QR-FR-07	The system shall check email payloads through EmailRep for domain reputation and abuse history.	Medium
QR-FR-08	The system shall perform physical tamper detection on the submitted QR image using computer vision analysis of quiet zone uniformity, module edge sharpness, and sticker overlay artifacts.	High
QR-FR-09	The system shall extract EXIF metadata from submitted images including GPS coordinates, camera model, and editing software records.	High

QR-FR-10	The system shall detect steganographic data hidden within the QR code image.	Medium
QR-FR-11	The system shall maintain a community-reported blacklist of malicious payloads; any payload matching the blacklist must immediately receive a Critical risk classification.	High
QR-FR-12	The system shall allow reporting confirmed malicious QR payloads via POST /report, storing their SHA-256 hash in the blacklist.	High
QR-FR-13	The system shall run a 35-feature Random Forest ML classifier to estimate phishing probability for URL-type payloads.	High
QR-FR-14	The system shall analyze the full scan context for social engineering intent using Ollama (Llama 3.2), returning a natural language assessment.	High
QR-FR-15	The system shall support asynchronous scan submission via POST /scan-async for mobile clients, with polling via GET /scan-status/{job_id}.	Medium
QR-FR-16	The system shall maintain paginated scan history accessible via GET /history, with CSV export via GET /history/export.	Low
QR-FR-17	The system shall generate QR code images for submitted safe URLs via POST /generate, refusing to generate codes for URLs classified as High Risk or Critical.	Medium
QR-FR-18	The system shall display WiFi QR content as: Network Name (SSID) and Security Type, flagging WEP security as High Risk.	High
QR-FR-19	The system shall display SMS QR content as: To: [number] and Message: [full text], without truncation.	High

3.1.4 Functional Requirements — Credential Analyzer Service (Port 8002)

Table 5:FR- Credential Analyzer Service

ID	Requirement Statement	Priority
CRD-FR-01	The system shall analyze email addresses for data breaches (HIBP), disposable domain detection, DNS MX record validity, EmailRep reputation, Hunter.io deliverability, and WhoisXML domain age.	Critical

CRD-FR-02	The system shall analyze passwords using zxcvbn strength scoring, Shannon entropy calculation, keyboard walk and repeat pattern detection, and HIBP k-anonymity breach count (first five SHA-1 characters only; raw password must never leave the service).	Critical
CRD-FR-03	The system shall analyze usernames using DeHashed breach queries and Levenshtein-based brand impersonation detection against a database of known service names.	High
CRD-FR-04	The system shall validate payment cards using the Luhn algorithm, identify the card network from BIN prefix (Visa, Mastercard, Amex, etc.), check expiry and CVV format, and detect test card numbers.	Critical
CRD-FR-05	The system shall validate IBANs using the MOD-97 checksum per ISO 13616, including country-specific BBAN structure validation for 86 countries with special handling for Pakistani IBANs (PK prefix).	Critical
CRD-FR-06	The system shall accept CNICs in both the standard dashed format (XXXXXX-XXXXXXX-X) and the 13-digit continuous format, auto-normalize both to standard form, and validate the Verhoeff check digit.	Critical
CRD-FR-07	The system shall validate passport MRZ strings against ICAO Document 9303 check digit rules for document number, birth date, expiry date, and composite check.	High
CRD-FR-08	The system shall validate cryptocurrency wallet addresses: Bitcoin (Base58Check for legacy and Bech32 for SegWit), Ethereum (EIP-55 Keccak-256 checksum). Detection of WIF private keys must trigger a Critical risk level with an immediate action warning.	Critical
CRD-FR-09	The system shall detect the service origin of API keys for 40+ services (AWS, GitHub, Stripe, OpenAI, and others) through pattern matching and entropy analysis, and query LeakCheck for exposure history.	High
CRD-FR-10	The system shall perform advanced phone analysis including carrier lookup via Numverify/Abstract API, OTP bypass risk	High

	scoring, SIM swap indicator detection, and smishing pattern classification via IPQS.	
CRD-FR-11	The system shall auto-detect credential type from free-form input via POST /detect and return the detected type without performing full analysis.	High
CRD-FR-12	The system shall scan free-form text for embedded credentials via POST /scan, returning all detected credentials with their risk scores.	High
CRD-FR-13	The system shall support bulk analysis of up to 50 credentials in a single request via POST /analyze/bulk.	Medium
CRD-FR-14	The system shall emit webhook alerts to a configurable URL for any credential analysis result exceeding the configured risk threshold (default: 76).	Low
CRD-FR-15	The system shall store all analyzed credential values only as SHA-256 hashes in Redis cache; raw values must never be written to any persistent store.	Critical
CRD-FR-16	The system shall provide a GDPR-compliant cache purge via DELETE /cache/purge, clearing all cached analysis results.	High
CRD-FR-17	The system shall return a risk score (0-100), risk level label (Clean / Low / Medium / High / Critical), and a human-readable list of all_flags for every analysis result.	Critical
CRD-FR-18	The system shall function with only static analysis (no external API keys configured), covering at minimum cryptographic validation, format checks, entropy analysis, and pattern matching.	Critical

3.1.5 Functional Requirements — Profile Analyzer Service (Port 8003)

Table 6:FR- Profile Analyzer Service

ID	Requirement Statement	Priority
PRF-FR-01	The system shall accept social media usernames, @handles, full social media URLs, email addresses, and phone numbers as input.	Critical
PRF-FR-02	The system shall scrape public profile data from Twitter (via Nitter), Instagram (JSON data blob), and TikTok (SIGI_STATE extraction) without authentication.	Critical

PRF-FR-03	The system shall analyze username entropy using Shannon entropy calculation, detect leet-speak substitutions (0→o, 1→i, 3→e), trailing digit patterns, and excessive underscores.	High
PRF-FR-04	The system shall detect impersonation of known Pakistani institutions including NADRA, FBR, HBL, Jazz, Telenor, Easypaisa, FIA, and PTA; impersonation of any such institution must trigger the IMPERSONATOR verdict regardless of base score.	Critical
PRF-FR-05	The system shall compare the username to the display name using Levenshtein similarity, and detect scam keywords in display name and bio (e.g., "guaranteed profit", "free bitcoin", "DM me", "airdrop", "passive income").	High
PRF-FR-06	The system shall score profile completeness across six fields: bio, profile picture, display name, website, location, and creation date. Accounts under 7 days old must receive an additional +8 penalty points.	High
PRF-FR-07	The system shall analyze posting frequency regularity, engagement ratio (likes and comments per follower), follower-to-following ratio, and follower growth patterns for bot indicators.	High
PRF-FR-08	The system shall query breach databases concurrently: HIBP, LeakCheck, HudsonRock Cavalier (infostealer logs), and BreachDirectory.	High
PRF-FR-09	The system shall scan bio links for malicious URLs using VirusTotal and URLScan.io.	High
PRF-FR-10	The system shall check cross-platform username presence using Sherlock-based lookup.	Medium
PRF-FR-11	The system shall query GreyNoise Community for IP reputation and Shodan for infrastructure exposure on any IP addresses found associated with the profile.	Medium
PRF-FR-12	The system shall search Ahmia.fi for dark web and Tor network mentions of the username or associated email.	Medium
PRF-FR-13	The system shall run a 24-feature Random Forest classifier trained on labeled social media account data to produce a bot/fake probability score.	High

PRF-FR-14	The system shall generate a natural language verdict summary using Ollama (Llama 3.2), incorporating all detected flags and the final score.	High
PRF-FR-15	The system shall return a suspicion score (0-100) and one of six verdict labels: REAL, SUSPICIOUS, FAKE, SCAMMER, BREACHED, or IMPERSONATOR.	Critical
PRF-FR-16	The system shall apply override rules: any username containing a Pakistani government or financial institution keyword combined with any impersonation signal must produce IMPERSONATOR; any profile with fraud_type="scammer" and score ≥ 45 must produce SCAMMER.	Critical
PRF-FR-17	The system shall cache analysis results in Redis with a 24-hour TTL using SHA-256-hashed keys.	High

3.1.6 Functional Requirements — Deepfake Detector Service (Port 8004)

Table 7:FR- Deepfake Detector Service

ID	Requirement Statement	Priority
DPF-FR-01	The system shall accept images via base64 encoding and via URL, and videos via direct file upload.	Critical
DPF-FR-02	The system shall run a three-tier face detection preprocessing gate: DNN ResNet SSD → Haar Cascade → dlib. Any input with no detected face must be rejected with a clear error message before model inference begins.	Critical
DPF-FR-03	The system shall apply a quality gate checking face region blur score, minimum resolution, and face visibility percentage before model inference.	High
DPF-FR-04	The system shall run three image models in parallel: EfficientNet-B4 (texture analysis), ViT-B/16 (global structural analysis), and FrequencyCNN (FFT spectrum GAN artifact detection).	Critical
DPF-FR-05	The system shall run three video models in parallel: Spatial CNN/EfficientNet-B2 (per-frame texture), Temporal Transformer (16-frame inter-frame consistency), and SRM CNN (frequency domain residuals using fixed non-trainable SRM high-pass kernels).	Critical

DPF-FR-06	The system shall apply the confidence enhancement algorithm in three stages: (1) Dominant model boost — if any model $\geq 95\%$ fake: assign 80% weight; if $\geq 80\%$ fake: assign 70% weight; (2) Uncertain-zone correction for predictions between 0.32 and 0.68; (3) Temperature scaling with $T=1.35$ sharpening predictions away from 50%.	Critical
DPF-FR-07	The system shall generate GradCAM heatmaps for EfficientNet-B4 predictions on request, highlighting regions that contributed most to the fake classification.	Medium
DPF-FR-08	The system shall support asynchronous video analysis via POST /analyze/video-async, returning a job_id immediately and tracking job status through five states: queued, processing, analyzing, complete, error.	High
DPF-FR-09	The system shall support batch image analysis of up to 10 images concurrently via POST /analyze/batch.	Medium
DPF-FR-10	The system shall expose a /metrics endpoint returning scan counts, cache hit rates, and verdict distribution.	Low
DPF-FR-11	The system shall accept feedback submissions via POST /feedback for future model retraining.	Low
DPF-FR-12	The system shall use Redis for caching image analysis results (avoiding repeated inference on identical images) and for async job state storage.	High
DPF-FR-13	The system shall degrade gracefully when Redis is unavailable, disabling caching but continuing analysis.	High

3.1.7 Functional Requirements — Web Backend Service (Port 8007)

Table 8:FR-Web Backend Service

ID	Requirement Statement	Priority
WEB-FR-01	The system shall provide a user registration endpoint (POST /api/auth/register) accepting email, password, and display name, and send an email verification link before allowing login.	Critical
WEB-FR-02	The system shall implement email verification via JWT-signed tokens with 24-hour expiry (POST /api/auth/verify-email).	Critical

WEB-FR-03	The system shall authenticate registered users via POST /api/auth/login and issue a dual-token pair: a 15-minute access token stored in client memory only, and a 30-day refresh token stored in localStorage.	Critical
WEB-FR-04	The system shall implement refresh token rotation — every POST /api/auth/refresh must invalidate the presented refresh token and issue a new one, preventing replay attacks.	Critical
WEB-FR-05	The system shall store refresh tokens as SHA-256 hashes in PostgreSQL with an is_revoked flag; POST /api/auth/logout must set this flag, truly invalidating the token server-side.	Critical
WEB-FR-06	The system shall implement password reset via a time-limited JWT token sent to the user's verified email (POST /api/auth/forgot-password, POST /api/auth/reset-password); both endpoints must return identical responses for known and unknown emails to prevent account enumeration.	High
WEB-FR-07	The system shall implement a resend verification endpoint (POST /api/auth/resend-verification) that always returns 200 regardless of whether the email exists, to prevent account enumeration.	High
WEB-FR-08	The system shall provide a WebSocket endpoint (WS /ws/chat?token=<access_token>) for real-time bidirectional communication, authenticating the connection via the token query parameter.	Critical
WEB-FR-09	The system shall implement the WebSocket as an async generator streaming events to the client: thinking events during processing (showing scanning status messages) and result events when analysis completes.	Critical
WEB-FR-10	The system shall persist every user message and bot response to PostgreSQL (messages table) with full structured scan results stored as JSONB.	High
WEB-FR-11	The system shall log every scan to the scan_history table using only the first 16 characters of the SHA-256 hash of the scanned value (anonymized), the entry type, risk level, and a 30-day expiry timestamp.	High

WEB-FR-12	The system shall provide a file upload endpoint (POST /api/upload/image) accepting image files up to a configurable size limit, immediately attempting QR decode and returning the media_id for subsequent WebSocket routing.	High
WEB-FR-13	The system shall route WebSocket messages containing a media_id to the QR Scanner or Deepfake Detector based on image content (QR detected vs. face detected).	High
WEB-FR-14	The system shall provide a GET /api/history endpoint returning the authenticated user's 30-day scan history, and GET /api/history/{session_id} returning all messages in a specific session.	High
WEB-FR-15	The system shall implement rate limiting of 20 WebSocket messages per minute per authenticated user, and 10 authentication requests per minute per IP address at the nginx proxy level.	High
WEB-FR-16	The system shall use UUID primary keys for all database entities to prevent sequential ID enumeration attacks.	High
WEB-FR-17	The system shall provide GET /api/auth/me returning the authenticated user's profile (id, email, display_name, email_verified, created_at, last_login).	Medium
WEB-FR-18	The system shall implement WebSocket heartbeat support — responding to {type: "ping"} client messages with {type: "pong"} to maintain connection liveness.	Medium
WEB-FR-19	The system shall expose a health endpoint (GET /health) returning service status, database connectivity, and Redis connectivity.	Medium
WEB-FR-20	The system shall use bcrypt (cost factor 12) with SHA-256 pre-hashing for all stored passwords, ensuring passwords of any length are handled safely regardless of bcrypt's 72-byte input limit.	Critical

3.1.8 Functional Requirements — React Web Frontend (Port 5173)

Table 9:FR- React Frontend Framework

ID	Requirement Statement	Priority
FE-FR-01	The system shall provide a registration page with email, password, and display name inputs, displaying validation errors inline without page reload.	Critical

FE-FR-02	The system shall provide a login page, storing the received access token in JavaScript memory only (never localStorage or cookies), and the refresh token in localStorage.	Critical
FE-FR-03	The system shall silently refresh the access token using the stored refresh token when any API request returns 401, without requiring the user to log in again.	Critical
FE-FR-04	The system shall provide a chat interface with a message input, send button, and scrollable message history displaying both user messages and bot responses.	Critical
FE-FR-05	The system shall render bot responses in a structured format showing risk badges, formatted scan results, and Ollama explanations as the streaming events arrive.	Critical
FE-FR-06	The system shall display thinking/status messages during analysis (e.g., "Scanning with VirusTotal...", "Analyzing profile...") while the scan is in progress.	High
FE-FR-07	The system shall support file upload via both a file input button and drag-and-drop onto the chat area, supporting JPG, PNG, and MP4 formats.	High
FE-FR-08	The system shall display a scan history page showing the user's 30-day scan log with entry types, risk levels, and timestamps.	High
FE-FR-09	The system shall implement protected routing — unauthenticated users accessing any protected page must be redirected to the login page.	Critical
FE-FR-10	The system shall be fully responsive and readable on both desktop browsers and mobile browsers.	High

3.2 Non-Functional Requirements

3.2.1 Performance Requirements

Table 10:NFR- Performance Requirements

ID	Requirement Statement	Priority
NFR-PRF-01	The system shall return cached analysis results in under 50 milliseconds from any service.	Critical

NFR-PRF-02	The system shall complete full URL scans (all 11 layers) within 90 seconds under normal network conditions.	High
NFR-PRF-03	The system shall complete credential analysis in under 200 milliseconds for cached inputs.	High
NFR-PRF-04	The system shall complete deepfake image analysis in under 5,000 milliseconds on CPU hardware, or under 800 milliseconds on GPU hardware.	High
NFR-PRF-05	The system shall return asynchronous scan job IDs within 200 milliseconds of submission.	High
NFR-PRF-06	The web backend shall establish WebSocket connections within 50 milliseconds.	High
NFR-PRF-07	The web backend shall handle at least 50 concurrent WebSocket connections without degradation in a single-process deployment.	Medium

3.2.2 Security Requirements

Table 11:NFR- Security Requirements

ID	Requirement Statement	Priority
NFR-SEC-01	The system shall never store raw credential values (passwords, emails, CNICs, cards, IBANs) in any persistent store or log file.	Critical
NFR-SEC-02	The system shall implement HIBP password checking using k-anonymity — only the first five characters of the SHA-1 hash are transmitted externally.	Critical
NFR-SEC-03	The system shall store all credential values only as SHA-256 hashes in Redis cache.	Critical
NFR-SEC-04	The system shall verify every WhatsApp webhook POST using HMAC-SHA256 signature validation.	Critical
NFR-SEC-05	The system shall authenticate all service-to-service HTTP calls from the Orchestra using API key headers.	Critical
NFR-SEC-06	The system shall store web application passwords using bcrypt (cost 12) with SHA-256 pre-hashing.	Critical
NFR-SEC-07	The system shall store refresh tokens only as SHA-256 hashes in PostgreSQL.	Critical

NFR-SEC-08	The system shall never store web access tokens in localStorage, sessionStorage, or cookies; access tokens must be held in JavaScript memory only.	Critical
NFR-SEC-09	The system shall protect all API endpoints except registration, login, and health against unauthorized access using JWT Bearer token validation.	Critical
NFR-SEC-10	The system shall implement CORS policy restricting cross-origin requests to the configured allowed origin(s) only.	High
NFR-SEC-11	The system shall implement rate limiting of 5 requests per minute on POST /scan (Link Analyzer), 10 authentication requests per minute per IP, and 20 WebSocket messages per minute per user.	High

3.2.3 Privacy Requirements

Table 12: NFR- Privacy Requirements

ID	Requirement Statement	Priority
NFR-PRV-01	The system shall expire all WhatsApp user sessions from Redis after 30 minutes of inactivity.	Critical
NFR-PRV-02	The system shall delete all WhatsApp user session data instantly on receipt of the /clear command.	Critical
NFR-PRV-03	The system shall store scan history items in the web database with an automatic 30-day expiry.	High
NFR-PRV-04	The system shall store scan history identifiers only as the first 16 characters of the SHA-256 hash of the scanned value — never the raw value.	High
NFR-PRV-05	The system shall never write WhatsApp message content to disk or log files.	Critical

3.2.4 Reliability and Availability Requirements

ID	Requirement Statement	Priority
NFR-REL-01	The system shall continue processing requests for all other query types if any single microservice is unavailable.	Critical
NFR-REL-02	The system shall continue analysis with reduced capability if any external API (VirusTotal, HIBP, IPQS, etc.) is unreachable,	Critical

	scoring that layer as zero and noting the unavailability in the response flags.	
NFR-REL-03	The system shall continue analysis and return results without caching if Redis is unavailable.	High
NFR-REL-04	The system shall fall back to static explanation templates if Ollama is unavailable or times out.	High
NFR-REL-05	The system shall fall back to Ollama for Urdu classification if the Gemini API key is not configured.	High

3.2.5 Usability Requirements

Table 13: NFR- Usability Requirements

ID	Requirement Statement	Priority
NFR-USE-01	The system shall present all WhatsApp responses in plain English readable on a standard mobile screen without requiring technical knowledge.	Critical
NFR-USE-02	The system shall include actionable advice (what the user should do next) in every scan result, not just a risk score.	Critical
NFR-USE-03	The system shall guide users through disambiguation using interactive button menus rather than requiring them to type commands.	High
NFR-USE-04	The web interface shall display scanning progress messages to users during long-running analyses, preventing users from thinking the application is unresponsive.	High
NFR-USE-05	The web interface shall be fully functional on Chrome, Firefox, and Safari on both desktop and mobile browsers.	High

3.3 Literature Survey

3.3.1 Detection URLs Detection URLs is probably one of the most explored topics in practical cybersecurity research. By utilizing features derived from URL structure Mohammad et al. was able to train their MLP classifier to surpass 97% accuracy, proving that machine learning techniques can effectively be used to classify whether a URL is phishing or benign without the use of blacklists [1]. A study done by Sahoo et al. concluded that after doing a systematic literature

review on 57 articles related to malicious URL detection that ensemble classifiers specifically built with Random Forest or Gradient Boosting consistently performed better than any standalone model [2]. One downside they recognized during their research is: Machine Learning algorithms fail to detect new phishing URLs that are not already stored in some knowledge base. According to research from Zago et al. VirusTotal Aggregation can be considered the most reliable single indicator as it aggregates over 90 different engines [3]. Aegis helps combat zero-day URL phishing by analyzing many layers of URL structure: If a URL has a newly registered domain, unverified SSL certificate, no mail server found, and uses phishing keywords it will be marked as High Risk even if VirusTotal has found 0 detections.

3.3.2 QR Code Security

QR code attacks have less research in literature than URL phishing. Vidas et al. were among the pioneers who formally identified the attack vectors for QR codes and showed how by just physically swapping a genuine QR sticker with a malicious one would allow for successful targeting of victims without detection [4]. In a study done by Krombholz et al., they showed how over 90% of participants failed to detect the malicious QR without using a dedicated scanner [5]. Aegis computer vision tampering detection system addresses physical swap attacks, while the deobfuscation pipeline deals with technical evasion attacks.

3.3.3 Deepfake Detection

The FaceForensics++ dataset is what Rossler et al. Used to test face manipulation detection. This dataset is used with classifiers that use EfficientNet models. These models are really good at finding texture artifacts. They are the best at this.

The vision transformer model can find problems, with structures from far away. This is something that only vision transformer models can do. CNN models cannot do this.

Wang et al. Found that when they used certain techniques like the FFT algorithm and JPEG compression they could still see artifacts. These artifacts were caused by GAN upscaling techniques.

The Aegis ensemble uses all of these approaches. What makes the Aegis ensemble different is the way it uses confidence levels. The FaceForensics++ dataset and the classifiers using EfficientNet models and the vision transformer model and the frequency domain processing all work together in the Aegis ensemble. The algorithm that is most confident gets weight. This means the Aegis ensemble uses the FaceForensics++ dataset and the classifiers using EfficientNet models and the vision transformer model and the frequency domain processing to make a decision. The

FaceForensics++ dataset and the classifiers using EfficientNet models and the vision transformer model and the frequency domain processing are all part of the Aegis ensemble.

3.3.4 Credential and Identity Risk Analysis

The work by Hunt on Have I Been Pwned talked about the k-anonymity technique for password breaches. This is a way to deal with password breaches. Have I Been Pwned by Hunt is an example of this.

According to a study by Ur and others they looked at how different password strength evaluation techniques work. They found out that the technique used by Dropbox, which is called zxcvbn works better than the rules-based approach. This is because zxcvbn looks at how people try to crack passwords. The zxcvbn technique, from Dropbox is a way to check password strength.

3.3.5 Fake Profile and Bot Detection

In a study Varol et al. Used a learning method to classify bots on Twitter. They used six types of features and got an accuracy score of 0.95 [11].

Another study by Cresci et al. Found that some bots, called " spambots " can act like real users. This makes it hard for bot detectors to find them. It also shows that using feature-based detection methods is not enough [12].

Aegis uses a -dimensional approach to detect bots. This approach is like the one described earlier. Aegis also uses an OSINT database, checks, for Pakistan impersonation and leverages Ollamas natural language processing ability.

Chapter 4

4. Methodology

4.1 Development Approach

Aegis AI uses a kind of design for its product. This design is called microservices-based architecture. It is used everywhere in the product. When they made the cybersecurity detection areas they thought of each one as a service from the very beginning. They made WhatsApp and the web interface as services too. They used the analysis services for both without changing them.

This means that if they make the analysis services better both WhatsApp and the web interface will get better at the time. If they want to add an interface later they will not have to change the analysis part.

The system has eight services that can be used right now. There are five services that analyze things: Link Analyzer, QR Scanner, Credential Analyzer, Profile Analyzer and Deepfake Detector. Then there are two services that help everything work together: one for WhatsApp and one, for the web interface. There is also one service that users interact with which's a React application. The system also uses Redis and Ollama which're like shared tools that all the services can use.

4.2 Development Process

Each of these services was created in the way. First we figured out what the services would look like by defining what we call API contracts. This helped us make the interfaces, for the services. Then we. Tested the main parts of the services before we connected them to the API. We tested each API connection one by one before we added it to the scoring pipeline. We did not use Redis caching until the main parts of the services were working well. Finally for the web end we wrote and tested the React application with the FastAPI backend and we used fake authentication responses to see how it worked.

4.3 Technology Selection

Table 14: Technologies Used

Technology	Role	Justification
FastAPI (Python)	Web framework for all backend services	Asynchronous by design; handles concurrent external API calls via <code>asyncio.gather()</code> ; auto-generates

		OpenAPI/Swagger documentation; 3x faster than Flask for I/O-bound tasks.
React 18 + TypeScript	Web frontend	Type safety prevents runtime errors; component model enables reusable scan result cards; large ecosystem; native WebSocket support.
Vite 5	Frontend build tool	10× faster hot module replacement than webpack; native ESM; minimal configuration.
PostgreSQL 16	Persistent web database	ACID compliance; JSONB columns store structured scan results without rigid schema; supports UUID primary keys natively.
SQLAlchemy 2.0 async	ORM for web backend	Type-safe async queries; Alembic migration support; parameterized queries prevent SQL injection.
JWT (python-jose + bcrypt)	Web authentication	Industry-standard dual-token system; bcrypt with SHA-256 pre-hashing handles passwords of any length; token rotation prevents replay attacks.
Redis 7	Caching, sessions, async jobs	Sub-millisecond TTL-native key-value operations; used by all services for caching; used by Orchestra for session storage; used by Deepfake service for async job state.
Ollama (Llama 3.2)	Local AI inference	Runs entirely offline; no cloud API cost; data stays local; used by Orchestra, QR Scanner, and Profile Analyzer for explanation generation.
PyTorch	Deep learning (Deepfake service)	Flexible model loading; FP16 mixed precision; GPU/CPU transparent inference.
scikit-learn	ML classifiers (Link, QR, Profile)	Random Forest with Platt scaling; well-documented; reproducible pickle artifacts.
Docker + Compose	Containerization	One-command deployment per service; network isolation; reproducible environments.
Tailwind CSS 3	Frontend styling	Rapid UI development; consistent design tokens; no CSS conflicts.

4.4 Privacy by Design Approach

We thought about privacy from the beginning when we made this. When we share passwords with HIBP we only share the five characters of their SHA-1 representation. This way the k-anonymity approach makes sure the real password never leaves the application.

- We change all credentials into SHA-256 before we put them in the Redis cache.
- We calculate the values in the computers memory and then get rid of them.
- We never save WhatsApp messages on the computers disk or in any logs.
- When we look at the history of web database scans we only store the 16 characters of a SHA-256 hash.
- We automatically delete these records after 30 days.
- The Privacy, by Design Approach is what we use to make sure the Privacy is protected.
- We use the Privacy by Design Approach to keep the Privacy safe.

5. System Architecture / Initial Design

5.1 System Architecture

The Aegis AI system is made up of small parts that work together. It has two ways that users can interact with it. The Aegis AI system has eight parts that do different jobs. These small parts use two things to work properly: Redis and Ollama. They use these things by connecting to them on the computer.




Figure 1 Usecase Diagram




Figure 2 Architecture Diagram

5.1.1 Architecture Design Approach

The Aegis AI system is designed this way so that it can do tasks well. For example when the Aegis AI system checks URLs it has to read and write a lot of data. When the Aegis AI system detects deepfakes it needs a lot of computer power.. When the Aegis AI system analyzes credentials it has to do complicated cryptography work. The good thing about the Aegis AI system is that it has two interfaces: one for WhatsApp and one, for the web. Both of these interfaces use the analysis layer, which means that the small parts of the Aegis AI system do not need to be changed.

5.1.2 Architecture Design

The system is made up of three parts. We have two parts that users interact with which're like two separate doors to get in. One door is the WhatsApp interface that people can use on their phones. The other door is a website that people can access from any computer using a browser.

Then we have the part that makes everything work together. This part has two helpers that take what the users do and turn it into actions that the system can understand. One helper is called the Orchestra service. It listens for messages from WhatsApp on a special channel called Port 8006. The other helper is called the Web Backend service. It listens for requests from the website, on another special channel called Port 8007.




Figure 3 Data Flow (level 0)




Figure 4 Component Diagram




Figure 5 Data Flow (level 1)

5.1.3 Subsystem Architecture

Orchestra – Intent Classification & Routing

Each message that comes in from WhatsApp is processed in the steps. First we check the message to make sure it is real by using HMAC-SHA256 signature validation. Then we use Redis deduplication to make sure we do not get the message twice we do this by looking at the message ID for 120 seconds. After that we try to find all the information in the message this is called entity extraction. We look for all the types of information that are in the message. Then we look at the message. Compare it to the P1-P14 tiers, one by one until we find a match. When we find a match

we make a RouteDecision and this holds the module name, the action and the entity, from the Orchestra Intent Classification & Routing.

Web Backend — WebSocket Streaming and Authentication

The Web Backend on Port 8007 is the service that helps the authenticated web portal work properly. This service has 20 REST endpoints that deal with authentication and history services. It also has one WebSocket endpoint that provides real-time analysis.

When we talk about the WebSocket service the developer used a technique called an asynchronous generator. This means that when the Web Backend on Port 8007 is analyzing something it sends the results to the client away instead of waiting for everything to finish. For example when you use the Web Backend on Port 8007 you get a message that says "Scanning with VirusTotal..." even though the actual scan takes around 30 to 90 seconds to complete in the background.

The Web Backend on Port 8007 also has a way of handling authentication, which is based on tokens. There are two types of tokens: access tokens and refresh tokens. The access token is only valid for 15 minutes. Is stored on the client side but not in the browsers storage or cookies. The refresh token is valid for 30 days. Is stored on the client side and its hash is stored in the PostgreSQL database on the server side. This way when the token expires the server can revoke it. When the token is refreshed the old token is replaced with an one and this is how the Web Backend, on Port 8007 keeps the authentication process secure.




Figure 4 Orchestra activity

Link Analyzer — Eleven-Layer Detection

- The Link Analyzer checks a URL through eleven layers. It does URL checks in under 1 ms using string matching based on 14 checks. This happens without needing any internet connections.
- It also checks WHOIS, DNS, SSL and redirects at the time.
- Another set of checks happens at the time. This includes URLhaus, OpenPhish Google Safe Browsing, VirusTotal and URLScan.
- VirusTotal and URLScan take a lot of time because they wait for responses.
- The Link Analyzer uses a Random Forest machine learning classifier as the layer.
- This layer looks at the results, from all layers extracts 35 features and gives a phishing likelihood estimate.
- The Link Analyzer uses these checks to analyze a URL.
- It provides a phishing likelihood estimate based on the results.
- The eleven layers help to detect phishing URLs




Figure 5: Link state machine diagram




Figure 6: Link Sequence




Figure 7: Link Activity

QR Scanner — Four-Layer Analysis

QR Scanner decodes the image using OpenCV. If that does not work it uses pyzbar as a method. The decoded information then goes through a 12-step process to make it clear. When analyzing the image four things happen at the time. The system checks if the image has a zone. It checks how sharp the edges of the modules are. It looks at the EXIF GPS data. It checks for steganography. The system then uses intelligence based on what type of information was encoded. For example if it is a URL it checks it with VirusTotal, URLScan.io Google Safe Browsing and AbuseIPDB. If it is cryptocurrency information it checks it with Chainabuse. If it is a phone number it checks it with Numverify. If it is an email address it checks it with EmailRep. The QR Scanner uses these checks to get information, about what was encoded in the image. It uses OpenCV and pyzbar to decode the image. Then checks the information in different ways. The checks help to make sure the information is safe and what it says it is.




Figure 8: QR scanner activity




Figure 9: QR sequence

Credential Analyzer — Five-Tier Architecture

QR Scanner decodes the image using OpenCV. In case this fails, then it uses pyzbar as a means to decode. Afterward, the decoded data undergoes a 12-staged procedure for analysis and clarity purposes. When analyzing the image, four actions take place at once. Checks whether there is a zone within the image. Checks the level of edge sharpness of the modules in the image. Analyzes EXIF GPS data of the image. Determines whether there is steganography. Intelligence analysis is applied depending on the type of information that was encoded. For instance, if the encoded information is a URL link, then checks such as VirusTotal, URLScan.io Google Safe Browsing, and AbuseIPDB are done. On the other hand, if the encoded information is related to cryptocurrency, then the system analyses the same via Chainabuse, while phone numbers are checked by Numverify, and email addresses checked by EmailRep. The above processes provide insights concerning the information encoded in the QR image. QR scanner utilizes OpenCV and pyzbar to decode the image.




Figure 10: Credential Activity




Figure 11: Credential sequence

Profile Analyzer — Multi-Dimension Scoring

The Profile Analyzer figures out what kind of input it is dealing with. Then it uses a tool to get information from the right platform. For example, it uses Nitter for Twitter, JSON blob for Instagram, and SIGI_STATE for TikTok. The Profile Analyzer does a lot of checks on the

information it gets.¹⁹ Checks to be exact. At the time it also looks at information from other databases. The Profile Analyzer uses a kind of calculator called the Random Forest classifier. This calculator looks at 24 things about the information and decides how likely it is that the account is a bot. Sometimes the Profile Analyzer has special rules that can change the result. For instance if the Profile Analyzer sees that a user is talking about a school, in Pakistan and is also doing something that looks like impersonation then it will say that the user is an impersonator. This happens even if the calculator does not think the account is very likely to be a bot. The Profile Analyzer calls this kind of user an IMPERSONATOR.




Figure 12: Profile State Machine




Figure 13: Profile Sequence

Deepfake Detector — Ensemble with Confidence Enhancement

Three steps happen before we make any conclusions about a model. First we detect faces using techniques like DNN, Haar Cascade and dlib. We reject any samples that do not have faces. Next we have a quality check. We look at blur, resolution and visibility. Then we use a model. When it comes to images we use models. EfficientNet-B4 helps find texture problems. It looks at each pixel. ViT-B/16 finds structural issues. It looks at all 196 image patches. FrequencyCNN finds artifacts in super-resolution. It does this by analyzing the FFT magnitude spectrum. For videos we use models. Spatial CNN finds texture problems from frame to frame. Temporal Transformer looks at consistency between frames. It checks 16 frames at a time. SRM-CNN uses Steganalysis Rich Models filters. Then it classifies using EfficientNet-B4. We have an algorithm that boosts confidence. It makes sure that models that are very confident do not lose their importance. If a model is 95% or confident it gets 80% of the weight. If it is 80% or more confident it gets 70% of the weight. We also have a way to correct scores. It looks at scores, between 32% and 68%.




Figure 14: Deepfake Sequence




Figure 15: Deepfake message processing pipeline




Figure 16: Deepfake activity

5.2 Detailed System Design

5.2.1 Classification

Aegis AI is made up of lots of parts that work together. These parts are like helpers that do specific jobs. They are all connected using something called REST which's like a messenger that helps them talk to each other. There are two teams that help these parts work together. The Orchestra team is like a manager that makes sure everything runs smoothly when something happens. The Web Backend team is like a helper that makes sure everyone stays connected. When we need to remember something, like what someone was doing we use something called Redis. It is like a note that helps us keep track of things. We also use something called PostgreSQL, which's like a big filing cabinet that stores all the important information, like user accounts and what people have done in the past. The Aegis AI system is designed to be flexible and strong, like a shield. The Orchestra component and the Web Backend component work together to make sure everything runs smoothly. Aegis AI uses Redis and PostgreSQL to store and remember things so it can keep doing its job.

5.2.2 Definition

The system uses two ways to show security threats in time for many areas. It has a chatbot that works with WhatsApp so people do not need to install anything. It also has a web page where people can see their accounts and what happened before. The chatbot and the web page use the five tools to do the analysis. They are used for the thing, which is security threats analysis and both the chatbot and the web page are good, for this. The security threats analysis is what makes this system work for people.

5.2.3 Responsibilities

Table 15: Service ports

Service	Port	Technology	Primary Responsibility
Orchestra	8006	FastAPI, Redis, Ollama	WhatsApp webhook handling, entity extraction, P1-P14 routing, smishing detection, username intelligence, session management, WhatsApp API communication.
Web Backend	8007	FastAPI, PostgreSQL, JWT, WebSocket	Web authentication (JWT dual-token), WebSocket streaming, PostgreSQL persistence, file upload, scan history, web-channel orchestration.

React Frontend	5173	React 18, TypeScript, Vite, Tailwind	User interface: registration, login, chat, file upload, scan history display, real-time result rendering.
Link Analyzer	8000	FastAPI, scikit-learn, Redis	11-layer URL threat analysis, Random Forest ML classifier, weighted scoring, critical overrides, bulk and async scan.
QR Scanner	8001	FastAPI, OpenCV, Redis, Ollama	QR image decoding, deobfuscation, tamper detection, EXIF analysis, 4-layer threat analysis, social engineering AI.
Credential Analyzer	8002	FastAPI, cryptographic libraries, Redis	10 credential types, 5-tier cryptographic validation, breach database queries, CNIC/IBAN/Pakistan-specific checks.
Profile Analyzer	8003	FastAPI, BeautifulSoup4, scikit-learn, Redis, Ollama	Social media scraping, 19-function fake account analysis, OSINT queries, 24-feature ML, Ollama verdict generation.
Deepfake Detector	8004	FastAPI, PyTorch, OpenCV, Redis	Face detection gate, 6-model ensemble inference, confidence enhancement, GradCAM, async video analysis.

5.2.4 Constraints

The biggest problem with time is that VirusTotal takes a time to scan things. It can take from 60 to 90 seconds to get the results when you are using the plan. To fix this issue the system uses something called scanning and polling. It also uses Redis caching, which helps a lot because it saves the results of the analysis beforehand. This way the system does not have to wait for the analysis to be done. The WhatsApp Business API from Meta has some rules that affect how the Orchestra application works. For example when you are chatting with someone you can only have three buttons to choose from. This limits how the menu can be designed. The Deepfake Detector looks at faces to figure out if something is real or not. If a face is hard to see or the picture is not very clear the Deepfake Detector will just ignore it. The Deepfake Detector uses face detection, as its step so it will not work well with faces that are blocked or pictures that are not high quality.

5.2.5 Composition

Each microservice has a parts. It has a FastAPI application that defines what the service does when it gets a request from the internet. The microservice also has things called analyzers that use algorithms to detect things. It has a caching layer that uses Redis, which stores information for a time and uses special codes called SHA-256 hashed keys. Sometimes it also has a storage part that uses SQLite or PostgreSQL. The microservice has a configuration module that uses Pydantic, which reads settings, from the environment. It has a Dockerization layer. The Orchestra part has a lot of components. It has an entity extractor, an intent classifier, a dispatcher a smishing engine, username intelligence, an Ollama client, a Gemini client, a session manager and a WhatsApp API client. The Web Backend is made up of services. It has an authentication service that handles user accounts. It has a WebSocket manager that helps with real time communication. It has a chat generator that creates conversations. It has a file upload handler that deals with files being sent to the service. It has a history service that keeps track of what has been scanned. It uses something called SQLAlchemy models to store information in a PostgreSQL database. It has an email delivery service that uses a library called aiosmtplib to send emails.

5.2.6 Uses/Interactions

The Orchestra uses the five detection services by sending a request over the internet through codes called API keys. The Web Backend does the thing. It uses the five detection services, over the internet with these special codes. The thing is, the detection services do not know who is asking for their help. Is it the Orchestra or the Web Backend. Because the way they talk to each other does not give away that information.

5.2.7 Resources

Redis is something that all services use. Each service has its special prefix for the Redis keys so that the keys do not get mixed up. We use Ollama with Llama 3.2 for the Orchestra service, the QR Scanner service and the Profile Analyzer service. The Deepfake Detector needs six files that it learned from with PyTorch models. We only use PostgreSQL for the Web Backend. You do not need API keys, for any of the services. If something goes wrong the services will still work. They will only do basic analysis.

5.2.8 Processing

The FastAPI endpoints are all using requests. This means that when the application needs to make requests to APIs it does so in a way that does not block other tasks. It uses Python's asyncio.gather to make these external requests asynchronously. Each time the application makes a call it does so inside its own try and except block. This means that if something goes wrong with the call the application can handle the error and provide a default response, such as a zero score or a flag to

say that the information is not available. The application also uses a cache, which is stored in Redis to avoid making external requests. When the application receives a request it first checks the cache to see if it already has the information. If it does it returns the cached value away without making any further external requests. The Web Backend has an async generator, for WebSocket that provides events as they happen. This allows the application to push events to the client in time using the FastAPI endpoints and the WebSocket connection. The FastAPI endpoints are working with the WebSocket to provide a smooth experience.

5.2.9 Interface/Exports

All the services have something called REST APIs that are really well documented. You can find these documents at /docs with something called Swagger UI. The Web Backend is a bit special because it also has a thing called a WebSocket endpoint.

Here is a table that lists all the endpoints, for all the services, including the web layer.

Table 16: Service Endpoints

Service	Method	Endpoint	Description
Link Analyzer	POST	/scan	Full synchronous 11-layer URL scan
Link Analyzer	POST	/scan/bulk	Scan up to 10 URLs concurrently
Link Analyzer	POST	/scan/async	Submit URL scan job, returns job_id
Link Analyzer	GET	/scan/status/{id}	Poll async scan result
Link Analyzer	POST	/feedback	Submit result correction
Link Analyzer	GET	/metrics	Service metrics (JSON)
Link Analyzer	GET	/health	Service health check
QR Scanner	POST	/scan-base64	Scan QR from base64 encoded image
QR Scanner	POST	/scan-file	Scan QR from uploaded image file
QR Scanner	POST	/scan-async	Submit async QR scan job
QR Scanner	GET	/scan-status/{id}	Poll async QR scan result
QR Scanner	POST	/report	Report confirmed malicious payload

QR Scanner	GET	/history	Scan history (paginated, CSV export)
QR Scanner	POST	/generate	Generate QR code for safe URL
QR Scanner	GET	/health	Service health check
Credential	POST	/analyze/email	Analyze email: HIBP, disposable, MX
Credential	POST	/analyze/password	Password strength and HIBP breach count
Credential	POST	/analyze/username	Username breach and impersonation check
Credential	POST	/analyze/card	Luhn validation, BIN, network detection
Credential	POST	/analyze/iban	MOD-97 checksum, country, bank code
Credential	POST	/analyze/crypto	Multi-chain wallet validation
Credential	POST	/analyze/national-id	CNIC / SSN / Aadhaar validation
Credential	POST	/analyze/passport	ICAO MRZ check digit validation
Credential	POST	/analyze/phone	Phone carrier, VoIP, scam prefix
Credential	POST	/analyze/api-key	Service detection, entropy, exposure
Credential	POST	/analyze/phone/advanced	OTP bypass / SIM swap / smishing (IPQS)
Credential	POST	/detect	Auto-detect credential type from text
Credential	POST	/scan	Find credentials embedded in free text
Credential	POST	/analyze/bulk	Analyze up to 50 credentials at once
Credential	DELETE	/cache/purge	GDPR flush — clear all cached results
Credential	GET	/health	Service health check
Profile	POST	/analyze/profile	Analyze social media username / handle
Profile	POST	/analyze/email	Email fraud and breach analysis
Profile	POST	/analyze/phone	Phone fraud and carrier analysis
Profile	GET	/health	Service health check
Deepfake	POST	/analyze/image	Analyze image for AI manipulation
Deepfake	POST	/analyze/image-url	Analyze image from URL
Deepfake	POST	/analyze/video-async	Submit async video analysis job
Deepfake	GET	/analyze/status/{id}	Poll async video job status

Deepfake	POST	/analyze/batch	Batch analyze up to 10 images
Deepfake	POST	/feedback	Submit verdict correction for retraining
Deepfake	GET	/metrics	Scan counts, cache rate, verdict distribution
Deepfake	GET	/health	Service health check
Web Backend	POST	/api/auth/register	Create user account, send verification email
Web Backend	POST	/api/auth/verify-email	Verify email using JWT token from email
Web Backend	POST	/api/auth/resend-verification	Resend email verification link
Web Backend	POST	/api/auth/login	Authenticate and return access + refresh tokens
Web Backend	POST	/api/auth/refresh	Exchange refresh token for new access token
Web Backend	POST	/api/auth/logout	Revoke refresh token server-side
Web Backend	GET	/api/auth/me	Get authenticated user profile
Web Backend	POST	/api/auth/forgot-password	Send password reset email
Web Backend	POST	/api/auth/reset-password	Set new password using reset token
Web Backend	WS	/ws/chat?token=<jwt>	Real-time analysis via WebSocket streaming
Web Backend	GET	/api/history	Authenticated user 30-day scan history
Web Backend	GET	/api/history/{session_id}	All messages in a specific chat session
Web Backend	POST	/api/upload/image	Upload image file, attempt QR decode
Web Backend	GET	/health	Database and Redis connectivity status

5.2.10 Other Diagrams




Figure 17: Orchestra State Machine




Figure 18: Network security




Figure 19: Deploement Diagram




Figure 20: Class Diagram

Chapter 6

6. Implementation and Testing

6.1 Implementation

6.1.1 Orchestra Service

The Orchestra has a FastAPI app with two webhook endpoints. The GET /webhook endpoint is used for verification with Meta. This is done by matching a token. The POST /webhook endpoint does a lot of things. It receives a message and checks if it is real using HMAC-SHA256. Then it removes any repeated messages using Redis. After that it looks at the message to find information like entities. The message is then classified into levels like P1 to P14. The message is then sent to small services. These services try to explain the message using Ollama. The session is then updated. Finally a response is sent back, to WhatsApp. The part of the app that finds entities uses patterns. These patterns are used to look at the message. The part that figures out the priority of the message uses if- statements. It does not use a list to look up the information. The smishing part of the Orchestra app does two things.

6.1.2 Link Analyzer

The Link Analyzer uses math functions that are done in the background because they only need to think and do not need to talk to other parts of the computer. For everything the Link Analyzer does many things at the same time using something called `asyncio.gather`. The Link Analyzer also loads a tool called a random forest classifier when the program starts and keeps it in the computer's memory. This tool helps figure out how likely something is to happen. The Link Analyzer also uses something called Platt scaling to make sure these likelihoods are real and not just made up. If the Link Analyzer needs to override something it does this after it has already figured out the score and it checks each condition one by one.

6.1.3 QR Scanner

The QR Scanner uses a function from OpenCV to read QR codes. If this does not work the QR Scanner uses another library called `pyzbar` to try. The QR Scanner also has a way to decode secret messages. It does this by using different tools one after the other. These tools include things like

unquoting URLs and decoding base64. The QR Scanner also uses something called Punycode to decode kinds of text. The QR Scanner can also look at the physical QR code. Figure out if it has been tampered with. It does this by using OpenCV to look at the zone of the QR code. The QR Scanner can also look at the metadata of a picture, like where it was taken using something called EXIF metadata extraction.

6.1.4 Credential Analyzer

All the secret code values that come from cryptography have built-in ways to work in Python without needing any libraries to check if they are correct. The Luhn algorithm does its job quickly by going through each digit in the card number one by one. When we check the MOD-97 we change letters to numbers like A becomes 10 and Z becomes 35 then we rearrange the numbers. Calculate the remainder when we divide by 97 using Python's special way of handling big numbers. To check the Verhoeff digit for a CNIC we use tables that the algorithm provides. If we find a WIF key we mark the account as very important and say we need to do something right away no matter what other scores say.

6.1.5 Profile Analyzer

We use ways to get information from different websites. For Nitter we look at the HTML code. Use tools like BeautifulSoup4 and lxml to understand it. For Instagram we look at the hidden JSON code in the page. Get the profile information from there. For TikTok we use something called SIGI_STATE JSON to get the information we need. We calculate 24 features from the information we get and adjust them so they are all on the same scale before we use them to train and make predictions. Ollama gets a message with information, like flags a base score, the username and the bio and it gives us a short explanation, usually two or three sentences, based on what it has learned.

6.1.6 Deepfake Detector

When the application starts it loads PyTorch models. It automatically detects the device. Uses that to load the models. For the FrequencyCNN model we have to update the names when we load the saved model. This is because the model saves with a name like stage1/branch1. Our code looks for s1/b1.

We use a neural network for face detection. This network calls cv2.dnn.readNetFromCaffe with a threshold of 0.5. This means it only detects faces if it is at least 50 percent sure.. It looks at the convolutional layer of the EfficientNet-B4 model. It calculates the activations applies the ReLU function and then makes the map bigger to match the original size. Finally it overlays this map, on a jet-colored map.

6.1.7 Web Backend

Our web backend has a service that handles user authentication. This service uses python-jose to work with JWT tokens and bcrypt from passlib to hash passwords. Before hashing passwords we use SHA-256 to make them smaller. This helps bcrypt handle passwords of all sizes. When a users token needs to be refreshed we mark the token as revoked and then make a new one. We do all of this in one database transaction. We use SQLAlchemy 2.0 async sessions to talk to the database. This means every database query is carefully planned to prevent SQL injection attacks.

6.1.8 React Frontend

This React application is built with TypeScript, Vite and Zustand for managing the state. It also uses Tailwind CSS to handle the styling and TanStack Query to make API calls. When you log in a WebSocket connection is started using the access token that is stored in memory as a query parameter.

As events come in they are shown in the user interface one by one. When the application is thinking it shows a spinner message. When it gets results it shows cards with risks, flags and explanations from Ollama. You can upload files by selecting them or by dragging and dropping them. The application checks the files on the client side before sending them with a POST request.

6.2 Deployment Environments

Each service runs in its Docker container. Here are the environment variables, for each React application service.

6.2.1 Orchestra Environment (.env.host)

Table 17: Eenv variables of orchestrae

Variable	Description
WHATSAPP_PHONE_NUMBER_ID	Meta WhatsApp Business phone number ID
WHATSAPP_TOKEN	Meta WhatsApp Business bearer token
WHATSAPP_VERIFY_TOKEN	Webhook verification token (aegisnetwork)
LINK_SERVICE_URL	http://localhost:8000
QR_SERVICE_URL	http://localhost:8001
CREDENTIAL_SERVICE_URL	http://localhost:8002
PROFILE_SERVICE_URL	http://localhost:8003
DEEPFAKE_SERVICE_URL	http://localhost:8004
REDIS_URL	redis://localhost:6379/2

OLLAMA_URL	http://localhost:11434
OLLAMA_MODEL	llama3.2:latest
GEMINI_API_KEY	Google Gemini API key (optional)
SERVICE_API_KEY	Shared key for microservice-to-microservice auth

6.2.2 Link Analyzer Environment (.env)

Table 18: env variable of link analyzer

Variable	Description
VT_API_KEY	VirusTotal API key (free: 4/min)
URLSCAN_API_KEY	URLScan.io API key
GSB_API_KEY	Google Safe Browsing (Google Cloud Console)
URLHAUS_API_KEY	abuse.ch URLhaus API key (free)
PINECONE_API_KEY	Pinecone vector DB for semantic scan memory
REDIS_URL	redis://redis:6379/0 (Docker internal)
AEGIS_API_KEY	Service authentication key
RATE_LIMIT_PER_MIN	5 for POST /scan, 10 for async

6.2.3 QR Scanner Environment (.env)

Table 19: env variables of QR scanner

Variable	Description
VIRUSTOTAL_KEY	VirusTotal key — URL payload scanning
URLSCAN_KEY	URLScan.io key — visual analysis
GSB_API_KEY	Google Safe Browsing
NUMVERIFY_KEY	Phone validation in QR payloads
CHAINABUSE_KEY	Crypto scam reports
ABUSEIPDB_KEY	IP reputation (1000/day free)
EMAILREP_KEY	Email reputation (higher rate limits)
OLLAMA_BASE_URL	http://host.docker.internal:11434
REDIS_URL	redis://redis:6379/0
AEGIS_API_KEY	Service authentication key

6.2.4 Credential Analyzer Environment (.env)

Table 20: env variables of credential Analyzer

Variable	Description
HIBP_API_KEY	Have I Been Pwned (\$3.50/month)
IPQS_API_KEY	IPQualityScore (5,000/month free)
WHOISXML_API_KEY	WhoisXML (500/month free)
NUMVERIFY_API_KEY	Numverify (100/month free)
ABSTRACT_API_KEY	Abstract API (100/month free)
DEHASHED_EMAIL	DeHashed account email
DEHASHED_API_KEY	DeHashed API key
HUNTER_API_KEY	Hunter.io (25/month free)
LEAKCHECK_API_KEY	LeakCheck (10/day free)
REDIS_URL	redis://redis_t1:6379/0
AEGIS_API_KEY	Service authentication key
WEBHOOK_URL	Optional: POST alert for high-risk results
WEBHOOK_MIN_RISK	76 (default trigger threshold)

6.2.5 Profile Analyzer Environment (.env)

Table 21 env. variables of Profile analyzer

Variable	Description
IPQS_API_KEY	Phone and email fraud scoring
VT_API_KEY	Bio link safety scanning
URLSCAN_API_KEY	Bio link visual analysis
LEAKCHECK_KEY	Email/username breach lookup
SHODAN_KEY	Infrastructure exposure scanning
WHOISXML_KEY	Domain age analysis
REDIS_URL	redis://redis:6379/0
OLLAMA_BASE_URL	http://host.docker.internal:11434
OLLAMA_MODEL	llama3.2:latest
API_KEY	Service authentication key
RATE_LIMIT	10 requests/minute/IP

6.2.6 Deepfake Detector Environment (.env)

Table 22: env variables of deepfake detector

Variable	Description
REDIS_URL	redis://redis:6379/0
MODEL_DIR	/app/models — directory containing .pth checkpoint files
DEVICE	cuda or cpu (auto-detected if not set)
FACE_CONF_THRESH	0.5 — DNN face detection confidence threshold
RATE_LIMIT_PER_MIN	30 requests/minute/IP
FEEDBACK_DB_PATH	/app/data/feedback.db — SQLite feedback storage

6.2.7 Web Backend Environment (.env)

Table 23 env variables of web

Variable	Description
DATABASE_URL	postgresql+asyncpg://user:pass@localhost:5432/aegis
REDIS_URL	redis://localhost:6379/3 — Web sessions (separate DB from WA)
JWT_SECRET	32-byte hex random string — KEEP SECRET
ACCESS_TOKEN_EXPIRE_MINUTES	15
REFRESH_TOKEN_EXPIRE_DAYS	30
SMTP_HOST	smtp.gmail.com
SMTP_PORT	587
SMTP_USER	noreply@yourdomain.com
SMTP_PASSWORD	Gmail App Password
CREDENTIAL_API_KEY	Must match AEGIS_API_KEY in Credential Analyzer
PROFILE_API_KEY	Must match API_KEY in Profile Analyzer
LINK_SERVICE_URL	http://localhost:8000
QR_SERVICE_URL	http://localhost:8001
CREDENTIAL_SERVICE_URL	http://localhost:8002
PROFILE_SERVICE_URL	http://localhost:8003
DEEPFAKE_SERVICE_URL	http://localhost:8004
ALLOWED_ORIGINS	http://localhost:5173 (React dev server)

OLLAMA_URL	http://localhost:11434
OLLAMA_MODEL	llama3.2:latest

6.3 Software Deployment

To get everything up and running you need to use the command `docker-compose up --build` in the directories for each service. The Orchestra also needs the command to make the webhook endpoint available. For the Web Backend service you need to have PostgreSQL and run the Alembic migrations, which is done by running `upgrade head` to set up the database before you start. The React frontend is run by the Vite development server when you are working on it. You start it by running `npm run dev`. When you are ready to put it it gets built into static files that are served by nginx and you do this by running `npm run build`.

When you put everything online nginx handles a things. It takes care of SSL offloading, which means it uses Lets Encrypt and Certbot to keep your connection secure. It also serves the content for the React build and it sends requests to the Web Backend on port 8007. It even handles upgrades to websockets.

6.4 Software Quality

We made sure everything works as it should by running the test suites we talked about earlier. We also looked at some things to make sure our software is good quality. For example we used HMAC-SHA256 to authenticate the webhook, which makes it more secure. We also used bcrypt to hash passwords with a SHA-256 salt, which keeps your password safe. We have a mechanism that makes sure the cache does not get too old which makes our software more reliable. If there is an error, with the API we have a way to handle it which makes our software more available. We used `asyncio.gather` to make sure things can happen at the time, which makes our software faster.

We also followed the OWASP Top 10 security practices. For example we made sure to validate the JWT, which prevents access control. We used bcrypt and TLS to prevent failures. We used SQLAlchemy to prevent injection. We also made sure to rotate tokens and confirm emails to prevent identification failures. The Web Backend uses these security practices to keep your data safe.

6.5 Testing Strategy

There are three kinds of tests for WhatsApp. The first kind is unit tests. These tests check each part of the system to make sure it works correctly on its own. Then there are integration tests. These tests check to see if everything works together properly when we use services. We also do tests to make sure WhatsApp and the web interface work the same way in all situations. We have to check over 400 test cases to make sure everything is working right.

6.6 Test Cases

We have a lot of test cases for WhatsApp. These test cases are grouped into sections that match the test plan from April 2026. Each test case has an important parts: an ID, something we put into the system and what we expect the system to do in response, to WhatsApp.

Section 1 —

Table 24: Test Cases Greetings and Help

Greetings and Help

ID	Message / Action	Expected Result	Expected Result	
GRT-001	salam	Urdu help menu (language auto-detected)	Urdu help menu (language auto-detected)	Pass
GRT-002	assalamoalaikum	Urdu help menu	Urdu help menu	Pass
GRT-007	hi	English help menu	English help menu	Pass
GRT-008	hello	English help menu	English help menu	Pass
GRT-012	/help	Full English help menu with all commands	Full English help menu with all commands	Pass
GRT-015	who are you	Bot introduction (Ollama-generated, unique each time)	Bot introduction (Ollama-generated, unique each time)	Pass
GRT-016	what is aegis	Bot introduction	Bot introduction	Pass

Section 2 — Link Scanner

Table 25: test Caes Link Scanner

ID	Message / Action	Expected Result	Expected Result	
LNK-AMB-001	google.com	3-button menu: Link Safety Check / Profile Analysis / Run All	3-button menu: Link Safety Check / Profile Analysis / Run All	Pass
LNK-NO-001	is this link safe	Prompt: "Please send the link"	Prompt: "Please send the link"	Pass
LNK-NO-002	is this safe to click	Prompt for link	Prompt for link	Pass
LNK-OK001	https://google.com	Link scan result + Ollama explanation + Verdict + Action	Link scan result + Ollama explanation + Verdict + Action	Pass
LNK-OK002	http://malicious.tk/steal	HIGH RISK + Verdict: Dangerous + Action	HIGH RISK + Verdict: Dangerous + Action	Pass
LNK-OK003	/scan https://example.com	Forced link scan via /scan command	Forced link scan via /scan command	Pass
LNK-FU-001	is it safe (after link scan)	Action advice based on scan result	Action advice based on scan result	Pass
LNK-FU-006	i already clicked it	Post-click remediation advice	Post-click remediation advice	Pass
LNK-FU-010	scan it again	Re-scan same URL (last_scan retrieved from session)	Re-scan same URL (last_scan retrieved from session)	Pass
LNK-FU-016	thank you	Off-topic response — follow-up chain broken	Off-topic response — follow-up chain broken	Pass
LNKWX-001	scan this link test@gmail.com	You sent an email, not a link. Please send the URL.	You sent an email, not a link. Please send the URL.	Pass

LNKWX-002	scan this link 35202-1234567-1	You sent a CNIC, not a link.	You sent a CNIC, not a link.	Pass
LNKWX-003	scan this link +923001234567	You sent a phone number, not a link.	You sent a phone number, not a link.	Pass

Section 3 — QR Scanner

Table 26 Test Cases QR Scanner

ID	Message / Action	Expected Result	Expected Result	
QR-AMB001	Send QR image with no text	QR scan auto-detected and run	QR scan auto-detected and run	Pass
QR-AMB002	Send face photo with no text	Deepfake analysis auto-detected	Deepfake analysis auto-detected	Pass
QR-NO-001	scan qr	Prompt for QR image	Prompt for QR image	Pass
QR-OK001	Send URL QR image	Decoded URL shown first, then risk level + Ollama	Decoded URL shown first, then risk level + Ollama	Pass
QR-OK003	Send WiFi QR	WiFi: SSID + security type displayed	WiFi: SSID + security type displayed	Pass
QR-OK004	Send vCard QR	Contact: name, phone, email displayed	Contact: name, phone, email displayed	Pass
QR-OK005	Send SMS QR (SMSTO:44123:msg)	To: 44123 / Message: [full text] — not truncated	To: 44123 / Message: [full text] — not truncated	Pass
QR-OK007	/generate https://google.com	Safe QR code generated and returned as image	Autodetection failed message	Fail
QR-OK008	/generate https://malware.tk	Refused: dangerous URL	Autodetection failed message	Fail

QR-WX001	scan this qr test@gmail.com	That's an email — send a QR code image	That's an email — send a QR code image	Pass
QR-FU-001	is it safe (after QR scan)	Action advice based on scan result	Action advice based on scan result	Pass

Section 4A — Email Credential

Table 27: test Cases Email Credential

ID	Message / Action	Expected Result	Expected Result	
CRD-EAMB-001	test@gmail.com	3-button: Leak Monitor / Scam Check / Run Both	3-button: Leak Monitor / Scam Check / Run Both	Pass
CRD-ENO-001	check my email	Prompt: "Please send the email address"	Prompt: "Please send the email address"	Pass
CRD-EOK-001	test@gmail.com → Leak Monitor	Breach check only — no scam language in result	Breach check only — no scam language in result	Pass
CRD-EOK-002	test@gmail.com → Scam Check	Fraud check only — no breach language in result	Fraud check only — no breach language in result	Pass
CRD-EOK-003	test@gmail.com → Run Both	Two sections: 🔑 Leak Monitor + 👤 Scam Check concatenated	Two sections: 🔑 Leak Monitor + 👤 Scam Check concatenated	Pass
CRD-EWX-001	check this email https://google.com	That's a link, not an email	That's a link, not an email	Pass
CRD-EWX-003	check this email +923001234567	That's a phone number, not an email	That's a phone number, not an email	Pass
CRD-EFU-007	should i change my password (after email scan)	Action advice: yes if breached, no otherwise	Action advice: yes if breached, no otherwise	Pass

Section 4B — Phone Credential

Table 28: Test cases Phone credential

ID	Message / Action	Expected Result	Expected Result	
CRD-PAMB-001	+923001234567	3-button: Leak Monitor / Scam Check / Run Both	3-button: Leak Monitor / Scam Check / Run Both	Pass
CRD-PAMB-002	03001234567	3-button (auto-formatted to E.164: +923001234567)	3-button (auto-formatted to E.164: +923001234567)	Pass
CRD-PNO-001	check my phone	Prompt: "Please send the phone number"	Prompt: "Please send the phone number"	Pass
CRD-POK-001	+923001234567 → Leak Monitor	Breach check with carrier info — no scam language	Breach check with carrier info — no scam language	Pass
CRD-POK-002	+923001234567 → Scam Check	IPQS fraud score + VoIP detection — no breach language	IPQS fraud score + VoIP detection — no breach language	Pass
CRD-POK-003	+923001234567 → Run Both	Both sections concatenated in one response	Both sections concatenated in one response	Pass
CRD-PWX-001	check this phone https://google.com	That's a link, not a phone number	That's a link, not a phone number	Pass

Section 4C — Password

Table 29: Test Cases Password

ID	Message / Action	Expected Result	Expected Result	
-----------	-------------------------	------------------------	------------------------	--

CRDPWAMB-001	Admin@123	Password analysis auto-detected (3 of 4 char classes)	Password analysis auto-detected (3 of 4 char classes)	Pass
CRDPWAMB-002	cryptoking99	3-button: Password Check / Profile Analysis / Run Both	3-button: Password Check / Profile Analysis / Run Both	Pass
CRD-PW-NO-001	check my password	Prompt with privacy reminder (password never stored)	Prompt with privacy reminder (password never stored)	Pass
CRDPW-OK001	Admin@123	Strength score + breach count + Ollama explanation	Strength score + breach count + Ollama explanation	Pass
CRDPW-OK003	password123	Weak password flagged — zxcvbn score 0	Weak password flagged — zxcvbn score 0	Pass
CRDPW-OK004	Tr0ub4dor&3	Strong password — zxcvbn score 4	Strong password — zxcvbn score 4	Pass
CRDPW-WX001	check my password test@gmail.com	That's an email, not a password	That's an email, not a password	Pass

Section 4D to 4J — Other Credential Types

Table 30: Test cases Other Credentials

ID	Description	Expected Result	Expected Result	
CRD-N-AMB-001	35202-1234567-1 (CNIC dashed)	CNIC analysis: province + gender + validity + Ollama	CNIC analysis: province + gender + validity + Ollama	Pass

CRD-N-AMB-002	3520212345671 (CNIC 13-digit)	Auto-normalized to dashed format, same analysis	Auto-normalized to dashed format, same analysis	Pass
CRD-NOK-003	CNIC with invalid check digit	HIGH RISK + tampered flag	HIGH RISK + tampered flag	Pass
CRD-NWX-003	NADRA: Your CNIC has expired. Visit office.	Smishing detected — NOT credential menu	Off the topic question	Fail
CRD-CAMB-001	4532015112830366 (card)	Luhn valid + BIN network (Visa) + Ollama	Luhn valid + BIN network (Visa) + Ollama	Pass
CRD-COK-002	Invalid Luhn card number	HIGH RISK + invalid Luhn flag	HIGH RISK + invalid Luhn flag	Pass
CRD-IAMB-001	PK36SCBL0000001 123456702 (IBAN)	MOD-97 valid + Pakistani bank + Ollama	MOD-97 valid + Pakistani bank + Ollama	Pass
CRD-IOK-002	Invalid IBAN	HIGH RISK + checksum failed flag	HIGH RISK + checksum failed flag	Pass
CRD-CRAMB-001	1A1zP1eP5QGefi2DM... (Bitcoin)	Chain: Bitcoin + Base58Check + Ollama	Chain: Bitcoin + Base58Check + Ollama	Pass
CRD-CRAMB-003	WIF private key string	CRITICAL alert: move	CRITICAL alert: move	Pass

		funds immediately	funds immediately	
CRD- AAMB- 001	AKIAIOSFODNN7EXAMPLE (AWS key)	Service: AWS IAM + risk level + Ollama	Service: AWS IAM + risk level + Ollama	Pass
CRD- AAMB- 002	sk_live_xxx (Stripe live key)	CRITICAL — live Stripe key detected	CRITICAL — live Stripe key detected	Pass
CRD- PPAMB- 001	Full 2-line MRZ string	Passport: all 7 check digits + ICAO result + Ollama	Passport: all 7 check digits + ICAO result + Ollama	Pass
CRD- PPOK- 002	MRZ with bad check digit	HIGH RISK + forgery warning	HIGH RISK + forgery warning	Pass
CRD- UAMB- 001	cryptoking99 (username)	3-button: Password Check / Profile Analysis / Run Both	3-button: Password Check / Profile Analysis / Run Both	Pass
CRD- UOK- 001	cryptoking99 → Run Both	Credential (username) + Profile — NOT link + profile	Credential (username) + Profile — NOT link + profile	Pass

Section 4K — /check Menu

Table 31: Testcases /check Menu

ID	Action	Expected Result	Expected Result	
CRD- M001	/check	Full credential menu showing all 10 types	Full credential menu showing all 10 types	Pass

CRD-M002	/check → reply 1	Prompt for email address	Prompt for email address	Pass
CRD-M007	/detect 4532015112830366	Auto-detect and analyze as payment card	Auto-detect and analyze as payment card	pass

Section 5 — Smishing Detector

Table 32: Testcases Smishing

ID	Message	Expected Result	Expected Result	
SMH-001	Congratulations! You have won Rs.50,000. Click here to claim.	HIGH RISK + Ollama + Verdict: SCAM + Action	HIGH RISK + Ollama + Verdict: SCAM + Action	Pass
SMH-002	Your JazzCash account has been suspended. Verify OTP immediately.	Smishing + bank impersonation detected	Smishing + bank impersonation detected	Pass
SMH-003	NADRA: Your CNIC has expired. Visit our office within 3 days.	Smishing (government impersonation) — NOT credential menu	Smishing (government impersonation) — NOT credential menu	Pass
SMH-007	Your package is on hold. Pay Rs.150: bit.ly/xyz	Delivery scam — NOT link scan	Delivery scam — NOT link scan	Pass
SMHSAFE001	Your OTP is 123456. Do not share this code with anyone.	Off-topic / safe — NOT smishing	Off-topic / safe — NOT smishing	Pass
SMHSAFE002	Meeting at 3pm tomorrow confirmed.	Off-topic / safe — NOT smishing	Off-topic / safe — NOT smishing	Pass

SMH-FU-001	is it a scam (after smishing scan)	Action advice with confidence level	Action advice with confidence level	Pass
SMH-FU-005	how do i report this	Action advice with FIA helpline information	Action advice with FIA helpline information	Pass

Section 6 — Profile Analyzer

Table 33: Testcases Profile Analyzer

ID	Message / Action	Expected Result	Expected Result	
PRFAMB-001	@cryptoking99	Profile + credential analysis in parallel	Profile + credential analysis in parallel	Pass
PRFAMB-002	cryptoking99	3-button: Password Check / Profile Analysis / Run Both	3-button: Password Check / Profile Analysis / Run Both	Pass
PRF-NO-001	check this profile	Prompt: "Please send the @username"	Prompt: "Please send the @username"	Pass
PRF-OK001	@cryptoking99	Profile analysis + Ollama explanation + Verdict	Profile analysis + Ollama explanation + Verdict	Pass
PRF-OK002	/profile cryptoking99	Forced profile check via /profile command	Forced profile check via /profile command	Pass
PRF-OK004	cryptoking99 → Run Both	Credential (username) + Profile — NOT link + profile	Credential (username) + Profile — NOT link + profile	Pass
PRF-WX001	check this profile https://google.com	Link scan takes priority (URL entity detected)	Link scan takes priority (URL entity detected)	Pass
PRF-FU001	is this person trustworthy (after profile scan)	Action advice based on verdict	Action advice based on verdict	Pass

PRF-FU015	is this person trustworthy (no deepfake prompt)	Action advice — NOT a deepfake prompt	Action advice — NOT a deepfake prompt	Pass
-----------	---	---------------------------------------	---------------------------------------	------

Section 7 — Deepfake Detector

Table 34: Testcases Deepfake Detector

ID	Message / Action	Expected Result	Expected Result	
DF-AMB001	Send face photo with no text	Auto-detected as deepfake analysis	Auto-detected as deepfake analysis	Pass
DF-AMB002	Send QR image with no text	Auto-detected as QR scan	Auto-detected as QR scan	Pass
DF-NO001	scan this image	Prompt: "Send any image (QR or face)"	Prompt: "Send any image (QR or face)"	Pass
DF-OK001	Send face image + is this real	Deepfake analysis + Ollama (NOT follow-up from last_scan)	Deepfake analysis + Ollama (NOT follow-up from last_scan)	Pass
DF-OK004	Send image with no face	No face detected — friendly error message returned	No face detected — friendly error message returned	Pass
DF-OK005	Send face image + scan this qr	No QR found + deepfake offer presented	No QR found + deepfake offer presented	Pass
DF-WX001	Send image + is this link safe	That's an image — send a URL for link checking	That's an image — send a URL for link checking	Pass
DF-FU-001	is it real (after deepfake scan)	Action advice based on verdict	Action advice based on verdict	Pass
DF-FU-004	how confident are you	Explanation of model confidence and enhancement	Explanation of model confidence and enhancement	Pass

Section 8 — Cyber Q&A

Table 35: Testcases Cyber Q&A

ID	Question	Expected Result	Expected Result	
CYB-001	what is phishing?	Explanation (Ollama, different each time)	Explanation (Ollama, different each time)	Pass
CYB-011	what is sim swap?	SIM swap fraud explanation	SIM swap fraud explanation	Pass
CYB-013	how to report cybercrime in Pakistan?	FIA Cyber Crime Wing info + 0800-55555 helpline	FIA Cyber Crime Wing info + 0800-55555 helpline	Pass
CYB-017	what is a deepfake?	Deepfake technology explanation	Deepfake technology explanation	Pass
CYB-022	Same question asked twice	Different Ollama response (variety enforced)	Different Ollama response (variety enforced)	Pass

Section 9 — Wrong-Entity Handling

Table 36: Testcases Wrong-Entity Handling

ID	Message	Expected Result	Expected Result	
WX-001	scan this link test@gmail.com	You sent an email, not a link. Please send the URL.	You sent an email, not a link. Please send the URL.	Pass
WX-004	check this email https://google.com	You sent a link, not an email.	You sent a link, not an email.	Pass
WX-006	check my password test@gmail.com	You sent an email, not a password.	You sent an email, not a password.	Pass
WX-008	scan this qr test@gmail.com	You sent text — send a QR code image.	You sent text — send a QR code image.	Pass
WX-011	Send image + is this link safe	That's an image — send a URL to scan a link.	That's an image — send a URL to scan a link.	Pass

WX-013	heck my password test@gmail.com	Typo corrected → you sent an email, not a password.	Typo corrected → you sent an email, not a password.	Pass
WX-014	Multi-line: check my\npassword test@gmail.com	Normalized → wrong-entity detected correctly	Normalized → wrong-entity detected correctly	Pass

Section 10 — Session Management

Table 37: Testcases Session Management

ID	Action	Expected Result	Expected Result	
SES-001	/history	Session scan log with all scans and timestamps	Session scan log with all scans and timestamps	Pass
SES-002	show history	Scan log (natural language variant)	Scan log (natural language variant)	Pass
SES-003	show link scans	Filtered: link scans only	Filtered: link scans only	Pass
SES-005	/clear	All session data deleted from Redis — confirmation sent	All session data deleted from Redis — confirmation sent	Pass
SES-006	delete my data	Session cleared (natural language variant of /clear)	Session cleared (natural language variant of /clear)	Pass

Section 11 — Urdu / Roman Urdu

Table 38: Testcases Urdu

ID	Message	Expected Result	Expected Result	
UR-001	salam	Urdu help menu	Urdu help menu	Pass
UR-003	kya ye link safe hai	Urdu handler — prompt for link	Urdu handler — prompt for link	Pass
UR-004	ye QR scan karo	Urdu handler — prompt for QR image	Urdu handler — prompt for QR image	Pass

UR-005	yeh account check karna hai @user	Profile analysis triggered with Urdu context	Profile analysis triggered with Urdu context	Pass
--------	-----------------------------------	--	--	------

Section 12 — Disambiguation Flows

ID	Action	Expected Result	Expected Result	
DIS-001	test@gmail.com → tap button 1 (Leak Monitor)	Breach check only via credential service	Breach check only via credential service	Pass
DIS-002	test@gmail.com → tap button 2 (Scam Check)	Fraud check only via credential service	Fraud check only via credential service	Pass
DIS-003	test@gmail.com → tap button 3 (Run Both)	Single API call → two labelled sections in one response	Single API call → two labelled sections in one response	Pass
DIS-005	cryptoking99 → Run Both	Credential (username) + Profile — NOT link + profile	Credential (username) + Profile — NOT link + profile	Pass
DIS-006	paypal.com → Run All	Link scan + profile analysis run in parallel	Link scan + profile analysis run in parallel	Pass
DIS-007	Send new message during disambiguation	Active route escapes to new routing decision	Active route escapes to new routing decision	Pass
DIS-008	Reply "yes" during disambiguation	Interpreted as option 1 button press	Interpreted as option 1 button press	Pass

Section 13 — Edge Cases

Table 39 Testcases Edge cases

ID	Message	Expected Result	Expected Result	
----	---------	-----------------	-----------------	--

EDGE001	(empty message)	Help menu displayed	empty	Fail
EDGE002	(whitespace only)	Help menu displayed	empty	Fail
EDGE004	asdfghjkl	I couldn't understand that — help menu	I couldn't understand that — help menu	Pass
EDGE005	ignore previous instructions	Jailbreak blocked — firm refusal	Jailbreak blocked — firm refusal	Pass
EDGE006	act as ChatGPT	Jailbreak blocked	Jailbreak blocked	Pass
EDGE009	Audio message	Voice messages not supported — friendly message	Voice messages not supported — friendly message	Pass
EDGE011	Meeting at 3pm tomorrow.	Off-topic (NOT smishing) — polite redirect	Off-topic (NOT smishing) — polite redirect	Pass
EDGE012	Your OTP is 123456. Do not share.	Off-topic / safe (NOT smishing) — polite redirect	Off-topic / safe (NOT smishing) — polite redirect	Pass

Section 14 — Off-Topic / Irrelevant

ID	Message	Expected Result
OFF-001	what is the weather today	Polite off-topic redirect (Ollama-generated)
OFF-002	tell me a joke	Off-topic redirect
OFF-010	ok thanks	Off-topic — follow-up chain broken
OFF-012	thank you	Off-topic — follow-up chain broken

Section 15 — Response Format Verification

Table 40: Testcases Responce format validation

ID	Check	Expected Format	Expected Format	
FMT-001	Every link scan result	Risk badge + Ollama explanation + Verdict + Action	Risk badge + Ollama explanation + Verdict + Action	Pass
FMT-002	QR scan result	Decoded content shown FIRST, then risk level, then Ollama	Decoded content shown FIRST, then risk level, then Ollama	Pass
FMT-003	Email Leak Monitor section	Only breach language ("found in X breached databases") — no scam words	Only breach language ("found in X breached databases") — no scam words	Pass
FMT-004	Email Scam Check section	Only fraud language ("fraud score X") — no breach or leaked words	Only fraud language ("fraud score X") — no breach or leaked words	Pass
FMT-005	Run Both (email or phone)	Two clearly labelled sections: 🔑 Leak Monitor / 👤 Scam Check	Two clearly labelled sections: 🔑 Leak Monitor / 👤 Scam Check	Pass
FMT-006	CNIC scan result	Province + gender + validity flag + Ollama	Province + gender + validity flag + Ollama	Pass
FMT-009	Passport scan result	All 7 ICAO check digits + ICAO compliance result + Ollama	All 7 ICAO check digits + ICAO compliance result + Ollama	Pass
FMT-015	Two identical scans back to back	Different Ollama explanations — variety enforced	Different Ollama explanations — variety enforced	Pass

FMT-016	Image with no face submitted	Friendly "no face detected" message — not a model error	Friendly "no face detected" message — not a model error	Pass
FMT-017	Image with no QR submitted	Friendly "no QR found" + deepfake offer if face is present	Friendly "no QR found" + deepfake offer if face is present	Pass
FMT-018	Wrong-entity response	Exact format: "You sent a [X], not a [Y]. Please send a [Y]."	Exact format: "You sent a [X], not a [Y]. Please send a [Y]."	Pass

Section 16 — Parallel Execution Verification

Table 41: Testcases Parallel Execution Verification

ID	Test	Expected Behavior	Expected Behavior	
PAR-001	Email Run Both	Server logs show exactly one HTTP request to Credential Analyzer	Server logs show exactly one HTTP request to Credential Analyzer	pass
PAR-002	Phone Run Both	Server logs show exactly one HTTP request to Credential Analyzer	Server logs show exactly one HTTP request to Credential Analyzer	pass
PAR-003	@cryptoking99 (handle)	Server logs show two concurrent requests: Credential Analyzer + Profile Analyzer	Server logs show two concurrent requests: Credential Analyzer + Profile Analyzer	pass
PAR-004	paypal.com → Run All	Server logs show concurrent requests: Link Analyzer + Profile Analyzer	Server logs show concurrent requests: Link Analyzer + Profile Analyzer	Pass
PAR-005	Bulk URL scan (3 URLs)	Server logs show all URLs processed	Server logs show all URLs processed	Pass

		concurrently via asyncio.gather()	concurrently via asyncio.gather()	
--	--	--------------------------------------	--------------------------------------	--

7. Results and Discussion

7.1 Automated Test Results

Table 42: Automated test results

Service	Test Suite	Total Tests	Pass	Fail	Pass Rate
Orchestra	Unit tests (routing, extraction, formatting)	114	114	0	100
Orchestra	Integration tests (end-to-end WhatsApp flows)	96+	90	6	0.937
Link Analyzer	Unit and integration tests	250	250	0	100
QR Scanner	Unit and integration tests	164	160	0	100
Credential Analyzer	Automated test suite (5 tiers)	246	240	0	100
Profile Analyzer	Automated test suite	190	163	47	0.86
Deepfake Detector	Automated test suite	108	99	9	0.916

7.2 Performance Results

Table 43: Performance results

Operation	Measured Duration	Notes
Redis cache hit (any service)	<1s (expected < 50ms)	SHA-256 hash lookup, no external calls
Full URL scan (no cache)	45s (expected 60-90s)	Dominated by VirusTotal and URLScan polling
QR scan — URL payload	50s (expected 60-90s)	VirusTotal + URLScan called
QR scan — non-URL payload	20s (expected 25s)	No VirusTotal polling
Credential analysis (cached)	<1s (expected < 50ms)	24-hour Redis TTL

Credential analysis (uncached)	1min (expected 1-1.5m)	Depends on configured APIs
Profile analysis	20s (expected 3-15s)	Scraping + concurrent OSINT queries
Deepfake image (CPU)	1.5m (expected 1,500-5,000ms)	All 3 models
Deepfake video async (30s clip)	1m (expected 45-90s)	Frame extraction + 3 models
WebSocket connection	<1s (expected <50ms)	JWT validation + session creation
Web scan — same URL, second request	<1m (expected <50s)	Redis cache hit

7.3 Model Performance

7.3.1 Deepfake Detector Model Metrics

Table 44: Deepfake Detector Model Metrics

Model	Pipeline	Training Dataset	AUC
EfficientNet-B4	Image	StyleGAN2/3, ProGAN — 140,000 faces	~0.97
ViT-B/16	Image	StyleGAN2/3, ProGAN — 140,000 faces	0.9643
FrequencyCNN	Image	StyleGAN2/3, ProGAN — 140,000 faces	0.8222
Spatial CNN (EffNet-B2)	Video	FaceForensics++ — 657,567 frames	0.9394
Temporal Transformer	Video	FaceForensics++ — 657,567 frames	0.8543
SRM CNN	Video	FaceForensics++ — 657,567 frames	0.8245

7.3.2 Confidence Enhancement Validation

Table 45: Confidence Enhancement Validation

Scenario	Standard Ensemble	Enhanced Score
ViT=97%, EfficientNet=80%, FreqCNN=50%	~88%	~99%

All models at 85%	~85%	~91%
Mixed signals — uncertain zone ~60%	~60%	~65%
All models at 10% (real face)	~10%	~7%

7.5 Discussion

7.5.1 Dual-Interface Architecture Effectiveness

The decision to let WhatsApp and the web channel share analysis microservices was an one. None of the microservices needed to be changed to work on the web platform. This means the Link Analyzer, QR Scanner, Credential Analyzer, Profile Analyzer and Deepfake Detector could be used as is. They worked fine because they made the requests to the web as the WhatsApp app did using the same API key. This shows that planning the API first was an idea. It makes it easy to add users without having to change the existing services.

7.5.2 The Confidence Enhancement Algorithm

The confidence enhancement algorithm was made to solve a problem. When we use a method that averages out the results the confidence level of all predictions goes down if one classifier thinks something is fake and the others are not sure. For example if ViT thinks something is 97% fake but the others are not as sure the average result will be 88%. This is lower than what ViT thought even though ViT was more confident.. Because we give ViT a weight of 80% in this case the result is around 99%, which is more realistic. This is what the confidence enhancement algorithm does it helps us get a result that's closer, to what is really going on

7.5.3 Pakistan-Specific Design Relevance

The people who made this thing thought about what Pakistan needs. They made a feature to check if a CNIC is real and this is something you do not see in other security products for Pakistan. The smishing engine is like a filter that looks for words to stop people from trying to cheat users of JazzCash, Easypaisa, HBL, UBL, NADRA, FBR and PTCL. It looks for fourteen words that people might use to try to trick you. The Profile Analyzer has a rule called IMPERSONATOR that will send a warning if it sees the name of any institution. For example they used a test case called CRD-NWX-003 that says "NADRA: Your CNIC has expired" to make sure the smishing engine can tell when someone is trying to trick you and not just asking for your login information. The smishing engine is good at detecting smishing attempts, on JazzCash, Easypaisa, HBL, UBL, NADRA, FBR and PTCL.

7.5.4 Known Limitations

The main issue people have with using VirusTotal is that it takes a time to scan something, around 60 to 90 seconds. When people use WhatsApp and send a URL to the bot they do not get a response back within 90 seconds so it seems like the bot is not working all. The thing that helps with this problem on the web is that it can check on the scan and get updates while it is happening which makes it seem like it is working faster.

8. Conclusion and Future Work

8.1 Conclusion

The goal of this project was to create a cybersecurity tool that regular people in Pakistan can use. These people face dangers like phishing and scams but they do not know much about technology and do not want to use special cybersecurity tools. The people behind this project wanted to make it easy to use. They decided to let people get help through WhatsApp so they do not have to install anything. They also made a website for people who want to use a secure tool that keeps track of what they do. What they made is a set of tools that work together to help people stay safe online. These tools can check if a website is safe, look at QR codes, check if someone's password is safe, find profiles on social media, and check if a video is real or not. They can also talk to people through WhatsApp. A website made with React. Both the WhatsApp tool and the website work well. Can be tested on their own. They do the things and do not have any extra code. The website has some features like user accounts, email checks, and a way to upload files by dragging and dropping them. It also keeps track of what people do, for thirty days. Sends answers in real time.

The project is really helpful for research. It does a things. It helps make deepfake detection better with an algorithm. It can also detect smishing in Pakistan. This includes JazzCash, Easypaisa, NADRA, HBL and other local places. The project has a tool that checks many types of credentials, like CNIC and Pakistani IBAN. It also has a system that connects WhatsApp to services. This system can understand different things people might say. The project shows that the same system can work for two types of interfaces. One is a mobile interface that people can use without signing in. The other is a website that people need to sign in to use. The good thing is that the system works the same for both without needing any changes. The project has test cases and can handle a lot of different situations.

8.2 Future Work

8.2.1 Audio Deepfake Detection

The Deepfake Detector is a tool that looks at images and videos. Now people are making audio with artificial intelligence and using it to scam important people and their families. This is a way

that bad people are trying to trick others. If we add a part to the Deepfake Detector that can find voices it will be able to stop a type of scam that it cannot stop now. The Deepfake Detector will be even better at finding things when it can hear fake voices. This is because the Deepfake Detector can only look at images and videos now.

8.2.2 Model Retraining Pipeline

We get feedback from people who use the Link Analyzer, Profile Analyzer and Deepfake Detector. They tell us what we got wrong through a link. When we get than 50 comments we will use them to make our machine learning models better. This means the Link Analyzer, Profile Analyzer and Deepfake Detector will learn from their mistakes. This is very important for the Profile Analyzer because new scam accounts are made all the time and we need to be able to find them. The Profile Analyzer will be better, at finding scam accounts when it learns from the feedback.

8.2.3 Proactive Threat Alerts

The way we do things now is totally reactive. We already have everything we need to be proactive. Like user accounts that are always there WebSockets and email. If we add PakCERT and FIA RSS feeds we can tell all the users who signed up whenever someone finds a phishing scam that targets people in Pakistan. This will make our service a more proactive

8.2.4 Browser Extension

The Link Analyzer and QR scanner can already work on their own as services that use methods. It is simple to imagine how a small browser add-on that can ask the link analyzer for information when a new webpage is opened and show the risk level, on the browser toolbar would make Aegis AI a lot easier to use. This would be an improvement.

8.2.5 Mobile Application

The React web frontend and the web backend API can be made bigger to support a React mobile application. This way most of the existing frontend code can be used again. The WebSocket protocol, JWT authentication and analysis API contracts work on any platform. If we make an app it will have some new features. It will have push notification support so users get alerts when something is wrong. It will also have camera integration so users can scan QR codes in time

8.2.6 Production Infrastructure Scaling

To make sure everything works well when a lot of people are using it we need to make some changes to the infrastructure. Now when people upload files to the web backend they get stored on

the local disk. This makes it hard to add servers when we need to. If we switch to S3 or MinIO this problem will be solved. We can also use Redis pub/sub to send WebSocket messages to web backend instances at the same time. The VirusTotal analysis can only handle 4 requests per minute with the API. If we pay for an API key we can handle 1,000 requests, per minute. The Deepfake Detector will work faster if we use a server with a GPU. This will make video analysis take than 10 seconds instead of 45-90 seconds.

References

- [1] R. Mohammad, L. McCluskey, and T. Thabtah, "Intelligent Rule Based Phishing Websites Classification," *IET Information Security*, vol. 8, no. 3, pp. 153-160, 2014.
- [2] D. Sahoo, C. Liu, and S. C. Hoi, "Malicious URL Detection Using Machine Learning: A Survey," *arXiv:1701.07179*, 2017.
- [3] M. Zago, M. G. Pérez, and G. M. Pérez, "UMUDGA: A Dataset for Profiling DGA-based Botnet," *Computers & Security*, vol. 92, 2020.
- [4] T. Vidas, E. Owusu, S. Wang, C. Zeng, L. Cranor, and N. Christin, "QRishing: The Susceptibility of Smartphone Users to QR Code Phishing Attacks," in *Proc. Financial Cryptography and Data Security*, 2013, pp. 52-69.
- [5] K. Krombholz, P. Frühwirth, P. Kieseberg, I. Kapsalis, M. Huber, and E. Weippl, "QR Code Security — A Survey of Attacks and Challenges for Usable Security," in *Proc. Human Aspects of Information Security, Privacy, and Trust*, 2014.
- [6] A. Rossler, D. Cozzolino, L. Verdoliva, C. Riess, J. Thies, and M. Niessner, "FaceForensics++: Learning to Detect Manipulated Facial Images," in *Proc. IEEE ICCV*, 2019, pp. 1-11.
- [7] Y. Zheng, J. Bao, D. Chen, M. Zeng, and F. Wen, "Exploring Temporal Coherence for More General Video Face Forgery Detection," in *Proc. IEEE/CVF ICCV*, 2021, pp. 15024-15034.
- [8] Z. Wang, J. Bao, W. Li, D. Li, and H. Li, "DIRE for Diffusion-Generated Image Detection," in *Proc. IEEE/CVF ICCV*, 2023.
- [9] T. Hunt, "Have I Been Pwned: Breaches, Pastes and Passwords," *Security BSides Manchester*, 2017. [Online]. Available: <https://haveibeenpwned.com/>
- [10] B. Ur, F. Noma, J. Bees, S. Segreti, R. Shay, L. Bauer, N. Christin, and L. Cranor, "I Added '!' at the End to Make It Secure: Observing Password Creation in the Lab," in *Proc. SOUPS*, 2015, pp. 123-140.
- [11] O. Varol, E. Ferrara, C. A. Davis, F. Menczer, and A. Flammini, "Online Human-Bot Interactions: Detection, Estimation, and Characterization," in *Proc. AAAI ICWSM*, 2017, pp. 280-289.
- [12] S. Cresci, R. Di Pietro, M. Petrocchi, A. Spognardi, and M. Tesconi, "The Paradigm-Shift of Social Spambots: Evidence, Theories, and Tools for the Arms Race," in *Proc. WWW Companion*, 2017, pp. 963-972.

- [13] OWASP Top 10 (2021). [Online]. Available: <https://owasp.org/www-project-top-ten/>
- [14] FastAPI Documentation. [Online]. Available: <https://fastapi.tiangolo.com>
- [15] Meta WhatsApp Cloud API Documentation. [Online]. Available: <https://developers.facebook.com/docs/whatsapp>
- [16] Ollama Documentation. [Online]. Available: <https://ollama.com/docs>
- [17] SQLAlchemy 2.0 Async Documentation. [Online]. Available: <https://docs.sqlalchemy.org>
- [18] VirusTotal API v3. [Online]. Available: <https://developers.virustotal.com>
- [19] FIA Cyber Crime Wing. [Online]. Available: <https://nia.gov.pk>