

UNIVERSITY OF ENGINEERING & TECHNOLOGY PESHAWAR

(Jalozai Campus)



NAME: AZKA KARIM

REG NO: 24JZELE0557

DEPARTMENT: ELECTRICAL

SUBJECT: INTRODUCTION TO AI

TEACHER NAME: SIR IRSHAD

ASSIGNMENT NO 2

Introduction

The goal is to manually read a CSV file using Python and the `csv` module. The file contains three columns: **Day**, **Hour**, and **Consumption** (in watts).

We needed to store each column separately, then group the consumption values:

- First by **hour**,
- Then by **day**.

After grouping, the program calculates averages, peak values, and totals.

Objectives

1. Load the CSV file using the `csv` module

- Store each column into separate lists:
 - `days = []`
 - `hours = []`
 - `consumptions = []`

2. Group consumption by hour

Create a dictionary like:

```
{ 1: [200, 700, 800, 500],  
  2: [300, 600, 700, 400],  
  3: [500, 400, 600, 650] }
```

Then compute:

- Average consumption per hour
- Peak consumption per hour

3. Group consumption by day

Create a dictionary such as:

```
{ 7: [200,300,500,700,600,400],  
  8: [800,700,600,500,400,650] }
```

Then compute:

- Total consumption per day
- Daily average consumption

Methodology

1. The CSV is opened using `csv.reader`.
2. The header row is skipped.

3. Each value of Day, Hour, and Consumption is extracted and stored in the three lists.
4. Two dictionaries are used:
 - One for grouping by hour
 - One for grouping by day
5. Basic Python functions (sum, max, division) are used to compute the statistics.
6. Results are printed in a clear and simple format.

Python Code Used

```
import csv
days = [ ]
hours = [ ]
consumptions = [ ]

with open("assignment.csv") as file:
    reader = csv.reader(file)
    next(reader) # skip header

    for row in reader:
        days.append(int(row[0]))
        hours.append(int(row[1]))
        consumptions.append(float(row[2]))

hour_groups = { }

for i in range(len(hours)):
    h = hours[i]
    c = consumptions[i]

    if h not in hour_groups:
        hour_groups[h] = []
    hour_groups[h].append(c)

# Compute hour-wise stats
print(" Consumption Grouped by Hour ")

for h in hour_groups:
    values = hour_groups[h]
    avg = sum(values) / len(values)
    peak = max(values)

    print("Hour:", h)
    print(" Values:", values)
    print(" Average:", avg)
    print(" Peak:", peak)
    print()

day_groups = { }

for i in range(len(days)):
```

```

d = days[i]
c = consumptions[i]

if d not in day_groups:
    day_groups[d] = [ ]
    day_groups[d].append(c)

print("Consumption Grouped by Day ")

for d in day_groups:
    values = day_groups[d]
    total = sum(values)
    avg = total / len(values)

    print("Day:", d)
    print(" Values:", values)
    print(" Total:", total)
    print(" Average:", avg)
    print()

```

Results

Consumption Grouped by Hour

Hour	Values	Average	Peak
1	[200, 700, 800, 500]	550	800
2	[300, 600, 700, 400]	500	700
3	[500, 400, 600, 650]	537.5	650

Consumption Grouped by Day

Day	Values	Total	Average
7	[200,300,500,700,600,400]	2700	450
8	[800,700,600,500,400,650]	3650	608.33

Conclusion

This assignment helped me understand how to:

- Read CSV files manually without pandas
- Store columns in separate lists
- Perform manual "group by" operations
- Use dictionaries to organize data
- Calculate averages, totals, and peak values



Assignment 2

By: Azka Karim

This program groups consumption by hour and by day from a CSV file

and calculates averages and totals.

```
In [1]: import csv
```

```
days = []  
hours = []  
consumptions = []
```

```
In [ ]: with open("assignment.csv") as file:
```

```
    reader = csv.reader(file)  
    next(reader)  
  
    for row in reader:  
        days.append(int(row[0]))  
        hours.append(int(row[1]))  
        consumptions.append(float(row[2]))
```

```
In [4]: hour_groups = {}
```

```
for i in range(len(hours)):  
    h = hours[i]  
    c = consumptions[i]  
  
    if h not in hour_groups:  
        hour_groups[h] = []  
    hour_groups[h].append(c)
```

```
In [5]: print("Consumption Grouped by Hour ")
```

```
for h in hour_groups:  
    values = hour_groups[h]  
    avg = sum(values) / len(values)  
    peak = max(values)  
  
    print("Hour:", h)  
    print("  Values:", values)  
    print("  Average:", avg)  
    print("  Peak:", peak)
```

```
print()
```

Consumption Grouped by Hour

Hour: 1

Values: [200.0, 700.0, 800.0, 500.0]

Average: 550.0

Peak: 800.0

Hour: 2

Values: [300.0, 600.0, 700.0, 400.0]

Average: 500.0

Peak: 700.0

Hour: 3

Values: [500.0, 400.0, 600.0, 650.0]

Average: 537.5

Peak: 650.0

```
In [6]: day_groups = {}

for i in range(len(days)):
    d = days[i]
    c = consumptions[i]

    if d not in day_groups:
        day_groups[d] = []
    day_groups[d].append(c)
```

```
In [7]: print("Consumption Grouped by Day ")

for d in day_groups:
    values = day_groups[d]
    total = sum(values)
    avg = total / len(values)

    print("Day:", d)
    print("  Values:", values)
    print("  Total:", total)
    print("  Average:", avg)
    print()
```

Consumption Grouped by Day

Day: 7

Values: [200.0, 300.0, 500.0, 700.0, 600.0, 400.0]

Total: 2700.0

Average: 450.0

Day: 8

Values: [800.0, 700.0, 600.0, 500.0, 400.0, 650.0]

Total: 3650.0

Average: 608.3333333333334