



PSCRB (Proficiency in Survival Craft and Rescue Boats)

101 Practice Questions and Answers for STCW Exams

Updated for DG Shipping India Exams | Source: brightmariner.com

Practice Set 1

Q1. You are picking up a person who has fallen overboard. A rescue boat should be maneuvered to normally approach the victim with the

- A) victim to leeward
- B) victim to windward
- C) wind on your port side
- D) wind on your starboard side

Correct Answer: A (victim to leeward)

Q2. Which will be the worst of emergencies that you would face, if that happens?

- A) Flooding
- B) Collision
- C) Grounding
- D) Foundering

Correct Answer: D (Foundering)

Q3. What is the biggest danger to life when your vessel has collided with another ship?

- A) Oil Pollution
- B) Breaching of Compartments
- C) Damage to the ship
- D) Possibility of Capsizing

Correct Answer: D (Possibility of Capsizing)

Q4. If the hydrostatic release mechanism for an inflatable life raft is not periodically serviced and becomes inoperative, it will NOT

- A) set the water lights on immersion
- B) release the dye-maker for the life raft
- C) free the life raft from a sinking vessel
- D) break the seal on the carbon dioxide cylinder

Correct Answer: C (free the life raft from a sinking vessel)



- A) drag the raft ashore and lash it down for shelter
- B) find some wood for a fire
- C) get the provisions out of the raft
- D) set the raft back out to sea so someone may spot it

Correct Answer: A (drag the raft ashore and lash it down for shelter)

Q6. When a person who has fallen overboard is being picked up by a rescue boat, the boat should normally approach with the wind

- A) astern and the victim just off the bow
- B) ahead and the victim just off the bow
- C) just off the bow and the victim to windward
- D) just off the bow and the victim to leeward

Correct Answer: D (just off the bow and the victim to leeward)

Q7. A person has fallen overboard and is being picked up with a rescue boat. If the person appears in danger of drowning, the rescue boat should be maneuvered to make

- A) An approach from leeward
- B) an approach from windward
- C) the most direct approach
- D) an approach across the wind

Correct Answer: C (the most direct approach)

Q8. If the hydrostatic release mechanism for an inflatable life raft is not periodically serviced and becomes inoperable, it will fail to

- A) set the water lights on immersion
- B) release the dye marker from the life raft
- C) free the life raft from the vessel
- D) break the seal on the carbon dioxide cylinder

Correct Answer: C (free the life raft from the vessel)

Q9. If you are forced to abandon ship in a lifeboat, you should

- A) remain in the immediate vicinity
- B) head for the nearest land
- C) head for the closest sea-lanes
- D) vote on what to do, so all hands will have a part in the decision

Correct Answer: A (remain in the immediate vicinity)

Q10. When making a permanent repair to an inflatable life raft using a repair kit, how long after the repair is made should you hold off 'topping up' the lost air?

- A) You do not have to hold off
- B) 12 hours
- C) 24 hours
- D) 2 hours



Q11. What prevents an inflated liferaft from being pulled under by a vessel which sinks in water over 100 feet in depth?

- A) The hydrostatic release
- B) Nothing
- C) A Rottmer release
- D) The weak link in the painter line

Correct Answer: D (The weak link in the painter line)

Q12. What is placed on the underside of an inflatable liferaft to help prevent it from being skidded by the wind or overturned?

- A) Ballast bags
- B) A keel
- C) Strikes
- D) Sea anchor

Correct Answer: A (Ballast bags)

Q13. The purpose for the bag or box on top of some survival craft is to

- A) right the craft in case of capsizing
- B) increase area for radar detection
- C) act as a sail in case of a power loss
- D) steady the craft in heavy seas

Correct Answer: A (right the craft in case of capsizing)

Q14. If your vessel is equipped with inflatable life rafts, how should they be maintained?

- A) Have your crew check them annually
- B) They do not need any maintenance
- C) Have them sent ashore to an approved maintenance facility annually
- D) Have them serviced by the shipyard annually

Correct Answer: C (Have them sent ashore to an approved maintenance facility annually)

Q15. On most makes of inflatable life rafts, the batteries to operate the light on the inside of rafts can be made to last longer by

- A) unscrewing the bulb during daylight
- B) operating the switch for the light
- C) taking no action as there is no way of preserving power
- D) taking no action as they shut off automatically in daylight

Correct Answer: B (operating the switch for the light)



- A) on the port side
- B) on the starboard side
- C) aft of the forward lifeboat on the port side
- D) aft of the forward lifeboat on the starboard side

Correct Answer: B (on the starboard side)

Q17. If your vessel is equipped with inflatable life rafts, how should they be maintained?

- A) Have your crew check them annually.
- B) They do not need any maintenance.
- C) Have them sent ashore to an approved maintenance facility. =D) Have them serviced by the shipyard.

Correct Answer: C (Have them sent ashore to an approved maintenance facility. =D) Have them serviced by the shipyard.

Q18. The marine evacuation system shall be capable of transfer of persons from ship within

- A) 5 min in the case of a passenger ship
- B) 10 min in the case of a passenger ship
- C) 20 min in the case of a passenger ship
- D) 30 min in the case of a passenger ship

Correct Answer: D (30 min in the case of a passenger ship)

Q19. The marine evacuation system shall be capable of deployment

- A) by one person
- B) by two persons
- C) by three persons
- D) by four persons

Correct Answer: A (by one person)

Q20. If you must abandon a ship in VERY HEAVY SEAS, in a survival craft, when should you remove the safety pin and pull the hook release?

- A) Immediately upon launching
- B) One to three feet before first wave contact
- C) Upon first wave contact
- D) Only when waterborne

Correct Answer: B (One to three feet before first wave contact)

Q21. Provided every effort is used to produce, as well as preserve body moisture content by avoiding perspiration, how long is it normally possible to survive without stored quantities of water?

- A) Up to 3 days
- B) 8 to 14 days
- C) 15 to 20 days
- D) 25 to 30 days

Correct Answer: B (8 to 14 days)



- A) when there is no load on the cable
- B) when there is a load on the cable
- C) only when the doors are closed
- D) when the engine is started

Correct Answer: A (when there is no load on the cable)

Q23. A life line must be connected to the life raft

- A) at the bow
- B) at the stern
- C) in the middle
- D) all around

Correct Answer: D (all around)

Q24. Your ship is sinking rapidly. A container containing an inflatable life raft has bobbed to the surface upon functioning of the hydrostatic release. Which action should you take?

- A) Cut the painter so it will not pull the life raft container down.
- B) Swim away from the container so you will not be in danger as it goes down.
- C) Take no action because the painter will cause the life raft to inflate and open the container.
- D) Manually open the container and inflate the life raft with the hand pump.

Correct Answer: C (Take no action because the painter will cause the life raft to inflate and open the container.)

Q25. Limit switches on gravity davits should be tested by

- A) the engineers, from a panel in the engine room
- B) shutting off the current to the winch
- C) pushing the switch lever arm while the winch is running

Correct Answer: C (pushing the switch lever arm while the winch is running)

Q26. The hand brake of a lifeboat winch is

- A) manually disengaged when hoisting a boat
- B) applied by dropping the counterweighted lever
- C) controlled by the centrifugal brake mechanism
- D) automatically engaged if lowering speed is excessive

Correct Answer: B (applied by dropping the counterweighted lever)

Q27. The sea painter of an inflatable life raft should be

- A) free running on deck
- B) faked out next to the case
- C) secured to a permanent object on deck via a weak link
- D) stowed near the raft

Correct Answer: C (secured to a permanent object on deck via a weak link)



- A) To cut off the power when the davits hit the track safety stops
- B) To stop the davits from going too fast
- C) To cut off the power when the davits are about 12 inches or more from the track safety stops

Correct Answer: C (To cut off the power when the davits are about 12 inches or more from the track safety stops)

Q29. To turn over an inflatable life raft that is upside down, you should pull on the

- A) canopy
- B) manropes
- C) sea painter
- D) righting strap

Correct Answer: D (righting strap)

Q30. The purpose of the tripping line on a sea anchor is to

- A) aid in casting off
- B) direct the drift of the vessel
- C) aid in its recovery
- D) maintain maximum resistance to broaching

Correct Answer: C (aid in its recovery)

Practice Set 2

Q1. In normal conditions, in exterior spaces the minimum sound pressure levels for broadcasting emergency announcements shall be

- A) 50 DB
- B) 100 DB
- C) 75 DB
- D) 80 DB

Correct Answer: D (80 DB)

Q2. Sea sickness is caused by rolling or rocking motions which affect the fluids in the

- A) Stomach
- B) Lower intestine
- C) Inner ear
- D) Bladder

Correct Answer: C (Inner ear)



- A) 15000 CD
- B) 20000 CD
- C) 25000 CD
- D) None of the above

Correct Answer: A (15000 CD)

Q4. The marine evacuation system shall be capable of transfer of persons from ship within

- A) 5 min in the case of a passenger ship
- B) 10 min in the case of a passenger ship
- C) 20 min in the case of a passenger ship
- D) 30 min in the case of a passenger ship

Correct Answer: D (30 min in the case of a passenger ship)

Q5. The maximum length of a rescue boat

- A) 8.5 meter
- B) 7.3 meter
- C) 3.8 meter
- D) None of the above

Correct Answer: A (8.5 meter)

Q6. The duration of life jacket self-igniting light is

- A) 4 hours
- B) 5 hours
- C) 6 hours
- D) 8 hours

Correct Answer: D (8 hours)

Q7. The luminous intensity of a life jacket light

- A) 0.25 CD
- B) 0.50 CD
- C) 0.75 CD
- D) 0.85 CD

Correct Answer: C (0.75 CD)

Q8. How many buoyant smoke signals are available in life raft?

- A) 2
- B) 4
- C) 6
- D) 8

Correct Answer: A (2)



- A) 1 liter
- B) 2 liters
- C) 1.5 liter
- D) 3 liters

Correct Answer: C (1.5 liter)

Q10. What is the range of SART for detecting aircraft?

- A) 10 nm
- B) 20 nm
- C) 30 nm
- D) None of the above

Correct Answer: C (30 nm)

Q11. SART lithium battery voltage

- A) 2 V
- B) 4 V
- C) 5 V
- D) None of the above

Correct Answer: C (5 V)

Q12. The immersion suit does not allow the body temperature to drop by more than when immersed for a period of when the water temperature is between 0 and 2 degrees

- A) 2 degrees, 4 hours
- B) 2 degrees, 6 hours
- C) 1 degree, 4 hours
- D) 1 degree, 6 hours

Correct Answer: A (2 degrees, 4 hours)

Q13. Your small vessel is broken down and rolling in heavy seas. You can reduce the possibility of capsizing by

- A) Rigging a sea anchor
- B) Constantly shifting the rudder
- C) Moving all personnel forward and low
- D) Moving all personnel aft

Correct Answer: A (Rigging a sea anchor)

Q14. Which statement concerning homing signals in the GMDSS is false?

- A) A homing signal provides a bearing for rescue personnel to follow to the signal's source
- B) A homing signal is detected by the COSPAS-SARSAT satellites
- C) A homing signal cannot be detected by a GPS receiver
- D) A homing signal may be transmitted by equipment attached to the survival craft

Correct Answer: B (A homing signal is detected by the COSPAS-SARSAT satellites)



- A) Hand-held red flare
- B) Self-contained rocket-propelled parachute red flare
- C) Hand-held orange smoke distress flare
- D) Red aerial pyrotechnic flare

Correct Answer: C (Hand-held orange smoke distress flare)

Q16. How can a SART's effective range be mixed?

- A) The SART should be placed in water immediately upon activation
- B) The SART should be held as high as possible
- C) Switch the SART into the "high" power position
- D) If possible, the SART should be mounted horizontally so that its signal matches that of the searching radar signal

Correct Answer: B (The SART should be held as high as possible)

Q17. Your vessel has 3 lifeboats on each side. The after most boat on the star board side is designated as boat number

- A) 6
- B) 5
- C) 3
- D) 3 STARBOARD

Correct Answer: B (5)

Q18. What is the first action in case of man overboard?

- A) Throw a life buoy
- B) Inform bridge
- C) Raise alarm
- D) None of the above

Correct Answer: A (Throw a life buoy)

Q19. All pyrotechnics have a shelf life of

- A) 48 months
- B) 3 years
- C) 5 years
- D) None of the above

Correct Answer: A (48 months)

Q20. VHF EPIRB is designed to be used in which areas?

- A) Area A1
- B) Area A1-A2
- C) Area A4
- D) None of the above

Correct Answer: A (Area A1)



- A) Drink a gallon of water
- B) Take anti sea sickness tablet
- C) Use fishing tackle and fish
- D) All of the above

Correct Answer: B (Take anti sea sickness tablet)

Q22. As per the regulation life savings appliances need NOT to have?

- A) Bright color with reflective tape
- B) Resistant to sunlight
- C) Ready accessible and easy to launch
- D) None of the above

Correct Answer: B (Resistant to sunlight)

Q23. Davit of rescue boats due to limit switch how much before the end ?

- A) 10 inches
- B) 2 inches
- C) 1 inch
- D) 15 inches

Correct Answer: C (1 inch)

Q24. How much is the maximum capacity of the life boat?

- A) 20 persons
- B) 100 persons
- C) 150 persons
- D) 60 persons

Correct Answer: C (150 persons)

Q25. Frequency at which the SART operates

- A) 5 Ghz, 3 cm X band
- B) 9 Ghz, 9 cm X band
- C) 9 Ghz, 3 cm X band
- D) 5 Ghz, 9 cm X band

Correct Answer: C (9 Ghz, 3 cm X band)

Q26. How much is the duration of the hand flare for the time it works?

- A) 60 seconds
- B) 90 seconds
- C) 5 seconds
- D) 30 seconds

Correct Answer: A (60 seconds)



- A) Can be launched in calm weather only
- B) 5-degree list
- C) 10-degree list
- D) Up to 20 degrees

Correct Answer: D (Up to 20 degrees)

Q28. At what maximum trim of a vessel, the lifeboats are designed to be launched

- A) 15 degrees
- B) Calm weather
- C) 10 degrees
- D) 30 degrees

Correct Answer: C (10 degrees)

Q29. Safety training on board to the personnel is provided as per the?

- A) SOLAS
- B) MLC
- C) ISM
- D) STCW

Correct Answer: D (STCW)

Q30. Hatches on the life boat are designed such that?

- A) Watertight and can be opened and closed from both sides
- B) Watertight and can be opened and closed from only inside
- C) Self-closing type
- D) Bolted type with watertight capabilities

Correct Answer: A (Watertight and can be opened and closed from both sides)

Practice Set 3

Q1. Good housekeeping is considered necessary for preventing accidents at sea, what is true regarding same?

- A) Securing tools after work is not needed as we need them next day also
- B) Engine room should be locked, when no one is inside
- C) Wearing dirty clothes in a galley or mess room should be avoided
- D) None of the above

Correct Answer: C (Wearing dirty clothes in a galley or mess room should be avoided)

Q2. How can you indicate that your vessel is distress?

- A) Sounding five or more short and rapid blasts on the whistle
- B) Continuously sounding the fog whistle
- C) Displaying a large red flag
- D) Displaying three black balls in a vertical line

Correct Answer: B (Continuously sounding the fog whistle)



- A) Removing the rubber packing strip
- B) Pulling a cord
- C) Throwing the center container overboard
- D) Cutting the wire restraining bands

Correct Answer: C (Throwing the center container overboard)

Q4. "Thermal protective aids" are required for what percentage of the persons a survival craft is equipped to carry?

- A) 10%
- B) 50%
- C) 75%
- D) 100%

Correct Answer: A (10%)

Q5. Which gas is mostly used in filling the cylinder of inflatable life raft

- A) Oxygen
- B) CO2
- C) Nitrogen
- D) Carbon mono oxide

Correct Answer: B (CO2)

Q6. Regulations regarding lifeboats on board is best described by?

- A) Two life boats on each side, with each having a carrying capacity of 125%
- B) Lifeboat color can be any as available
- C) Engine fitted on lifeboats should be air started
- D) Lifeboats cannot be used as rescue boats

Correct Answer: A (Two life boats on each side, with each having a carrying capacity of 125%)

Q7. SART works on which radar

- A) S band
- B) X band
- C) Y Band

Correct Answer: B (X band)

Q8. Which item in the life boat is a study material?

- A) Instruction on how to survive
- B) Sea sickness kit
- C) Bailer
- D) Heliograph

Correct Answer: A (Instruction on how to survive)



- A) SOLAS under chapter II (2) and (3)
- B) COSWP
- C) Local regulation
- D) ISPS code

Correct Answer: A (SOLAS under chapter II (2) and (3))

Q10. How long SART operate in standby mode

- A) 8 hrs.
- B) 24 hrs.
- C) 96 hrs.
- D) None of the above

Correct Answer: C (96 hrs.)

Q11. Which of the following is consumable

- A) Food ration
- B) Drinking water
- C) Anti-sea sickness tablets
- D) All of the above

Correct Answer: D (All of the above)

Q12. Life jacket light shall have a source of energy capable of providing luminous intensity of for a period of

- A) .75 cd/8 hrs
- B) .50 cd/8 hrs
- C) .75 cd/6 hrs
- D) .50 cd/ 6 hrs.

Correct Answer: A (.75 cd/8 hrs)

Q13. Which one of the listed requirements regarding the buoyant smoke signal doesn't respond to present regulation? The buoyant smoke signal shall

- A) Emit smoke for at least 3 min when floating in calm water
- B) Continue to EMIT smoke when submerged in water image
- C) Not be swamped in a seaway
- D) Give a bright red during the inter emission time

Correct Answer: D (Give a bright red during the inter emission time)

Q14. The working duration of man overboard smoke signal is

- A) 3 minutes
- B) 5 minutes
- C) 15 minutes
- D) 10 minutes

Correct Answer: C (15 minutes)



- A) To secure bow of the lifeboat to the main deck bollards
- B) To hold the lifeboat close to the embarkation deck
- C) A stretcher for safe embarkation of injured persons
- D) To hold the life boat alongside the ship after launching

Correct Answer: B (To hold the lifeboat close to the embarkation deck)

Q16. Before lifting a life boat from the water, it must be ensured that

- A) Sea anchor is steamed
- B) Engine id going astern
- C) Bottom plug is shipped tight
- D) Fall wires are clear and hooked securely

Correct Answer: D (Fall wires are clear and hooked securely)

Q17. Which of the listed requirements do not correspond to the present regulation regarding weak link? weak link shall

- A) Be of sufficient strength to permit inflation of the life raft
- B) Release the life raft at a depth of not more than 4 meters
- C) Not break by force required to pull the painter from the life raft container
- D) Break under a strain of approximately 2.2 KN

Correct Answer: B (Release the life raft at a depth of not more than 4 meters)

Q18. What is the minimum number of crew required in rescue boats?

- A) Two persons
- B) Three persons
- C) Five persons
- D) Four persons

Correct Answer: C (Five persons)

Q19. Which of the listed requirements do not correspond to present regulations? The life raft shall have

- A) A manually controlled lamp visible of at least two miles fitted at the top of the canopy
- B) All entrances fitted with rigid boarding ramps for boarding the life raft at sea
- C) Floor preventing the ingress of water
- D) Manually controlled lamp fitted inside the life raft

Correct Answer: D (Manually controlled lamp fitted inside the life raft)

Q20. SART is the search and rescue radar transponder. How is this device activated?

- A) It has to be switched on by the master when the order to abandon ship is given
- B) It has to be thrown into the sea where it will self-activate
- C) It will be activated by the nearest coast station
- D) It is carried into the survival craft and switched on by the occupants

Correct Answer: D (It is carried into the survival craft and switched on by the occupants)



- A) 7.3 meters
- B) 8.5 meters
- C) 3.8 meters
- D) None of the above

Correct Answer: A (7.3 meters)

Q22. The shelf life of EPIRB battery is

- A) 1 year
- B) 3 to 5 years
- C) 5 years
- D) 10 years

Correct Answer: B (3 to 5 years)

Q23. How long will a parachute flare burn after it has been fired into the air?

- A) Minimum of five minutes
- B) Minimum of two minutes
- C) Minimum of 30 seconds
- D) Minimum of 40 seconds

Correct Answer: D (Minimum of 40 seconds)

Q24. VHF EPIRB is designed to be used in which area?

- A) Area A1
- B) Area A1-A2
- C) Area A4
- D) None of the above

Correct Answer: A (Area A1)

Q25. When floating, a life raft must be able to withstand repeated jumps onto it, both with and without the canopy erected, from a height above its floor of at least

- A) 18 meters
- B) 10 meters
- C) 4.5 meters
- D) 20 meters

Correct Answer: C (4.5 meters)

Q26. Which equipment of the following SOLAS PACK B life raft does not have?

- A) Fishing tackle + food + drinking water
- B) Fishing tackle + drinking water + bailer
- C) Fishing tackle + sea sick bags + drinking water
- D) None of the above

Correct Answer: A (Fishing tackle + food + drinking water)



- A) 8
- B) 10
- C) 12
- D) 14

Correct Answer: A (8)

Q28. In cargo vessel what is the requirement of child life jacket?

- A) 10%
- B) 15%
- C) 20%
- D) 25%

Correct Answer: A (10%)

Q29. Life raft equipment should have

- A) 2 buoyant rescue quoits attached not less than 30 m buoyant line
- B) 2 buoyant rescue quoits attached not less than 15 m buoyant line
- C) 1 buoyant rescue quoits attached not less than 30 m buoyant line
- D) 1 buoyant rescue quoits attached not less than 15 m buoyant line

Correct Answer: A (2 buoyant rescue quoits attached not less than 30 m buoyant line)

Q30. How many hand flares should each life raft normally carry?

- A) 2
- B) 4
- C) 6
- D) 10

Correct Answer: C (6)

Practice Set 4

Q1. Which of the following regarding immersion suit is true?

- A) It's zip to be greased using manufacture recommended lubricants
- B) It's fireproof
- C) Both a and b
- D) None of the above

Correct Answer: A (It's zip to be greased using manufacture recommended lubricants)

Q2. The lamp on the top of a life raft canopy must operate continuously or flash at the specified rate for at least

- A) 8 hours
- B) 2 hours
- C) 12 hours
- D) 4 hours

Correct Answer: C (12 hours)



- A) Distilled water and pure ethyl alcohol
- B) Distilled water and isopropyl alcohol
- C) Distilled water and methyl alcohol
- D) None of the above

Correct Answer: A (Distilled water and pure ethyl alcohol)

Q4. The number of lifebuoys on a cargo ship of length less than 100 meters is

- A) 4
- B) 6
- C) 8
- D) 10

Correct Answer: C (8)

Q5. The duration of the buoyant smoke marker is

- A) 1 min
- B) 10 min
- C) 15 min
- D) 3 min

Correct Answer: D (3 min)

Q6. Which of the following is/are the SOLAS requirements for rocket parachute flare?

- A) The rocket shall, when fired vertically, reach an altitude of not less than 300m
- B) Burn uniformly with an average luminous intensity of not less than 30000 cd
- C) Having a burning period of not less than 40s
- D) All of the above

Correct Answer: D (All of the above)

Q7. The breaking strength of line throwing appliances should not be less than

- A) 2 KN
- B) 4 KN
- C) 6 KN
- D) 8 KN

Correct Answer: A (2 KN)

Q8. Which of the following statements is true concerning life jackets?

- A) Buoyant vests may be substituted for life jackets
- B) Life jackets are designed to turn an unconscious person's face clear of water
- C) Lifejackets must always be worn with the same side facing outwards to float
- D) Lightly stained or faded life jackets will fall in the water and should not be used

Correct Answer: B (Life jackets are designed to turn an unconscious person's face clear of water)



- A) Heat exchange lessening posture
- B) Heat exchange lessening period
- C) Heat exchange lessening point
- D) None of the above

Correct Answer: A (Heat exchange lessening posture)

Q10. Passenger vessels 240 meters and over in length should have

- A) 8 life buoys
- B) 12 life buoys
- C) 20 life buoys
- D) 30 life buoys

Correct Answer: D (30 life buoys)

Q11. Sea anchor is used to reduce the of survival craft

- A) Fuel consumption
- B) ETA
- C) Drift rate

Correct Answer: C (Drift rate)