

WIA2005: Algorithm Design and Analysis

Semester 2, Session 2016/17

Lecture 3: Divide and Conquer

Learning objectives

- Know and understand the following:
 - Merge sort
 - Quick sort
 - Binary search
 - Powering a number
 - Fibonacci numbers
 - Matrix multiplication

The divide-and-conquer design paradigm

- 1.Divide* the problem (instance) into subproblems.
- 2.Conquer* the subproblems by solving them recursively.
- 3.Combine* subproblem solutions.

Divide and conquer sorting





- Merge Sort
- Quick Sort

Merge algorithm






MERGE(A, p, q, r)

```
1   $n_1 = q - p + 1$ 
2   $n_2 = r - q$ 
3  let  $L[1..n_1 + 1]$  and  $R[1..n_2 + 1]$  be new arrays
4  for  $i = 1$  to  $n_1$ 
5       $L[i] = A[p + i - 1]$ 
6  for  $j = 1$  to  $n_2$ 
7       $R[j] = A[q + j]$ 
8   $L[n_1 + 1] = \infty$ 
9   $R[n_2 + 1] = \infty$ 
10  $i = 1$ 
11  $j = 1$ 
12 for  $k = p$  to  $r$ 
13     if  $L[i] \leq R[j]$ 
14          $A[k] = L[i]$ 
15          $i = i + 1$ 
16     else  $A[k] = R[j]$ 
17          $j = j + 1$ 
```

Merge operation



Merge operation Cont..




Merge sort algorithm

MERGE-SORT(A, p, r)

```
1  if  $p < r$ 
2       $q = \lfloor (p + r) / 2 \rfloor$ 
3      MERGE-SORT( $A, p, q$ )
4      MERGE-SORT( $A, q + 1, r$ )
5      MERGE( $A, p, q, r$ )
```


Merge sort operation



Merge sort

1.Divide: Trivial.

2.Conquer: Recursively sort 2 subarrays.

3.Combine: Linear-time merge.

Merge sort

1.Divide: Trivial.

2.Conquer: Recursively sort 2 subarrays.

3.Combine: Linear-time merge.

$$T(n) = 2T(n/2) + \Theta(n)$$

subproblems

subproblem size

work dividing and combining

Master theorem (reprise)

$$T(n) = a T(n/b) + f(n)$$

CASE 1: $f(n) = O(n^{\log_b a - \varepsilon})$, constant $\varepsilon > 0$

$$\Rightarrow T(n) = \Theta(n^{\log_b a}) .$$

CASE 2: $f(n) = \Theta(n^{\log_b a} \lg^k n)$, constant $k \geq 0$

$$\Rightarrow T(n) = \Theta(n^{\log_b a} \lg^{k+1} n) .$$

CASE 3: $f(n) = \Omega(n^{\log_b a + \varepsilon})$, constant $\varepsilon > 0$,
and regularity condition

$$\Rightarrow T(n) = \Theta(f(n)) .$$

Master theorem (reprise)

$$T(n) = a T(n/b) + f(n)$$

CASE 1: $f(n) = O(n^{\log_b a - \varepsilon})$, constant $\varepsilon > 0$

$$\Rightarrow T(n) = \Theta(n^{\log_b a}) .$$

CASE 2: $f(n) = \Theta(n^{\log_b a} \lg^k n)$, constant $k \geq 0$

$$\Rightarrow T(n) = \Theta(n^{\log_b a} \lg^{k+1} n) .$$

CASE 3: $f(n) = \Omega(n^{\log_b a + \varepsilon})$, constant $\varepsilon > 0$,
and regularity condition

$$\Rightarrow T(n) = \Theta(f(n)) .$$

Merge sort: $a = 2, b = 2 \Rightarrow n^{\log_b a} = n^{\log_2 2} = n$

$$\Rightarrow \text{CASE 2 } (k = 0) \Rightarrow T(n) = \Theta(n \lg n) .$$

Quicksort

- Proposed by C.A.R. Hoare in 1962.
- Divide-and-conquer algorithm.
- Sorts “in place” (like insertion sort, but not like merge sort).
- Very practical (with tuning).

Example

Quicksort an n -element array:

1. Divide: Partition the array into two subarrays around a **pivot** x such that elements in lower subarray $\leq x \leq$ elements in upper subarray.



2. Conquer: Recursively sort the two subarrays.

3. Combine: Trivial.


Key: *Linear-time partitioning subroutine.*

Partitioning subroutine

```
PARTITION( $A, p, q$ )  $\triangleleft A[p \dots q]$   
   $x = A[p]$   $\triangleleft$  pivot =  $A[p]$   
   $i = p$   
  for  $j = p + 1$  to  $q$   
    do if  $A[j] \leq x$   
      then  $i = i + 1$   
           exchange  $A[i] \leftrightarrow A[j]$   
  exchange  $A[p] \leftrightarrow A[i]$   
  return  $i$ 
```

Running time
= $O(n)$ for n
elements.


Invariant:




Example of partitioning

6	10	13	5	8	3	2	11
i	j						


Example of partitioning




Example of partitioning




Example of partitioning




Example of partitioning




Example of partitioning




Example of partitioning




Example of partitioning



Example of partitioning




Example of partitioning



i

j

Example of partitioning



Example of partitioning

6	10	13	5	8	3	2	11
---	----	----	---	---	---	---	----

6	5	13	10	8	3	2	11
---	---	----	----	---	---	---	----

6	5	3	10	8	13	2	11
---	---	---	----	---	----	---	----

6	5	3	2	8	13	10	11
---	---	---	---	---	----	----	----

2	5	3	6	8	13	10	11
---	---	---	---	---	----	----	----

Pseudocode for quicksort

```
QUICKSORT( $A, p, r$ )  
  if  $p < r$   
    then  $q \leftarrow \text{PARTITION}(A, p, r)$   
         QUICKSORT( $A, p, q-1$ )  
         QUICKSORT( $A, q+1, r$ )
```

Initial call: QUICKSORT($A, 1, n$)

Analysis of quicksort

- Assume all input elements are distinct.
- In practice, there are better partitioning algorithms for when duplicate input elements may exist.
- Let $T(n)$ = worst-case running time on an array of n elements.

Worst-case of quicksort

- Input sorted or reverse sorted.
- Partition around min or max element.
- One side of partition always has no elements.

$$\begin{aligned}T(n) &= T(0) + T(n-1) + \Theta(n) \\&= \Theta(1) + T(n-1) + \Theta(n) \\&= T(n-1) + \Theta(n) \\&= \Theta(n^2) \quad (\textit{arithmetic series})\end{aligned}$$

Worst-case recursion tree


$$T(n) = T(0) + T(n-1) + cn$$

Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn \quad T(n)$$


Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$




Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$




Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$




Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$



Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$



Best-case analysis

(For intuition only!)

If we're lucky, PARTITION splits the array evenly:

$$\begin{aligned} T(n) &= 2T(n/2) + \Theta(n) \\ &= \Theta(n \lg n) \quad (\text{same as merge sort}) \end{aligned}$$

What if the split is always $\frac{1}{10} : \frac{9}{10}$?


$$T(n) = T\left(\frac{1}{10}n\right) + T\left(\frac{9}{10}n\right) + \Theta(n)$$

What is the solution to this recurrence?


Analysis of “almost-best” case

$$T(n)$$


Analysis of “almost-best” case




Analysis of “almost-best” case



Analysis of “almost-best” case



Analysis of “almost-best” case



More intuition

Suppose we alternate lucky, unlucky, lucky, unlucky, lucky,

$$L(n) = 2U(n/2) + \Theta(n) \quad \textit{lucky}$$

$$U(n) = L(n-1) + \Theta(n) \quad \textit{unlucky}$$

Solving:

$$L(n) = 2(L(n/2 - 1) + \Theta(n/2)) + \Theta(n)$$

$$= 2L(n/2 - 1) + \Theta(n)$$

$$= \Theta(n \lg n) \quad \textit{Lucky!}$$

How can we make sure we are usually lucky?

Randomized quicksort

IDEA: Partition around a *random* element.

- Running time is independent of the input order.
- No assumptions need to be made about the input distribution.
- No specific input elicits the worst-case behavior.
- The worst case is determined only by the output of a random-number generator.

Binary search

- Find an element in a sorted array:
 - 1.Divide:* Check middle element.
 - 2.Conquer:* Recursively search **1** subarray.
 - 3.Combine:* Trivial.


Binary search

- Find an element in a sorted array:
 - 1.Divide:* Check middle element.
 - 2.Conquer:* Recursively search 1 subarray.
 - 3.Combine:* Trivial.
- *Example:* Find 9


- 

Binary search

- Find an element in a sorted array:
 - 1.Divide:* Check middle element.
 - 2.Conquer:* Recursively search **1** subarray.
 - 3.Combine:* Trivial.
- *Example:* Find **9**




Binary search

- Find an element in a sorted array:
 - 1.Divide:* Check middle element.
 - 2.Conquer:* Recursively search 1 subarray.
 - 3.Combine:* Trivial.
- *Example:* Find 9
 - 3 5 7 8 

Binary search

- Find an element in a sorted array:
 - 1.Divide:* Check middle element.
 - 2.Conquer:* Recursively search 1 subarray.
 - 3.Combine:* Trivial.
- *Example:* Find 9

• 3 5 7 8



Binary search

- Find an element in a sorted array:
 - 1.Divide:* Check middle element.
 - 2.Conquer:* Recursively search **1** subarray.
 - 3.Combine:* Trivial.
- *Example:* Find **9**

• 3 5 7 8  12 15

Binary search

- Find an element in a sorted array:
 - 1.Divide:* Check middle element.
 - 2.Conquer:* Recursively search **1** subarray.
 - 3.Combine:* Trivial.
- *Example:* Find **9**

• 3 5 7 8  12 15

Recurrence for binary search

$$T(n) = 1 T(n/2) + \Theta(1)$$

subproblems

subproblem size

*work dividing
and combining*

Recurrence for binary search

$$T(n) = 1 T(n/2) + \Theta(1)$$

subproblems *subproblem size* *work dividing and combining*

$$n^{\log_b a} = n^{\log_2 1} = n^0 = 1 \Rightarrow \text{CASE 2 } (k = 0)$$
$$\Rightarrow T(n) = \Theta(\lg n).$$

Powering a number

Problem: Compute a^n , where $n \in \mathbb{N}$.

Naive algorithm: $\Theta(n)$.

Powering a number

Problem: Compute a^n , where $n \in \mathbb{N}$.

Naive algorithm: $\Theta(n)$.

Divide-and-conquer algorithm:

$$a^n = \begin{cases} a^{n/2} \cdot a^{n/2} & \text{if } n \text{ is even;} \\ a^{(n-1)/2} \cdot a^{(n-1)/2} \cdot a & \text{if } n \text{ is odd.} \end{cases}$$

Powering a number

Problem: Compute a^n , where $n \in \mathbb{N}$.

Naive algorithm: $\Theta(n)$.

Divide-and-conquer algorithm:

$$a^n = \begin{cases} a^{n/2} \cdot a^{n/2} & \text{if } n \text{ is even;} \\ a^{(n-1)/2} \cdot a^{(n-1)/2} \cdot a & \text{if } n \text{ is odd.} \end{cases}$$

$$T(n) = T(n/2) + \Theta(1) \Rightarrow T(n) = \Theta(\lg n).$$

Fibonacci numbers

Recursive definition:

$$F_n = \begin{cases} 1 & \text{if } n = 0; \\ 1 & \text{if } n = 1; \\ F_{n-1} + F_{n-2} & \text{if } n \geq 2. \end{cases}$$

0 1 1 2 3 5 8 13 21 34 L

Fibonacci numbers

Recursive definition:

$$F_n = \begin{cases} 0 & \text{if } n = 0; \\ 1 & \text{if } n = 1; \\ F_{n-1} + F_{n-2} & \text{if } n \geq 2. \end{cases}$$

0 1 1 2 3 5 8 13 21 34 L

Naive recursive algorithm: $\Omega(\phi^n)$
(exponential time), where $\phi = (1 + \sqrt{5})/2$
is the *golden ratio*.

Computing Fibonacci numbers

Bottom-up:

- Compute $F_0, F_1, F_2, \dots, F_n$ in order, forming each number by summing the two previous.
- Running time: $\Theta(n)$.

Computing Fibonacci numbers

Bottom-up:

- Compute $F_0, F_1, F_2, \dots, F_n$ in order, forming each number by summing the two previous.
- Running time: $\Theta(n)$.

Naïve recursive squaring:

$F_n = \phi^n / \sqrt{5}$ rounded to the nearest integer.

- Recursive squaring: $\Theta(\lg n)$ time.
- This method is unreliable, since floating-point arithmetic is prone to round-off errors.

Recursive squaring

Theorem:
$$\begin{bmatrix} F_{n+1} & F_n \\ F_n & F_{n-1} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^n .$$

Algorithm: Recursive squaring.

Time = $\Theta(\lg n)$.

Proof of theorem. (Induction on n .)

Base ($n = 1$):
$$\begin{bmatrix} F_2 & F_1 \\ F_1 & F_0 \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^1 .$$

Recursive squaring

Inductive step ($n \geq 2$):

$$\begin{aligned}\begin{bmatrix} F_{n+1} & F_n \\ F_n & F_{n-1} \end{bmatrix} &= \begin{bmatrix} F_n & F_{n-1} \\ F_{n-1} & F_{n-2} \end{bmatrix} \cdot \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix} \\ &= \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^{n-1} \cdot \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix} \\ &= \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^n \quad \blacksquare\end{aligned}$$

Matrix Multiplication

Suppose that we partition each of A, B, and C into four $n/2 \times n/2$ matrices

$$A = \begin{pmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{pmatrix}, \quad B = \begin{pmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{pmatrix}, \quad C = \begin{pmatrix} C_{11} & C_{12} \\ C_{21} & C_{22} \end{pmatrix}, \quad (4.9)$$

so that we rewrite the equation $C = A.B$ as

$$\begin{pmatrix} C_{11} & C_{12} \\ C_{21} & C_{22} \end{pmatrix} = \begin{pmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{pmatrix} \cdot \begin{pmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{pmatrix}. \quad (4.10)$$

Equation (4.10) corresponds to the four equations

$$C_{11} = A_{11} \cdot B_{11} + A_{12} \cdot B_{21}, \quad (4.11)$$

$$C_{12} = A_{11} \cdot B_{12} + A_{12} \cdot B_{22}, \quad (4.12)$$

$$C_{21} = A_{21} \cdot B_{11} + A_{22} \cdot B_{21}, \quad (4.13)$$

$$C_{22} = A_{21} \cdot B_{12} + A_{22} \cdot B_{22}. \quad (4.14)$$

Matrices simple algorithm

```
1   $n = A.rows$ 
2  let  $C$  be a new  $n \times n$  matrix
3  if  $n == 1$ 
4       $c_{11} = a_{11} \cdot b_{11}$ 
5  else partition  $A$ ,  $B$ , and  $C$  as in equations (4.9)
6       $C_{11} = \text{SQUARE-MATRIX-MULTIPLY-RECURSIVE}(A_{11}, B_{11})$ 
            $+ \text{SQUARE-MATRIX-MULTIPLY-RECURSIVE}(A_{12}, B_{21})$ 
7       $C_{12} = \text{SQUARE-MATRIX-MULTIPLY-RECURSIVE}(A_{11}, B_{12})$ 
            $+ \text{SQUARE-MATRIX-MULTIPLY-RECURSIVE}(A_{12}, B_{22})$ 
8       $C_{21} = \text{SQUARE-MATRIX-MULTIPLY-RECURSIVE}(A_{21}, B_{11})$ 
            $+ \text{SQUARE-MATRIX-MULTIPLY-RECURSIVE}(A_{22}, B_{21})$ 
9       $C_{22} = \text{SQUARE-MATRIX-MULTIPLY-RECURSIVE}(A_{21}, B_{12})$ 
            $+ \text{SQUARE-MATRIX-MULTIPLY-RECURSIVE}(A_{22}, B_{22})$ 
10 return  $C$ 
```

Running time

$$T(n) = \begin{cases} \Theta(1) & \text{if } n = 1, \\ 8T(n/2) + \Theta(n^2) & \text{if } n > 1. \end{cases} \quad (4.17)$$


From master methods:

$$T(n) = \Theta(n^3).$$

Reference

- MIT open courseware, Introduction to Algorithms, 2005.
- Cormen, Lieserson and Rivest, Introduction to Algorithms, Third Edition, MIT Press, 2009.

In the next lecture..



Lecture 4: Probabilistic Analysis and
randomize algorithm