



# PlatEMO

*Evolutionary Multi-Objective  
Optimization Platform*

User Manual 4.3

BIMK Group

September 19, 2023

Thank you very much for using PlatEMO. The copyright of PlatEMO belongs to the BIMK Group of Anhui University, China. This platform is only for research and educational purposes. The codes were implemented based on our understanding of the algorithms published in literatures. You should not rely upon the material or information provided by the platform as a basis for making any business, legal or any other decisions. We assume no responsibilities for any consequences of your using any codes in the platform. All publications using the platform should acknowledge the use of "PlatEMO" and cite one of the following two papers:

[1] Ye Tian, Ran Cheng, Xingyi Zhang, and Yaochu Jin, "PlatEMO: A MATLAB platform for evolutionary multi-objective optimization [educational forum]," IEEE Computational Intelligence Magazine, 2017, 12(4): 73-87.

[2] Ye Tian, Weijian Zhu, Xingyi Zhang, and Yaochu Jin, "A practical tutorial on solving optimization problems via PlatEMO," Neurocomputing, 2023, 518: 190-205.

If you have any comment or suggestion to PlatEMO, please send it to [field910921@gmail.com](mailto:field910921@gmail.com) (Dr. Ye Tian). If you want to add your code to PlatEMO, please send the ready-to-use code and the relevant literature to [field910921@gmail.com](mailto:field910921@gmail.com) as well. You can obtain the newest version of PlatEMO from GitHub.

# Contents

I. Quick Start.....	1
II. Using PlatEMO without GUI .....	3
A. Solving Benchmark Problems.....	3
B. Solving User-Defined Problems .....	5
C. Collecting the Results .....	9
III. Using PlatEMO with GUI .....	11
A. Functions of Test Module .....	11
B. Functions of Application Module .....	12
C. Functions of Experiment Module .....	13
D. Labels of Algorithms, Problems, and Metrics .....	13
IV. Extending PlatEMO .....	16
A. ALGORITHM Class.....	16
B. PROBLEM Class .....	18
C. SOLUTION Class.....	24
D. Whole Procedure of One Run .....	25
E. Metric Function.....	26
V. List of Algorithms .....	28
VI. List of Problems .....	37

# I. Quick Start

**Requirement:** MATLAB R2018a or higher (PlatEMO without GUI) or MATLAB R2020b or higher (PlatEMO with GUI) with Parallel Computing Toolbox and Statistics and Machine Learning Toolbox

PlatEMO is an open-source platform for solving optimization problems, whose input is an optimization problem and output is the found optimal solutions. An optimization problem is defined as

$$\begin{aligned} \min_{\mathbf{x}} \quad & \mathbf{f}(\mathbf{x}) = (f_1(\mathbf{x}), f_2(\mathbf{x}), \dots, f_M(\mathbf{x})) \\ \text{s. t.} \quad & \mathbf{x} = (x_1, x_2, \dots, x_D) \in \Omega \\ & g_1(\mathbf{x}), g_2(\mathbf{x}), \dots, g_K(\mathbf{x}) \leq 0 \end{aligned}$$

where  $\mathbf{x}$  denotes a **solution** or **decision vector** for the problem, which consists of  $D$  **decision variables**  $x_i$ , and each decision variable can be a real number, integer, binary number, or others.  $\Omega$  denotes the **search space** of the problems, which consists of the **lower bound**  $l_1, l_2, \dots, l_D$  and the **upper bound**  $u_1, u_2, \dots, u_D$ , i.e., each decision variable should always satisfy that  $l_i \leq x_i \leq u_i$ .  $f_1(\mathbf{x}), f_2(\mathbf{x}), \dots, f_M(\mathbf{x})$  denote the  $M$  **objective values** of the solution, and  $g_1(\mathbf{x}), g_2(\mathbf{x}), \dots, g_K(\mathbf{x})$  denote the  $K$  **constraint violations** of the solution.

To define an optimization problem, users should input at least the following contents:

- The encoding scheme of each decision variable (real, integer, binary, etc.);
- The lower bound  $l_1, l_2, \dots, l_D$  and the upper bound  $u_1, u_2, \dots, u_D$ ;
- At least one objective function  $f_1(\mathbf{x})$ .

To define an optimization problem more precisely, users can also input the following contents:

- Multiple objective functions  $f_1(\mathbf{x}), f_2(\mathbf{x}), \dots, f_M(\mathbf{x})$ ;
- Multiple constraint functions  $g_1(\mathbf{x}), g_2(\mathbf{x}), \dots, g_K(\mathbf{x})$ ;
- Function for initializing solutions;
- Function for repairing invalid solutions;
- Function for evaluating solutions;
- Gradient functions of objectives  $f'_1(\mathbf{x}), f'_2(\mathbf{x}), \dots, f'_M(\mathbf{x})$ ;
- Gradient functions of constraints  $g'_1(\mathbf{x}), g'_2(\mathbf{x}), \dots, g'_K(\mathbf{x})$ ;
- Data used in the calculation of all functions (an arbitrary constant).

The above functions are MATLAB functions rather than mathematical functions, which

should have specified inputs and outputs but need not have explicit mathematical expressions. Moreover, users can define the settings of optimization algorithms, to achieve the improvement of optimization performance via selecting suitable algorithms and parameter settings.

In MATLAB, users can call the main file `platemo.m` in the following three ways:

1) Calling the main function with parameters:

```
platemo('problem',@SOP_F1,'algorithm',@GA);
```

Then the specified benchmark problem will be solved by the specified algorithm with specified parameter settings, where the result can be displayed, saved, or returned (see *Solving Benchmark Problems* for details).

2) Calling the main function with parameters:


```
f1 = @(x) sum(x);  
f2 = @(x) 1-sum(x);  
platemo('objFcn',f1,'conFcn',f2,'algorithm',@GA);
```

Then the user-defined problem will be solved by the specified algorithm with specified parameter settings (see *Solving User-Defined Problems* for details).

3) Calling the main function without parameter:

```
platemo();
```

Then a GUI with three modules will be displayed, where the test module is used to visually investigate the performance of an algorithm on a benchmark problem (see *Functions of Test Module* for details), the application module is used to solve user-defined problems (see *Functions of Application Module* for details), and the experiment module is used to statistically analyze the performance of multiple algorithms on multiple benchmark problems (see *Functions of Experiment Module* for details).



## II. Using PlatEMO without GUI

### A. Solving Benchmark Problems

Users can use PlatEMO without GUI by calling the main function `platemo()` with parameters like

```
platemo('Name1',Value1,'Name2',Value2,'Name3',Value3,...);
```

where all the acceptable names and values are

Name	Data type	Default value	Description
'algorithm'	Function handle or cell	dependent	Class of algorithm
'problem'	Function handle or cell	dependent	Class of problem
'N'	Positive integer	100	Population size
'M'	Positive integer	dependent	Number of objectives
'D'	Positive integer	dependent	Number of variables
'maxFE'	Positive integer	10000	Maximum number of function evaluations
'maxRuntime'	Positive number	inf	Maximum runtime
'save'	Integer	-10	Number of saved populations
'outputFcn'	Function handle	@DefaultOutput	Function called before each iteration Input 1: Class of algorithm Input 2: Class of problem Output: None

- 'algorithm' denotes the algorithm to be run, whose value should be the function handle of an algorithm, such as @GA. The value can also be a cell like {@GA,p1,p2,...}, where p1,p2,... specify the parameter values of the algorithm. For example, the following code solves the default problem via the algorithm @GA with specified parameters:

```
platemo('algorithm',{@GA,1,30,1,30});
```

- 'problem' denotes the benchmark problem to solve, whose value should be the function handle of a benchmark problem, such as @SOP\_F1. The value can also be a cell like {@SOP\_F1,p1,p2,...}, where p1,p2,... specify the parameter values of the benchmark problem. For example, the following code solves the problem

@WFG1 with specified parameters via the default algorithm:

```
platemo('problem',{@WFG1,20});
```

- 'N' denotes the population size of the algorithm, which usually equals the number of solutions in the final population. For example, the following code solves the problem @SOP\_F1 via the algorithm @GA with a population size of 50:

```
platemo('algorithm',@GA,'problem',@SOP_F1,'N',50);
```

- 'M' denotes the number of objectives of the benchmark problem, which is valid for some multi-objective benchmark problems. For example, the following code solves the problem @SOP\_F1 via the algorithm @GA with a population size of 50:

```
platemo('algorithm',@GA,'problem',@SOP_F1,'N',50);
```

- 'D' denotes the number of decision variables of the benchmark problem, which is valid for some benchmark problems. For example, the following code solves the problem @SOP\_F1 with 100 variables via the algorithm @GA:

```
platemo('algorithm',@GA,'problem',@SOP_F1,'D',100);
```

- 'maxFE' denotes the maximum number of available function evaluations, which usually equals the product of population size and number of generations. For example, the following code sets the maximum number of function evaluations to 20000 for the algorithm:

```
platemo('algorithm',@GA,'problem',@SOP_F1,'maxFE',20000);
```

- 'maxRuntime' denotes the maximum runtime (in second). When 'maxRuntime' equals its default value `inf`, the algorithm will terminate after 'maxFE' function evaluations; otherwise, the algorithm will terminate after 'maxRuntime' seconds. For example, the following code sets the maximum runtime to 10 seconds for the algorithm:

```
platemo('algorithm',@GA,'problem',@SOP_F1,'maxRuntime',10);
```

- 'save' denotes the number of saved populations, where the populations are saved to a file if the value is positive and displayed in a figure if the value is negative (see *Collecting the Results* for details).
- 'outputFcn' denotes the function called before each iteration of the algorithm. An output function has two inputs and no output, where the first input is the current ALGORITHM object and the second input is the current PROBLEM object. The default 'outputFcn' saves or displays the populations according the value of 'save'.

Note that users need not specify all the parameters as each of them has a default value.

## B. Solving User-Defined Problems

When the parameter '`problem`' is not specified, users can define their own problem by specifying the following parameters:

Name	Data type	Default value	Description
' <code>objFcn</code> '	Function handle, matrix, or cell	{ }	Objective functions; all the objectives are to be minimized Input: A decision vector Output: Objective value (scalar)
' <code>encoding</code> '	Scalar or row vector	1	Encoding scheme of each variable
' <code>lower</code> '	Scalar or row vector	0	Lower bound of each variable
' <code>upper</code> '	Scalar or row vector	1	Upper bound of each variable
' <code>conFcn</code> '	Function handle, matrix, or cell	{ }	Constraint functions; a constraint is satisfied if and only if the constraint violation is not positive Input: A decision vector Output: Constraint violation (scalar)
' <code>decFcn</code> '	Function handle	{ }	Function for repairing an invalid solution Input: A decision vector Output: Repaired decision vector
' <code>evalFcn</code> '	Function handle	{ }	Function for evaluating a solution Input: A decision vector Output 1: Repaired decision vector Output 2: All objective values (vector) Output 3: All constraint violations (vector)
' <code>initFcn</code> '	Function handle	{ }	Function for initializing a population Input: Population size Output: A matrix consisting of the decision vectors of all solutions
' <code>objGradFcn</code> '	Function handle or cell	{ }	Gradient functions of objectives Input: A decision vector Output: Gradient (vector)
' <code>conGradFcn</code> '	Function handle or cell	{ }	Gradient functions of constraints Input: A decision vector Output: Gradient (vector)
' <code>data</code> '	Any	{ }	Data of the problem

- '`objFcn`' denotes the objective functions of the problem, whose value can be a function handle (a single objective), a matrix (a function is automatically fitted),



or cell (multiple objectives). An objective function has one input and one output, where the input is a decision vector and the output is the objective value. All the objectives are to be minimized. For example, the following code solves a bi-objective optimization problem with six real variables via the default algorithm:

```
f1 = @(x)x(1)+sum(x(2:end));
f2 = @(x)sqrt(1-x(1)^2)+sum(x(2:end));
platemo('objFcn',{f1,f2},'D',6);
```

where the first objective is  $x_1 + \sum_{i=2}^D x_i$  and the second objective is  $\sqrt{1-x_1^2} + \sum_{i=2}^D x_i$ . If an objective function is a matrix, a function will be automatically fitted via Gaussian process regression, where each row of the matrix is a sample and each column of the matrix is a variable (except for the last column) or a function value (the last column). For example, the following code solves the same problem, while the objective functions are automatically fitted:

```
x = rand(50,6);
y1 = x(:,1)+sum(x(:,2:end),2);
y2 = sqrt(1-x(:,1).^2)+sum(x(:,2:end),2);
platemo('objFcn',[x,y1],[x,y2],'D',6);
```

- `'encoding'` denotes the encoding scheme of each variable, whose value can be a scalar or row vector, and the value of each dimension can be 1 (real number), 2 (integer), 3 (label), 4 (binary number), or 5 (permutation number). The algorithms may generate solutions via different strategies for different encoding schemes. For example, the following code specifies three real variables, two integer variables, and one binary variable:

```
f1 = @(x)x(1)+sum(x(2:end));
f2 = @(x)sqrt(1-x(1)^2)+sum(x(2:end));
platemo('objFcn',{f1,f2},'encoding',[1,1,1,2,2,4]);
```

the number of variables  $D$  is automatically set to the length of `'encoding'`.

- `'lower'` and `'upper'` denote the lower and upper bound of each variable, respectively, whose values can be scalars or row vectors, and the value of each dimension should be real. `'lower'` and `'upper'` should have the same length as `'encoding'`. For example, the following code specifies a search space  $[0,1] \times [0,9]^5$ :

```
f1 = @(x)x(1)+sum(x(2:end));
f2 = @(x)sqrt(1-x(1)^2)+sum(x(2:end));
platemo('objFcn',{f1,f2},'encoding',[1,1,1,2,2,4],...
'lower',0,'upper',[1,9,9,9,9,9]);
```

- `'conFcn'` denotes the constraint functions of the problem, whose value can be a function handle (a single constraint), a matrix (a function is automatically fitted), or cell (multiple constraints). A constraint function has one input and one output, where the input is a decision vector and the output is the constraint violation. A constraint is satisfied if and only if the constraint violation is not positive. For example, the following code solves a bi-objective optimization problem via the default algorithm:

```
f1 = @(x)x(1)+sum(x(2:end));
f2 = @(x)sqrt(1-x(1)^2)+sum(x(2:end));
g1 = @(x)1-sum(x(2:end));
platemo('objFcn',{f1,f2},'encoding',[1,1,1,2,2,4],...
'conFcn',g1,'lower',0,'upper',[1,9,9,9,9,9]);
```

and adds a constraint  $\sum_{i=2}^6 x_i \geq 1$ . Note that equality constraints should be converted into inequality constraints, the details of which can be found in Section 3.2 of *this paper*. If a constraint function is a matrix, a function will be automatically fitted via Gaussian process regression, where each row of the matrix is a sample and each column of the matrix is a variable (except for the last column) or a function value (the last column). For example, the following code solves the same problem, while the constraint function is automatically fitted:

```
f1 = @(x)x(1)+sum(x(2:end));
f2 = @(x)sqrt(1-x(1)^2)+sum(x(2:end));
x = rand(50,6);
y = 1-sum(x(:,2:end),2);
platemo('objFcn',{f1,f2},'encoding',[1,1,1,2,2,4],...
'conFcn',[x,y],'lower',0,'upper',[1,9,9,9,9,9]);
```

- `'decFcn'` denotes the function for repairing an invalid solution, whose value should be a function handle having one input and one output, where the input is a decision vector and the output is the repaired decision vector. For example, the following code makes  $x_1$  always be a multiple of 0.1:

```
f1 = @(x)x(1)+sum(x(2:end));
f2 = @(x)sqrt(1-x(1)^2)+sum(x(2:end));
g1 = @(x)1-sum(x(2:end));
h = @(x)[round(x(1)/0.1)*0.1,x(2:end)];
platemo('objFcn',{f1,f2},'encoding',[1,1,1,2,2,4],...
'conFcn',g1,'decFcn',h,'lower',0,'upper',[1,9,9,9,9,9]);
```

- `'evalFcn'` denotes the function for evaluating a solution, whose value should be a function handle having one input and three output, where the input is a decision vector, the first output is the repaired decision vector, the second output is the

vector of objective values, and the third vector is the vector of constraint violations. The default `'evalFcn'` calls `'decFcn'`, `'objFcn'`, and `'conFcn'` in sequence to evaluate a solution, while the following code defines a new `'evalFcn'` to achieve solution repair, objective calculation, and constraint calculation simultaneously:

```
function [x,f,g] = Eval(x)
    x = [round(x(1)/0.1)*0.1,x(2:end)];
    x = max(0,min([1,9,9,9,9,9],x));
    f(1) = x(1)+sum(x(2:end));
    f(2) = sqrt(1-x(1)^2)+sum(x(2:end));
    g = 1-sum(x(2:end));
end
```

Then, the following codes solve the same problem by specifying only the evaluation function:

```
platemo('evalFcn',@Eval,'encoding',[1,1,1,2,2,4],...
'lower',0,'upper',[1,9,9,9,9,9]);
```

- `'initFcn'` denotes the function for initializing a population, whose value should be a function handle having one input and one output, where the input is the number of solutions in the population and the output is a matrix consisting of the decision vectors in the population. The default `'initFcn'` randomly generates solutions in the whole search space, while the following code defines a new `'initFcn'` to accelerate the convergence:

```
q = @(N)rand(N,6);
platemo('evalFcn',@Eval,'encoding',[1,1,1,2,2,4],...
'initFcn',q,'lower',0,'upper',[1,9,9,9,9,9]);
```

- `'objGradFcn'` and `'conGradFcn'` denote the gradient functions of objectives and constraints, respectively, whose values can be function handles or cells. Each gradient function should have one input and one output, where the input is a decision vector and the output is the gradient. The default gradient function estimates the gradient via finite difference, while the following code defines a new `'objGradFcn'` to accelerate the convergence and ensure the population diversity:

```
fg = @(x)[0,x(2:end)];
platemo('evalFcn',@Eval,'encoding',[1,1,1,2,2,4],...
'objGradFcn',fg,'lower',0,'upper',[1,9,9,9,9,9]);
```

Note that only a few algorithms will use gradient information.

- `'data'` denotes the data of the problem, which can be a constant of any type. If

'data' is specified, all the above functions should have an additional input to receive 'data'. For example, the following code solves a rotated single-objective optimization problem:

```
d = rand(RandStream('mlfg6331_64','Seed',28),10)*2-1;
[d,~] = qr(d);
f1 = @(x,d)sum((x*d-0.5).^2);
platemo('objFcn',f1,'encoding',ones(1,10),'data',d);
```

In addition to the above way for defining a problem, a problem object can be created and solved by specified algorithm objects. For example, the following code solves the problem via the algorithm @GA and the algorithm @DE.

```
d = rand(RandStream('mlfg6331_64','Seed',28),10)*2-1;
[d,~] = qr(d);
f1 = @(x,d)sum((x*d-0.5).^2);
PRO = UserProblem('objFcn',f1,'encoding',ones(1,10),'data',d);
ALG1 = GA();
ALG2 = DE();
ALG1.Solve(PRO);
ALG2.Solve(PRO);
```

### C. Collecting the Results

The generated populations can be displayed, saved, or returned after the algorithm terminates. If the main function is called like

```
[Dec,Obj,Con] = platemo(...);
```

Then the final population will be returned, where `Dec` is a matrix consisting of the decision vectors in the final population, `Obj` is a matrix consisting of the objective values in the final population, and `Con` is a matrix consisting of the constraint violations in the final population. If the main function is called like

```
platemo('save',Value,...);
```

Then the generated populations will be displayed in a figure if `Value` is negative (default), where various plots can be displayed by switching the `Data source` menu on the figure. While if `Value` is positive, the generated populations will be saved to a MAT file named as `PlatEMO\Data\alg\alg_pro_M_D_run.mat`, where `alg` is the algorithm name, `pro` is the problem name, `M` is the number of objectives, `D` is the number of variables, and `run` automatically increases from 1 until the file name does not exist. A file saves a cell `result` consisting of the generated populations and a struct `metric` consisting of the metric values. The whole optimization process of the

algorithm is divided into `Value` equal intervals, where the first column of `result` stores the number of consumed function evaluations at the last iteration of each interval, the second column of `result` stores the population at the last iteration of each interval, and `metric` stores the metric values of the stored populations. The above are achieved by the default output function `@DefaultOutput`, while users can collect the results in their own ways by specifying the value of `'outputFcn'` to the handle of a user-defined output function.

<pre>result = 6x2 cell array { [ 1650]} {1x50 SOLUTION} { [ 3300]} {1x50 SOLUTION} { [ 5000]} {1x50 SOLUTION} { [ 6650]} {1x50 SOLUTION} { [ 8300]} {1x50 SOLUTION} { [10000]} {1x50 SOLUTION}</pre>	<pre>metric = struct with fields:  runtime: 0.3317 IGD: [6x1 double]</pre>
--	--

Besides, the metric values can be automatically calculated and saved in the experiment module of the GUI. To calculate the metric values manually, users should load a population, construct a `PROBLEM` object, and call its method `CalMetric`, for example,

```
% Load result before performing the following code  
pro = DTLZ2();  
pro.CalMetric('IGD', result{end});
```

where `'IGD'` is the name of the calculated metric (see *Metric Function* for details). In particular, IGD and HV are the most popular metrics for multi-objective optimization, whose application scopes and methods for defining reference points can be found in Section 5.3 of *this paper*.


## III. Using PlatEMO with GUI

### A. Functions of Test Module

Users can use PlatEMO with GUI by calling the main function `platemo()` without parameter like

```
platemo();
```

Then the test module of the GUI will be displayed, which is used to visually investigate the performance of an algorithm on a benchmark problem.




In this module, the performance investigation can be achieved by the following steps:

- Step (1) Select multiple labels to determine the type of problems (see *Labels of Algorithms, Problems, and Metrics* for details).
- Step (2) Select an algorithm from the list.
- Step (3) Select a benchmark problem from the list.
- Step (4) Set the parameters of the algorithm and benchmark problem. Different algorithms and benchmark problems may have different parameters, the details of which can be obtained by hovering over each parameter.
- Step (5) Start, pause, stop, or back off the current execution; save the current result to a file. The current result can be saved as a matrix with  $N$  rows and  $D + M + K$  columns, where  $N$  denotes the number of solutions,  $D$  denotes the number of variables,  $M$  denotes the number of objectives, and  $K$  denotes the number of constraints.
- Step (6) Select a data to display, such as the objective values, variables, and metric values of the current population.
- Step (7) Select a historical result to display.

## B. Functions of Application Module

Users can press the menu button to switch to the application module, which is used to solve user-defined problems.




In this module, the solving of problems can be achieved by the following steps:

- Step (1) Define a problem, the contents of which are the same as those in *Solving User-Defined Problems*, where **Encoding scheme** corresponds to 'encoding', **Decision space** corresponds to 'lower' and 'upper', **Data** corresponds to 'data', **Initialization function** corresponds to 'initFcn', **Repair function** corresponds to 'decFcn', **Objective functions** corresponds to 'objFcn', **Constraint functions** corresponds to 'conFcn', and **Evaluation function** corresponds to 'evalFcn'.
- Step (2) Save or load a problem; check the validity of the problem; select a problem template. The saved problem can be opened and solved in other modules.
- Step (3) Select an algorithm from the list. The labels are automatically determined according to the problem definition (see *Labels of Algorithms, Problems, and Metrics* for details).
- Step (4) Set the parameters of the algorithm. Different algorithms may have different parameters, the details of which can be obtained by hovering over each parameter.
- Step (5) Start, pause, stop, or back off the current execution; save the current result to a file. The current result can be saved as a matrix with  $N$  rows and  $D + M + K$  columns, where  $N$  denotes the number of solutions,  $D$  denotes the number of variables,  $M$  denotes the number of objectives, and  $K$  denotes the number of constraints.
- Step (6) Select a data to display, such as the objective values, variables, and metric values of the current population.

### C. Functions of Experiment Module

Users can press the menu button to switch to the experiment module, which is used to statistically analyze the performance of multiple algorithms on multiple problems.



In this module, comparative experiments can be achieved by the following steps:

- Step (1) Select multiple labels to determine the type of problems (see *Labels of Algorithms, Problems, and Metrics* for details).
- Step (2) Select multiple algorithms from the list.
- Step (3) Select multiple benchmark problems from the list.
- Step (4) Set the number of repeated runs, number of saved populations in each run, and path for saving results (see *Collecting the Results* for details).
- Step (5) Set the parameters of the algorithms and benchmark problems. Different algorithms and benchmark problems may have different parameters, the details of which can be obtained by hovering over each parameter.
- Step (6) Start or stop the experiment; perform multiple runs in sequence (on a single CPU) or in parallel (on all CPUs).
- Step (7) Select a metric; select a statistical method; save the table to a file; display the results of the selected cells in a figure.

### D. Labels of Algorithms, Problems, and Metrics

Each algorithm, benchmark problem, and metric should be tagged with labels by the comment in the second line of its main function. For example, in the code of `PSO.m`:

```
classdef PSO < ALGORITHM
% <single> <real/integer> <large/none> <constrained/none>
```

which indicates the types of problems the algorithm can solve. All the labels are



Label	Description
<single>	Single-objective optimization: The problem has a single objective
<multi>	Multi-objective optimization: The problem has two or three objectives
<many>	Many-objective optimization: The problem has four or more objectives
<real>	Continuous optimization: The decision variables are real numbers
<integer>	Integer optimization: The decision variables are integers
<label>	Label optimization: The decision variables are labels
<binary>	Binary optimization: The decision variables are binary numbers
<permutation>	Permutation optimization: All decision variables constitute a permutation
<large>	Large-scale optimization: The problem has 100 or more variables
<constrained>	Constrained optimization: The problem has at least one constraint
<expensive>	Expensive optimization: The objectives are computationally expensive, only a limited number of function evaluations are available
<multimodal>	Multimodal optimization: There exist multiple optimal solutions with similar objective values but considerably different decision vectors, all of which should be found
<sparse>	Sparse optimization: Most variables of the optimal solutions are zero
<dynamic>	Dynamic optimization: The objectives and constraints vary over time
<multitask>	Multitasking optimization: Optimize multiple problems simultaneously, each problem may have multiple objectives and constraints
<bilevel>	Bilevel optimization: Find the feasible and optimal solution for the upper-level problem, where a solution is feasible for the upper-level problem if and only if it is optimal for the lower-level problem
<robust>	Robust optimization: The objectives and constraints are affected by noise, the robust and optimal solutions should be found
<none>	Empty label
<min>	(for metrics only) The metric value is the smaller the better
<max>	(for metrics only) The metric value is the larger the better

An algorithm may have multiple sets of labels, where the Cartesian product between all the label sets constitutes all the types of problems that can be solved by the algorithm. If the label sets of an algorithm are <single> <real> <constrained/none>, it will be able to solve single-objective continuous optimization problems with or without constraints. On the other hand, the label sets <single> <real> mean that the algorithm can only solve unconstrained problems, the label sets <single> <real> <constrained> mean that the algorithm can only solve constrained problems, and the label sets <single> <real/binary> mean that the algorithm can solve problems with either real variables or binary variables.

Each algorithm, benchmark problem, and metric should be tagged with at least one

label, otherwise it will not be appeared in the lists in the GUI. After selecting multiple labels in the GUI, only the algorithms, benchmark problems, and metrics containing the same labels will be appeared. Details of the label based filter strategy can be found *here*. The labels of all the algorithms and benchmark problems in PlatEMO are referred to *List of Algorithms* and *List of Problems*, respectively.

## IV. Extending PlatEMO

### A. *ALGORITHM Class*

An algorithm should be written as a subclass of `ALGORITHM` and put in the folder `PlatEMO\Algorithms`, which contains the following properties and methods:

Property	Specified by	Description
parameter	Users	Parameters of the algorithm
save	Users	Number of populations saved in an execution
outputFcn	Users	Function called in <code>NotTerminated()</code>
pro	<code>Solve()</code>	Problem solved in current execution
result	<code>NotTerminated()</code>	Populations saved in current execution
metric	<code>NotTerminated()</code>	Metric values of saved populations
Method	Be redefined	Description
<code>ALGORITHM</code>	Cannot	Set the properties specified by users Input: Parameter settings like ' <a href="#">Name</a> ', <code>Value</code> , ... Output: <code>ALGORITHM</code> object
<code>Solve</code>	Cannot	Solve a problem via the algorithm Input: <code>PROBLEM</code> object Output: None
<code>main</code>	Must	Main procedure of the algorithm Input: <code>PROBLEM</code> object Output: None
<code>NotTerminated</code>	Cannot	Function called before each iteration in <code>main()</code> Input: An array of <code>SOLUTION</code> objects, i.e., a population Output: Whether the algorithm terminates (logical)
<code>ParameterSet</code>	Cannot	Set the parameter values according to <code>parameter</code> Input: Default parameter settings Output: User-specified parameter settings

Each algorithm should inherit `ALGORITHM` and redefine the method `main()`. For example, the code of `GA.m` is

```

1 classdef GA < ALGORITHM
2 % <single><real/integer/label/binary/permutation><large/none><constrained/none>
3 % Genetic algorithm
4 % proC --- 1 --- Probability of crossover
5 % disC --- 20 --- Distribution index of crossover
6 % proM --- 1 --- Expectation of the number of mutated variables

```

```

7 % disM --- 20 --- Distribution index of mutation
8
9 %----- Reference -----
10 % J. H. Holland, Adaptation in Natural and Artificial
11 % Systems, MIT Press, 1992.
12 %-----
13
14     methods
15         function main(Alg,Pro)
16             [proC,disC,proM,disM] = Alg.ParameterSet(1,20,1,20);
17             P = Pro.Initialization();
18             while Alg.NotTerminated(P)
19                 Q = TournamentSelection(2,Pro.N,FitnessSingle(P));
20                 O = OperatorGA(P(Q),{proC,disC,proM,disM});
21                 P = [P,O];
22                 [~,rank] = sort(FitnessSingle(P));
23                 P = P(rank(1:Pro.N));
24             end
25         end
26     end
27 end

```

The functions of each line are as follows:

- Line 1: Inheriting the ALGORITHM class;
- Line 2: Tagging the algorithm with labels (see *Labels of Algorithms, Problems, and Metrics* for details);
- Line 3: Full name of the algorithm;
- Lines 4-7: Parameter name --- default value --- description, which are shown in the parameter setting list in the GUI;
- Lines 9-12: Reference of the algorithm;
- Line 15: Redefining the method of main procedure;
- Line 16: Obtaining the parameter values specified by users, where 1, 20, 1, 20 are default values of the four parameters proC, disC, proM, disM;
- Line 17: Obtaining an initial population by calling a method of the problem;
- Line 18: Storing the population and checking whether the algorithm terminates; if so, the algorithm will immediately terminate by throwing an error;
- Line 19: Binary tournament based mating selection achieved by a public function;
- Line 20: Offspring generation achieved by a public function;
- Line 21: Combing the current population with the offspring population;
- Line 22: Sorting the solutions based on their fitness calculated by a public function;
- Line 23: Retaining half the solutions with better fitness for the next iteration.

In the above codes, the functions `ParameterSet()` and `NotTerminated()` are provided by the `ALGORITHM` class, and the function `Initialization()` is provided by the `PROBLEM` class. Besides, the functions `TournamentSelection()`, `FitnessSingle()`, and `OperatorGA()` are public functions in the folder `PlatEMO\Algorithms\Utility` functions. The following table lists the functions that can be used in algorithms, where the details of them are referred to the comments in their codes. Besides, their techniques for efficiency improvement can be found *here*.

Function Name	Description
ALGORITHM. NotTerminated	Function called before each iteration of the algorithm, which stores the current population and check whether the algorithm terminates
ALGORITHM. ParameterSet	Set the parameter values specified by users
PROBLEM. Initialization	Initialize a population for the problem
PROBLEM. Evaluation	Evaluate a population and generate an array of SOLUTION object
CrowdingDistance	Crowding distance calculation for multi-objective optimization
FitnessSingle	Fitness calculation for single-objective optimization
NDSort	Non-dominated sorting for multi-objective optimization
OperatorDE	The variation operator of differential evolution
OperatorFEP	The variation operator of fast evolutionary programming
OperatorGA	The variation operators of genetic algorithm
OperatorGAhalf	The variation operators of genetic algorithm, where only the first half of offspring solutions are returned
OperatorPSO	The variation operator of particle swarm optimization
RouletteWheel Selection	Roulette-wheel selection
Tournament Selection	Tournament selection
UniformPoint	Generate a set of uniformly distributed points

## B. PROBLEM Class

A problem should be written as a subclass of `PROBLEM` and put in the folder `PlatEMO\Problems`, which contains the following properties and methods:

Property	Specified by	Description
N	Users	Population size of algorithms
M	Users and Setting()	Number of objectives of the problem
D	Users and Setting()	Number of decision variables of the problem

maxFE	Users	Maximum number of function evaluations
FE	Evaluation()	Number of function evaluations consumed in current execution
maxRuntime	Users	Maximum runtime
encoding	Setting()	Encoding scheme of each variable
lower	Setting()	Lower bound of each variable
upper	Setting()	Upper bound of each variable
optimum	GetOptimum()	Optimal values of the problem, such as the minimum objective value of single-objective optimization problems and a set of points on the Pareto front of multi-objective optimization problems
PF	GetPF()	Pareto front of the problem, such as a 1-D curve of bi-objective optimization problems, a 2-D surface of tri-objective optimization problems, and feasible regions of constrained optimization problems
parameter	Users	Parameters of the problem
<b>Method</b>	<b>Be redefined</b>	<b>Description</b>
PROBLEM	Cannot	Set the properties specified by users Input: Parameter settings like 'Name', Value, ... Output: ALGORITHM object
Setting	Must	Default settings of the problem Input: None Output: None
Initialization	Can	Initialize a population Input: Population size Output: An array of SOLUTION objects, i.e., a population
Evaluation	Can	Evaluate a population and generate solution objects Input: A matrix consisting of decision vectors Output: An array of SOLUTION objects, i.e., a population
CalDec	Can	Repair invalid solutions in a population Input: A matrix consisting of decision vectors Output: A matrix consisting of repaired decision vectors
CalObj	Must	Calculate the objective values of solutions in a population. All objectives are to be minimized Input: A matrix consisting of decision vectors Output: A matrix consisting of objective values
CalCon	Can	Calculate the constraint violations of solutions in a population. A constraint is satisfied if and only if the constraint violation is not positive Input: A matrix consisting of decision vectors Output: A matrix consisting of constraint violations
CalObjGrad	Can	Calculate the gradients of a solution on objectives

		Input: A decision vector Output: A Jacobian matrix
CalConGrad	Can	Calculate the gradients of a solution on constraints Input: A decision vector Output: A Jacobian matrix
GetOptimum	Can	Generate the optimal values and store in optimum Input: The number of optimal values Output: Optimal values (a matrix)
GetPF	Can	Generate the Pareto front and store in PF Input: None Output: Data for plotting the Pareto front (a matrix or cell)
CalMetric	Can	Calculate the metric value of a population Input 1: Metric name Input 2: An array of SOLUTION objects, i.e., a population Output: Metric value (scalar)
DrawDec	Can	Display the decision variables of a population Input: An array of SOLUTION objects, i.e., a population Output: None
DrawObj	Can	Display the objective values of a population Input: An array of SOLUTION objects, i.e., a population Output: None
ParameterSet	Cannot	Set the parameter values according to parameter Input: Default parameter settings Output: User-specified parameter settings

Each benchmark problem should inherit `PROBLEM` and redefine the methods `Setting()` and `CalObj()`. For example, the code of `SOP_F1.m` is

```

1  classdef SOP_F1 < PROBLEM
2  % <single><real><expensive/none>
3  % Sphere function
4
5  %----- Reference -----
6  % X. Yao, Y. Liu, and G. Lin, Evolutionary programming made
7  % faster, IEEE Transactions on Evolutionary Computation,
8  % 1999, 3(2): 82-102.
9  %-----
10
11  methods
12      function Setting(obj)
13          obj.M = 1;
14          if isempty(obj.D); obj.D = 30; end
15          obj.lower = zeros(1,obj.D) - 100;

```

```

16         obj.upper = zeros(1,obj.D) + 100;
17         obj.encoding = ones(1,obj.D);
18     end
19     function PopObj = CalObj(obj,PopDec)
20         PopObj = sum(PopDec.^2,2);
21     end
22 end
23 end

```

The functions of each line are as follows:

- Line 1: Inheriting the `PROBLEM` class;
- Line 2: Tagging the problem with labels (see *Labels of Algorithms, Problems, and Metrics* for details);
- Line 3: Full name of the problem;
- Lines 5-9: Reference of the problem;
- Line 12: Redefining the method of default parameter settings;
- Line 13: Setting the number of objectives;
- Line 14: Setting the number of decision variables if it is not specified by users;
- Lines 15-16: Setting the lower bounds and upper bounds of decision variables;
- Line 17: Setting the encoding schemes of decision variables;
- Line 19: Redefining the method of calculating objective values;
- Line 20: Calculating the objective values of solutions in a population.

The default method `Initialization()` randomly initializes a population. This method can be redefined to specify a novel initialization strategy. For example, `Sparse_NN.m` initializes a population in which half the decision variables are zero:

```

function Population = Initialization(obj,N)
    if nargin < 2; N = obj.N; end
    PopDec = (rand(N,obj.D)-0.5)*2.*randi([0 1],N,obj.D);
    Population = SOLUTION(PopDec);
end

```

The default method `CalDec()` repairs invalid solutions in a population, where each decision variable will be set to the boundary values if it is larger than the upper bound or smaller than the lower bound. This method can be redefined to specify a novel repair strategy. For example, `MOKP.m` repairs solutions that exceed the capacity, so that no constraint needs to be defined in this problem:

```

function PopDec = CalDec(obj,PopDec)
    C = sum(obj.W,2)/2;
    [~,rank] = sort(max(obj.P./obj.W));
    for i = 1 : size(PopDec,1)

```



```
while any(obj.W*PopDec(i,:) '>C')
    k = find(PopDec(i,rank),1);
    PopDec(i,rank(k)) = 0;
end
end
end
```

The default method `CalCon()` returns zero as the constraint violation of the solutions in a population, i.e., all the solutions are feasible. This method can be redefined to specify constraint functions for the problem. For example, `CF4.m` calculates a constraint for each solution:

```
function PopCon = CalCon(obj,X)
    t = X(:,2)-sin(6*pi*X(:,1)+2*pi/size(X,2))-0.5*X(:,1)+0.25;
    PopCon = -t./(1+exp(4*abs(t)));
end
```

Use `all(PopCon<=0,2)` to determine whether each solution is feasible or not. Note that equality constraints should be converted into inequality constraints, the details of which can be found in Section 3.2 of *this paper*. The default method `Evaluation()` calls `CalDec()`, `CalObj()`, and `CalCon()` in sequence to instantiate `SOLUTION` objects, and also adds the number of consumed function evaluations `FE`. This method can be redefined to perform solution repair, objective calculation, and constraint calculation in a single function, where `CalDec()`, `CalObj()`, and `CalCon()` will not be called anymore. For example, `MW2.m` calculates objective values and constraint violations in a single function:

```
function Population = Evaluation(obj,varargin)
    X = varargin{1};
    X=max(min(X, repmat(obj.upper, size(X,1),1)), repmat(obj.lower, size(X,1),1));
    z=1-exp(-10*(X(:,obj.M:end)-(repmat(obj.M:obj.D, size(X,1),1)-1)/obj.D).^2);
    g = 1+sum((1.5+(0.1/obj.D)*z.^2-1.5*cos(2*pi*z)),2);
    PopObj(:,1) = X(:,1);
    PopObj(:,2) = g.*(1-PopObj(:,1)./g);
    L = sqrt(2)*PopObj(:,2)-sqrt(2)*PopObj(:,1);
    PopCon = sum(PopObj,2)-1-0.5*sin(3*pi*L).^8;
    Population = SOLUTION(X, PopObj, PopCon, varargin{2:end});
    obj.FE = obj.FE+length(Population);
end
```

The default method `CalObjGrad()` estimates the gradients of objectives via finite difference, while this method can be redefined to calculate gradients more accurately. Similarly, the default method `CalConGrad()` estimates the gradients of constraints via finite difference, while this method can be redefined to calculate gradients more

accurately. The method `GetOptimum()` can be redefined to specify the optimal values of the problem, which are used for metric calculation. For example, `SOP_F8.m` returns the optimal value of the objective function:

```
function R = GetOptimum(obj,N)
    R = -418.9829*obj.D;
end
```

and `DTLZ2.m` returns a set of uniformly distributed points on the Pareto front:

```
function R = GetOptimum(obj,N)
    R = UniformPoint(N,obj.M);
    R = R./repmat(sqrt(sum(R.^2,2)),1,obj.M);
end
```

The strategies for sampling points on different Pareto fronts can be found *here*. The method `GetPF()` can be redefined to specify the Pareto front or feasible regions of multi-objective optimization problems for the visualization achieved in `DrawObj()`. For example, `DTLZ2.m` returns the data for plotting the 2-D and 3-D Pareto fronts:

```
function R = GetPF(obj)
    if obj.M == 2
        R = obj.GetOptimum(100);
    elseif obj.M == 3
        a = linspace(0,pi/2,10)';
        R = {sin(a)*cos(a'), sin(a)*sin(a'), cos(a)*ones(size(a'))};
    else
        R = [];
    end
end
```

and `MW1.m` returns the data for plotting the feasible regions:

```
function R = GetPF(obj)
    [x,y] = meshgrid(linspace(0,1,400),linspace(0,1.5,400));
    z = nan(size(x));
    fes = x+y-1-0.5*sin(2*pi*(sqrt(2)*y-sqrt(2)*x)).^8 <= 0;
    z(fes&0.85*x+y>=1) = 0;
    R = {x,y,z};
end
```

The default method `CalMetric()` feeds a population and the optimal values `optimum` to a metric function to calculate the metric value. This method can be redefined to feed different variables to metric functions. For example, `SMMOP1.m` feeds the Pareto optimal set rather than the points on the Pareto front when calculating the metric value

of IGD<sub>X</sub>:

```
function score = CalMetric(obj,metName,Population)
    switch metName
        case 'IGDX'
            score = feval(metName,Population,obj.POS);
        otherwise
            score = feval(metName,Population,obj.optimum);
    end
end
```

The method `DrawDec()` displays the decision variables of a population, which is used for the visualization of results in the GUI. This method can be redefined to specify a novel visualization method. For example, `TSP.m` displays the route of the best solution:

```
function DrawDec(obj,P)
    [~,best] = min(P.objs);
    Draw(obj.R(P(best).dec([1:end,1]),:),'-k','LineWidth',1.5);
    Draw(obj.R);
end
```

The method `DrawObj()` displays the objective values of a population, which is used for the visualization of results in the GUI. This method can be redefined to specify a novel visualization method. For example, `Sparse_CD.m` adds labels to the axes:

```
function DrawObj(obj,P)
    Draw(P.objs,{ 'Kernel k-means', 'Ratio cut', [] });
end
```

where `Draw()` is a function in the folder `PlatEMO\GUI` for displaying data.

### C. SOLUTION Class

A `SOLUTION` object denotes an individual, and an array of `SOLUTION` objects denote a population. The `SOLUTION` class contains the following properties and methods:

Property	Specified by	Description
<code>dec</code>	Users	Decision variables of the solution
<code>obj</code>	<code>SOLUTION()</code>	Objective values of the solution
<code>con</code>	<code>SOLUTION()</code>	Constraint violations of the solution
<code>add</code>	<code>adds()</code>	Additional properties (e.g., velocity) of the solution
Method		Description
<code>SOLUTION</code>	Generate <code>SOLUTION</code> objects Input 1: A matrix consisting of decision vectors Input 2: A matrix consisting of objective values	

	Input 3: A matrix consisting of constraint violations Input 4: A matrix consisting of additional properties Output: An array of SOLUTION objects
decs	Get the decision variables of multiple solutions Input: None Output: A matrix consisting of decision vectors
objs	Get the objective values of multiple solutions Input: None Output: A matrix consisting of objective values
cons	Get the constraint violations of multiple solutions Input: None Output: A matrix consisting of constraint violations
adds	Set and get the additional properties of multiple solutions Input: Default additional properties Output: A matrix consisting of additional properties
best	Get the feasible and best solution for single-objective optimization, or the feasible and non-dominated solutions for multi-objective optimization Input: None Output: A subarray of best SOLUTION objects in the population

For example, the following code generates a population with ten solutions, then gets the objective matrix of the best solutions in the population:

```
Population = SOLUTION(rand(10,5),rand(10,1),zeros(10,1));
BestObjs   = Population.best.objs
```

Note that SOLUTION() should be called only in the method Evaluation() of PROBLEM class.

### D. Whole Procedure of One Run

The following code uses the genetic algorithm to solve the sphere function:

```
Alg = GA();
Pro = SOP_F1();
Alg.Solve(Pro);
```

where the functions called in the execution of Alg.Solve(Pro) are as follows.



## E. Metric Function

A metric should be written as a function and put in the folder PlatEMO\Metrics. For example, the code of IGD.m is

```

1 function score = IGD(Population, optimum)
2 % <min> <multi/many> <real/integer/label/binary/permutation>
3 % <large> <constrained> <expensive>
4 % <multimodal> <sparse> <dynamic> <robust>
5 % Inverted generational distance
6 %----- Reference -----
7 % C. A. Coello Coello and N. C. Cortes, Solving
8 % multiobjective optimization problem using an artificial
9 % immune system, Genetic Programming and Evolvable

```

```

9 % Machines, 2005, 6(2): 163-190.
10 %-----
11
12     PopObj = Population.best.objs;
13     if size(PopObj,2) ~= size(optimum,2)
14         score = nan;
15     else
16         score = mean(min(pdist2(optimum,PopObj),[],2));
17     end
18 end

```

The functions of each line are as follows:

- Line 1: Function declaration, where the first input is a population (i.e., an array of SOLUTION objects), the second input is the optimums of a problem (i.e., the optimum property of the problem), and the output is the metric value;
- Line 2: Tagging the metric with labels (see *Labels of Algorithms, Problems, and Metrics* for details); note that <min> or <max> should be the first label;
- Line 3: Full name of the metric;
- Lines 5-10: Reference of the metric;
- Line 12: Obtaining the feasible and non-dominated solutions in the population;
- Lines 13-14: Returns nan if there is no feasible solution in the population;
- Lines 15-16: Returns the IGD value of the feasible and non-dominated solutions.

## V. List of Algorithms

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
1	ABC	Artificial bee colony algorithm	√			√	√				√	√							
2	AB-SAEA	Adaptive Bayesian based surrogate-assisted evolutionary algorithm		√	√	√	√						√						
3	ACO	Ant colony optimization	√							√	√								
4	Adam	Adaptive moment estimation	√			√					√								
5	AdaW	Evolutionary algorithm with adaptive weights		√	√	√	√	√	√	√									
6	ADSAPSO	Adaptive dropout based surrogate-assisted particle swarm optimization		√	√	√	√						√						
7	AGE-II	Approximation-guided evolutionary multi-objective algorithm II		√		√	√	√	√	√									
8	AGE-MOEA	Adaptive geometry estimation-based many-objective evolutionary algorithm		√	√	√	√	√	√	√		√							
9	AGE-MOEA-II	Adaptive geometry estimation-based many-objective evolutionary algorithm II		√	√	√	√	√	√	√		√							
10	A-NSGA-III	Adaptive NSGA-III		√	√	√	√	√	√	√		√							
11	AR-MOEA	Adaptive reference points based multi-objective evolutionary algorithm		√	√	√	√	√	√	√		√							
12	BCE-IBEA	Bi-criterion evolution based IBEA		√	√	√	√	√	√	√									
13	BCE-MOEA/D	Bi-criterion evolution based MOEA/D		√	√	√	√	√	√	√									
14	BFGS	A quasi-Newton method proposed by Broyden, Fletcher, Goldfarb, and Shanno	√			√					√								
15	BiCo	Bidirectional coevolution constrained multiobjective evolutionary algorithm		√		√	√	√	√	√		√							
16	BiGE	Bi-goal evolution			√	√	√	√	√	√									
17	BLEAQII	Bilevel evolutionary algorithm based on quadratic approximations II		√		√						√						√	
18	BSPGA	Binary space partition tree based genetic algorithm	√						√		√	√							
19	C3M	Constraint, multiobjective, multi-stage, multi-constraint evolutionary algorithm		√		√	√	√	√	√		√							
20	CAEAD	Dual-population evolutionary algorithm based on alternative evolution and degeneration		√		√	√	√	√	√		√							
21	CA-MOEA	Clustering based adaptive multi-objective evolutionary algorithm		√		√	√	√	√	√									
22	CCGDE3	Cooperative coevolution GDE3		√		√	√				√								
23	CCMO	Coevolutionary constrained multi-objective optimization framework		√		√	√	√	√	√		√							
24	c-DPEA	Constrained dual-population evolutionary algorithm		√		√	√	√	√	√		√							
25	CLIA	Evolutionary algorithm with cascade clustering and reference point incremental learning		√	√	√	√	√	√	√									
26	CMA-ES	Covariance matrix adaptation evolution strategy	√			√	√				√	√							

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
27	CMEGL	Constrained evolutionary multitasking with global and local auxiliary tasks		√		√	√	√	√	√		√							
28	CMME	Constrained many-objective evolutionary algorithm with enhanced mating and environmental selections		√		√	√	√	√	√		√							
29	CMMO	Coevolutionary multi-modal multi-objective optimization framework		√		√	√	√	√	√				√					
30	CMOCSO	Competitive and cooperative swarm optimization constrained multi-objective optimization algorithm		√		√					√	√							
31	C-MOEA/D	Constraint-MOEA/D		√	√	√	√	√	√	√		√							
32	CMOEA-MS	Constrained multiobjective evolutionary algorithm with multiple stages		√		√	√	√	√	√		√							
33	CMOEMT	Constrained multi-objective optimization based on evolutionary multitasking optimization		√		√						√							
34	CMOPSO	Competitive mechanism based multi-objective particle swarm optimizer		√		√	√												
35	CMOQLMT	Constrained multi-objective optimization based on Q-learning and multitasking		√		√						√							
36	CMOSMA	Constrained multi-objective evolutionary algorithm with self-organizing map		√	√	√	√					√							
37	CNSDE/DVC	Constrained nondominated sorting differential evolution based on decision variable classification		√		√	√												√
38	CoMMEA	Coevolutionary multimodal multi-objective evolutionary algorithm		√		√	√	√	√	√				√					
39	CPS-MOEA	Classification and Pareto domination based multi-objective evolutionary		√		√	√						√						
40	CSEA	Classification based surrogate-assisted evolutionary algorithm		√	√	√							√						
41	CSO	Competitive swarm optimizer	√			√	√				√	√							
42	C-TAEA	Two-archive evolutionary algorithm for constrained MOPs		√	√	√	√	√	√	√		√							
43	C-TSEA	Constrained two-stage evolutionary algorithm		√	√	√	√	√	√	√		√							
44	DAEA	Duplication analysis based evolutionary algorithm		√					√										
45	DCNSGA-III	Dynamic constrained NSGA-III		√	√	√	√	√	√	√		√							
46	DE	Differential evolution	√			√	√				√	√							
47	DEA-GNG	Decomposition based evolutionary algorithm guided by growing neural gas		√	√	√	√	√	√	√									
48	DGEA	Direction guided evolutionary algorithm		√	√	√	√				√								
49	DMOEA-eC	Decomposition-based multi-objective evolutionary algorithm with the e-constraint framework		√		√	√	√	√	√									
50	dMOPSO	MOPSO based on decomposition		√		√	√												
51	DN-NSGA-II	Decision space based niching NSGA-II		√		√	√							√					
52	DNSGA-II	Dynamic NSGA-II		√		√	√	√	√	√						√			
53	DP-PPS	Tri-population based push and pull search		√		√						√							
54	DSPCMDE	Dynamic selection preference-assisted constrained multiobjective differential evolution		√		√	√					√							
55	DWU	Dominance-weighted uniformity multi-objective evolutionary algorithm		√		√	√	√	√	√									



	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
56	EAG-MOEA/D	External archive guided MOEA/D		√		√	√	√	√	√									
57	EDN-ARMOEA	Efficient dropout neural network based AR-MOEA		√	√	√	√						√						
58	EFR-RR	Ensemble fitness ranking with a ranking restriction scheme		√	√	√	√	√	√	√									
59	EGO	Efficient global optimization	√			√	√						√						
60	EIM-EGO	Expected improvement matrix based efficient global optimization		√		√	√						√						
61	EMCMO	Evolutionary multitasking-based constrained multiobjective optimization		√		√	√	√	√	√		√							
62	EMMOEA	Expensive multi-/many-objective evolutionary algorithm		√		√	√						√						
63	e-MOEA	Epsilon multi-objective evolutionary algorithm		√	√	√	√	√	√	√									
64	EMyO/C	Evolutionary many-objective optimization algorithm with clustering-based		√	√	√	√												
65	ENS-MOEA/D	Ensemble of different neighborhood sizes based MOEA/D		√	√	√	√												
66	ESBCEO	Bayesian co-evolutionary optimization based entropy search		√		√							√						
67	FDV	Fuzzy decision variable framework with various internal optimizers		√	√	√	√				√								
68	FEP	Fast evolutionary programming	√			√	√				√	√							
69	FLEA	Fast sampling based evolutionary algorithm		√	√	√					√								
70	FRCG	Fletcher-Reeves conjugate gradient	√			√					√								
71	FRCGM	Fletcher-Reeves conjugate gradient (for multi-objective optimization)		√	√	√					√	√							
72	FROFI	Feasibility rule with the incorporation of objective function information	√			√	√				√	√							
73	GA	Genetic algorithm	√			√	√	√	√	√	√	√							
74	GDE3	Generalized differential evolution 3		√		√	√					√							
75	GFM-MOEA	Generic front modeling based multi-objective evolutionary algorithm		√	√	√	√	√	√	√									
76	GLMO	Grouped and linked mutation operator algorithm		√		√	√				√								
77	g-NSGA-II	g-dominance based NSGA-II		√		√	√	√	√	√									
78	GPSO	Gradient based particle swarm optimization algorithm	√			√					√	√							
79	GPSOM	Gradient based particle swarm optimization algorithm (for multi-objective optimization)		√	√	√					√	√							
80	GrEA	Grid-based evolutionary algorithm			√	√	√	√	√	√									
81	HeE-MOEA	Multiobjective evolutionary algorithm with heterogeneous ensemble based infill criterion		√		√	√						√						
82	HHC-MMEA	Hybrid hierarchical clustering based multimodal multi-objective evolutionary algorithm		√		√					√			√	√				
83	hpaEA	Hyperplane assisted evolutionary algorithm		√	√	√	√	√	√	√									
84	HREA	Hierarchy ranking based evolutionary algorithm		√		√	√							√					

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
85	HypE	Hypervolume estimation algorithm		√	√	√	√	√	√	√									
86	IBEA	Indicator-based evolutionary algorithm		√	√	√	√	√	√	√									
87	ICMA	Indicator based constrained multi-objective algorithm		√		√	√					√							
88	I-DBEA	Improved decomposition-based evolutionary algorithm		√	√	√	√	√	√	√		√							
89	IM-MOEA	Inverse modeling based multiobjective evolutionary algorithm		√		√	√				√								
90	IM-MOEA/D	Inverse modeling multiobjective evolutionary algorithm based on decomposition		√		√	√				√								
91	IMODE	Improved multi-operator differential evolution	√			√	√				√	√							
92	IMTCMO	Improved evolutionary multitasking-based CMOEA		√		√	√	√	√	√		√							
93	I-SIBEA	Interactive simple indicator-based evolutionary algorithm		√		√	√	√	√	√									
94	Izui	An aggregative gradient based multi-objective optimizer proposed by Izui et al.		√	√	√					√	√							
95	KnEA	Knee point driven evolutionary algorithm			√	√	√	√	√	√		√							
96	K-RVEA	Surrogate-assisted RVEA		√	√	√	√						√						
97	KTA2	Kriging-assisted Two_Arch2		√	√	√	√						√						
98	KTS	Kriging-assisted evolutionary algorithm with two search modes		√	√		√					√	√						
99	LCSA	Linear combination-based search algorithm		√	√	√	√				√								
100	LERD	Large-scale evolutionary algorithm with reformulated decision variable analysis		√	√	√					√								
101	LMEA	Evolutionary algorithm for large-scale many-objective optimization		√	√	√	√				√								
102	LMOCSSO	Large-scale multi-objective competitive swarm optimization algorithm		√	√	√	√				√	√							
103	LMOEA-DS	Large-scale evolutionary multi-objective optimization assisted by directed sampling		√		√	√				√								
104	LMPFE	Evolutionary algorithm with local model based Pareto front estimation		√	√	√	√	√	√	√									
105	LSMOF	Large-scale multi-objective optimization framework with NSGA-II		√		√	√				√								
106	MaOEA-CSS	Many-objective evolutionary algorithms based on coordinated selection		√	√	√	√	√	√	√									
107	MaOEA-DDFC	Many-objective evolutionary algorithm based on directional diversity and favorable convergence		√	√	√	√	√	√	√									
108	MaOEA/IGD	IGD based many-objective evolutionary algorithm			√	√	√	√	√	√									
109	MaOEA/IT	Many-objective evolutionary algorithms based on an independent two-stage		√	√	√	√					√							
110	MaOEA-R&D	Many-objective evolutionary algorithm based on objective space reduction			√	√	√	√	√	√									
111	MCCMO	Multi-population coevolutionary constrained multi-objective optimization		√		√	√	√	√	√		√							
112	MCEA/D	Multiple classifiers-assisted evolutionary		√	√	√	√						√						

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
		algorithm based on decomposition																	
113	MFEA	Multifactorial evolutionary algorithm	√			√	√	√	√	√	√						√		
114	MFEA-II	Multifactorial evolutionary algorithm II	√			√	√	√	√	√	√						√		
115	MMEA-WI	Weighted indicator-based evolutionary algorithm for multimodal multi-objective optimization		√		√	√							√					
116	MMOPSO	MOPSO with multiple search strategies		√		√	√												
117	MO_Ring_PSO_SCD	Multiobjective PSO using ring topology and special crowding distance		√		√	√							√					
118	MOCeII	Cellular genetic algorithm		√		√	√	√	√	√		√							
119	MOCGDE	Multi-objective conjugate gradient and differential evolution algorithm		√	√	√					√	√							
120	MO-CMA	Multi-objective covariance matrix adaptation evolution strategy		√		√	√												
121	MOEA/D	Multiobjective evolutionary algorithm based on decomposition		√	√	√	√	√	√	√									
122	MOEA/D-AWA	MOEA/D with adaptive weight adjustment		√	√	√	√	√	√	√									
123	MOEA/D-CMA	MOEA/D with covariance matrix adaptation evolution strategy		√	√	√	√												
124	MOEA/DD	Many-objective evolutionary algorithm based on dominance and decomposition		√	√	√	√	√	√	√		√							
125	MOEA/D-DAE	MOEA/D with detect-and-escape strategy		√		√	√	√	√	√		√							
126	MOEA/D-DCWV	MOEA/D with distribution control of weight vector set		√	√	√	√	√	√	√									
127	MOEA/D-DE	MOEA/D based on differential evolution		√	√	√	√												
128	MOEA/D-DRA	MOEA/D with dynamical resource allocation		√	√	√	√												
129	MOEA/D-DU	MOEA/D with a distance based updating strategy		√	√	√	√	√	√	√									
130	MOEA/D-DYTS	MOEA/D with dynamic Thompson sampling		√	√	√	√												
131	MOEA/D-EGO	MOEA/D with efficient global optimization		√		√	√						√						
132	MOEA/D-FRRMAB	MOEA/D with fitness-rate-rank-based multiarmed bandit		√	√	√	√												
133	MOEA/D-M2M	MOEA/D based on MOP to MOP		√		√	√												
134	MOEA/D-MRDL	MOEA/D with maximum relative diversity loss		√		√	√												
135	MOEA/D-PaS	MOEA/D with Pareto adaptive scalarizing approximation		√	√	√	√												
136	MOEA/D-PFE	MOEA/D with Pareto front estimation		√	√	√	√	√	√	√									
137	MOEA/D-STM	MOEA/D with stable matching		√	√	√	√												
138	MOEA/D-UR	MOEA/D with update when required		√	√	√	√	√	√	√									
139	MOEA/D-URAW	MOEA/D with uniform randomly adaptive weights		√	√	√	√	√	√	√									
140	MOEA/DVA	Multi-objective evolutionary algorithm based on decision variable		√		√	√				√								
141	MOEA/D-VOV	MOEA/D with virtual objective vectors		√	√	√	√	√	√	√									

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
142	MOEA/IGD-NS	Multi-objective evolutionary algorithm based on an enhanced IGD		√		√	√	√	√	√									
143	MOEA-PC	Multiobjective evolutionary algorithm based on polar coordinates		√		√	√												
144	MOEA/PSL	Multi-objective evolutionary algorithm based on Pareto optimal subspace		√		√	√		√		√	√			√				
145	MOEA-RE	Multi-objective evolutionary algorithm with robustness enhancement		√		√	√	√	√	√									√
146	MO-EGS	Multi-objective evolutionary gradient search		√		√					√								
147	MOMBI-II	Many objective metaheuristic based on the R2 indicator II		√	√	√	√	√	√	√									
148	MO-MFEA	Multi-objective multifactorial evolutionary algorithm		√		√	√	√	√	√		√					√		
149	MO-MFEA-II	Multi-objective multifactorial evolutionary algorithm II		√		√	√	√	√	√		√					√		
150	MOPSO	Multi-objective particle swarm optimization		√		√	√												
151	MOPSO-CD	MOPSO with crowding distance		√		√	√												
152	MOSD	Multiobjective steepest descent		√		√					√	√							
153	M-PAES	Memetic algorithm with Pareto archived evolution strategy		√		√	√												
154	MP-MMEA	Multi-population multi-modal multi-objective evolutionary algorithm		√		√	√				√			√	√				
155	MPSO/D	Multi-objective particle swarm optimization algorithm based on decomposition		√	√	√	√												
156	MSCMO	Multi-stage constrained multi-objective evolutionary algorithm		√		√	√	√	√	√		√							
157	MSEA	Multi-stage multi-objective evolutionary algorithm		√		√	√	√	√	√									
158	MSKEA	Multi-stage knowledge-guided evolutionary algorithm		√		√	√		√		√	√			√				
159	MSOPS-II	Multiple single objective Pareto sampling II		√	√	√	√					√							
160	MTCMO	Multitasking constrained multi-objective optimization		√		√	√	√	√	√		√							
161	MTS	Multiple trajectory search		√		√	√												
162	MultiObjective EGO	Multi-objective efficient global optimization		√		√	√					√	√						
163	MyO-DEMR	Many-objective differential evolution with mutation restriction		√	√	√	√												
164	NBLEA	Nested bilevel evolutionary algorithm		√		√						√						√	
165	NelderMead	The Nelder-Mead algorithm	√			√													
166	NMPSO	Novel multi-objective particle swarm optimization		√	√	√	√												
167	NNIA	Nondominated neighbor immune algorithm		√		√	√	√	√	√									
168	NSGA-II	Nondominated sorting genetic algorithm II		√		√	√	√	√	√		√							
169	NSGA-II+ARSBX	NSGA-II with adaptive rotation based simulated binary crossover		√		√	√					√							
170	NSGA-II-conflict	NSGA-II with conflict-based partitioning strategy			√	√	√	√	√	√									

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
171	NSGA-II-DTI	NSGA-II of Deb's type I robust version		√		√	√	√	√	√		√							√
172	NSGA-III	Nondominated sorting genetic algorithm III		√	√	√	√	√	√	√		√							
173	NSGA-II/SDR	NSGA-II with strengthened dominance relation			√	√	√	√	√	√									
174	NSLS	Multiobjective optimization framework based on nondominated sorting and local search		√		√	√												
175	OFA	Optimal foraging algorithm	√			√	√				√	√							
176	one-by-one EA	Many-objective evolutionary algorithm using a one-by-one selection		√	√	√	√	√	√	√									
177	OSP-NSDE	Non-dominated sorting differential evolution with prediction in the objective space		√		√	√												
178	ParEGO	Efficient global optimization for Pareto optimization		√		√	√						√						
179	PB-NSGA-III	NSGA-III based on Pareto based bi-indicator infill sampling criterion		√	√	√	√						√						
180	PB-RVEA	RVEA based on Pareto based bi-indicator infill sampling criterion		√	√	√	√						√						
181	PC-SAEA	Pairwise comparison based surrogate-assisted evolutionary algorithm		√	√								√						
182	PeEA	Pareto front shape estimation based evolutionary algorithm		√	√	√	√	√	√	√									
183	PESA-II	Pareto envelope-based selection algorithm II		√		√	√	√	√	√									
184	PICEA-g	Preference-inspired coevolutionary algorithm with goals		√	√	√	√	√	√	√									
185	PM-MOEA	Pattern mining based multi-objective evolutionary algorithm		√		√	√		√		√	√			√				
186	POCEA	Paired offspring generation based constrained evolutionary algorithm		√		√	√				√	√							
187	PPS	Push and pull search algorithm		√	√	√	√					√							
188	PREA	Promising-region based EMO algorithm		√	√	√	√	√	√	√									
189	PSO	Particle swarm optimization	√			√	√				√	√							
190	REMO	Expensive multiobjective optimization by relation learning and prediction		√	√	√							√						
191	RM-MEDA	Regularity model-based multiobjective estimation of distribution		√		√	√												
192	RMOEA/DVA	Robust multi-objective evolutionary algorithm with decision variable assortment		√		√	√												√
193	RMSProp	Root mean square propagation	√			√					√								
194	r-NSGA-II	r-dominance based NSGA-II		√		√	√	√	√	√									
195	RPD-NSGA-II	Reference point dominance-based NSGA-II		√	√	√	√	√	√	√									
196	RPEA	Reference points-based evolutionary algorithm			√	√	√	√	√	√									
197	RSEA	Radial space division based evolutionary algorithm		√	√	√	√	√	√	√									
198	RVEA	Reference vector guided evolutionary algorithm		√	√	√	√	√	√	√		√							
199	RVEAa	RVEA embedded with the reference vector regeneration strategy			√	√	√	√	√	√									
200	RVEA-iGNG	RVEA based on improved growing neural gas		√	√	√	√	√	√	√									

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
201	S3-CMA-ES	Scalable small subpopulations based covariance matrix adaptation		√	√	√	√				√								
202	SA	Simulated annealing	√			√	√				√	√							
203	SACC-EAM-II	Surrogate-assisted cooperative co-evolutionary algorithm of Minamo	√			√	√						√						
204	SACOSO	Surrogate-assisted cooperative swarm optimization	√			√	√				√		√						
205	SADE-Sammon	Sammon mapping assisted differential evolution	√			√	√						√						
206	SAMSO	Multiswarm-assisted expensive optimization	√			√	√				√		√						
207	S-CDAS	Self-controlling dominance area of solutions			√	√	√	√	√	√									
208	SD	Steepest descent	√			√					√								
209	S-ECSSO	Enhanced competitive swarm optimizer for sparse optimization		√		√					√				√				
210	SSEA	Steady-state and generational evolutionary algorithm		√		√	√	√	√	√		√				√			
211	SGECF	Sparsity-guided elitism co-evolutionary framework		√		√			√		√	√			√				
212	SHADE	Success-history based adaptive differential evolution	√			√	√				√	√							
213	SIBEA	Simple indicator-based evolutionary algorithm		√		√	√	√	√	√									
214	SIBEA-kEMOSS	SIBEA with minimum objective subset of size k with minimum error			√	√	√	√	√	√									
215	SLMEA	Super-large-scale multi-objective evolutionary algorithm		√		√	√		√		√	√			√				
216	SMEA	Self-organizing multiobjective evolutionary algorithm		√		√	√												
217	SMOA	Supervised multi-objective optimization algorithm		√		√							√						
218	SMPSO	Speed-constrained multi-objective particle swarm optimization		√		√	√												
219	SMS-EGO	S metric selection based efficient global optimization		√		√	√						√						
220	SMS-EMOA	S metric selection based evolutionary multiobjective optimization		√		√	√	√	√	√									
221	S-NSGA-II	Sparse NSGA-II		√		√					√	√			√				
222	SparseEA	Evolutionary algorithm for sparse multi-objective optimization problems		√		√	√		√		√	√			√				
223	SparseEA2	Improved SparseEA		√		√	√		√		√	√			√				
224	SPEA2	Strength Pareto evolutionary algorithm 2		√		√	√	√	√	√									
225	SPEA2+SDE	SPEA2 with shift-based density estimation			√	√	√	√	√	√									
226	SPEA/R	Strength Pareto evolutionary algorithm based on reference direction		√	√	√	√	√	√	√									
227	SQP	Sequential quadratic programming	√			√					√	√							
228	SRA	Stochastic ranking algorithm			√	√	√	√	√	√									
229	t-DEA	theta-dominance based evolutionary algorithm		√	√	√	√	√	√	√									
230	TiGE-2	Tri-Goal Evolution Framework for CMaOPs			√	√	√	√	√	√		√							
231	ToP	Two-phase framework with NSGA-II		√		√	√					√							

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
232	TriMOEA-TA&R	Multi-modal MOEA using two-archive and recombination strategies		√		√	√							√					
233	TriP	Tri-population based coevolutionary algorithm		√	√	√	√					√							
234	TS-NSGA-II	Two stage NSGA-II		√	√	√	√	√	√	√									
235	TSTI	Two-stage evolutionary algorithm with three indicators		√		√	√	√	√	√		√							
236	Two_Arch2	Two-archive algorithm 2		√	√	√	√	√	√	√									
237	URCMO	Utilizing the relationship between constrained and unconstrained Pareto fronts for constrained multi-objective optimization		√		√	√					√							
238	VaEA	Vector angle based evolutionary algorithm		√	√	√	√	√	√	√									
239	WOF	Weighted optimization framework		√		√	√				√								
240	WV-MOEA-P	Weight vector based multi-objective optimization algorithm with preference		√		√	√												

## VI. List of Problems

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
1	BT1	Benchmark MOP with bias feature		√		√					√								
2	BT2	Benchmark MOP with bias feature		√		√					√								
3	BT3	Benchmark MOP with bias feature		√		√					√								
4	BT4	Benchmark MOP with bias feature		√		√					√								
5	BT5	Benchmark MOP with bias feature		√		√					√								
6	BT6	Benchmark MOP with bias feature		√		√					√								
7	BT7	Benchmark MOP with bias feature		√		√					√								
8	BT8	Benchmark MOP with bias feature		√		√					√								
9	BT9	Benchmark MOP with bias feature		√		√					√								
10	C10MOP1	Neural architecture search on CIFAR-10		√		√					√		√						
11	C10MOP2	Neural architecture search on CIFAR-10		√		√					√		√						
12	C10MOP3	Neural architecture search on CIFAR-10		√		√					√		√						
13	C10MOP4	Neural architecture search on CIFAR-10		√		√					√		√						
14	C10MOP5	Neural architecture search on CIFAR-10		√		√					√		√						
15	C10MOP6	Neural architecture search on CIFAR-10		√		√					√		√						
16	C10MOP7	Neural architecture search on CIFAR-10		√		√					√		√						
17	C10MOP8	Neural architecture search on CIFAR-10		√		√					√		√						
18	C10MOP9	Neural architecture search on CIFAR-10		√		√					√		√						
19	CEC2008_F1	Shifted sphere function	√			√					√		√						
20	CEC2008_F2	Shifted Schwefel's function	√			√					√		√						
21	CEC2008_F3	Shifted Rosenbrock's function	√			√					√		√						
22	CEC2008_F4	Shifted Rastrign's function	√			√					√		√						
23	CEC2008_F5	Shifted Griewank's function	√			√					√		√						
24	CEC2008_F6	Shifted Ackley's function	√			√					√		√						
25	CEC2008_F7	FastFractal 'DoubleDip' function	√			√					√		√						
26	CEC2010_F1	CEC'2010 constrained optimization benchmark problem	√			√						√							
27	CEC2010_F2	CEC'2010 constrained optimization benchmark problem	√			√						√							
28	CEC2010_F3	CEC'2010 constrained optimization benchmark problem	√			√						√							
29	CEC2010_F4	CEC'2010 constrained optimization benchmark problem	√			√						√							
30	CEC2010_F5	CEC'2010 constrained optimization benchmark problem	√			√						√							



	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
31	CEC2010_F6	CEC'2010 constrained optimization benchmark problem	√			√						√							
32	CEC2010_F7	CEC'2010 constrained optimization benchmark problem	√			√						√							
33	CEC2010_F8	CEC'2010 constrained optimization benchmark problem	√			√						√							
34	CEC2010_F9	CEC'2010 constrained optimization benchmark problem	√			√						√							
35	CEC2010_F10	CEC'2010 constrained optimization benchmark problem	√			√						√							
36	CEC2010_F11	CEC'2010 constrained optimization benchmark problem	√			√						√							
37	CEC2010_F12	CEC'2010 constrained optimization benchmark problem	√			√						√							
38	CEC2010_F13	CEC'2010 constrained optimization benchmark problem	√			√						√							
39	CEC2010_F14	CEC'2010 constrained optimization benchmark problem	√			√						√							
40	CEC2010_F15	CEC'2010 constrained optimization benchmark problem	√			√						√							
41	CEC2010_F16	CEC'2010 constrained optimization benchmark problem	√			√						√							
42	CEC2010_F17	CEC'2010 constrained optimization benchmark problem	√			√						√							
43	CEC2010_F18	CEC'2010 constrained optimization benchmark problem	√			√						√							
44	CEC2013_F1	Shifted elliptic function	√			√					√								
45	CEC2013_F2	Shifted Rastrigin's function	√			√					√								
46	CEC2013_F3	Shifted Ackley's function	√			√					√								
47	CEC2013_F4	7-nonseparable, 1-separable shifted and rotated elliptic function	√			√					√								
48	CEC2013_F5	7-nonseparable, 1-separable shifted and rotated Rastrigin's function	√			√					√								
49	CEC2013_F6	7-nonseparable, 1-separable shifted and rotated Ackley's function	√			√					√								
50	CEC2013_F7	7-nonseparable, 1-separable shifted and rotated Schwefel's function	√			√					√								
51	CEC2013_F8	20-nonseparable shifted and rotated elliptic function	√			√					√								
52	CEC2013_F9	20-nonseparable shifted and rotated Rastrigin's function	√			√					√								
53	CEC2013_F10	20-nonseparable shifted and rotated Rastrigin's function	√			√					√								
54	CEC2013_F11	20-nonseparable shifted and rotated Schwefel's function	√			√					√								
55	CEC2013_F12	Shifted Rosenbrock's function	√			√					√								
56	CEC2013_F13	Shifted Schwefel's function with conforming overlapping subcomponents	√			√					√								
57	CEC2013_F14	Shifted Schwefel's function with conflicting	√			√					√								

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
		overlapping subcomponents																	
58	CEC2013_F15	Shifted Schwefel's function	√			√					√								
59	CEC2017_F1	CEC'2017 constrained optimization benchmark problem	√			√						√							
60	CEC2017_F2	CEC'2017 constrained optimization benchmark problem	√			√						√							
61	CEC2017_F3	CEC'2017 constrained optimization benchmark problem	√			√						√							
62	CEC2017_F4	CEC'2017 constrained optimization benchmark problem	√			√						√							
63	CEC2017_F5	CEC'2017 constrained optimization benchmark problem	√			√						√							
64	CEC2017_F6	CEC'2017 constrained optimization benchmark problem	√			√						√							
65	CEC2017_F7	CEC'2017 constrained optimization benchmark problem	√			√						√							
66	CEC2017_F8	CEC'2017 constrained optimization benchmark problem	√			√						√							
67	CEC2017_F9	CEC'2017 constrained optimization benchmark problem	√			√						√							
68	CEC2017_F10	CEC'2017 constrained optimization benchmark problem	√			√						√							
69	CEC2017_F11	CEC'2017 constrained optimization benchmark problem	√			√						√							
70	CEC2017_F12	CEC'2017 constrained optimization benchmark problem	√			√						√							
71	CEC2017_F13	CEC'2017 constrained optimization benchmark problem	√			√						√							
72	CEC2017_F14	CEC'2017 constrained optimization benchmark problem	√			√						√							
73	CEC2017_F15	CEC'2017 constrained optimization benchmark problem	√			√						√							
74	CEC2017_F16	CEC'2017 constrained optimization benchmark problem	√			√						√							
75	CEC2017_F17	CEC'2017 constrained optimization benchmark problem	√			√						√							
76	CEC2017_F18	CEC'2017 constrained optimization benchmark problem	√			√						√							
77	CEC2017_F19	CEC'2017 constrained optimization benchmark problem	√			√						√							
78	CEC2017_F20	CEC'2017 constrained optimization benchmark problem	√			√						√							
79	CEC2017_F21	CEC'2017 constrained optimization benchmark problem	√			√						√							
80	CEC2017_F22	CEC'2017 constrained optimization benchmark problem	√			√						√							
81	CEC2017_F23	CEC'2017 constrained optimization benchmark problem	√			√						√							

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
82	CEC2017_F24	CEC'2017 constrained optimization benchmark problem	√			√						√							
83	CEC2017_F25	CEC'2017 constrained optimization benchmark problem	√			√						√							
84	CEC2017_F26	CEC'2017 constrained optimization benchmark problem	√			√						√							
85	CEC2017_F27	CEC'2017 constrained optimization benchmark problem	√			√						√							
86	CEC2017_F28	CEC'2017 constrained optimization benchmark problem	√			√						√							
87	CEC2020_F1	Bent cigar function	√			√													
88	CEC2020_F2	Shifted and rotated Schwefel's function	√			√													
89	CEC2020_F3	Shifted and rotated Lunacek bi-Rastrigin function	√			√													
90	CEC2020_F4	Expanded Rosenbrock's plus Griewangk's function	√			√													
91	CEC2020_F5	Hybrid function 1	√			√													
92	CEC2020_F6	Hybrid function 2	√			√													
93	CEC2020_F7	Hybrid function 3	√			√													
94	CEC2020_F8	Composition function 1	√			√													
95	CEC2020_F9	Composition function 2	√			√													
96	CEC2020_F10	Composition function 3	√			√													
97	CF1	Constrained benchmark MOP		√		√					√	√							
98	CF2	Constrained benchmark MOP		√		√					√	√							
99	CF3	Constrained benchmark MOP		√		√					√	√							
100	CF4	Constrained benchmark MOP		√		√					√	√							
101	CF5	Constrained benchmark MOP		√		√					√	√							
102	CF6	Constrained benchmark MOP		√		√					√	√							
103	CF7	Constrained benchmark MOP		√		√					√	√							
104	CF8	Constrained benchmark MOP		√		√					√	√							
105	CF9	Constrained benchmark MOP		√		√					√	√							
106	CF10	Constrained benchmark MOP		√		√					√	√							
107	CI_HS	Multitasking problem (Griewank function + Rastrigin function)	√			√					√						√		
108	CI_LS	Multitasking problem (Ackley function + Schwefel function)	√			√					√						√		
109	CI_MS	Multitasking problem (Ackley function + Rastrigin function)	√			√					√						√		
110	Community Detection	The community detection problem with label based encoding	√					√			√		√						
111	DAS-CMOP1	Difficulty-adjustable and scalable constrained benchmark MOP		√		√					√	√							
112	DAS-CMOP2	Difficulty-adjustable and scalable constrained		√		√					√	√							

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
		benchmark MOP																	
113	DAS-CMOP3	Difficulty-adjustable and scalable constrained benchmark MOP		√		√					√	√							
114	DAS-CMOP4	Difficulty-adjustable and scalable constrained benchmark MOP		√		√					√	√							
115	DAS-CMOP5	Difficulty-adjustable and scalable constrained benchmark MOP		√		√					√	√							
116	DAS-CMOP6	Difficulty-adjustable and scalable constrained benchmark MOP		√		√					√	√							
117	DAS-CMOP7	Difficulty-adjustable and scalable constrained benchmark MOP		√		√					√	√							
118	DAS-CMOP8	Difficulty-adjustable and scalable constrained benchmark MOP		√		√					√	√							
119	DAS-CMOP9	Difficulty-adjustable and scalable constrained benchmark MOP		√		√					√	√							
120	DOC1	Benchmark MOP with constraints in decision and objective spaces		√		√						√							
121	DOC2	Benchmark MOP with constraints in decision and objective spaces		√		√						√							
122	DOC3	Benchmark MOP with constraints in decision and objective spaces		√		√						√							
123	DOC4	Benchmark MOP with constraints in decision and objective spaces		√		√						√							
124	DOC5	Benchmark MOP with constraints in decision and objective spaces		√		√						√							
125	DOC6	Benchmark MOP with constraints in decision and objective spaces		√		√						√							
126	DOC7	Benchmark MOP with constraints in decision and objective spaces		√		√						√							
127	DOC8	Benchmark MOP with constraints in decision and objective spaces		√		√						√							
128	DOC9	Benchmark MOP with constraints in decision and objective spaces		√		√						√							
129	DTLZ1	Benchmark MOP proposed by Deb, Thiele, Laumanns, and Zitzler		√	√	√					√		√						
130	DTLZ2	Benchmark MOP proposed by Deb, Thiele, Laumanns, and Zitzler		√	√	√					√		√						
131	DTLZ3	Benchmark MOP proposed by Deb, Thiele, Laumanns, and Zitzler		√	√	√					√		√						
132	DTLZ4	Benchmark MOP proposed by Deb, Thiele, Laumanns, and Zitzler		√	√	√					√		√						
133	DTLZ5	Benchmark MOP proposed by Deb, Thiele, Laumanns, and Zitzler		√	√	√					√		√						
134	DTLZ6	Benchmark MOP proposed by Deb, Thiele, Laumanns, and Zitzler		√	√	√					√		√						
135	DTLZ7	Benchmark MOP proposed by Deb, Thiele, Laumanns, and Zitzler		√	√	√					√		√						
136	DTLZ8	Benchmark MOP proposed by Deb, Thiele, Laumanns, and Zitzler		√	√	√					√	√	√						

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
137	DTLZ9	Benchmark MOP proposed by Deb, Thiele, Laumanns, and Zitzler		√	√	√					√	√	√						
138	CDTLZ2	Convex DTLZ2		√	√	√					√		√						
139	IDTLZ1	Inverted DTLZ1		√	√	√					√		√						
140	IDTLZ2	Inverted DTLZ2		√	√	√					√		√						
141	SDTLZ1	Scaled DTLZ1		√	√	√					√		√						
142	SDTLZ2	Scaled DTLZ2		√	√	√					√		√						
143	C1-DTLZ1	Constrained DTLZ1		√	√	√					√	√	√						
144	C1-DTLZ3	Constrained DTLZ3		√	√	√					√	√	√						
145	C2-DTLZ2	Constrained DTLZ2		√	√	√					√	√	√						
146	C3-DTLZ4	Constrained DTLZ4		√	√	√					√	√	√						
147	DC1-DTLZ1	DTLZ1 with constrains in decision space		√	√	√					√	√	√						
148	DC1-DTLZ3	DTLZ3 with constrains in decision space		√	√	√					√	√	√						
149	DC2-DTLZ1	DTLZ1 with constrains in decision space		√	√	√					√	√	√						
150	DC2-DTLZ3	DTLZ3 with constrains in decision space		√	√	√					√	√	√						
151	DC3-DTLZ1	DTLZ1 with constrains in decision space		√	√	√					√	√	√						
152	DC3-DTLZ3	DTLZ3 with constrains in decision space		√	√	√					√	√	√						
153	FCP1	Benchmark constrained MOP proposed by Yuan		√		√						√							
154	FCP2	Benchmark constrained MOP proposed by Yuan		√		√						√							
155	FCP3	Benchmark constrained MOP proposed by Yuan		√		√						√							
156	FCP4	Benchmark constrained MOP proposed by Yuan		√		√						√							
157	FCP5	Benchmark constrained MOP proposed by Yuan		√		√						√							
158	FDA1	Benchmark dynamic MOP proposed by Farina, Deb, and Amato		√		√					√					√			
159	FDA2	Benchmark dynamic MOP proposed by Farina, Deb, and Amato		√		√					√					√			
160	FDA3	Benchmark dynamic MOP proposed by Farina, Deb, and Amato		√		√					√					√			
161	FDA4	Benchmark dynamic MOP proposed by Farina, Deb, and Amato		√		√					√					√			
162	FDA5	Benchmark dynamic MOP proposed by Farina, Deb, and Amato		√		√					√					√			
163	IMMOEA_F1	Benchmark MOP for testing IM-MOEA		√		√					√								
164	IMMOEA_F2	Benchmark MOP for testing IM-MOEA		√		√					√								
165	IMMOEA_F3	Benchmark MOP for testing IM-MOEA		√		√					√								
166	IMMOEA_F4	Benchmark MOP for testing IM-MOEA		√		√					√								
167	IMMOEA_F5	Benchmark MOP for testing IM-MOEA		√		√					√								
168	IMMOEA_F6	Benchmark MOP for testing IM-MOEA		√		√					√								
169	IMMOEA_F7	Benchmark MOP for testing IM-MOEA		√		√					√								
170	IMMOEA_F8	Benchmark MOP for testing IM-MOEA		√		√					√								
171	IMMOEA_F9	Benchmark MOP for testing IM-MOEA		√		√					√								

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
172	IMMOEA_F10	Benchmark MOP for testing IM-MOEA		√		√					√								
173	IMOP1	Benchmark MOP with irregular Pareto front		√		√							√						
174	IMOP2	Benchmark MOP with irregular Pareto front		√		√							√						
175	IMOP3	Benchmark MOP with irregular Pareto front		√		√							√						
176	IMOP4	Benchmark MOP with irregular Pareto front		√		√							√						
177	IMOP5	Benchmark MOP with irregular Pareto front		√		√							√						
178	IMOP6	Benchmark MOP with irregular Pareto front		√		√							√						
179	IMOP7	Benchmark MOP with irregular Pareto front		√		√							√						
180	IMOP8	Benchmark MOP with irregular Pareto front		√		√							√						
181	IN1KMOP1	Neural architecture search on ImageNet 1K		√		√					√		√						
182	IN1KMOP2	Neural architecture search on ImageNet 1K		√		√					√		√						
183	IN1KMOP3	Neural architecture search on ImageNet 1K		√		√					√		√						
184	IN1KMOP4	Neural architecture search on ImageNet 1K		√		√					√		√						
185	IN1KMOP5	Neural architecture search on ImageNet 1K		√		√					√		√						
186	IN1KMOP6	Neural architecture search on ImageNet 1K		√		√					√		√						
187	IN1KMOP7	Neural architecture search on ImageNet 1K		√		√					√		√						
188	IN1KMOP8	Neural architecture search on ImageNet 1K		√		√					√		√						
189	IN1KMOP9	Neural architecture search on ImageNet 1K		√		√					√		√						
190	Instance1	Multitasking multi-objective problem (ZDT4-R + ZDT4-G)		√		√					√						√		
191	Instance2	Multitasking multi-objective problem (ZDT4-RC + ZDT4-A)		√		√					√	√					√		
192	KP	The knapsack problem	√						√		√	√							
193	LIR-CMOP1	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
194	LIR-CMOP2	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
195	LIR-CMOP3	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
196	LIR-CMOP4	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
197	LIR-CMOP5	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
198	LIR-CMOP6	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
199	LIR-CMOP7	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
200	LIR-CMOP8	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
201	LIR-CMOP9	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
202	LIR-CMOP10	Constrained benchmark MOP with large infeasible regions		√		√					√	√							

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
203	LIR-CMOP11	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
204	LIR-CMOP12	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
205	LIR-CMOP13	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
206	LIR-CMOP14	Constrained benchmark MOP with large infeasible regions		√		√					√	√							
207	LSMOP1	Large-scale benchmark MOP		√	√	√					√								
208	LSMOP2	Large-scale benchmark MOP		√	√	√					√								
209	LSMOP3	Large-scale benchmark MOP		√	√	√					√								
210	LSMOP4	Large-scale benchmark MOP		√	√	√					√								
211	LSMOP5	Large-scale benchmark MOP		√	√	√					√								
212	LSMOP6	Large-scale benchmark MOP		√	√	√					√								
213	LSMOP7	Large-scale benchmark MOP		√	√	√					√								
214	LSMOP8	Large-scale benchmark MOP		√	√	√					√								
215	LSMOP9	Large-scale benchmark MOP		√	√	√					√								
216	MaF1	Inverted DTLZ1		√	√	√					√								
217	MaF2	DTLZ2BZ		√	√	√					√								
218	MaF3	Convex DTLZ3		√	√	√					√								
219	MaF4	Inverted and scaled DTLZ3		√	√	√					√								
220	MaF5	Scaled DTLZ4		√	√	√					√								
221	MaF6	DTLZ5IM		√	√	√					√								
222	MaF7	DTLZ7		√	√	√					√								
223	MaF8	MP-DMP		√	√	√													
224	MaF9	ML-DMP		√	√	√													
225	MaF10	WFG1		√	√	√					√								
226	MaF11	WFG2		√	√	√					√								
227	MaF12	WFG9		√	√	√					√								
228	MaF13	P7		√	√	√					√								
229	MaF14	LSMOP3		√	√	√					√								
230	MaF15	Inverted LSMOP8		√	√	√					√								
231	MaOPP_binary	Many-objective pathfinding problem based on binary encoding			√				√		√		√						
232	MaOPP_real	Many-objective pathfinding problem based on real encoding			√	√					√		√						
233	MLDMP	The multi-line distance minimization problem		√	√	√													
234	MMF1	Multi-modal multi-objective test function		√		√								√					
235	MMF2	Multi-modal multi-objective test function		√		√								√					
236	MMF3	Multi-modal multi-objective test function		√		√								√					



	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
237	MMF4	Multi-modal multi-objective test function		√		√								√					
238	MMF5	Multi-modal multi-objective test function		√		√								√					
239	MMF6	Multi-modal multi-objective test function		√		√								√					
240	MMF7	Multi-modal multi-objective test function		√		√								√					
241	MMF8	Multi-modal multi-objective test function		√		√								√					
242	MMMOP1	Multi-modal multi-objective optimization problem		√	√	√								√					
243	MMMOP2	Multi-modal multi-objective optimization problem		√	√	√								√					
244	MMMOP3	Multi-modal multi-objective optimization problem		√	√	√								√					
245	MMMOP4	Multi-modal multi-objective optimization problem		√	√	√								√					
246	MMMOP5	Multi-modal multi-objective optimization problem		√	√	√								√					
247	MMMOP6	Multi-modal multi-objective optimization problem		√	√	√								√					
248	MOEADDE_F1	Benchmark MOP for testing MOEA/D-DE		√		√					√								
249	MOEADDE_F2	Benchmark MOP for testing MOEA/D-DE		√		√					√								
250	MOEADDE_F3	Benchmark MOP for testing MOEA/D-DE		√		√					√								
251	MOEADDE_F4	Benchmark MOP for testing MOEA/D-DE		√		√					√								
252	MOEADDE_F5	Benchmark MOP for testing MOEA/D-DE		√		√					√								
253	MOEADDE_F6	Benchmark MOP for testing MOEA/D-DE		√		√					√								
254	MOEADDE_F7	Benchmark MOP for testing MOEA/D-DE		√		√					√								
255	MOEADDE_F8	Benchmark MOP for testing MOEA/D-DE		√		√					√								
256	MOEADDE_F9	Benchmark MOP for testing MOEA/D-DE		√		√					√								
257	MOEADM2M_F1	Benchmark MOP for testing MOEA/D-M2M		√		√					√								
258	MOEADM2M_F2	Benchmark MOP for testing MOEA/D-M2M		√		√					√								
259	MOEADM2M_F3	Benchmark MOP for testing MOEA/D-M2M		√		√					√								
260	MOEADM2M_F4	Benchmark MOP for testing MOEA/D-M2M		√		√					√								
261	MOEADM2M_F5	Benchmark MOP for testing MOEA/D-M2M		√		√					√								
262	MOEADM2M_F6	Benchmark MOP for testing MOEA/D-M2M		√		√					√								
263	MOEADM2M_F7	Benchmark MOP for testing MOEA/D-M2M		√		√					√								
264	MOKP	The multi-objective knapsack problem		√	√				√		√								
265	MONRP	The multi-objective next release problem		√					√		√								
266	MOTSP	The multi-objective traveling salesman problem		√	√					√	√								
267	MPDMP	The multi-point distance minimization problem		√	√	√													
268	mQAP	The multi-objective quadratic assignment problem		√	√					√	√								
269	MW1	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
270	MW2	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
271	MW3	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
272	MW4	Constrained benchmark MOP proposed by		√	√	√					√	√							



	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
		Ma and Wang																	
273	MW5	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
274	MW6	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
275	MW7	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
276	MW8	Constrained benchmark MOP proposed by Ma and Wang		√	√	√					√	√							
277	MW9	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
278	MW10	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
279	MW11	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
280	MW12	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
281	MW13	Constrained benchmark MOP proposed by Ma and Wang		√		√					√	√							
282	MW14	Constrained benchmark MOP proposed by Ma and Wang		√	√	√					√	√							
283	NI_HS	Multitasking problem (Rosenbrock function + Rastrigin function)	√			√					√						√		
284	NI_MS	Multitasking problem (Griewank function + Weierstrass function)	√			√					√						√		
285	RMEDA_F1	Benchmark MOP for testing RM-MEDA		√		√					√								
286	RMEDA_F2	Benchmark MOP for testing RM-MEDA		√		√					√								
287	RMEDA_F3	Benchmark MOP for testing RM-MEDA		√		√					√								
288	RMEDA_F4	Benchmark MOP for testing RM-MEDA		√		√					√								
289	RMEDA_F5	Benchmark MOP for testing RM-MEDA		√		√					√								
290	RMEDA_F6	Benchmark MOP for testing RM-MEDA		√		√					√								
291	RMEDA_F7	Benchmark MOP for testing RM-MEDA		√		√					√								
292	RMEDA_F8	Benchmark MOP for testing RM-MEDA		√		√					√								
293	RMEDA_F9	Benchmark MOP for testing RM-MEDA		√		√					√								
294	RMEDA_F10	Benchmark MOP for testing RM-MEDA		√		√					√								
295	RWMOP1	Pressure vessal problem		√		√						√							
296	RWMOP2	Vibrating platform		√		√						√							
297	RWMOP3	Two bar truss design problem		√		√						√							
298	RWMOP4	Weldan beam design problem		√		√						√							
299	RWMOP5	Disc brake design problem		√		√						√							
300	RWMOP6	Speed reducer design problem		√		√						√							
301	RWMOP7	Gear train design problem		√		√						√							
302	RWMOP8	Car side impact design problem		√		√						√							

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
303	RWMOP9	Four bar plane truss		√		√						√							
304	RWMOP10	Two bar plane truss		√		√						√							
305	RWMOP11	Water resource management problem		√		√						√							
306	RWMOP12	Simply supported I-beam design		√		√						√							
307	RWMOP13	Gear box design		√		√						√							
308	RWMOP14	Multiple-disk clutch brake design problem		√		√						√							
309	RWMOP15	Spring design problem		√		√						√							
310	RWMOP16	Cantilever beam design problem		√		√						√							
311	RWMOP17	Bulk carriers design problem		√		√						√							
312	RWMOP18	Front rail design problem		√		√						√							
313	RWMOP19	Multi-product batch plant		√		√						√							
314	RWMOP20	Hydro-static thrust bearing design problem		√		√						√							
315	RWMOP21	Crash energy management for high-speed train		√		√						√							
316	RWMOP22	Haverly's pooling problem		√		√						√							
317	RWMOP23	Reactor network design		√		√						√							
318	RWMOP24	Heat exchanger network design		√		√						√							
319	RWMOP25	Process synthesis problem		√		√						√							
320	RWMOP26	Process sythesis and design problem		√		√						√							
321	RWMOP27	Process flow sheeting problem		√		√						√							
322	RWMOP28	Two reactor problem		√		√						√							
323	RWMOP29	Process synthesis problem		√		√						√							
324	RWMOP30	Synchronous pptimal pulse-width modulation of 3-level inverters		√		√						√							
325	RWMOP31	Synchronous pptimal pulse-width modulation of 5-level inverters		√		√						√							
326	RWMOP32	Synchronous pptimal pulse-width modulation of 7-level inverters		√		√						√							
327	RWMOP33	Synchronous pptimal pulse-width modulation of 9-level inverters		√		√						√							
328	RWMOP34	Synchronous pptimal pulse-width modulation of 11-level inverters		√		√						√							
329	RWMOP35	Synchronous pptimal pulse-width modulation of 13-level inverters		√		√						√							
330	RWMOP36	Optimal sizing of single phase distributed generation with reactive power support for phase balancing at main transformer/grid and active power loss		√		√						√							
331	RWMOP37	Optimal Sizing of Single Phase Distributed Generation with reactive power support for Phase Balancing at Main Transformer/Grid and reactive Power loss		√		√						√							
332	RWMOP38	Optimal sizing of single phase distributed generation with reactive power support for active and reactive power loss		√		√						√							

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
333	RWMOP39	Optimal sizing of single phase distributed generation with reactive power support for phase balancing at main transformer/grid and active and reactive power loss		√		√						√							
334	RWMOP40	Optimal power flow for minimizing active and reactive power loss		√		√						√							
335	RWMOP41	Optimal power flow for minimizing voltage deviation, active and reactive power loss		√		√						√							
336	RWMOP42	Optimal power flow for minimizing voltage deviation, and active power loss		√		√						√							
337	RWMOP43	Optimal power flow for minimizing fuel cost, and active power loss		√		√						√							
338	RWMOP44	Optimal power flow for minimizing fuel cost, active and reactive power loss		√		√						√							
339	RWMOP45	Optimal power flow for minimizing fuel cost, voltage deviation, and active power loss		√		√						√							
340	RWMOP46	Optimal power flow for minimizing fuel cost, voltage deviation, active and reactive power loss		√		√						√							
341	RWMOP47	Optimal droop setting for minimizing active and reactive power loss		√		√						√							
342	RWMOP48	Optimal droop setting for minimizing voltage deviation and active power loss		√		√						√							
343	RWMOP49	Optimal droop setting for minimizing voltage deviation, active, and reactive power loss		√		√						√							
344	RWMOP50	Power distribution system planning		√		√						√							
345	SDC1	Scalable high-dimensional decision constraint benchmark		√		√						√							
346	SDC2	Scalable high-dimensional decision constraint benchmark		√		√						√							
347	SDC3	Scalable high-dimensional decision constraint benchmark		√		√						√							
348	SDC4	Scalable high-dimensional decision constraint benchmark		√		√						√							
349	SDC5	Scalable high-dimensional decision constraint benchmark		√		√						√							
350	SDC6	Scalable high-dimensional decision constraint benchmark		√		√						√							
351	SDC7	Scalable high-dimensional decision constraint benchmark		√		√						√							
352	SDC8	Scalable high-dimensional decision constraint benchmark		√		√						√							
353	SDC9	Scalable high-dimensional decision constraint benchmark		√		√						√							
354	SDC10	Scalable high-dimensional decision constraint benchmark		√		√						√							
355	SDC11	Scalable high-dimensional decision constraint benchmark		√		√						√							
356	SDC12	Scalable high-dimensional decision constraint benchmark		√		√						√							

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
357	SDC13	Scalable high-dimensional decision constraint benchmark		✓		✓						✓							
358	SDC14	Scalable high-dimensional decision constraint benchmark		✓		✓						✓							
359	SDC15	Scalable high-dimensional decision constraint benchmark		✓		✓						✓							
360	SMD1	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓												✓	
361	SMD2	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓												✓	
362	SMD3	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓												✓	
363	SMD4	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓												✓	
364	SMD5	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓												✓	
365	SMD6	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓												✓	
366	SMD7	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓												✓	
367	SMD8	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓												✓	
368	SMD9	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓						✓						✓	
369	SMD10	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓						✓						✓	
370	SMD11	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓						✓						✓	
371	SMD12	Bilevel optimization problems proposed by Sinha, Malo, and Deb		✓		✓						✓						✓	
372	Sparse_CD	The community detection problem		✓					✓		✓		✓		✓				
373	Sparse_CN	The critical node detection problem		✓					✓		✓		✓		✓				
374	Sparse_FS	The feature selection problem		✓					✓		✓		✓		✓				
375	Sparse_IS	The instance selection problem		✓					✓		✓		✓		✓				
376	Sparse_KP	The sparse multi-objective knapsack problem		✓	✓				✓		✓								
377	Sparse_NN	The neural network training problem		✓		✓					✓		✓		✓				
378	Sparse_PM	The pattern mining problem		✓					✓		✓		✓		✓				
379	Sparse_PO	The portfolio optimization problem		✓		✓					✓		✓		✓				
380	Sparse_SR	The sparse signal reconstruction problem		✓		✓					✓		✓		✓				
381	SMMOP1	Sparse multi-modal multi-objective optimization problem		✓	✓	✓					✓			✓	✓				
382	SMMOP2	Sparse multi-modal multi-objective optimization problem		✓	✓	✓					✓			✓	✓				
383	SMMOP3	Sparse multi-modal multi-objective optimization problem		✓	✓	✓					✓			✓	✓				
384	SMMOP4	Sparse multi-modal multi-objective		✓	✓	✓					✓			✓	✓				

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
		optimization problem																	
385	SMMOP5	Sparse multi-modal multi-objective optimization problem		√	√	√					√			√	√				
386	SMMOP6	Sparse multi-modal multi-objective optimization problem		√	√	√					√			√	√				
387	SMMOP7	Sparse multi-modal multi-objective optimization problem		√	√	√					√			√	√				
388	SMMOP8	Sparse multi-modal multi-objective optimization problem		√	√	√					√			√	√				
389	SMOP1	Benchmark MOP with sparse Pareto optimal solutions		√	√	√					√		√		√				
390	SMOP2	Benchmark MOP with sparse Pareto optimal solutions		√	√	√					√		√		√				
391	SMOP3	Benchmark MOP with sparse Pareto optimal solutions		√	√	√					√		√		√				
392	SMOP4	Benchmark MOP with sparse Pareto optimal solutions		√	√	√					√		√		√				
393	SMOP5	Benchmark MOP with sparse Pareto optimal solutions		√	√	√					√		√		√				
394	SMOP6	Benchmark MOP with sparse Pareto optimal solutions		√	√	√					√		√		√				
395	SMOP7	Benchmark MOP with sparse Pareto optimal solutions		√	√	√					√		√		√				
396	SMOP8	Benchmark MOP with sparse Pareto optimal solutions		√	√	√					√		√		√				
397	SOP_F1	Sphere function	√			√							√						
398	SOP_F2	Schwefel's function 2.22	√			√							√						
399	SOP_F3	Schwefel's function 1.2	√			√							√						
400	SOP_F4	Schwefel's function 2.21	√			√							√						
401	SOP_F5	Generalized Rosenbrock's function	√			√							√						
402	SOP_F6	Step function	√			√							√						
403	SOP_F7	Quartic function with noise	√			√							√						
404	SOP_F8	Generalized Schwefel's function 2.26	√			√							√						
405	SOP_F9	Generalized Rastrigin's function	√			√							√						
406	SOP_F10	Ackley's function	√			√							√						
407	SOP_F11	Generalized Griewank's function	√			√							√						
408	SOP_F12	Generalized penalized function	√			√							√						
409	SOP_F13	Generalized penalized function	√			√							√						
410	SOP_F14	Shekel's foxholes function	√			√							√						
411	SOP_F15	Kowalik's function	√			√							√						
412	SOP_F16	Six-hump camel-back function	√			√							√						
413	SOP_F17	Branin function	√			√							√						
414	SOP_F18	Goldstein-price function	√			√							√						

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
415	SOP_F19	Hartman's family	√			√							√						
416	SOP_F20	Hartman's family	√			√							√						
417	SOP_F21	Shekel's family	√			√							√						
418	SOP_F22	Shekel's family	√			√							√						
419	SOP_F23	Shekel's family	√			√							√						
420	TP1	Test problem for robust multi-objective optimization		√		√					√								√
421	TP2	Test problem for robust multi-objective optimization		√		√					√								√
422	TP3	Test problem for robust multi-objective optimization		√		√					√								√
423	TP4	Test problem for robust multi-objective optimization		√		√					√								√
424	TP5	Test problem for robust multi-objective optimization		√		√					√								√
425	TP6	Test problem for robust multi-objective optimization		√		√					√								√
426	TP7	Test problem for robust multi-objective optimization		√		√					√								√
427	TP8	Test problem for robust multi-objective optimization		√		√					√								√
428	TP9	Test problem for robust multi-objective optimization		√		√					√								√
429	TP10	Test problem for robust multi-objective optimization		√		√					√	√							√
430	TREE1	The time-varying ratio error estimation problem		√		√					√	√	√						
431	TREE2	The time-varying ratio error estimation problem		√		√					√	√	√						
432	TREE3	The time-varying ratio error estimation problem		√		√					√	√	√						
433	TREE4	The time-varying ratio error estimation problem		√		√					√	√	√						
434	TREE5	The time-varying ratio error estimation problem		√		√					√	√	√						
435	TREE6	The time-varying ratio error estimation problem		√		√					√	√	√						
436	TSP	The traveling salesman problem	√							√	√								
437	UF1	Unconstrained benchmark MOP		√		√					√								
438	UF2	Unconstrained benchmark MOP		√		√					√								
439	UF3	Unconstrained benchmark MOP		√		√					√								
440	UF4	Unconstrained benchmark MOP		√		√					√								
441	UF5	Unconstrained benchmark MOP		√		√					√								
442	UF6	Unconstrained benchmark MOP		√		√					√								
443	UF7	Unconstrained benchmark MOP		√		√					√								
444	UF8	Unconstrained benchmark MOP		√		√					√								
445	UF9	Unconstrained benchmark MOP		√		√					√								
446	UF10	Unconstrained benchmark MOP		√		√					√								
447	VNT1	Benchmark MOP proposed by Viennet		√		√													
448	VNT2	Benchmark MOP proposed by Viennet		√		√													
449	VNT3	Benchmark MOP proposed by Viennet		√		√													
450	VNT4	Benchmark MOP proposed by Viennet		√		√						√							
451	WFG1	Benchmark MOP proposed by Walking Fish Group		√	√	√					√		√						

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
452	WFG2	Benchmark MOP proposed by Walking Fish Group		√	√	√					√		√						
453	WFG3	Benchmark MOP proposed by Walking Fish Group		√	√	√					√		√						
454	WFG4	Benchmark MOP proposed by Walking Fish Group		√	√	√					√		√						
455	WFG5	Benchmark MOP proposed by Walking Fish Group		√	√	√					√		√						
456	WFG6	Benchmark MOP proposed by Walking Fish Group		√	√	√					√		√						
457	WFG7	Benchmark MOP proposed by Walking Fish Group		√	√	√					√		√						
458	WFG8	Benchmark MOP proposed by Walking Fish Group		√	√	√					√		√						
459	WFG9	Benchmark MOP proposed by Walking Fish Group		√	√	√					√		√						
460	ZDT1	Benchmark MOP proposed by Zitzler, Deb, and Thiele		√		√					√		√						
461	ZDT2	Benchmark MOP proposed by Zitzler, Deb, and Thiele		√		√					√		√						
462	ZDT3	Benchmark MOP proposed by Zitzler, Deb, and Thiele		√		√					√		√						
463	ZDT4	Benchmark MOP proposed by Zitzler, Deb, and Thiele		√		√					√		√						
464	ZDT5	Benchmark MOP proposed by Zitzler, Deb, and Thiele		√					√		√		√						
465	ZDT6	Benchmark MOP proposed by Zitzler, Deb, and Thiele		√		√					√		√						
466	ZXH_CF1	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
467	ZXH_CF2	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
468	ZXH_CF3	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
469	ZXH_CF4	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
470	ZXH_CF5	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
471	ZXH_CF6	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
472	ZXH_CF7	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
473	ZXH_CF8	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
474	ZXH_CF9	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
475	ZXH_CF10	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
476	ZXH_CF11	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
477	ZXH_CF12	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
478	ZXH_CF13	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							

	Abbreviation	Full name	single	multi	many	real	integer	label	binary	permutation	large	constrained	expensive	multimodal	sparse	dynamic	multitask	bilevel	robust
479	ZXH_CF14	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
480	ZXH_CF15	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							
481	ZXH_CF16	Constrained benchmark MOP proposed by Zhou, Xiang, and He		√	√	√					√	√							