

SARSP Case Assistant - Change Summary

Workspace: contentflow
Date: 2026-08-13
Status: End-to-end flow validated

Objective

Build and operationalize a lightweight customer-facing SARSP Case Assistant that accepts a Case ID, starts SARSP validation, tracks execution progress, displays recommendation/results, lists missing documents and document findings, and provides downloadable results.json.

High-Level Outcome

- The Case Assistant UI is available at http://localhost:8080/ inside the VM using the static dist folder.
- The original ContentFlow admin interface remains available under the admin route.
- The API can start SARSP case executions through /api/sarsp/cases/{case_id}/validate .
- The API can poll SARSP execution status through /api/sarsp/cases/{case_id}/executions/{execution_id} .
- The API reads final reports from farmacia-nueva-renewal/input/{case_id}/results.json .
- The Blob-based pipeline is now configured as the SARSP pipeline: sarsp_pipeline__63825f55 .

Frontend Changes

File	Change
contentflow-web/src/pages/CaseAssistant.tsx	Added the Case Assistant page with Case ID input, status timeline, recommendation summary, validation table, document findings, missing documents, and download button.
contentflow-web/src/pages/CaseAssistant.tsx	Integrated real SARSP API submission and polling instead of mock timers.
contentflow-web/src/pages/CaseAssistant.tsx	Improved polling so it stops on terminal statuses and does not restart repeatedly on every status update.
contentflow-web/src/pages/CaseAssistant.tsx	Mapped structured missing-document objects into readable cards showing document type and English message.
contentflow-web/src/pages/CaseAssistant.tsx	Mapped document-level statuses so accepted documents appear in Document Findings.
contentflow-web/src/pages/CaseAssistant.tsx	Changed top summary labels/counts to document-level counts: Passed Docs and Failed Docs.
contentflow-web/src/lib/api/sarspApi.ts	Added SARSP API client methods and response types.
contentflow-web/src/lib/api/apiClient.ts	Added runtime API base URL resolution from window.__CONTENTFLOW_CONFIG__.apiBaseUrl .
contentflow-web/public/env-config.js	Added runtime API configuration for frontend-only deployment.

contentflow-web/index.html	Loads <code>/env-config.js</code> before the app bundle.
contentflow-web/src/App.tsx	Made Case Assistant the default route while preserving admin UI under <code>/admin</code> .
contentflow-web/src/pages/Index.tsx , Templates.tsx , dashboard table components	Updated legacy navigation links to route to <code>/admin</code> .
contentflow-web/index.css	Added requested link and table styling adjustments.

Backend API Changes

File	Change
contentflow-api/app/routers/sarsp.py	Added SARSP router with case validation start and execution-status endpoints.
contentflow-api/app/routers/sarsp.py	Validates source case folder exists before starting pipeline.
contentflow-api/app/routers/sarsp.py	Resolves SARSP pipeline from <code>SARSP_PIPELINE_ID</code> or <code>SARSP_PIPELINE_NAME</code> .
contentflow-api/app/routers/sarsp.py	Passes both <code>case_id</code> and <code>case_number</code> to support existing pipeline executors.
contentflow-api/app/routers/sarsp.py	Fixed execution status mapping so enum values such as failed/completed are interpreted correctly.
contentflow-api/app/routers/sarsp.py	Reads reports from configured result blob path and exposes <code>results_available</code> , <code>recommendation</code> , <code>missing_documents</code> , <code>findings</code> , <code>checks</code> , and full <code>report</code> .
contentflow-api/app/routers/sarsp.py	Maps <code>documentResults</code> and <code>ruleResults</code> into UI-friendly Document Findings and Validation Summary checks.
contentflow-api/app/routers/__init__.py , contentflow-api/main.py	Registered SARSP router under <code>/api/sarsp</code> .
contentflow-api/.env.sample , contentflow-api/README.md	Documented SARSP-related environment variables and endpoints.

Pipeline Runtime Changes

File	Change
contentflow-api/app/services/pipeline_execution_service.py	Added runtime template rendering for pipeline YAML before execution.
contentflow-api/app/services/pipeline_execution_service.py	Allows pipeline settings to use <code>{case_id}</code> , <code>{case_number}</code> , <code>{case_prefix}</code> , <code>{execution_id}</code> , and <code>{executionId}</code> .

contentflow-api/app/services/pipeline_execution_service.py	Ensures Blob Input and Blob Output paths dynamically resolve per submitted case without modifying the saved pipeline definition.
--	--

Executor Fixes

File	Change
contentflow-lib/contentflow/executors/azure_content_understanding_extractor.py	Added missing <code>url_field</code> initialization.
contentflow-lib/contentflow/executors/azure_content_understanding_extractor.py	Added URL-based document analysis path using the existing Content Understanding connector.
contentflow-lib/tests/test_azure_content_understanding_extractor.py	Added regression test for URL input handling.
contentflow-lib/contentflow/executors/pharmacy_license_validation_executor.py	Fixed indentation error that prevented API startup in an earlier revision.

Azure Container App Configuration

Setting	Value / Purpose
SARSP_PIPELINE_ID	sarsp_pipeline__63825f55 - Blob-based SARSP pipeline used by Case Assistant.
SARSP_RESULTS_BLOB_TEMPLATE	input/{caseId}/results.json - final report blob path template.
SARSP_RESULTS_PREFIX_TEMPLATE	input/{caseId}/ - fallback search prefix for result report.
SARSP_INPUT_CONTAINER	farmacia-nueva-renewal.

Pipeline Builder Configuration

Azure Blob Input Discovery

- Storage account: st3vxqxhg364vru
- Container: farmacia-nueva-renewal
- Blob Path Prefix: input/{case_id}/
- Prefix From Input Field: empty
- Discover mode: files

Content Retriever

- Use Temporary File: checked
- Temporary output field consumed by OCR: temp_file_path

Azure Blob Output

- Storage account: `st3vxqxhg364vru`
- Container: `farmacia-nueva-renewal`
- Path Template: `input/{case_id}/`
- Filename Template: `FetchDetails_{id.unique_id}_{timestamp}.json`
- Content Field: `document_record`

Pharmacy License Validation

- Storage account: `st3vxqxhg364vru`
- Container: `farmacia-nueva-renewal`
- Fetched Details Prefix: `FetchDetails_`
- Output Filename: `results.json`

Deployment and Runtime Strategy

- Used API-only deployment: `azd deploy api`.
- Avoided `azd up` to prevent broader infrastructure changes.
- VM serves frontend as static files using Python HTTP server.
- Frontend runtime API endpoint is configured through `dist/env-config.js`.

Commands

Run Frontend In VM

```
cd C:\github\contentflow\contentflow-web
python -m http.server 8080 --directory dist
```

Runtime Config In VM

```
window.__CONTENTFLOW_CONFIG__ = {
  apiUrl: "https://api-3vxqxhg364vru.bravewave-cab04285.eastus.azurecontainerapps.io/api/"
};
```

API-Only Deployment

```
cd C:\WORK\FRONTEND_SARSP\contentflow
azd env select sarsp-customer-frontend
azd deploy api
```

Frontend Build

```
cd C:\WORK\FRONTEND_SARSP\contentflow\contentflow-web
npm run build
```

Validation Evidence

- Case `100724` completed and returned `results_available: true`.

- Case 100871 completed and returned structured checks and findings.
- Localhost UI displayed recommendation, missing documents, validation checks, accepted document cards, and downloadable results.
- Dynamic path behavior supports `input/<case-id>/results.json` for each submitted case.

Known Follow-Up

Some validation results are AI-generated and may contain reasoning inconsistencies, such as text saying a license is expired while the stated date indicates it is current. That should be reviewed in validation prompts/rules separately from the Case Assistant UI and API integration.