
Implementing Real-Time Analysis with Hadoop in Azure HDInsight

02 | Using Storm for Streaming Data



- What is a Stream?
- What is Apache Storm?
- How is Storm Supported in Azure HDInsight?
- What is a Storm Topology?
- How is Event Data Defined?
- How Does Storm Distribute Stream Processing?
- How Does Storm Guarantee Message Processing?
- How Do I Aggregate Data in a Stream?


What is a Stream?



- A unbounded sequence of event data
- Stream processing is continuous
- Aggregation is based on temporal windows


What is Apache Storm?

- An event processor for data streams
- Defines a streaming topology that consists of:
 - Spouts: Consume data sources and emit streams that contain tuples
 - Bolts: Operate on tuples in streams
- Storm topologies run continuously on streams of data
 - Real-time monitoring
 - Event aggregation and logging



How is Storm Supported in Azure HDInsight?

- HDInsight supports an **Storm** cluster type
 - Choose Cluster Type in the Azure Portal
- Can be provisioned in a virtual network




Provisioning a Storm Cluster

What is a Storm Topology?

• Spouts emit tuples in streams


 Spouts can emit multiple streams

- Bolts process tuples
- Bolts can also emit tuples
- There can be multiple spouts and bolts in a topology
- Bolts can process multiple streams




How do I Create a Topology?

- Implement Spout and Bolt classes
 - Native language of Storm is Java
 - Microsoft SCP.NET package enables development in C#
- Use a TopologyBuilder class to connect the components
- Build and package the code, and submit the topology to a Storm cluster



```
TopologyBuilder tb = new TopologyBuilder();
tb.setSpout ("spout", myspout,...);
tb.setBolt("bolt", mybolt...).shuffleGrouping("spout");
```



How is Event Data Defined?

 Declare schema for each stream in each component


 Java OutputFieldsDeclarer class defines output schema for a stream

 Microsoft SCP.NET class templates include input and output schema declarations for spouts and bolts



Spout


Output



Creating a Storm Topology with C#

How Does Storm Distribute Stream Processing?


- Master node runs Nimbus
 - Assigns processing across the cluster
- Worker nodes run *Supervisor*
 - Manages processing on the node
- Cluster coordination is managed using Zookeeper
 - Apache project for distributed processing



- A topology has one or more worker processes
- A worker process spawns one or more executors (threads) per component
 - Set using parallelism hint

```
TopologyBuilder tb = new TopologyBuilder();
tb.setSpout ("spout", myspout, 1, ...);
tb.setBolt("bolt", mybolt, 3, ...).shuffleGrouping("spout");
```

 Each executor runs one or more task




- Use stream groupings to determine affinity between tasks
 - Shuffle grouping

```
TopologyBuilder tb = new TopologyBuilder();
tb.setSpout ("spout", myspout, 1, ...);
tb.setBolt("bolt", mybolt, 3, ...).shuffleGrouping("spout");
```

Fields grouping

```
TopologyBuilder tb = new TopologyBuilder();
tb.setSpout ("spout", myspout, 1, ...);
tb.setBolt("bolt", mybolt, 3, ...).fieldsGrouping("spout", "f1");
```


- Others
 - All, Global, ...



Using the Parallelism Hint


How Does Storm Guarantee Message Processing?

- Non-Transactional (no Ack)
 - Enforces at most once semantics
 - Simplest programming model
 - Possible data loss
- Non-Transactional (with Ack)
 - Enforces at least once semantics
 - Requires explicit retry logic
- Transactional
 - Enforces exactly once semantics
 - Works well for batches
 - Use TransactionalTopologyBuilder
 - Implement a committer bolt




Implementing Guaranteed Message Processing

How Do I Aggregate Data in a Stream?



- Events are aggregate within temporal windows
- Use a tumbling window to aggregate events in a fixed timespan
 - For example: every hour, count the events in the preceding hour
- Use a sliding window to aggregate events in overlapping timespans
 - For example: every 10 minutes, count the events in the preceding hour

- Cache field values from each tuple
- Configure a *Tick Tuple* for the window duration
- On each tick, start a new window:
 - For a tumbling window:
 - Aggregate cached fields
 - Delete all cached fields
 - For a sliding window
 - Delete stale fields
 - Aggregate remaining fields



Implementing a Sliding Window

- What is a Stream?
- What is Apache Storm?
- How is Storm Supported in Azure HDInsight?
- What is a Storm Topology?
- How is Event Data Defined?
- How Does Storm Distribute Stream Processing?
- How Does Storm Guarantee Message Processing?
- How Do I Aggregate Data in a Stream?



©2014 Microsoft Corporation. All rights reserved. Microsoft, Windows, Office, Azure, System Center, Dynamics and other product names are or may be registered trademarks and/or trademarks in the U.S. and/or other countries. The information herein is for informational purposes only and represents the current view of Microsoft Corporation as of the date of this presentation. Because Microsoft must respond to changing market conditions, it should not be interpreted to be a commitment on the part of Microsoft, and Microsoft cannot guarantee the accuracy of any information provided after the date of this presentation. MICROSOFT MAKES NO WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, AS TO THE INFORMATION IN THIS PRESENTATION.