TOP GLOVE, TOP QUALITY, TOP EFFICIENCY, GOOD HEALTH, SAFETY FIRST & BE HONEST QA DEPARTMENT Nitrile Examination Glove Compliance with International Standard

			EN455 - 2:2009 + A1: 2011			ASTM D6319-00a ^{c3}			AS / NZ 4011 : 97			ISO 11193 -1 : 2008		
Type of Glove		EN455 – 1 :	20		EN455 – 3 : 2006 (Powder Level & Protein)					Phy Dim		Phy Dim		
		2000 (Freedon From Holes)	Physical Dimension	Physical Properties		Freedom From Holes (Water Tight Test)	Thickness :Palm/Finger Min 0.05 mm	Physical Properties	Freedom From Holes (Water Tight Test)	Thickness :Palm/Finger Smooth : Min 0.08 mm Text: Min 0.10 mm	Physical Properties	Freedom From Holes (Water Tight Test)	Thickness :Palm/Finger Smooth : Min 0.08 mm Text : Min 0.11 mm	Physical Properties
Nitrile Powdered Textured (NPWT)	USEW90	√	√	- NT	√	√	√	√	V	√	NT	√	√	
	USAW46	√	√		√	√	√	√	√	x		√	х	NT
	USEWTT46	√	√		√	√	√	√	√	х		√	х	
	USEW46	x	√		√	x	√	√	x	x		x	x	
	EW44	x	√		√	x	√	√	x	x		x	х	
	NW42	x	√		√	x	√	x	x	x		x	x	
Nitrile Powdered Finger Textured (NPWFT)	ENHW50	√ √	√	√	√	√	√ V	√	√	√	√	√	√	
	EW44	x	√	x	√	x	√ V	√	x	x	NT	x	x	NT
	ENLW40	√	√	√	√	√	√	√	√	x		√	x	
		x		√ √	\ √	x	· √		x	x		x	x	
	ENLW35	√ √		· √	√ √	√	· √	· √	1 √	x		√	x	
	LW35	x		x	· √	x	· √		x	x		x	x	x
	LW30	x		x	\ √	√ (F2B)	· √		x	x		x	x	NT
	USAW40	X √	√ √	Α .	√ √	√ (F2B) √	√ √	√	X √			X √		111
Nitrile Polymer Powder Free Finger Textured (NPPFFT)	USEWTT40	√ √	√	NT	√ √	√ √	√ √	√	√	X	NT	√ √	X	NT
	LIGENI 40		√		√ √		√ √	√ √		X			X	
		X				X			X	X		X	X	
	LMLW38	X	√ /		√	X	√ /	√ /	X	X		X	X	
Nitrile Chlorinated Powder Free Textured OSC (NPFT)	LMLW35	X	√ /	NT - NT -	√	X	√	√	X	X	NT V	X	X	NT NT
	USEW62	X	<u>√</u>		√ .	X	√	√	X	√		X	√ .	
	USEW60	X	√		√	X	√	√	X	√		X	√ .	
	USAW50	√	√		√	√	√	√	√	√		√	√	
	USEWTT50	√	√		√	√	√	√	√	x		√	Х	
	USEW50	X	√		√	X	√	√	x	x		X	x	
	EW48	X	√		√	x	√	X	x	X		X	х	
	NW44	x	√		√	x	√	√	х	x		x	x	
Nitrile Chlorinated Powder Free Finger Textured OSC (NPFFT)	ENHW60	√	√	√	√	√	√	NT	√	√	NT NT	√	√	NT
	ENW54	√	√	√	√	√	√	111	√	x		√	x	
	USEWTT50	√	√	√	√	√	√	√	√	x	\checkmark	√	x	√
	USEW50	x	√	NIT	√	x	√	√	x	x		x	x	NT
	USAW50	√	√	NT	√	√	√	√	√	x	NT	√	x	
	USAW40	√	√		√	√	√	√	V	x		√	х	
	USEWTT40	√	√		√	√	√	NT	√	x		√	х	
	USEW40	x	√		√	x	√	√	х	x		x	х	
	ENLW40	√	√		√	√	√	√	√	x		√	x	
	LW40	x	√		√	x	√	√	x	x		x	x	
	LMLW38	x	√		√	x	√	√	x	x		x	x	
	LW38	x	√		√	x	√ V	NT	x	x		X	x	
	USAW38	√ √	√ √	x	√	√	√ .	√ √	√ V	x		√	x	
	ENLW30	1	√ √	A √	√ √	√ √	· √	· √	\ \ \	x		√ √	x	x
	LW30	x		√ √	√	x	√ √		x	x		x	x	
	USAW35	X √	√	NT	√ √	X √	√ √	√	x √	X		X √	x	NT
	ENLW35	√ √	√	√ V	√ √	√ √		√	√		NT	√ √		X
	LIVE W33	v .		V		V	X		· v	X		V	x	
	LW35	x	√	X	√	X	√	√	x	x		X	x	

Not Comply

* Excluded Nitrile Chlorinated ODC Prepared By, Siti Khadijah Kamali

Verify By Noorul Shamsidah / Husna Ishak

Rev 0 (February 2012)