

Football Match Result Database Specification Document, v1.2.0

Howard Hamilton

October 22, 2011

Contents

1	Mission Statement	5
2	Mission Objectives	5
3	Business Rules	5
4	Match Overview Tables	6
4.1	Match table (tblMatches)	6
4.1.1	matchID field	6
4.1.2	matchDate field	7
4.1.3	matchFirstHalfTime field	7
4.1.4	matchSecondHalfTime field	8
4.1.5	matchAttendance field	8
4.1.6	competitionID field	9
4.1.7	roundID field	9
4.1.8	venueID field	10
4.1.9	refereeID field	10
4.2	Competitions lookup table (tblCompetitions)	11
4.2.1	competitionID field	11
4.2.2	compName field	12
4.3	Competition Phase lookup table (tblRounds)	12
4.3.1	roundID field	13
4.3.2	roundDesc field	13
4.4	Venue lookup table (tblVenues)	14
4.4.1	venueID field	14
4.4.2	venCity field	15
4.4.3	countryID field	15
4.4.4	timezoneID field	16
4.4.5	venName field	16
4.4.6	venAltitude field	17
4.4.7	venLatitude field	17
4.4.8	venLongitude field	18
4.5	Venue History table (tblVenueHistory)	18
4.5.1	venuehistoryID field	19
4.5.2	venueID field	19
4.5.3	venuesurfaceID field	20
4.5.4	venueHistDate field	20
4.5.5	venueLength field	21
4.5.6	venueWidth field	21
4.5.7	venueHistCapacity field	22
4.5.8	venueHistSeats field	22

4.6	Venue Surfaces table (tblVenueSurfaces)	23
4.6.1	venuesurfaceID field	23
4.6.2	vensurfDesc field	24
4.7	Time Zones table (tblTimeZones)	24
4.7.1	timezoneID field	25
4.7.2	confedID field	25
4.7.3	tzName field	25
4.7.4	tzOffset field	26
4.8	Home Teams linking table (tblHomeTeams)	26
4.8.1	matchID field	27
4.8.2	countryID field	27
4.9	Away Teams linking table (tblAwayTeams)	28
4.9.1	matchID field	28
4.9.2	countryID field	28
4.10	Home Managers linking table (tblHomeManagers)	28
4.10.1	matchID field	28
4.10.2	managerID field	29
4.11	Away Managers linking table (tblAwayManagers)	29
4.11.1	matchID field	29
4.11.2	managerID field	30
4.12	Environments table (tblEnvironments)	30
4.12.1	enviroID field	31
4.12.2	matchID field	31
4.12.3	envKickoffTime field	32
4.12.4	envTemperature field	32
4.13	Weather conditions lookup table (tblWeather)	33
4.13.1	weatherID field	33
4.13.2	wxConditionDesc field	34
4.14	Kickoff weather linking table (tblWeatherKickoff)	34
4.14.1	enviroID field	35
4.14.2	weatherID field	36
4.15	Halftime weather linking table (tblWeatherHalftime)	36
4.15.1	enviroID field	36
4.15.2	weatherID field	36
4.16	Fulltime weather linking table (tblWeatherFulltime)	36
4.16.1	enviroID field	37
4.16.2	weatherID field	37
5	Personnel Tables	37
5.1	Players table (tblPlayers)	37
5.1.1	playerID field	37
5.1.2	countryID field	37
5.1.3	plyrBirthdate field	38
5.1.4	plyrFirstname field	38
5.1.5	plyrLastname field	39
5.1.6	plyrNickname field	39
5.1.7	plyrDefPosID field	40
5.2	Player History table (tblPlayerHistory)	40
5.2.1	playerhistoryID field	41
5.2.2	plyrHistDate field	41
5.2.3	plyrHistHeight field	42
5.2.4	plyrHistWeight field	42
5.3	Managers table (tblManagers)	43
5.3.1	managerID field	43

5.3.2	countryID field	43
5.3.3	mgrBirthdate field	43
5.3.4	mgrFirstname field	43
5.3.5	mgrLastname field	43
5.3.6	mgrNickname field	43
5.4	Referees table (tblReferees)	44
5.4.1	refereeID field	44
5.4.2	countryID field	44
5.4.3	refBirthdate field	44
5.4.4	refFirstName field	44
5.4.5	refLastName field	44
5.5	Country lookup table (tblCountries)	45
5.5.1	countryID field	45
5.5.2	ctyName field	46
5.5.3	confedID field	46
5.6	Confederations lookup table (tblConfederations)	47
5.6.1	confedID field	47
5.6.2	confedName field	48
5.7	Lineup table (tblLineups)	48
5.7.1	lineupID field	49
5.7.2	matchID field	49
5.7.3	teamID field	49
5.7.4	playerID field	50
5.7.5	positionID field	50
5.7.6	lpStarting field	51
5.7.7	lpCaptain field	51
5.8	Positions lookup table (tblPositions)	52
5.8.1	positionID field	52
5.8.2	posFieldID field	53
5.8.3	posFlankID field	53
5.9	Field position name table (tblFieldNames)	54
5.9.1	posFieldID field	54
5.9.2	posFieldName field	55
5.10	Flank name table (tblFlankNames)	55
5.10.1	posFlankID field	56
5.10.2	posFlankName field	56
6	Match Event Tables	57
6.1	Goals table (tblGoals)	57
6.1.1	goalID field	57
6.1.2	countryID field	58
6.1.3	lineupID field	58
6.1.4	gtsTypeID field	59
6.1.5	gteTypeID field	59
6.1.6	glsTime field	60
6.1.7	glsSTime field	60
6.2	Goal strike lookup table (tblGoalStrikes)	61
6.2.1	gtsTypeID field	61
6.2.2	gtsDesc field	62
6.3	Goal field event lookup table (tblGoalEvents)	62
6.3.1	gteTypeID field	63
6.3.2	gteDesc field	63
6.4	Penalties table (tblPenalties)	64
6.4.1	penaltyID field	64

6.4.2	lineupID field	64
6.4.3	foulID field	65
6.4.4	penOutcomeID field	65
6.4.5	penTime field	66
6.4.6	penSTime field	66
6.5	Penalty outcome lookup table (tblPenOutcomes)	67
6.5.1	penOutcomeID field	67
6.5.2	poDesc field	68
6.6	Offenses table (tblOffenses)	68
6.6.1	offenseID field	69
6.6.2	lineupID field	69
6.6.3	foulID field	69
6.6.4	cardID field	70
6.6.5	ofnsTime field	70
6.6.6	ofnsSTime field	71
6.7	Fouls lookup table (tblFouls)	71
6.7.1	foulID field	72
6.7.2	foulDesc field	72
6.8	Card lookup table (tblCards)	73
6.8.1	cardID field	73
6.8.2	cardType field	74
6.9	Substitution table (tblSubstitutions)	74
6.9.1	subsID field	75
6.9.2	subsTime field	75
6.9.3	subsSTime field	76
6.10	Players substituted into match linking table (tblInSubstitutions)	76
6.10.1	subsID field	77
6.10.2	lineupID field	77
6.11	Players substituted out of match linking table (tblOutSubstitutions)	78
6.11.1	subsID field	78
6.11.2	lineupID field	78
6.12	Switch Positions table (tblSwitchPositions)	78
6.12.1	switchID field	78
6.12.2	lineupID field	79
6.12.3	switchPositionID field	79
6.12.4	switchTime field	79
6.12.5	switchSTime field	80
7	Views	80
7.1	PlayersList view	80
7.2	ManagerList view	81
7.3	RefereeList view	81
7.4	HomeTeamList view	81
7.5	AwayTeamList view	81
7.6	PositionsList view	81
7.7	MatchList view	82
7.8	LineupList view	82
7.9	GoalsList view	82
7.10	PenaltiesList view	83
7.11	CautionsList view	83
7.12	ExpulsionsList view	83
7.13	InSubList view	84
7.14	OutSubList view	84
7.15	SubstitutionsList view	84

Abstract

The purpose of the Database is to collect match result data for national teams that participate in football league competitions in order to facilitate football analytics research. This document describes the table-, field- and relationship-level specifications of the Football Match Result Database. These specifications include the table names, descriptions, and member fields and their descriptions and types. The primary and foreign keys of each table will be identified and the characteristics between related tables will be defined from the perspective of the primary table. View specifications are defined in order to provide context-specific information from multiple tables, establish data security and confidentiality, and implement data integrity.

1 Mission Statement

The purpose of the Football Match Result Database is to maintain the match result data needed to support football research activities for the benefit of the football analytics community.

2 Mission Objectives

The Football Match Result Database will support the following:

- Maintain data on matches that occur within football league competitions, whether among national teams or domestic clubs.
- Maintain complete top-level information on the football match, including match date, competition name and stage, participating teams, venues, and environmental conditions.
- Maintain time-dependent surface and capacity data on football venues, including field surface type, field dimensions, total stadium capacity, and total number of seats.
- Maintain complete information on macro-events that occur during a match, including goals, penalties, disciplinary incidents, and substitutions.
- Maintain complete information on participating personnel, such as players, managers, and match referees.
- Maintain time-dependent height and weight data on football players.

3 Business Rules

The following business rules shall be enforced on the Football Match Result Database:

- Starting player lists shall consist of exactly 11 players of which exactly one player is designated as the goalkeeper.
- A maximum of 18 players from one team will appear in a lineup list that corresponds to a match.
- A player can only be substituted one time during a match.
- Maximum substitution rules are enforced during a match.
- If a goalkeeper is expelled from a match, a new goalkeeper must be designated by either switching the positions of a field player or substituting a field player for a goalkeeper.
- A goalscorer or a recipient of a caution/expulsion card must be a player in the lineup who meets one of two criteria:
 - A starting player who has not yet been substituted; or
 - A player who has been substituted before the time of goal or disciplinary incident.

4 Match Overview Tables

The following tables capture high-level information on the football match, such as the competition, matchday, matchdate, league teams, and venues. The major tables in this section are the Match table, which links to personnel and match event tables, and the Environment table, which captures information on the climactic conditions under which the match was played.

4.1 Match table (tblMatches)

tblMatches	High level information on the football match and its participants. The information in this table is required in order to track all matches played in a football competition as well as the teams, players, managers, and referees who participated in them.			
Primary Key	matchID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
competitionID	tblCompetitions	—	Optional	(0,N)
roundID	tblRounds	—	Optional	(0,N)
venueID	tblVenues	—	Optional	(0,N)
refereeID	tblReferees	—	Optional	(0,N)
—	tblHomeTeams	Restrict	Mandatory	(1,1)
—	tblAwayTeams	Restrict	Mandatory	(1,1)
—	tblHomeManagers	Restrict	Mandatory	(1,1)
—	tblAwayManagers	Restrict	Mandatory	(1,1)
—	tblEnvironments	Restrict	Mandatory	(1,1)
—	tblLineups	Restrict	Mandatory	(1,1)

4.1.1 matchID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblEnvironments, tblLineups, tblHomeTeams, tblAwayTeams, tblHomeManagers, tblAwayManagers
<i>Description</i>	A unique number used to identify matches in a football competition.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	0000000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	1000000-9999999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

4.1.2 matchDate field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The date on which the football match occurred, in ISO 8601 (YYYY-MM-DD) format.
<i>Data Type</i>	DateTime
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	YYYY-MM-DD
<i>Display Format</i>	Year Month Day
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	Subtraction

4.1.3 matchFirstHalfTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The total playing time of the first half of the football match (normal + stoppage time), in minutes.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0
<i>Range of Values</i>	> 0
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

4.1.4 matchSecondHalfTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The total playing time of the second half of the football match (normal + stoppage time), in minutes. This field accounts for matches that had to be abandoned.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	45
<i>Range of Values</i>	≥ 0
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

4.1.5 matchAttendance field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The reported attendance of the football match.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0
<i>Range of Values</i>	0 - 999999
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

4.1.6 competitionID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblCompetitions
<i>Source Specification</i>	competitionID in tblCompetitions table
<i>Description</i>	The identification number of the football competition
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing competitionID value in tblCompetitions
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.1.7 roundID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblRounds
<i>Source Specification</i>	roundID in tblRounds table
<i>Description</i>	The identification number of matchday or phase of football competition
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing roundID value in tblRounds
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	Subtraction

4.1.8 venueID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblVenues
<i>Source Specification</i>	venueID in tblVenues table
<i>Description</i>	The identification number of the venue used in the football match
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	####
<i>Display Format</i>	0000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing venueID value in tblVenues
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.1.9 refereeID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblReferees
<i>Source Specification</i>	refereeID in tblReferees table
<i>Description</i>	The identification number of the referee officiating the football match
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	####
<i>Display Format</i>	0000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing refereeID value in tblReferees
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.2 Competitions lookup table (tblCompetitions)

tblCompetitions	This table contains the names of the football competitions, and this information is used to track all matches played under a certain competition.			
Primary Key	competitionID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblMatches	Restrict	Mandatory	(1,1)

4.2.1 competitionID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblMatches
<i>Description</i>	A unique number used to differentiate football competitions.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	100-999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

4.2.2 compName field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The name of the football competition.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters, Numbers
<i>Length</i>	100
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.3 Competition Phase lookup table (tblRounds)

tblRounds	This table contains the names of the rounds of the football competition, and allows for tracking of matches and performances in a single round or multiple rounds. This table can be expanded for knockout or hybrid league/knockout competitions.			
Primary Key	roundID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblMatches	Restrict	Mandatory	(1,1)

4.3.1 roundID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblMatches
<i>Description</i>	A unique number used to identify the matchday or phase of the football competition.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	10-99
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.3.2 roundDesc field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The matchday number or phase of the football competition.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters, Numbers
<i>Length</i>	20
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a number or capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

4.4 Venue lookup table (tblVenues)

tblVenues	Contains the stadiums that are used in the football competition, and the clubs that predominately reside there. This table is used to perform performance studies against different venues or neutral sites.			
Primary Key	venueID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
countryID	tblCountries	—	Optional	(0,N)
timezoneID	tblTimeZones	—	Optional	(0,N)
—	tblMatches	Deny	Mandatory	(1,1)

4.4.1 venueID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblMatches
<i>Description</i>	A unique number used to identify venues used in football competitions.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	####
<i>Display Format</i>	0000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	1000-9999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.4.2 venCity field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The name of the city in which the football venue resides.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters, Numbers
<i>Length</i>	40
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

4.4.3 countryID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblCountries
<i>Source Specification</i>	countryID in tblCountries table
<i>Description</i>	The identification number of the country in which the venue is located
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing countryID value in tblCountries
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.4.4 timezoneID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblTimeZones
<i>Source Specification</i>	timezoneID in tblTimeZones table
<i>Description</i>	The identification number of the time zone region in which the venue resides
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing timezoneID value in tblTimeZones
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.4.5 venName field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The name of the football venue used in the football competition.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters, Numbers
<i>Length</i>	40
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

4.4.6 venAltitude field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The altitude above mean sea level at which the football match occurred, in meters.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	####
<i>Display Format</i>	0000 m
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	—

4.4.7 venLatitude field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The geographic latitude of the football stadium in decimal degrees, based on WGS 84 reference system.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	6
<i>Input Mask</i>	###.#####
<i>Display Format</i>	000.000000
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	—

4.4.8 venLongitude field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The geographic longitude of the football stadium in decimal degrees, based on WGS 84 reference system.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	6
<i>Input Mask</i>	###.#####
<i>Display Format</i>	000.000000
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	—

4.5 Venue History table (tblVenueHistory)

tblVenueHistory	Contains the field characteristics and seating capacity of a football venue over its history. This table is used to perform performance studies involving match venues over time.			
Primary Key	venuehistoryID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
venuesurfaceID	tblVenueSurfaces	—	Optional	(0,N)
—	tblVenues	—	Mandatory	(1,1)

4.5.1 venuehistoryID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblVenues
<i>Description</i>	A unique number used to identify a historical record of a match venue.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	5
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	00000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	10000-99999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.5.2 venueID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblVenues
<i>Source Specification</i>	venueID in tblVenues table
<i>Description</i>	The identification number of the match venue
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	####
<i>Display Format</i>	0000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing venueID value in tblVenues
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.5.3 venuesurfaceID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblVenueSurfaces
<i>Source Specification</i>	venuesurfaceID in tblVenueSurfaces table
<i>Description</i>	The identification number of the field surface
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing venuesurfaceID value in tblVenueSurfaces
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.5.4 venueHistDate field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The date on which the historical venue data are valid, in ISO 8601 (YYYY-MM-DD) format.
<i>Data Type</i>	DateTime
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	YYYY-MM-DD
<i>Display Format</i>	Year Month Day
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	Subtraction

4.5.5 venueLength field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The length of the football pitch (field), in meters.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	105
<i>Range of Values</i>	90-120
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

4.5.6 venueWidth field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The width of the football pitch (field), in meters.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	68
<i>Range of Values</i>	45-90
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

4.5.7 venueHistCapacity field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The total capacity of the football venue, considering seated and standing sections.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0
<i>Range of Values</i>	≥ 0
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

4.5.8 venueHistSeats field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The total number of seats in the football venue.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0
<i>Range of Values</i>	≥ 0
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

4.6 Venue Surfaces table (tblVenueSurfaces)

tblVenueSurfaces	Contains a list of surface types of a football pitch.			
Primary Key	venuesurfaceID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblVenues	Restrict	Mandatory	(1,1)

4.6.1 venuesurfaceID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblVenues
<i>Description</i>	A unique number used to identify playing surfaces.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	10-99
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.6.2 vensurfDesc field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The description of the playing surface.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters, Numbers
<i>Length</i>	30
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

4.7 Time Zones table (tblTimeZones)

tblTimeZones	Contains data on the time zone regions throughout the world, taken from the Olsen tz database. The information in this table is used to relate the local time of a match venue to any other time zone in the world.			
Primary Key	timezoneID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblVenues	Restrict	Mandatory	(1,1)

4.7.1 timezoneID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblVenues
<i>Description</i>	A unique number used to identify time zone regions.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	100-999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.7.2 confedID field

See specification in Section 5.5.3.

4.7.3 tzName field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The name of the time zone geographic region.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters, Numbers
<i>Length</i>	80
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

4.7.4 tzOffset field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The time offset of the time zone region from UTC, in decimal hours.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	2
<i>Input Mask</i>	##.##
<i>Display Format</i>	±00.00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0.0
<i>Range of Values</i>	-12.0 - 14.0
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	—

4.8 Home Teams linking table (tblHomeTeams)

tblHomeTeams	This table contains the names of the national teams that are designated home teams in a football match.			
Primary Key	matchID, countryID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
matchID	tblMatches	—	Optional	(1,1)
countryID	tblCountries	—	Optional	(1,N)

4.8.1 matchID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblMatches
<i>Source Specification</i>	matchID in tblMatches table
<i>Description</i>	The identification number of the match played in a football competition.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	0000000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Composite
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing matchID value in tblMatches
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

4.8.2 countryID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblCountries
<i>Source Specification</i>	countryID in tblCountries table
<i>Description</i>	The identification number of the designated home team
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Composite
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing countryID value in tblCountries
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal To
<i>Operations Allowed</i>	—

4.9 Away Teams linking table (tblAwayTeams)

tblAwayTeams	This table contains the names of the national teams that are designated away teams in a football match.			
Primary Key	matchID, countryID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
matchID	tblMatches	—	Mandatory	(1,1)
countryID	tblCountries	—	Mandatory	(1,N)

4.9.1 matchID field

See specification in Section 4.8.1.

4.9.2 countryID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblCountries
<i>Source Specification</i>	countryID in tblCountries table
<i>Description</i>	The identification number of the designated away team
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Composite
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing countryID value in tblCountries
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal To
<i>Operations Allowed</i>	—

4.10 Home Managers linking table (tblHomeManagers)

tblHomeManagers	This table contains the names of the managers of the home teams in a football match.			
Primary Key	matchID, managerID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
matchID	tblMatches	—	Mandatory	(1,1)
managerID	tblManagers	—	Mandatory	(1,N)

4.10.1 matchID field

See specification in Section 4.8.1.

4.10.2 managerID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblManagers
<i>Source Specification</i>	managerID in tblManagers table
<i>Description</i>	The identification number that refers to the club manager for the designated home team.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	####
<i>Display Format</i>	0000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Composite
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing managerID value in tblManagers
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

4.11 Away Managers linking table (tblAwayManagers)

tblAwayManagers	This table contains the names of the managers of the away teams in a football match.			
Primary Key	matchID, managerID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
matchID	tblMatches	—	Mandatory	(1,1)
managerID	tblManagers	—	Mandatory	(1,N)

4.11.1 matchID field

See specification in Section 4.8.1.

4.11.2 managerID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblManagers
<i>Source Specification</i>	managerID in tblManagers table
<i>Description</i>	The identification number that refers to the club manager for the designated away team.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	####
<i>Display Format</i>	0000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Composite
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing managerID value in tblManagers
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

4.12 Environments table (tblEnvironments)

tblEnvironments	Records the ambient conditions under which the football match took place. This table is used to track match performance relative to weather and other natural conditions.			
Primary Key	enviroID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
matchID	tblMatches	—	Optional	(1,1)
—	tblWeatherKickoff	Restrict	Mandatory	(0,1)
—	tblWeatherHalftime	Restrict	Mandatory	(0,1)
—	tblWeatherFulltime	Restrict	Mandatory	(0,1)

4.12.1 enviroID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblMatches
<i>Description</i>	A unique number used to tie environmental conditions to the matches in which they are played.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	0000000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	1000000-9999999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

4.12.2 matchID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblMatches
<i>Source Specification</i>	matchID in tblMatches table
<i>Description</i>	The identification number of the football match
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	0000000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing matchID value in tblMatches
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

4.12.3 envKickoffTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The time at which the football match kicked off.
<i>Data Type</i>	DateTime
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	HH:MM
<i>Display Format</i>	HH:MM
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	—

4.12.4 envTemperature field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The ambient temperature at kickoff, in degrees Celsius.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	1
<i>Input Mask</i>	##.##
<i>Display Format</i>	20.0°C
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	20.0
<i>Range of Values</i>	-15.0 - 40.0
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	—

4.13 Weather conditions lookup table (tblWeather)

tblWeather	Contains a list of specific weather conditions during a football match. These conditions are terms from NOAA National Weather Service.			
Primary Key	weatherID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblEnvironments	Restrict	Mandatory	(1,1)

4.13.1 weatherID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblEnvironments
<i>Description</i>	A unique number used to identify specific weather conditions.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	10-99
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

4.13.2 wxConditionDesc field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The description of the predominate weather condition during the football match.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	40
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

4.14 Kickoff weather linking table (tblWeatherKickoff)

tblWeatherKickoff	This table records the ambient weather conditions at kickoff of the football match.			
Primary Keys	enviroID,weatherID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
enviroID	tblEnvironments	—	Mandatory	(1,1)
weatherID	tblWeather	—	Mandatory	(1,1)

4.14.1 enviroID field

<i>Specification Type</i>	Unique
<i>Parent Table</i>	tblEnvironments
<i>Source Specification</i>	enviroID field in tblEnvironments table
<i>Description</i>	A unique number used to tie environmental conditions to the matches in which they are played.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	0000000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Composite
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing enviroID value in tblEnvironments
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

4.14.2 weatherID field

<i>Specification Type</i>	Unique
<i>Parent Table</i>	tblWeather
<i>Source Specification</i>	weatherID field in tblWeather table
<i>Description</i>	A unique number used to identify specific weather conditions.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Composite
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing weatherID value in tblWeather
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

4.15 Halftime weather linking table (tblWeatherHalftime)

tblWeatherHalftime	This table records the ambient weather conditions at halftime of the football match.			
Primary Keys	enviroID,weatherID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
enviroID	tblEnvironments	—	Mandatory	(1,1)
weatherID	tblWeather	—	Mandatory	(1,1)

4.15.1 enviroID field

See specification in Section 4.14.1.

4.15.2 weatherID field

See specification in Section 4.14.2.

4.16 Fulltime weather linking table (tblWeatherFulltime)

tblWeatherKickoff	This table records the ambient weather conditions at the end of the football match.			
Primary Keys	enviroID,weatherID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
enviroID	tblEnvironments	—	Mandatory	(1,1)
weatherID	tblWeather	—	Mandatory	(1,1)

4.16.1 enviroID field

See specification in Section 4.14.1.

4.16.2 weatherID field

See specification in Section 4.14.2.

5 Personnel Tables

The following tables capture data related to personnel associated with a football match, such as the players, managers, and central referees (but not assistant referees). The tactical positions of the players and the national origins of the personnel are also captured here. The major personnel table related to a match is the Lineup table, which tracks the player list (starting and bench) for a particular match.

5.1 Players table (tblPlayers)

tblPlayers	Contains the list of players who participate in the football competition, allowing for the tracking of player participation and performance in the club and the competition.			
Primary Key	playerID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
countryID	tblCountries	—	Optional	(0,N)
—	tblLineups	Restrict	Mandatory	(1,1)

5.1.1 playerID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblLineups
<i>Description</i>	A unique number used to identify players in a football competition.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	100000-999999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.1.2 countryID field

See specification in Section 4.4.3.

5.1.3 plyrBirthdate field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The birth date of the football player, in ISO 8601 (YYYY-MM-DD) format.
<i>Data Type</i>	DateTime
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	YYYY-MM-DD
<i>Display Format</i>	Year Month Day
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	Subtraction

5.1.4 plyrFirstname field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The player's first name.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	20
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

5.1.5 plyrLastname field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The player's last name.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	30
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

5.1.6 plyrNickname field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The player's nickname, if any.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	30
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	Nulls Allowed
<i>Values Entered By</i>	User
<i>Required Value</i>	No
<i>Default Value</i>	NULL
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

5.1.7 plyrDefPosID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblPositions
<i>Source Specification</i>	positionID in tblPositions table
<i>Description</i>	The identification number of the player's default football position
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing positionID value in tblPositions
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

5.2 Player History table (tblPlayerHistory)

tblPlayerHistory	Contains the physical characteristics of a football player over his playing history. This table is used to perform performance studies involving players over time.			
Primary Key	playerhistoryID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
playerID	tblPlayers	—	Optional	(0,N)

5.2.1 playerhistoryID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A unique number used to identify a historical record of a football player's physical characteristics.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	0000000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	1000000-9999999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

5.2.2 plyrHistDate field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The date on which the historical player data are valid, in ISO 8601 (YYYY-MM-DD) format.
<i>Data Type</i>	DateTime
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	YYYY-MM-DD
<i>Display Format</i>	Year Month Day
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	Subtraction

5.2.3 plyrHistHeight field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The height of the football player, in meters.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	1
<i>Input Mask</i>	#.##
<i>Display Format</i>	0.00 m
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	1.50
<i>Range of Values</i>	0.00 - 2.50
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	—

5.2.4 plyrHistWeight field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The weight of the football player, in kilograms.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000 kg
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	50
<i>Range of Values</i>	0 - 150
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal, Greater Than, Less Than
<i>Operations Allowed</i>	—

5.3 Managers table (tblManagers)

tblManagers	Contains the list of managers who participate in the football competition, allowing for the tracking of managerial changes at the club during a competition.			
Primary Key	managerID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
countryID	tblCountries	—	Optional	(0,N)
—	tblMatches	Restrict	Mandatory	(1,1)

5.3.1 managerID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblMatches
<i>Description</i>	A unique number used to identify managers in a football competition.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	####
<i>Display Format</i>	0000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	1000-9999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.3.2 countryID field

See specification in section 4.4.3.

5.3.3 mgrBirthdate field

Specification is identical to that defined in section 5.1.3.

5.3.4 mgrFirstname field

Specification is identical to that defined in section 5.1.4.

5.3.5 mgrLastname field

Specification is identical to that defined in section 5.1.5.

5.3.6 mgrNickname field

Specification is identical to that defined in section 5.1.6 .

5.4 Referees table (tblReferees)

tblReferees	Contains the list of match referees who participate in the football competition, allowing for the tracking of their participation and performance in the competition.			
Primary Key	refereeID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
countryID	tblCountries	—	Optional	(0,N)
—	tblMatches	Restrict	Mandatory	(1,1)

5.4.1 refereeID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblMatches
<i>Description</i>	A unique number used to identify match referees in a football competition.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	4
<i>Decimal Places</i>	0
<i>Input Mask</i>	####
<i>Display Format</i>	0000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	1000-9999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.4.2 countryID field

See specification in section 4.4.3.

5.4.3 refBirthdate field

Specification is identical to that defined in section 5.1.3.

5.4.4 refFirstName field

Specification is identical to that defined in section 5.1.4.

5.4.5 refLastName field

Specification is identical to that defined in section 5.1.5.

5.5 Country lookup table (tblCountries)

tblCountries	Contains the list of countries represented by personnel who participate in a football competition.			
Primary Key	countryID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblPlayers	Restrict	Mandatory	(1,1)
—	tblManagers	Restrict	Mandatory	(1,1)
—	tblReferees	Restrict	Mandatory	(1,1)
confedID	tblConfederations	—	Optional	(1,N)

5.5.1 countryID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblPlayers, tblManagers, tblReferees, tblTeams, tblVenues
<i>Description</i>	A unique number used to identify the country of personnel.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	100-999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.5.2 ctyName field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	Country name.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	60
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

5.5.3 confedID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblConfederations
<i>Source Specification</i>	confedID in tblConfederations table
<i>Description</i>	The identification number of the football confederation
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing confedID value in tblConfederations
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

5.6 Confederations lookup table (tblConfederations)

tblConfederations	Contains the list of football confederations.			
Primary Key	confedID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblCountries	Restrict	Mandatory	(1,1)
—	tblTimeZones	Restrict	Mandatory	(1,1)

5.6.1 confedID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblCountries
<i>Description</i>	A unique number used to identify the football confederation.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	N/A
<i>Range of Values</i>	10-99
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.6.2 confedName field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	Name of football confederation.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	40
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

5.7 Lineup table (tblLineups)

tblLineups	This table contains the players who participate in matches of the football competition, whether they are starting players or on the substitutes' list. The information is necessary to track the level of participation of players over a season.			
Primary Key	lineupID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
matchID	tblMatches	—	Optional	(22,36)
teamID	tblTeams	—	Optional	(1,N)
playerID	tblPlayers	—	Optional	(1,N)
positionID	tblPositions	—	Optional	(1,N)
—	tblGoals	Restrict	Mandatory	(1,1)
—	tblPenalties	Restrict	Mandatory	(1,1)
—	tblOffenses	Restrict	Mandatory	(1,1)
—	tblSubs	Restrict	Mandatory	(1,1)
—	tblSwitchPositions	Restrict	Mandatory	(1,1)

5.7.1 lineupID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblGoals, tblPenalties, tblOffenses, tblSubstitutions
<i>Description</i>	A unique number used to identify players who participate in football matches.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	0000000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	1000000-9999999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.7.2 matchID field

See specification in section 4.12.2.

5.7.3 teamID field

See specification in section ??.

5.7.4 playerID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblLineups
<i>Source Specification</i>	playerID in tblLineups table
<i>Description</i>	The identification number of the player who participates in the lineup.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing playerID value in tblPlayers
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

5.7.5 positionID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblPositions
<i>Source Specification</i>	positionID in tblPositions table
<i>Description</i>	The identification number of the football positions
<i>Data Type</i>	Numeric
<i>Character Support</i>	Alphanumeric
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing positionID value in tblPositions
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

5.7.6 lpStarting field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A flag to designate starting players in the match lineup.
<i>Data Type</i>	Boolean or Numeric
<i>Character Support</i>	Alphanumeric
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0 or FALSE
<i>Range of Values</i>	0-1 or TRUE/FALSE
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.7.7 lpCaptain field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A flag to designate the team captain in the match lineup.
<i>Data Type</i>	Boolean or Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0 or FALSE
<i>Range of Values</i>	0-1 or TRUE/FALSE
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.8 Positions lookup table (tblPositions)

tblPositions	This table contains information on the field positions (including goalkeeper) and their flanks they occupy on the field. The information is used to track the tactical organization of the lineup during a match.			
Primary Key	positionID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
posFieldID	tblFieldNames	—	Optional	(1,3)
posFlankID	tblFlankNames	—	Optional	(1,3)
—	tblLineups	Restrict	Mandatory	(1,1)

5.8.1 positionID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblLineups
<i>Description</i>	A unique number used to identify football positions.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	10-99
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.8.2 posFieldID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblFieldNames
<i>Source Specification</i>	posFieldID in tblFieldNames table
<i>Description</i>	The identification number of the football field positions
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing posFieldID value in tblFieldNames
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

5.8.3 posFlankID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblFlankNames
<i>Source Specification</i>	posFlankID in tblFlankNames table
<i>Description</i>	The identification number of the flank locations.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing posFlankID value in tblFlankNames
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

5.9 Field position name table (tblFieldNames)

tblFieldNames	This table contains a list of the basic field positions.			
Primary Key	posFieldID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblPositions	Restrict	Mandatory	(1,1)

5.9.1 posFieldID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblLineups
<i>Description</i>	A unique number used to identify football positions.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	1-9
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.9.2 posFieldName field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The description of the generic field position.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	15
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

5.10 Flank name table (tblFlankNames)

tblFlankNames	This table contains a list of the basic flanks on the field.			
Primary Key	posFlankID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblPositions	Restrict	Mandatory	(1,1)

5.10.1 posFlankID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblLineups
<i>Description</i>	A unique number used to identify flank areas.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	1-3
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	—

5.10.2 posFlankName field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The description of the flank area on the field.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	8
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	Nulls Allowed
<i>Values Entered By</i>	User
<i>Required Value</i>	No
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

6 Match Event Tables

The following tables capture data from match events. These events include goals scored in open play, penalty kick decisions, disciplinary events, substitutions, and tactical or enforced position changes.

6.1 Goals table (tblGoals)

tblGoals	This table contains information on the goals that were scored during a match, excluding penalties. The information in this table is used to track match scorelines, scoring records of players in a match, and the types of goals scored.			
Primary Key	goalID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
teamID	tblTeams	—	Optional	(0,N)
lineupID	tblLineups	—	Optional	(0,N)
gtsTypeID	tblGoalStrikes	—	Optional	(0,N)
gtfTypeID	tblGoalEvents	—	Optional	(0,N)

6.1.1 goalID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A unique number used to identify goals scored in a football match.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	100000-999999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.1.2 countryID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblCountries
<i>Source Specification</i>	countryID in tblCountries table
<i>Description</i>	The identification number of one of the teams credited with the goal scored in the football match
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	3
<i>Decimal Places</i>	0
<i>Input Mask</i>	###
<i>Display Format</i>	000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	tblHomeTeams.countryID, tblAwayTeams.countryID
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.1.3 lineupID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblLineups
<i>Source Specification</i>	lineupID in tblLineups table
<i>Description</i>	The identification number of player participations in match lineups
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	0000000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing lineupID value in tblLineups
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.1.4 gtsTypeID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblGoalStrikes
<i>Source Specification</i>	gtsTypeID in tblGoalStrikes table
<i>Description</i>	The identification number of body parts used to score goals from open play.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing gtsTypeID value in tblGoalStrikes
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.1.5 gteTypeID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblGoalEvents
<i>Source Specification</i>	gteTypeID in tblGoalEvents table
<i>Description</i>	The identification number of field events from which goals were scored.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing gteTypeID value in tblGoalEvents
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.1.6 glsTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time at which the goal was scored.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	0 - 90
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

6.1.7 glsSTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time during stoppage time at which the goal was scored.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	0-15 when glsTime = 45 or glsTime = 90, 0 otherwise
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

6.2 Goal strike lookup table (tblGoalStrikes)

tblGoalStrikes	This table contains a list of the body parts used to score goals from open play.			
Primary Key	gtsTypeID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblGoals	Restrict	Mandatory	(1,1)

6.2.1 gtsTypeID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblGoals
<i>Description</i>	A unique number that identifies the body part used to score open play goals.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	1-9
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.2.2 gtsDesc field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The description of the body part used to score open play goals.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	15
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

6.3 Goal field event lookup table (tblGoalEvents)

tblGoalEvents	This table contains a list of the types of plays from which open play goals are scored.			
Primary Key	gteTypeID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblGoals	Restrict	Mandatory	(1,1)

6.3.1 gteTypeID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	tblGoals
<i>Description</i>	A unique number used to identify match events that produced goals.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	1-9
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.3.2 gteDesc field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The description of the match event that led to a goal in open play.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	30
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

6.4 Penalties table (tblPenalties)

tblPenalties	This table lists the penalties given during a football competition. The information stored here will be used to track fouls that resulted in penalties, the referees who awarded them, and the performance of penalty kick takers and goalkeepers.			
Primary Key	penaltyID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
lineupID	tblLineups	—	Optional	(0,N)
foulID	tblFouls	—	Optional	(0,N)
penOutcomeID	tblPenOutcomes	—	Optional	(0,N)

6.4.1 penaltyID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A unique number used to identify penalties that occur during a football match.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	5
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	00000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	10000-99999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.4.2 lineupID field

See specification in section 6.1.3.

6.4.3 foulID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblFouls
<i>Source Specification</i>	foulID in tblFouls table
<i>Description</i>	The identification number of the types of fouls that result in bookings or penalties.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing foulID value in tblFouls
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.4.4 penOutcomeID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblPenOutcomes
<i>Source Specification</i>	penOutcomeID in tblPenOutcomes table
<i>Description</i>	The identification number of penalty kick outcomes.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing penOutcomeID value in tblPenOutcomes
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.4.5 penTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time at which the penalty was given.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	0 - 90
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

6.4.6 penSTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time during stoppage time at which the penalty was given.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0
<i>Range of Values</i>	0-15 when penTime = 45 or penTime = 90, 0 otherwise
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

6.5 Penalty outcome lookup table (tblPenOutcomes)

tblPenOutcomes	This table lists the possible penalty outcomes during a football match.			
Primary Key	penOutcomeID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblPenalties	Restrict	Mandatory	(1,1)

6.5.1 penOutcomeID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A unique number used to identify penalty kick outcomes.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	1-9
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.5.2 poDesc field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The description of the penalty kick outcome.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	15
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

6.6 Offenses table (tblOffenses)

tblOffenses	This table lists the cautions and expulsions given out during a football match. The information stored here will allow the tracking of disciplinary records of players and the performance of referees during a football competition.			
Primary Key	offenseID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
lineupID	tblLineups	—	Optional	(0,N)
foulID	tblFouls	—	Optional	(0,N)
cardID	tblPenOutcomes	—	Optional	(0,N)

6.6.1 offenseID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A unique number used to identify bookings that occur during a football match.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	100000-999999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.6.2 lineupID field

See specification in section 6.1.3.

6.6.3 foulID field

See specification in section 6.4.3.

6.6.4 cardID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblCards
<i>Source Specification</i>	cardID in tblCards table
<i>Description</i>	The identification number of caution/expulsion cards.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing cardID value in tblCards
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.6.5 ofnsTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time at which the booking occurred.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	0 - 90
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

6.6.6 ofnsSTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time during stoppage time at which the booking occurred.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0
<i>Range of Values</i>	0-15 when ofnsTime = 45 or ofnsTime = 90, 0 otherwise
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

6.7 Fouls lookup table (tblFouls)

tblFouls	This table lists the fouls that result in either penalties, cautions, or expulsions.			
Primary Key	foulID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblPenalties	Reject	Mandatory	(1,1)
—	tblOffenses	Reject	Mandatory	(1,1)

6.7.1 foulID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A unique number used to identify fouls that result in a booking or penalty.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	10-99
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.7.2 foulDesc field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The description of the foul that resulted in a booking.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters
<i>Length</i>	40
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

6.8 Card lookup table (tblCards)

tblCards	This table lists the type of cards that are shown during a football match.			
Primary Key	cardID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblOffenses	Reject	Mandatory	(1,1)

6.8.1 cardID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A unique number used to identify caution card types.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	1
<i>Decimal Places</i>	0
<i>Input Mask</i>	#
<i>Display Format</i>	0
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	1-3
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.8.2 cardType field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The description of the caution cards.
<i>Data Type</i>	Character
<i>Character Support</i>	Letters and Symbols
<i>Length</i>	12
<i>Decimal Places</i>	—
<i>Input Mask</i>	—
<i>Display Format</i>	Each description should start with a capital letter.
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	—
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	—
<i>Operations Allowed</i>	—

6.9 Substitution table (tblSubstitutions)

tblSubstitutions	This table stores the substitutions that occur during a football match. The data scored here would be used to track player participation during a football competition.			
Primary Key	subsID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
—	tblInSubstitutions	Reject	Mandatory	(1,1)
—	tblOutSubstitutions	Reject	Mandatory	(1,1)

6.9.1 subsID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A unique number used to identify substitutions that occur during a football match.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	100000-999999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.9.2 subsTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time at which the substitution was made.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	0 - 90
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

6.9.3 subsSTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time during stoppage time at which the substitution was made.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	0
<i>Range of Values</i>	0-15 when subsTime = 45 or subsTime = 90, 0 otherwise
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

6.10 Players substituted into match linking table (tblInSubstitutions)

tblInSubstitutions	This table lists the players in the match lineup who are substituted into a football match.			
Primary Keys	subsID, lineupID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
subsID	tblSubstitutions	—	Optional	(1,1)
lineupID	tblLineups	—	Optional	(1,1)

6.10.1 subsID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblSubstitutions
<i>Source Specification</i>	subsID in tblSubstitutions table
<i>Description</i>	A unique number used to identify substitutions that occur during a football match.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Composite
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing subsID value in tblSubstitutions
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.10.2 lineupID field

<i>Specification Type</i>	Replica
<i>Parent Table</i>	tblLineups
<i>Source Specification</i>	lineupID in tblLineups table
<i>Description</i>	The identification number of player participations in match lineups
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	7
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	0000000
<i>Key Type</i>	Foreign
<i>Key Structure</i>	Composite
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	Any existing lineupID value in tblLineups not already in tblInSubstitutions
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.11 Players substituted out of match linking table (tblOutSubstitutions)

tblOutSubstitutions	This table lists the players in the match lineup who are substituted out of a football match.			
Primary Keys	subsID, lineupID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
subsID	tblSubstitutions	—	Optional	(1,1)
lineupID	tblLineups	—	Optional	(1,1)

6.11.1 subsID field

See specification in Section 6.10.1.

6.11.2 lineupID field

See specification in Section 6.10.2.

6.12 Switch Positions table (tblSwitchPositions)

tblSwitchPositions	This table stores the instances in which field positions are switched during the match, whether required by goalkeeper expulsion or a tactical change.			
Primary Key	switchID			
Foreign Key	Related Table	Deletion Rule	Participation Type	Participation Degree
lineupID	tblLineups	—	Optional	(0,1)
positionID	tblPositions	—	Optional	(0,1)

6.12.1 switchID field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	A unique number used to identify position switches that occur during a football match.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	6
<i>Decimal Places</i>	0
<i>Input Mask</i>	#####
<i>Display Format</i>	000000
<i>Key Type</i>	Primary
<i>Key Structure</i>	Simple
<i>Uniqueness</i>	Unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	System
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	100000-999999
<i>Edit Rule</i>	Enter Now, Edits Not Allowed
<i>Comparisons Allowed</i>	Equal, Not Equal
<i>Operations Allowed</i>	—

6.12.2 lineupID field

See specification in section 6.1.3.

6.12.3 switchPositionID field

See specification in section 5.7.5.

6.12.4 switchTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time at which the position switch was made.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	0 - 90
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

6.12.5 switchSTime field

<i>Specification Type</i>	Unique
<i>Shared By</i>	—
<i>Description</i>	The match time during stoppage time at which the position switch was made.
<i>Data Type</i>	Numeric
<i>Character Support</i>	Numbers
<i>Length</i>	2
<i>Decimal Places</i>	0
<i>Input Mask</i>	##
<i>Display Format</i>	00
<i>Key Type</i>	Non-key
<i>Key Structure</i>	—
<i>Uniqueness</i>	Non-unique
<i>Null Support</i>	No Nulls
<i>Values Entered By</i>	User
<i>Required Value</i>	Yes
<i>Default Value</i>	—
<i>Range of Values</i>	0-15 when glsTime = 45 or glsTime = 90, 0 otherwise
<i>Edit Rule</i>	Enter Now, Edits Allowed
<i>Comparisons Allowed</i>	Equal To, Not Equal To
<i>Operations Allowed</i>	Subtraction

7 Views

This section presents specifications for virtual tables that are used to comprise views of the Football Match Result Database. These tables draw data from multiple base tables in order to provide context-specific information, preserve data security and confidentiality, and enforce data integrity.

7.1 PlayersList view

PlayersList	This view provides a list of the players who are participating in the football competition.
Type	Aggregate
Base Tables	tblPlayers, tblCountries
Field Name	Expression
playerID	tblPlayers.playerID
FullName	tblPlayers.plyrFirstName + ' ' + tblPlayers.plyrLastName
Country	tblCountries.ctyName

7.2 ManagerList view

ManagerList	This view provides a list of the managers who are coaching teams in the football competition.
Type	Aggregate
Base Tables	tblManagers, tblCountries
Field Name	Expression
managerID	tblManagers.managerID
FullName	tblManagers.mgrFirstName + ' ' + tblManagers.mgrLastName
Country	tblCountries.ctyName

7.3 RefereeList view

RefereeList	This view provides a list of the match referees who are participating in the football competition.
Type	Aggregate
Base Tables	tblReferees, tblCountries
Field Name	Expression
refereeID	tblReferees.refereeID
FullName	tblReferees.refFirstName + ' ' + tblReferees.refLastName
Country	tblCountries.ctyName

7.4 HomeTeamList view

HomeTeamList	This view provides a list of the national football teams that are designated home teams in their matches.
Type	Aggregate
Base Tables	tblMatches, tblCountries, tblHomeTeams
Field Name	Expression
matchID	tblMatches.matchID
Team	tblCountries.ctyName

7.5 AwayTeamList view

AwayTeamList	This view provides a list of national football teams that are designated away teams in their matches.
Type	Aggregate
Base Tables	tblMatches, tblCountries, tblAwayTeams
Field Name	Expression
matchID	tblMatches.matchID
Team	tblCountries.ctyName

7.6 PositionsList view

PositionsList	This view provides a list of player positions in a football match.
Type	Aggregate
Base Tables	tblPositions, tblFieldNames, tblFlankNames
Field Name	Expression
positionID	tblPositions.positionID
PositionName	tblFlankNames.posFlankName + ' ' + tblFieldNames.posFieldName

7.7 MatchList view

MatchList	This view provides a list of top-level information on the football match, the competitors, and the match referee.
Type	Aggregate
Base Tables	tblMatches, tblCompetitions, tblRounds, tblVenues, HomeTeamList, AwayTeamList, RefereeList
Field Name	Expression
matchID	tblMatches.matchID
competitionID	tblCompetitions.competitionID
roundID	tblRounds.roundID
Competition	tblCompetitions.compName
Round	tblRounds.roundDesc
Matchup	HomeTeamList.Team + ' vs ' + AwayTeamList.Team
Venue	tblVenues.venName
Referee	RefereeList.FullName

7.8 LineupList view

LineupList	This view provides a list of player appearances in a football match.
Type	Aggregate
Base Tables	tblCountries, tblLineups, MatchList, PlayersList, PositionsList
Field Name	Expression
lineupID	tblLineups.lineupID
Matchup	MatchList.Matchup
Team	tblCountries.ctyName
Player	PlayersList.FullName
PositionName	PositionsList.PositionName
Starter	tblLineups.lpStarting
Captain	tblLineups.lpCaptain

7.9 GoalsList view

GoalsList	This view provides a list of goals scored from open play in a match.
Type	Aggregate
Base Tables	tblCountries, LineupList, tblGoals, tblGoalStrikes, tblGoalEvents
Field Name	Expression
goalID	tblGoals.goalID
Matchup	LineupList.Matchup
Team	tblCountries.ctyName
Scorer	PlayersList.FullName
Strike	tblGoalStrikes.gtsDesc
Play	tblGoalEvents.gteDesc
Time	tblGoals.glsTime + ' ' if tblGoals.glsSTime = 0, tblGoals.glsTime + '+' tblGoals.glsSTime + ' ' if tblGoals.glsSTime > 0

7.10 PenaltiesList view

PenaltiesList	This view provides a list of penalty kick decisions and their outcomes in a football match.
Type	Aggregate
Base Tables	tblPenalties, LineupList, tblFouls, tblPenOutcomes
Field Name	Expression
penaltyID	tblPenalties.penaltyID
Matchup	LineupList.Matchup
Taker	PlayersList.FullName
Foul	tblFouls.foulDesc
Outcome	tblPenOutcomes.poDesc
Time	tblPenalties.penTime + ' ' ' if tblPenalties.penSTime = 0, tblPenalties.penTime + '+' tblPenalties.penSTime + ' ' ' if tblPenalties.penSTime > 0

7.11 CautionsList view

CautionsList	This view provides a list of yellow-card offenses in a football match.
Type	Aggregate
Base Tables	LineupList, tblOffenses, tblFouls
Field Name	Expression
offenseID	tblLineups.lineupID
Matchup	LineupList.Matchup
Player	LineupList.Player
Foul	tblFouls.foulDesc
Time	tblOffense.ofnsTime + ' ' ' if tblOffenses.ofnsSTime = 0, tblOffenses.ofnsTime + '+' tblOffenses.ofnsSTime + ' ' ' if tblOffenses.ofnsSTime > 0

7.12 ExpulsionsList view

ExpulsionsList	This view provides a list of second yellow-card offenses or direct red-card offenses in a football match.
Type	Aggregate
Base Tables	LineupList, tblOffenses, tblFouls
Field Name	Expression
lineupID	tblLineups.lineupID
Matchup	LineupList.Matchup
Player	LineupList.Player
Foul	tblFouls.foulDesc
Time	tblOffenses.ofnsTime + ' ' ' if tblOffenses.ofnsSTime = 0, tblOffenses.ofnsTime + '+' tblOffenses.ofnsSTime + ' ' ' if tblOffenses.ofnsSTime > 0

7.13 InSubList view

InSubList	This view provides a list of players substituted into a football match.
Type	Aggregate
Base Tables	tblInSubstitutions, LineupList
Field Name	Expression
subsID	tblInSubstitutions.subsID
Player	LineupList.Player

7.14 OutSubList view

OutSubList	This view provides a list of players substituted out of a football match.
Type	Aggregate
Base Tables	tblOutSubstitutions, LineupList
Field Name	Expression
subsID	tblOutSubstitutions.subsID
Player	LineupList.Player

7.15 SubstitutionsList view

SubstitutionsList	This view provides a list of player substitutions in a football match.
Type	Aggregate
Base Tables	LineupList, tblSubstitutions, InSubList, OutSubList
Field Name	Expression
subsID	tblSubstitutions.subsID
Matchup	LineupList.Matchup
InPlayer	InSubList.Player
OutPlayer	OutSubList.Player
Time	tblSubstitutions.subsTime + ' ' , if tblSubstitutions.subsSTime = 0, tblSubstitutions.subsTime + '+' tblSubstitutions.subsSTime + ' ' , if tblSubstitutions.subsSTime > 0

7.16 SwitchPosList view

SwitchPosList	This view provides a list of major tactical position changes during a match.
Type	Aggregate
Base Tables	tblSwitchPositions, LineupList, PositionsList
Field Name	Expression
switchID	tblSwitchPositions.subsID
Matchup	MatchList.Matchup
Player	LineupList.Player
OldPosition	LineupList.PositionName
NewPosition	PositionsList.PositionName
Time	tblSwitchPositions.subsTime + ' ' ' if tblSwitchPositions.subsSTime = 0, tblSwitchPositions.subsTime + '+' tblSwitchPositions.subsSTime + ' ' ' if tblSwitchPositions.subsSTime > 0