

PSSL 109
Leiden University & DutchCats
the 17th of November 2024

Higher dimensional semantics of axiomatic dependent type theories

Matteo Spadetto
University of Udine

Theories of dependent types

Theories that can make:

- ▶ **type judgements**, $A : \text{TYPE}$ (possibly relative to a context of variables, $\Gamma \vdash A : \text{TYPE}$), read as *A is a statement*

Theories of dependent types

Theories that can make:

- ▶ **type judgements**, $A : \text{TYPE}$ (possibly relative to a context of variables, $\Gamma \vdash A : \text{TYPE}$), read as *A is a statement*
- ▶ **term judgements**, $t : A$, read as *t is a proof of the statement A*

Theories of dependent types

Theories that can make:

- ▶ **type judgements**, $A : \text{TYPE}$ (possibly relative to a context of variables, $\Gamma \vdash A : \text{TYPE}$), read as *A is a statement*
- ▶ **term judgements**, $t : A$, read as *t is a proof of the statement A*
- ▶ **type equality judgements**, $A \equiv B$

Theories of dependent types

Theories that can make:

- ▶ **type judgements**, $A : \text{TYPE}$ (possibly relative to a context of variables, $\Gamma \vdash A : \text{TYPE}$), read as *A is a statement*
- ▶ **term judgements**, $t : A$, read as *t is a proof of the statement A*
- ▶ **type equality judgements**, $A \equiv B$
- ▶ **term equality judgements**, $t \equiv t' : A$

Theories of dependent types

Theories that can make:

- ▶ **type judgements**, $A : \text{TYPE}$ (possibly relative to a context of variables, $\Gamma \vdash A : \text{TYPE}$), read as *A is a statement*
- ▶ **term judgements**, $t : A$, read as *t is a proof of the statement A*
- ▶ **type equality judgements**, $A \equiv B$
- ▶ **term equality judgements**, $t \equiv t' : A$

Type constructors. Groups of deduction rules that encode pieces of logic.

Theories of dependent types

Theories that can make:

- ▶ **type judgements**, $A : \text{TYPE}$ (possibly relative to a context of variables, $\Gamma \vdash A : \text{TYPE}$), read as *A is a statement*
- ▶ **term judgements**, $t : A$, read as *t is a proof of the statement A*
- ▶ **type equality judgements**, $A \equiv B$
- ▶ **term equality judgements**, $t \equiv t' : A$

Type constructors. Groups of deduction rules that encode pieces of logic.

E.g.

identity type constructor, $t = t'$, for a notion of equality

dependent sum type constructor, $\Sigma_{x:A} B(x)$, for a notion of existential quantification (that we will focus on today)

Semantics of these theories

Semantics consists of *category theoretic copies* - formulated e.g. as **display map categories** - of a given theory, that *encode as morphisms* and properties between morphisms these type constructors.

Semantics of these theories

Semantics consists of *category theoretic copies* - formulated e.g. as **display map categories** - of a given theory, that *encode as morphisms* and properties between morphisms these type constructors.

There are essentially two approaches:

- ▶ a **syntactic** approach, *encoding type constructors in alignment with the syntax*
- ▶ a **categorical** approach, *characterising type constructors categorically*

Semantics of these theories

Semantics consists of *category theoretic copies* - formulated e.g. as **display map categories** - of a given theory, that *encode as morphisms* and properties between morphisms these type constructors.

There are essentially two approaches:

- ▶ a **syntactic** approach, *encoding type constructors in alignment with the syntax*
- ▶ a **categorical** approach, *characterising type constructors categorically*

The syntactic formulation can be used to **prove** things of the theory, while the categorical one to find specific models that can be used to **disprove** things of the theory.

Extensional theories (where identity proofs are irrelevant)

Extensional identity types

$$\frac{\vdash A : \text{TYPE}}{x, x' : A \vdash x = x' : \text{TYPE}} \\ x : A \vdash r(x) : x = x$$

$$\frac{\vdash A : \text{TYPE}}{x, x' : A, p : x = x' \vdash p \equiv x'} \\ x, x' : A, p : x = x' \vdash p \equiv r(x)$$

Dependent sum types

$$\frac{\vdash A : \text{TYPE} \\ x : A \vdash B(x) : \text{TYPE}}{\vdash \Sigma_{x:A} B(x) : \text{TYPE}} \\ x : A, y : B(x) \vdash \langle x, y \rangle : \Sigma_{x:A} B(x)$$

$$\frac{\vdash A : \text{TYPE} \\ x : A \vdash B(x) : \text{TYPE} \\ u : \Sigma_{x:A} B(x) \vdash C(u) : \text{TYPE} \\ x : A; y : B(x) \vdash c(x, y) : C(\langle x, y \rangle)}{u : \Sigma_{x:A} B(x) \vdash \text{split}(c, u) : C(u)} \\ x : A; y : B(x) \vdash \text{split}(c, \langle x, y \rangle) \equiv c(x, y)$$

Intensional theories (with computation rules)

Intensional identity types

$$\frac{\vdash A : \text{TYPE}}{x, x' : A \vdash x = x' : \text{TYPE}} \\ x : A \vdash r(x) : x = x$$

$$\frac{\begin{array}{c} \vdash A : \text{TYPE} \\ x, x' : A; p : x = x' \vdash C(x, x', p) : \text{TYPE} \\ x : A \vdash q(x) : C(x, x, r(x)) \end{array}}{x, x' : A; p : x = x' \vdash J(q, x, x', p) : C(x, x', p)} \\ x : A \vdash J(q, x, x, r(x)) \equiv q(x)$$

Dependent sum types

$$\frac{\begin{array}{c} \vdash A : \text{TYPE} \\ x : A \vdash B(x) : \text{TYPE} \end{array}}{\vdash \Sigma_{x:A} B(x) : \text{TYPE}} \\ x : A, y : B(x) \vdash \langle x, y \rangle : \Sigma_{x:A} B(x)$$

$$\frac{\begin{array}{c} \vdash A : \text{TYPE} \\ x : A \vdash B(x) : \text{TYPE} \\ u : \Sigma_{x:A} B(x) \vdash C(u) : \text{TYPE} \\ x : A; y : B(x) \vdash c(x, y) : C(\langle x, y \rangle) \end{array}}{u : \Sigma_{x:A} B(x) \vdash \text{split}(c, u) : C(u)} \\ x : A; y : B(x) \vdash \text{split}(c, \langle x, y \rangle) \equiv c(x, y)$$

Axiomatic theories (with computation *axioms*)

Axiomatic identity types

$$\frac{\vdash A : \text{TYPE}}{x, x' : A \vdash x = x' : \text{TYPE}} \\ x : A \vdash r(x) : x = x$$

$$\frac{\begin{array}{c} \vdash A : \text{TYPE} \\ x, x' : A; p : x = x' \vdash C(x, x', p) : \text{TYPE} \\ x : A \vdash q(x) : C(x, x, r(x)) \end{array}}{x, x' : A; p : x = x' \vdash J(q, x, x', p) : C(x, x', p)} \\ x : A \vdash J(q, x, x, r(x)) \not\equiv q(x)$$

Axiomatic dependent sum types

$$\frac{\begin{array}{c} \vdash A : \text{TYPE} \\ x : A \vdash B(x) : \text{TYPE} \end{array}}{\vdash \Sigma_{x:A} B(x) : \text{TYPE}} \\ x : A, y : B(x) \vdash \langle x, y \rangle : \Sigma_{x:A} B(x)$$

$$\frac{\begin{array}{c} \vdash A : \text{TYPE} \\ x : A \vdash B(x) : \text{TYPE} \\ u : \Sigma_{x:A} B(x) \vdash C(u) : \text{TYPE} \\ x : A; y : B(x) \vdash c(x, y) : C(\langle x, y \rangle) \end{array}}{u : \Sigma_{x:A} B(x) \vdash \text{split}(c, u) : C(u)} \\ x : A; y : B(x) \vdash \text{split}(c, \langle x, y \rangle) \not\equiv c(x, y)$$

Axiomatic theories (with computation *axioms*)

Axiomatic identity types

$$\frac{\vdash A : \text{TYPE}}{x, x' : A \vdash x = x' : \text{TYPE}} \\ x : A \vdash r(x) : x = x$$

$$\frac{\begin{array}{l} \vdash A : \text{TYPE} \\ x, x' : A; p : x = x' \vdash C(x, x', p) : \text{TYPE} \\ x : A \vdash q(x) : C(x, x, r(x)) \end{array}}{x, x' : A; p : x = x' \vdash J(q, x, x', p) : C(x, x', p)} \\ x : A \vdash H(q, x) : J(q, x, x, r(x)) = q(x)$$

Axiomatic dependent sum types

$$\frac{\begin{array}{l} \vdash A : \text{TYPE} \\ x : A \vdash B(x) : \text{TYPE} \end{array}}{\vdash \Sigma_{x:A} B(x) : \text{TYPE}} \\ x : A, y : B(x) \vdash \langle x, y \rangle : \Sigma_{x:A} B(x)$$

$$\frac{\begin{array}{l} \vdash A : \text{TYPE} \\ x : A \vdash B(x) : \text{TYPE} \\ u : \Sigma_{x:A} B(x) \vdash C(u) : \text{TYPE} \\ x : A; y : B(x) \vdash c(x, y) : C(\langle x, y \rangle) \end{array}}{u : \Sigma_{x:A} B(x) \vdash \text{split}(c, u) : C(u)} \\ x : A; y : B(x) \vdash \sigma(c, x, y) : \text{split}(c, \langle x, y \rangle) = c(x, y)$$

How semantics works

In a **display map category** we are given a family of display maps (notion introduced by **Paul Taylor**), denoted as $\Gamma.A \rightarrow \Gamma$ that interpret type judgements $\Gamma \vdash A : \text{TYPE}$. Term judgements $\Gamma \vdash t : A$ are interpreted as sections $\Gamma \rightarrow \Gamma.A$ of the corresponding display map.

How semantics works

In a **display map category** we are given a family of display maps (notion introduced by **Paul Taylor**), denoted as $\Gamma.A \rightarrow \Gamma$ that interpret type judgements $\Gamma \vdash A : \text{TYPE}$. Term judgements $\Gamma \vdash t : A$ are interpreted as sections $\Gamma \rightarrow \Gamma.A$ of the corresponding display map.

To have a model of a type constructor:

- ▶ In the **syntactic approach** one copies the type constructor into a display map category by means of a choice function in the language of the display map category.

How semantics works

In a **display map category** we are given a family of display maps (notion introduced by **Paul Taylor**), denoted as $\Gamma.A \rightarrow \Gamma$ that interpret type judgements $\Gamma \vdash A : \text{TYPE}$. Term judgements $\Gamma \vdash t : A$ are interpreted as sections $\Gamma \rightarrow \Gamma.A$ of the corresponding display map.

To have a model of a type constructor:

- ▶ In the **syntactic approach** one copies the type constructor into a display map category by means of a choice function in the language of the display map category.

Example:

- ▶ Extensional identity types. For every display map $\Gamma.A \rightarrow \Gamma$ there is a choice of a display map $\Gamma.A.A'.(x = x') \rightarrow \Gamma.A.A$ (formation rule) together with a choice of a section $\Gamma.A \rightarrow \Gamma.A.(x = x)$ of $\Gamma.A.(x = x) \rightarrow \Gamma.A$ (introduction rule), etc..
- ▶ Dependent sum types (in presence of extensional identities). Analogously.

How semantics works

In a **display map category** we are given a family of display maps (notion introduced by **Paul Taylor**), denoted as $\Gamma.A \rightarrow \Gamma$ that interpret type judgements $\Gamma \vdash A : \text{Type}$. Term judgements $\Gamma \vdash t : A$ are interpreted as sections $\Gamma \rightarrow \Gamma.A$ of the corresponding display map.

To have a model of a type constructor:

- ▶ In the **syntactic approach** one copies the type constructor into a display map category by means of a choice function in the language of the display map category.

Example:

- ▶ Extensional identity types. For every display map $\Gamma.A \rightarrow \Gamma$ there is a choice of a display map $\Gamma.A.A'.(x = x') \rightarrow \Gamma.A.A$ (formation rule) together with a choice of a section $\Gamma.A \rightarrow \Gamma.A.(x = x)$ of $\Gamma.A.(x = x) \rightarrow \Gamma.A$ (introduction rule), etc..
 - ▶ Dependent sum types (in presence of extensional identities). Analogously.
- ▶ In the **category theoretic approach** one looks for a 1-dimensional categorical property to give to display maps that *characterises* the type constructor, allowing *a choice function as in the syntactic approach to be induced* by this property.

How semantics works

In a **display map category** we are given a family of display maps (notion introduced by **Paul Taylor**), denoted as $\Gamma.A \rightarrow \Gamma$ that interpret type judgements $\Gamma \vdash A : \text{Type}$. Term judgements $\Gamma \vdash t : A$ are interpreted as sections $\Gamma \rightarrow \Gamma.A$ of the corresponding display map.

To have a model of a type constructor:

- ▶ In the **syntactic approach** one copies the type constructor into a display map category by means of a choice function in the language of the display map category.

Example:

- ▶ Extensional identity types. For every display map $\Gamma.A \rightarrow \Gamma$ there is a choice of a display map $\Gamma.A.A'.(x = x') \rightarrow \Gamma.A.A$ (formation rule) together with a choice of a section $\Gamma.A \rightarrow \Gamma.A.(x = x)$ of $\Gamma.A.(x = x) \rightarrow \Gamma.A$ (introduction rule), etc..
- ▶ Dependent sum types (in presence of extensional identities). Analogously.
- ▶ In the **category theoretic approach** one looks for a 1-dimensional categorical property to give to display maps that *characterises* the type constructor, allowing *a choice function as in the syntactic approach to be induced* by this property.

Example:

- ▶ Extensional identity types. For every display map $\Gamma.A \rightarrow \Gamma$, the unique diagonal arrow $\Gamma.A \rightarrow \Gamma.A.A'$ is itself a display map.
- ▶ Dependent sum types (in presence of extensional identities). Up to isomorphism, display maps are closed under composition.

How semantics works

In a **display map category** we are given a family of display maps (notion introduced by **Paul Taylor**), denoted as $\Gamma.A \rightarrow \Gamma$ that interpret type judgements $\Gamma \vdash A : \text{Type}$. Term judgements $\Gamma \vdash t : A$ are interpreted as sections $\Gamma \rightarrow \Gamma.A$ of the corresponding display map.

To have a model of a type constructor:

- ▶ In the **syntactic approach** one copies the type constructor into a display map category by means of a choice function in the language of the display map category.

Example:

- ▶ Extensional identity types. For every display map $\Gamma.A \rightarrow \Gamma$ there is a choice of a display map $\Gamma.A.A'.(x = x') \rightarrow \Gamma.A.A$ (formation rule) together with a choice of a section $\Gamma.A \rightarrow \Gamma.A.(x = x)$ of $\Gamma.A.(x = x) \rightarrow \Gamma.A$ (introduction rule), etc..
- ▶ Dependent sum types (in presence of extensional identities). Analogously.
- ▶ In the **category theoretic approach** one looks for a 1-dimensional categorical property to give to display maps that *characterises* the type constructor, allowing a *choice function as in the syntactic approach to be induced* by this property.

Example:

- ▶ Extensional identity types. For every display map $\Gamma.A \rightarrow \Gamma$, the unique diagonal arrow $\Gamma.A \rightarrow \Gamma.A.A'$ is itself a display map.
- ▶ Dependent sum types (in presence of extensional identities). Up to isomorphism, display maps are closed under composition.

Way easier to formulate!

How semantics works

For **extensional** dependent type theories, the categorical approach is clear and conceptually simple to formulate.

This is not the case for **intensional**, and **axiomatic**, dependent type theories: there aren't obvious categorical properties to characterise intensional and propositional inference rules.

How semantics works

For **extensional** dependent type theories, the categorical approach is clear and conceptually simple to formulate.

This is not the case for **intensional**, and **axiomatic**, dependent type theories: there aren't obvious categorical properties to characterise intensional and propositional inference rules.

Garner's approach: in order to characterise intensional type constructors, we can use **2-dimensional models**, *that still can be converted into ordinary models according to the syntactic approach*, and 2-dimensional - e.g. weakly universal - categorical properties.

How semantics works

For **extensional** dependent type theories, the categorical approach is clear and conceptually simple to formulate.

This is not the case for **intensional**, and **axiomatic**, dependent type theories: there aren't obvious categorical properties to characterise intensional and propositional inference rules.

Garner's approach: in order to characterise intensional type constructors, we can use **2-dimensional models**, *that still can be converted into ordinary models according to the syntactic approach*, and 2-dimensional - e.g. weakly universal - categorical properties.

This approach can also be used for axiomatic theories.

Goal. Having a 2-dimensional structure with natural categorical conditions that allow to interpret axiomatic theories.

2-dimensional semantics of propositional theories

Display map 2-categories. $(2,1)$ -dimensional categories with a specified class of 1-morphisms, called **display maps**, that satisfy the following conditions:

2-dimensional semantics of propositional theories

Display map 2-categories. (2,1)-dimensional categories with a specified class of 1-morphisms, called **display maps**, that satisfy the following conditions:

1. The class of display maps is closed under **2-dimensional re-indexing**.

$$\begin{array}{ccc} \Gamma.A & \Rightarrow & \Delta.A[f] \rightarrow \Gamma.A \\ \downarrow & & \downarrow \quad \lrcorner \quad \downarrow \\ \Delta - f \rightarrow \Gamma & & \Delta - f \rightarrow \Gamma \end{array}$$

2-dimensional semantics of propositional theories

Display map 2-categories. (2,1)-dimensional categories with a specified class of 1-morphisms, called **display maps**, that satisfy the following conditions:

1. The class of display maps is closed under **2-dimensional re-indexing**.

$$\begin{array}{ccc}
 \Gamma.A & \Rightarrow & \Delta.A[f] \rightarrow \Gamma.A \\
 \downarrow & & \downarrow \quad \lrcorner \quad \downarrow \\
 \Delta - f \rightarrow \Gamma & & \Delta - f \rightarrow \Gamma
 \end{array}$$

2. Every display map is a **cloven isofibration**.

$$\begin{array}{ccc}
 \Delta \longrightarrow \Gamma.A & & \Delta \xrightarrow{\quad} \Gamma.A \\
 \searrow \Rightarrow \downarrow & = & \searrow \xRightarrow{\quad} \downarrow \\
 & & \Gamma
 \end{array}$$

2-dimensional semantics of propositional theories

Display map 2-categories. (2,1)-dimensional categories with a specified class of 1-morphisms, called **display maps**, that satisfy the following conditions:

1. The class of display maps is closed under **2-dimensional re-indexing**.

$$\begin{array}{ccc} \Gamma.A & \Rightarrow & \Delta.A[f] \rightarrow \Gamma.A \\ \downarrow & & \downarrow \quad \lrcorner \quad \downarrow \\ \Delta - f \rightarrow \Gamma & & \Delta - f \rightarrow \Gamma \end{array}$$

2. Every display map is a **cloven isofibration**.

$$\begin{array}{ccc} \Delta \longrightarrow \Gamma.A & & \Delta \xrightarrow{\quad} \Gamma.A \\ \searrow \Rightarrow \downarrow & = & \searrow \xRightarrow{\quad} \downarrow \\ & & \Gamma \end{array}$$

3. Every display map has an **arrow object**.

$$\begin{array}{ccc} \Omega \xrightarrow{\quad} \Gamma.A & \text{s.t.} & \text{hom}_{\Gamma}(\Delta, \Omega) \\ \Downarrow \xrightarrow{\quad} \downarrow & & \parallel \\ & & \text{hom}_{\Gamma}(\Delta, \Gamma.A) \rightarrow \end{array}$$

2-dimensional semantics of propositional theories

Display map 2-categories. (2,1)-dimensional categories with a specified class of 1-morphisms, called **display maps**, that satisfy the following conditions:

1. The class of display maps is closed under **2-dimensional re-indexing**.

$$\begin{array}{ccc} \Gamma.A & \Rightarrow & \Delta.A[f] \rightarrow \Gamma.A \\ \downarrow & & \downarrow \quad \lrcorner \quad \downarrow \\ \Delta - f \rightarrow \Gamma & & \Delta - f \rightarrow \Gamma \end{array}$$

2. Every display map is a **cloven isofibration**.

$$\begin{array}{ccc} \Delta \longrightarrow \Gamma.A & & \Delta \xrightarrow{\quad} \Gamma.A \\ \searrow \Rightarrow \downarrow & = & \searrow \xRightarrow{\quad} \downarrow \\ & & \Gamma \end{array}$$

3. Every display map has an **arrow object**.

$$\begin{array}{ccc} \Omega \xrightarrow{\quad} \Gamma.A & \text{s.t.} & \text{hom}_{\Gamma}(\Delta, \Omega) \\ \Downarrow \xrightarrow{\quad} \downarrow & & \parallel \\ & & \text{hom}_{\Gamma}(\Delta, \Gamma.A) \rightarrow \end{array}$$

4. The class of display maps is closed under composition, up to **homotopy equiv..**

$$\begin{array}{ccc} \Gamma.A.B & \Rightarrow & \Gamma.A.B \simeq \Gamma.C \\ \downarrow & & \downarrow \quad \downarrow \\ \Gamma.A \longrightarrow \Gamma & & \Gamma.A \longrightarrow \Gamma \end{array}$$

2-dimensional semantics of propositional theories

Display map 2-categories. (2,1)-dimensional categories with a specified class of 1-morphisms, called **display maps**, that satisfy the following conditions:

1. To substitute into types and terms.

$$\begin{array}{ccc}
 \Gamma.A & \Rightarrow & \Delta.A[f] \rightarrow \Gamma.A \\
 \downarrow & & \downarrow \quad \lrcorner \quad \downarrow \\
 \Delta - f \rightarrow \Gamma & & \Delta - f \rightarrow \Gamma
 \end{array}$$

2. Every display map is a **cloven isofibration**.

$$\begin{array}{ccc}
 \Delta \longrightarrow \Gamma.A & & \Delta \xrightarrow{\quad} \Gamma.A \\
 \searrow \Rightarrow \downarrow & = & \searrow \xRightarrow{\quad} \downarrow \\
 & & \Gamma
 \end{array}$$

3. Every display map has an **arrow object**.

$$\begin{array}{ccc}
 \Omega \xrightarrow{\quad} \Gamma.A & \text{s.t.} & \text{hom}_{\Gamma}(\Delta, \Omega) \\
 \Downarrow \xrightarrow{\quad} \downarrow & & \parallel \\
 & & \text{hom}_{\Gamma}(\Delta, \Gamma.A) \rightarrow
 \end{array}$$

4. The class of display maps is closed under composition, up to **homotopy equiv.**.

$$\begin{array}{ccc}
 \Gamma.A.B & \Rightarrow & \Gamma.A.B \simeq \Gamma.C \\
 \downarrow & & \downarrow \quad \downarrow \\
 \Gamma.A \longrightarrow \Gamma & & \Gamma.A \longrightarrow \Gamma
 \end{array}$$

2-dimensional semantics of propositional theories

Display map 2-categories. (2,1)-dimensional categories with a specified class of 1-morphisms, called **display maps**, that satisfy the following conditions:

1. To substitute into types and terms.

$$\begin{array}{ccc} \Gamma.A & \Rightarrow & \Delta.A[f] \rightarrow \Gamma.A \\ \downarrow & & \downarrow \quad \lrcorner \quad \downarrow \\ \Delta - f \rightarrow \Gamma & & \Delta - f \rightarrow \Gamma \end{array}$$

2. Every display map is a **cloven isofibration**.

$$\begin{array}{ccc} \Delta \longrightarrow \Gamma.A & & \Delta \xrightarrow{\quad} \Gamma.A \\ \searrow \Rightarrow \downarrow & = & \searrow \xRightarrow{\quad} \downarrow \\ & & \Gamma \end{array}$$

3. To have identity types with *pseudo-elimination*.

$$\begin{array}{ccc} \Omega \xrightarrow{\quad} \Gamma.A & \text{s.t.} & \text{hom}_{\Gamma}(\Delta, \Omega) \\ \Downarrow \Rightarrow \downarrow & & \parallel \\ & & \text{hom}_{\Gamma}(\Delta, \Gamma.A) \rightarrow \end{array} \quad \begin{array}{c} \Gamma.A.A'.(x = x') \\ \parallel \\ \Omega \end{array}$$

4. The class of display maps is closed under composition, up to **homotopy equiv..**

$$\begin{array}{ccc} \Gamma.A.B & \Rightarrow & \Gamma.A.B \simeq \Gamma.C \\ \downarrow & & \downarrow \quad \downarrow \\ \Gamma.A \longrightarrow \Gamma & & \Gamma.A \longrightarrow \Gamma \end{array}$$

2-dimensional semantics of propositional theories

Display map 2-categories. (2,1)-dimensional categories with a specified class of 1-morphisms, called **display maps**, that satisfy the following conditions:

1. To substitute into types and terms.

$$\begin{array}{ccc} \Gamma.A & \Rightarrow & \Delta.A[f] \rightarrow \Gamma.A \\ \downarrow & & \downarrow \quad \lrcorner \quad \downarrow \\ \Delta - f \rightarrow \Gamma & & \Delta \multimap f \rightarrow \Gamma \end{array}$$

2. Every display map is a **cloven isofibration**.

$$\begin{array}{ccc} \Delta \longrightarrow \Gamma.A & & \Delta \xrightarrow{\quad} \Gamma.A \\ \searrow \Rightarrow \downarrow & = & \searrow \xRightarrow{\quad} \downarrow \\ & & \Gamma \end{array}$$

3. To have identity types with *pseudo-elimination*.

$$\begin{array}{ccc} \Omega \xrightarrow{\quad} \Gamma.A & \text{s.t.} & \text{hom}_{\Gamma}(\Delta, \Omega) \\ \Downarrow \Rightarrow \downarrow & & \parallel \\ & & \text{hom}_{\Gamma}(\Delta, \Gamma.A) \rightarrow \Gamma.A.A'.(x = x') \\ & & \parallel \\ & & \Omega \end{array}$$

4. To have dependent sum types with *pseudo-elimination*.

$$\begin{array}{ccc} \Gamma.A.B & \Rightarrow & \Gamma.A.B \simeq \Gamma.C \\ \downarrow & & \downarrow \quad \downarrow \\ \Gamma.A \longrightarrow \Gamma & & \Gamma.A \longrightarrow \Gamma \end{array} \quad \Sigma_A^B \quad \parallel \quad C$$

2-dimensional semantics of propositional theories

Display map 2-categories. (2,1)-dimensional categories with a specified class of 1-morphisms, called **display maps**, that satisfy the following conditions:

1. To substitute into types and terms.

$$\begin{array}{ccc} \Gamma.A & \Rightarrow & \Delta.A[f] \rightarrow \Gamma.A \\ \downarrow & & \downarrow \quad \lrcorner \quad \downarrow \\ \Delta - f \rightarrow \Gamma & & \Delta - f \rightarrow \Gamma \end{array}$$

2. To strictify eliminations in 3-4 in change of producing computation *axioms*.

$$\begin{array}{ccc} \Delta & \longrightarrow & \Gamma.A \\ & \searrow \Rightarrow & \downarrow \\ & & \Gamma \end{array} = \begin{array}{ccc} \Delta & \xrightarrow{\quad} & \Gamma.A \\ & \nearrow \uparrow & \downarrow \\ & \searrow = & \Gamma \end{array}$$

3. To have identity types with *pseudo-elimination*.

$$\begin{array}{ccc} \Omega & \begin{array}{c} \xrightarrow{\quad} \\ \Downarrow \\ \searrow \end{array} & \Gamma.A \\ & \searrow & \downarrow \\ & & \Gamma \end{array} \quad \text{s.t.} \quad \begin{array}{ccc} \text{hom}_{\Gamma}(\Delta, \Omega) & & \Gamma.A.A'.(x = x') \\ \parallel & & \parallel \\ \text{hom}_{\Gamma}(\Delta, \Gamma.A) \rightarrow & & \Omega \end{array}$$

4. To have dependent sum types with *pseudo-elimination*.

$$\begin{array}{ccccc} \Gamma.A.B & \Rightarrow & \Gamma.A.B \simeq \Gamma.C & \Sigma_A^B \\ \downarrow & & \downarrow & \downarrow & \parallel \\ \Gamma.A \longrightarrow \Gamma & & \Gamma.A \longrightarrow \Gamma & & C \end{array}$$

2-dimensional semantics of propositional theories

Main theorem. *Display map 2-categories are models of axiomatic dependent type theory.*

2-dimensional semantics of propositional theories

Main theorem. *Display map 2-categories are models of axiomatic dependent type theory.*

An application:

Theorem. *The judgemental computation rule for intensional identity type constructor is independent of the axiomatic dependent type theory.*

Proof

2-dimensional semantics of propositional theories

Main theorem. *Display map 2-categories are models of axiomatic dependent type theory.*

An application:

Theorem. *The judgemental computation rule for intensional identity type constructor is independent of the axiomatic dependent type theory.*

Proof i.e. a revisit of the groupoid model.

We consider the $(2,1)$ -category \mathbf{GRPD} of groupoids, functors, and natural transformations (i.e. natural isomorphisms) with **Grothendieck constructions of *pseudofunctors*** $\Gamma \rightarrow \mathbf{GRPD}$ as display maps over Γ .

2-dimensional semantics of propositional theories

Main theorem. *Display map 2-categories are models of axiomatic dependent type theory.*

An application:

Theorem. *The judgemental computation rule for intensional identity type constructor is independent of the axiomatic dependent type theory.*

Proof i.e. a revisit of the groupoid model.

We consider the $(2,1)$ -category \mathbf{GRPD} of groupoids, functors, and natural transformations (i.e. natural isomorphisms) with **Grothendieck constructions of *pseudofunctors*** $\Gamma \rightarrow \mathbf{GRPD}$ as display maps over Γ .

The model of axiomatic theory induced by this display map 2-category does not believe the judgemental computation rule, so the statement follows by soundness.

Do we obtain *every* model?

Do we obtain *every* model?

No,

Do we obtain *every* model?

No, because every such display map 2-category believes the following rule:

Discreteness

$$\frac{\vdash A : \mathsf{TYPE}}{x, y : A; \ p, q : x = y; \ \alpha : p = q \vdash p \equiv q}$$

Do we obtain *every* model?

No, because every such display map 2-category believes the following rule:

Discreteness

$$\frac{\vdash A : \mathsf{TYPE}}{x, y : A; \, p, q : x = y; \, \alpha : p = q \vdash p \equiv q}$$

Theorem. *The display map 2-categories are precisely the models (as in the syntactic formulation) of the axiomatic theory **extended with the discreteness rule**.*

Do we obtain *every* model?

No, because every such display map 2-category believes the following rule:

Discreteness

$$\frac{\vdash A : \text{TYPE}}{x, y : A; p, q : x = y; \alpha : p = q \vdash p \equiv q}$$

Theorem. *The display map 2-categories are precisely the models (as in the syntactic formulation) of the axiomatic theory **extended with the discreteness rule**.*

*Therefore, this notion of semantics is **sound** w.r.t. the axiomatic theory of dependent types, and it is **sound and complete** w.r.t. the axiomatic theory of dependent types extended with the discreteness rule.*