

Exercises: Stacks and Queues

Problems for exercises and homework for the ["CSharp Advanced" course @ Software University](#).

You can check your solutions here: <https://judge.softuni.bg/Contests/1447/Stacks-and-Queues-Exercise>

Problem 1. Basic Stack Operations

Play around with a stack. You will be given an integer **N** representing the number of elements to push into the stack, an integer **S** representing the number of elements to pop from the stack and finally an integer **X**, an element that you should look for in the stack. If it's found, print **"true"** on the console. If it isn't, print the **smallest** element currently present in the stack.

Input

- On the first line you will be given **N**, **S** and **X**, separated by a single space
- On the next line you will be given **N** number of integers

Output

- On a single line print either **true** if **X** is present in the stack, otherwise print the **smallest** element in the stack. If the stack is **empty**, print 0

Examples

Input	Output	Comments
5 2 13 1 13 45 32 4	true	We have to push 5 elements. Then we pop 2 of them. Finally, we have to check whether 13 is present in the stack. Since it is we print true .
4 1 666 420 69 13 666	13	

Problem 2. Basic Queue Operations

Play around with a queue. You will be given an integer **N** representing the number of elements to enqueue (**add**), an integer **S** representing the **number of elements to dequeue (remove)** from the queue and finally an integer **X**, an element that you should look for in the **queue**. If it is, print **true** on the console. If it's not print the **smallest element** currently present in the queue. If there are **no elements** in the sequence, print **0** on the console.

Examples

Input	Output	Comments
5 2 32 1 13 45 32 4	true	We have to enqueue 5 elements. Then we dequeue 2 of them. Finally, we have to check whether 13 is present in the queue. Since it is we print true .
4 1 666 666 69 13 420	13	
3 3 90 90 0 90	0	

Problem 3. Maximum and Minimum Element

You have an empty sequence, and you will be given **N** queries. Each query is one of these three types:

- 1 **x** – **Push** the element **x** into the stack.
- 2 – **Delete** the element present at the **top** of the **stack**.
- 3 – **Print** the **maximum** element in the stack.
- 4 – **Print** the **minimum** element in the stack.

After you go through all of the queries, print the stack in the following format:

"{n}, {n₁}, {n₂} ..., {n_n}"

Input

- The first line of input contains an integer, **N**
- The next **N** lines each contain an above-mentioned query. *(It is guaranteed that each query is valid.)*

Output

- For each type 3 or 4 query, print the **maximum**/minimum element in the stack on a new line

Constraints

- $1 \leq N \leq 105$
- $1 \leq x \leq 109$
- $1 \leq \text{type} \leq 4$

Examples

Input	Output
9 1 97 2 1 20 2 1 26 1 20 3 1 91 4	26 20 91, 20, 26
10 2 1 47 1 66 1 32 4 3 1 25 1 16 1 8 4	32 66 8 8, 16, 25, 32, 66, 47

Problem 4. Fast Food

You have a fast food restaurant and most of the food that you're offering is previously prepared. You need to know if you will have enough food to serve lunch to all of your customers. Write a program that checks the orders' quantity. You also want to know the client with the **biggest** order for the day, because you want to give him a discount the next time he comes.

First, you will be given the **quantity of the food** that you have for the day (an integer number). Next, you will be given **a sequence of integers**, each representing the **quantity of an order**. Keep the orders in a **queue**. Find the **biggest order** and **print** it. You will begin servicing your clients from the **first one** that came. Before each order, **check** if you have enough food left to complete it. If you have, **remove the order** from the queue and **reduce** the amount of food you have. If you succeeded in servicing all of your clients, print:

"Orders complete".

If not, print:

"Orders left: {order1} {order2} {orderN}".

Input

- On the first line you will be given the quantity of your food - **an integer** in the range [0, 1000]
- On the second line you will receive a sequence of integers, representing each order, **separated by a single space**

Output

- Print the quantity of biggest order
- Print "Orders complete" if the orders are complete
- If there are orders left, print them in the format given above

Constraints

- The input will always be valid

Examples

Input	Output
348 20 54 30 16 7 9	54 Orders complete
499 57 45 62 70 33 90 88 76	90 Orders left: 76

Problem 5. Fashion Boutique

You own a fashion boutique and you receive a delivery once a month in a huge box, which is full of clothes. You have to arrange them in your store, so you take the box and start **from the last piece** of clothing on the top of the pile **to the first one** at the bottom. Use a **stack** for the purpose. Each piece of clothing has its **value** (an integer). You have to **sum** their values, while you take them out of the box. You will be given an integer representing the **capacity** of a rack. While the sum of the clothes is **less** than the capacity, **keep summing** them. If the sum becomes **equal** to the capacity you have to **take a new rack** for the **next clothes**, if there are **any left** in the box. If it becomes **greater** than the capacity, **don't add** the piece of clothing to the current rack and take a new one. In the end, print **how many racks** you have used to hang all of the clothes.

Input

- On the first line you will be given a **sequence of integers**, representing the clothes in the box, separated by a **single space**
- On the second line, you will be given an **integer**, representing the capacity of a rack

Output

- Print the **number of racks**, needed to hang all of the clothes from the box

Constraints

- The values of the clothes will be integers in the range [0,20]
- There will never be more than 50 clothes in a box
- The capacity will be an integer in the range [0,20]
- None** of the integers from the box will be **greater** than then the **value** of the **capacity**

Examples

Input	Output
5 4 8 6 3 8 7 7 9 16	5
1 7 8 2 5 4 7 8 9 6 3 2 5 4 6 20	5

Problem 6. Auto Repair and Service

Winter is coming. All vehicles must prepare for it by changing their tires and other necessary procedures. It's a very busy time of the year for all of the auto services and they need help with the organization of their work.

Write a program that keeps track of the vehicles. The **first** vehicle that arrives for service, should be the **first** that **gets served**. After a vehicle gets served **it leaves** the auto service, but the workers also **keep** track of the **served vehicles**. If a client calls and asks for his vehicle, you should **look for** it and tell the client if it already has gotten served.

You will be given a **sequence of car models**, separated by a single space. After that you will be given a **few commands** until you receive the command "End". The commands are - "**Service**", "**CarInfo**-{modelName}" and "**History**". If you receive the command "**Service**", you should serve the **first received vehicle** and afterwards **print**:

"Vehicle {vehicleName} got served."

and **delete** it from the awaiting vehicles. If you receive the command "**CarInfo**", **check** if the car is waiting for service. If it is – print:

"Still waiting for service." and if not, print "Served."

If you receive the command "**History**", print the served vehicles starting from **the last served to the first**. After the End command, first print the **waiting** (if there are any left) and then the **served vehicles** in the following format:

"Vehicles for service: {modelName}, {modelName}, ..., {modelName}"

"Served vehicles: {modelName}, {modelName}, ..., {modelName}"

Input

- On the first line, you will be given a sequence of strings
- On the next n lines you will be given commands

Output

- While receiving the commands, print the proper messages described above
- After the command "End", print the waiting vehicles from the **first to the last** and the served vehicles from the **last to the first**

Constraints

- The input **will always be valid** and in the **formats** described above
- The **count** of the commands might be **more** than the **count of the vehicles**
- There will always be **at least one** served vehicle
- The vehicles that you should check for will always **exist** in the **list of vehicles** given to you

Examples

Input	Output
BMW60 SKODAOctavia MERCEDESClk PEUGEOT607 AUDI80 FIATPunto Service Service Service CarInfo-MERCEDESClk CarInfo-AUDI80 History End	Vehicle BMW60 got served. Vehicle SKODAOctavia got served. Vehicle MERCEDESClk got served. Served. Still waiting for service. MERCEDESClk, SKODAOctavia, BMW60 Vehicles for service: PEUGEOT607, AUDI80, FIATPunto Served vehicles: MERCEDESClk, SKODAOctavia, BMW60

Problem 7. Truck Tour

Suppose there is a circle. There are **N** petrol pumps on that circle. Petrol pumps are numbered 0 to (N-1) (both inclusive). You have **two pieces of information** corresponding to each of the petrol pump: (1) the **amount of petrol** that particular petrol pump will give, and (2) the **distance from that petrol pump** to the next petrol pump.

Initially, you have a tank of infinite capacity carrying no petrol. You can start the tour at **any** of the petrol pumps. Calculate the **first point** from where the truck will be able to complete the circle. Consider that the truck will stop at **each of the petrol pumps**. The truck will move one kilometer for each liter of the petrol.

Input

- The first line will contain the value of **N**
- The next **N** lines will contain a pair of integers each, i.e. the amount of petrol that petrol pump will give and the distance between that petrol pump and the next petrol pump

Output

- An integer which will be the smallest index of the petrol pump from which we can start the tour

Constraints

- $1 \leq N \leq 1000001$
- $1 \leq \text{Amount of petrol, Distance} \leq 1000000000$

Examples

Input	Output
3 1 5 10 3 3 4	1

Problem 8. Balanced Parentheses

Given a sequence consisting of parentheses, determine whether the expression is **balanced**. A sequence of parentheses is balanced if every **open parenthesis** can be **paired uniquely** with a **closed parenthesis** that occurs **after** the former. Also, the **interval between** them **must** be **balanced**. You will be given **three** types of parentheses: `()`, `{}`, and `[]`.

`{[()]}` - This is a **balanced** parenthesis.

`{[(())]}` - This is **not** a **balanced** parenthesis.

Input

- Each input consists of a single line, **the sequence of parentheses**.

Output

- For each test case, print on a new line "YES" if the parentheses are balanced. Otherwise, print "NO". Do not print the quotes.

Constraints

- $1 \leq \text{len}_s \leq 1000$, where len_s is the length of the sequence.
- Each character of the sequence **will be one of** `{, }, (,), [,]`.

Examples

Input	Output
<code>{[()]}</code>	YES
<code>{[(())]}</code>	NO
<code>{{[[((()))]]}}</code>	YES

Problem 9. Simple Text Editor

You are given an empty text. Your task is to implement 4 commands related to manipulating the text

- 1 `someString` - **appends** `someString` to the end of the text
- 2 `count` - **erases** the last *count* elements from the text
- 3 `index` - **returns** the element at position *index* from the text
- 4 - **undoes** the last not undone command of type 1 / 2 and returns the text to the state before that operation

Input

- The first line contains *n*, the number of operations.
- Each of the following *n* lines contains the name of the operation followed by the command argument, if any, separated by space in the following format **CommandName Argument**.

Output

- For each operation of type **3** print a single line with the returned character of that operation.

Constraints

- $1 \leq N \leq 105$
- The length of the text will not exceed 1000000
- All input characters are English letters.
- It is guaranteed that the sequence of input operation is possible to perform.

Examples

Input	Output
8	c
1 abc	y
3 3	a
2 3	
1 xy	
3 2	
4	
4	
3 1	

Explanation

- There are 8 operations. Initially, the text is empty.
- In the first operation, we append **abc** to the text.
- Then, we print its 3rd character, which is **c** at this point.
- Next, we erase its last 3 characters, **abc**.
- After that, we append **xy** to the text.
- The text becomes **xy** after these previous two modifications.
- Then, we are asked to return the 2nd character of the text, which is **y**.
- After that, we have to undo the last update to the text, so it becomes empty.
- The next operation asks us to undo the update before that, so the text becomes **abc** again.
- Finally, we are asked to print its 1st character, which is **a** at this point.

Problem 10. *Crossroads

Our favorite super-spy action hero Sam is back from his mission in the previous exam, and he has finally found some time to go on a **holiday**. He is taking his wife somewhere nice and they're going to have a really good time, but first, they have to get there. Even on his holiday trip, Sam is still going to run into some **problems** and the first one is, of course, getting to the airport. Right now, he is stuck in a traffic jam at a **very active crossroads** where a lot of **accidents** happen.

Your job is to keep track of traffic at the crossroads and report whether a **crash happened** or everyone **passed the crossroads safely** and our hero is one step closer to a much desired vacation.

The road Sam is on has a **single lane** where cars queue up until the **light goes green**. When it does, they start passing one by one during the **green light** and the **free window** before the **intersecting road's light goes green**. During **one second** only **one part** of a **car** (a **single character**) passes the crossroads. If a car is still in the crossroads when the **free window** ends, it will get hit at the **first character** that is still in the crossroads.

Input

- On the **first line**, you will receive the duration of the **green light** in seconds – an **integer in the range [1-100]**
- On the **second line**, you will receive the duration of the **free window** in seconds – an **integer in the range [0-100]**
- On the **following lines**, until you receive the **"END"** command, you will receive one of two things:
 - A **car** – a **string** containing any ASCII character, or
 - The command **"green"** which indicates the **start** of a **green light cycle**

A **green light cycle** goes as follows:

- During the **green light** cars will enter and exit the crossroads one by one
- During the **free window** cars will only exit the crossroads

Output

- If a **crash happens**, **end the program** and print:
`"A crash happened!"`
`"{car} was hit at {characterHit}."`
- If everything **goes smoothly** and you receive an **"END"** command, print:
`"Everyone is safe."`
`"{totalCarsPassed} total cars passed the crossroads."`

Constraints

- The input will be **within the constraints** specified above and will **always be valid**. There is **no need** to check it explicitly.

Examples

Input	Output	Comments
10 5 Mercedes green Mercedes BMW Skoda green END	Everyone is safe. 3 total cars passed the crossroads.	During the first green light (10 seconds), the Mercedes (8) passes safely. During the second green light, the Mercedes (8) passes safely and there are 2 seconds left. The BMW enters the crossroads and when the green light ends, it still has 1 part inside ('W'), but has 5 seconds to leave and passes successfully. The Skoda never enters the crossroads, so 3 cars passed successfully.
9 3 Mercedes Hummer green Hummer	A crash happened! Hummer was hit at e.	Mercedes (8) passes successfully and Hummer (6) enters the crossroads but only the 'H' passes during the green light. There are 3 seconds of free window, so

Mercedes green END		"umm" passes and the Hummer gets hit at 'e' and the program ends with a crash .
--------------------------	--	--

Problem 11. *Key Revolver

Our favorite super-spy action hero Sam is back from his mission in another exam, and this time he has an even more difficult task. He needs to **unlock a safe**. The problem is that the safe is **locked by several locks in a row**, which all have **varying sizes**.

Our hero possesses a special weapon though, called the **Key Revolver**, with special bullets. Each **bullet** can unlock a **lock** with a **size equal to or larger than** the **size** of the **bullet**. The bullet goes into the keyhole, then explodes, completely **destroying** it. Sam **doesn't know the size** of the locks, so he needs to just shoot at all of them, until the safe runs out of locks.

What's behind the safe, you ask? Well, intelligence! It is told that Sam's sworn enemy – **Nikoladze**, keeps his **top secret Georgian Chacha Brandy** recipe inside. It's valued differently across different times of the year, so Sam's boss will tell him what it's worth over the radio. One last thing, every bullet Sam fires will also cost him money, **which will be deducted from his pay** from the price of the intelligence.

Good luck, operative.

Input

- On the **first line** of input, you will receive the price of each **bullet** – an **integer in the range [0-100]**
- On the **second line**, you will receive the **size of the gun barrel** – an **integer in the range [1-5000]**
- On the **third line**, you will receive the **bullets** – a **space-separated integer sequence** with **[1-100] integers**
- On the **fourth line**, you will receive the **locks** – a **space-separated integer sequence** with **[1-100] integers**
- On the **fifth line**, you will receive the **value of the intelligence** – an **integer in the range [1-100000]**

After Sam receives all of his information and gear (**input**), he starts to **shoot the locks front-to-back**, while going through the bullets **back-to-front**.

If the **bullet** has a **smaller or equal** size to the **current lock**, print **"Bang!"**, then **remove the lock**. If not, print **"Ping!"**, leaving the lock **intact**. The bullet is removed in **both cases**.

If Sam runs out of bullets in his barrel, print **"Reloading!"** on the console, then continue shooting. If there aren't any bullets left, **don't** print it.

The program ends when Sam **either runs out of bullets**, or the safe **runs out of locks**.

Output

- If Sam **runs out of bullets** before the safe runs out of **locks**, print:
"Couldn't get through. Locks left: {locksLeft}"
- If Sam manages to **open the safe**, print:
"{bulletsLeft} bullets left. Earned \${moneyEarned}"

Make sure to account for the **price of the bullets** when calculating the **money earned**.

Constraints

- The input will be **within the constraints** specified above and will **always be valid**. There is **no need** to check it explicitly.
- There will **never** be a case where Sam breaks the lock and ends up with a **negative balance**.

Examples

Input	Output	Comments
50 2 11 10 5 11 10 20 15 13 16 1500	Ping! Bang! Reloading! Bang! Bang! Reloading! 2 bullets left. Earned \$1300	20 shoots lock 15 (ping) 10 shoots lock 15 (bang) 11 shoots lock 13 (bang) 5 shoots lock 16 (bang) Bullet cost: 4 * 50 = \$200 Earned: 1500 - 200 = \$1300
20 6 14 13 12 11 10 5 13 3 11 10 800	Bang! Ping! Ping! Ping! Ping! Ping! Couldn't get through. Locks left: 3	5 shoots lock 13 (bang) 10 shoots lock 3 (ping) 11 shoots lock 3 (ping) 12 shoots lock 3 (ping) 13 shoots lock 3 (ping) 14 shoots lock 3 (ping)
33 1 12 11 10 10 20 30 100	Bang! Reloading! Bang! Reloading! Bang! 0 bullets left. Earned \$1	10 shoots lock 10 (bang) 11 shoots lock 20 (bang) 12 shoots lock 30 (bang) Bullet cost: 3 * 33 = \$99 Earned: 100 - 99 = \$1

Problem 12. *Cups and Bottles

You will be given a **sequence of integers** – each indicating a **cup's capacity**. After that you will be given **another sequence of integers** – a **bottle with water** in it. Your job is to try to **fill up** all of the cups.

Filling is done by picking **exactly one** bottle at a time. You must start picking from **the last received bottle** and start filling from **the first entered cup**. If the current bottle has **N** water, you **give** the **first entered cup N** water and **reduce** its integer value by **N**.

When a cup's **integer value** reaches **0 or less**, it **gets removed**. It is **possible** that the current cup's value is **greater** than the current bottle's value. **In that case** you **pick bottles until** you reduce the cup's integer value to **0 or less**. If a bottle's value is **greater or equal** to the cup's **current** value, you fill up the cup and **the remaining water becomes wasted**. You should **keep track of the wasted litters of water** and **print it at the end of the program**.

If you **have managed** to **fill up all of the cups**, print the **remaining water bottles**, from the **last entered** – **to the first**, otherwise you must print the **remaining cups**, by **order of entrance** – from the **first entered** – **to the last**.

Input

- On the **first line** of input you will receive the integers, representing the **cups' capacity**, separated by a **single space**.
- On the **second line** of input you will receive the integers, representing the **filled bottles**, separated by a **single space**.

Output

- On the first line of output you must print the remaining bottles, or the remaining cups, depending on the case you are in. Just **keep the orders of printing exactly as specified**.
 - "Bottles: {remainingBottles}" or "Cups: {remainingCups}"
- On the second line print the wasted litters of water in the following format: "Wasted litters of water: {wastedLittersOfWater}".

Constraints

- All of the given numbers will be valid integers in the range [1, 500].
- It is safe to assume that there will be **NO** case in which the water is **exactly as much** as the cups' values, so that at the end there are no cups and no water in the bottles.
- Allowed time/memory: 100ms/16MB.

Examples

Input	Output	Comment
4 2 10 5 3 15 15 11 6	Bottles: 3 Wasted litters of water: 26	We take the first entered cup and the last entered bottle, as it is described in the condition. $6 - 4 = 2$ - we have 2 more so the wasted water becomes 2. $11 - 2 = 9$ - again, it is more, so we add it to the previous amount, which is 2 and it becomes 11. $15 - 10 = 5$ - wasted water becomes 16. $15 - 5 = 10$ - wasted water becomes 26. We've managed to fill up all of the cups, so we print the remaining bottles and the total amount of wasted water.
1 5 28 1 4 3 18 1 9 30 4 5	Cups: 4 Wasted litters of water: 35	
10 20 30 40 50 20 11	Cups: 30 40 50 Wasted litters of water: 1	

