







Software-Defined Networking

Prof. Ai-Chun Pang
Graduate Institute of Networking and Multimedia,
Dept. of Comp. Sci. and Info. Engr.,
National Taiwan University

Email: acpang@csie.ntu.edu.tw

http://www.csie.ntu.edu.tw/~acpang











Agenda

- What is Software-Defined Networking (SDN)?
- How does SDN work?
 - Infrastructure layer
 - Control layer
 - Application layer
- Research Issues
 - Scalability
 - Consistent network update
 - Flow scheduling
 - Security









What is SDN?









Current Status & Motivation (1/2)

Source: Nick Mckeown, Stanford



- Specialized software
- Specialized firmware
- Specialized hardware
- Specialized interface













Vertical-integrated

Horizontal-integrated











Current Status & Motivation (2/2)

- Traditional network is manually configured
 - Operating error may cause network tear down
 - High CAPEX and OPEX
 - Network equipment is vulnerable to software bugs
















What is SDN?

Source: Shmuel (Mooly) Sagiv, Tel Aviv Univ.

- SDN is an emerging network architecture
 - Decoupling of control and data planes

















Goal

- Simplified and efficient network management
 - Programmable networks
 - Flexible and dynamically customizable networks
 - Network Operating System (NOS)
 - Provide global view
 - Ensure consistent network
 - Standard open interface (Northbound/southbound API)
 - Backward compatibility











How does SDN work?












SDN Paradigm

Reference model_[1]












Operation












Infrastructure Layer_[1]

- Network equipment: router, switch, and middlebox
 - Control plane: flow table and secure channel
 - Data plane: packet switching/forwarding












Flow Table in Switch_[2-3]

- SDN commonly uses TCAM to store rules in flow tables
 - Match fields: Match packets based on packet's header
 - Action set: Forward, drop, and modify
 - Statistics: Bytes, packets, duration











SDN Switching Devices_[1]

OpenFlow Switch	Wireless AP	Network Hardware	Vendor	
Representative	OpenWRT	NetFPGA	Pica8	
Processing Speed	Low	Middle	High	
Flexibility	High	Middle	Low	






















Control Layer

- Software-based SDN controller
 - Provide consolidated control functionality by open interface_[1]











OpenFlow Controllers

	Controller	Open Source	Language	Multi-threaded	GUI	Origin
Q	NOX [32]	yes	C++/Python	no	yes	Nicira Networks
Ī	NOX-MT [46]	yes	C++	yes	no	Nicira Networks and Big Switch Networks
	POX [47]	yes	Python	-	yes	Nicira Networks
[Maestro [48]	yes	Java	yes	no	Rice University
[Beacon [49]	yes	Java	yes	yes	Stanford University
	SNAC [50]	no	C++/Python	no	yes	Nicira Networks
[RISE [51]	yes	C and Ruby	non-guaranteed	no	NEC
	Floodlight [52]	yes	Java	-	yes	Big Switch Networks
[McNettle [53]	yes	Nettle/Haskell	no	no	Yale University
	MUL [54]	yes	C	yes	yes	KulCloud
	RYU [55]	yes	Python	-	-	NTT OSRG and VA Linux
	OpenDaylight [56]	yes	Java	yes	yes	Multiple contributors









Application Layer

- Develop SDN applications/policies to manage the network
 - Using high-level API provided by controller
- SDN applications
 - Access control
 - Load balancing
 - Network virtualization
 - Energy efficiency





意学 National Taiwan University

SDN Research Issues













SDN Research Issues

- Controller scalability
- Consistent network update
- Flow scheduling
- Security












Controller Scalability

- Massive flow setups sent to controller
 - High flow arrival rate
 - Fine-grained flow control
 - Limited TCAM capacity

Why?












Solutions for Scalability (1/2)

- Capability enhancement for the centralized controller_[8]
 - Parallelism mechanisms (Multi-threading and multi-core CPU)
 - I/O batching
- Cooperation among multiple distributed controllers_[9-10]
 - Leverage multiple controllers to share the handling of flow setup requests
 - Horizontal/vertical control models












李学 National Taiwan University

Solutions for Scalability (2/2)

- Switch-assisted_[1]
 - Keep flow setups in data plane
 - Redirect flow setup sent to an authority switch













Consistent Network Update (1/2)

- What is network update?
 - Change network state to achieve some goal, e.g.,
 - Goal: VM migration
 - State: Forwarding entries and traffic distribution



- 20% of failures come from careless planned maintenance
 - Forwarding black-hole/forwarding loop
 - Link congestion and policy violation
- Consistent network update
 - Prevent specific problems during network update














Consistent Network Update (2/2)


- Forwarding loop
 - Reason: Asynchronous switch update







Loop State 2



Final State










Solutions for Consistent Network Update

- Goal: Ensure common consistent properties
 - Blackhole/loop free, congestion free, and waypoint enforcement
- A simple solution: Two-phase update_[13]
 - Add new rules into internal switches and ingress switch
 - Stamp packets with new version tag (VLAN or MPSL labeling)














Flow Scheduling

- Traditional routing protocol may cause substantial bandwidth loss due to long-term collisions
 - Example: ECMP_[14]












Solution for Flow Scheduling

- Observation
 - Network congestions are mainly caused by elephant/large flows
- Hedera_[14]: A well-known solution in data center











Security Issues

 SDN enables new opportunities to solve some legacy network security issues, and also faces several new challenges

- Existing issues
 - DDoS attack
 - Network scanning attack
- New SDN issues
 - Link fabrication attack_[15]
 - Policy enforcement attack












Link Fabrication Attack (1/2)

- SDN application requires topology to control the network behavior
- Topology discovery service_[15]










Link Fabrication Attack (2/2)

- However, topology discovery services provided by controllers can be tricked by adversaries
 - Link fabrication attack_[15]












Solution for Link Fabrication Attack

- Each port of switch has a flag to represent whether the port is connecting to a host/switch
- Controller uses the transition graph to update the flag value and detect the attack

 For example: An alert is raised if a port connecting to a host receives an LLDP packet













Reference

- [1] W. Xia, Y. Wen, C. H. Foh, D. Niyato and H. Xie, "A Survey on Software-Defined Networking," in *IEEE* Communications Surveys & Tutorials, vol. 17, no. 1, pp. 27-51, 2015.
- [2] Y. Jarraya, T. Madi, and M. Debbabi, "A Survey and a Layered Taxonomy of Software-Defined Networking, "IEEE Communications Surveys & Tutorials, vol. 16, no. 4, pp.1955-1980, 2014.
- [3] B. A. A. Nunes, M. Mendonca, X. N. Nguyen, K. Obraczka, and T. Turletti, "A Survey of Software-Defined Networking: Past, Present, and Future of Programmable Networks, " IEEE Communications Surveys & Tutorials, vol. 16, no. 3, pp.1617-1634, 2014.
- [4] F. Hu, Q. Hao, and K. Bao, "A Survey on Software-Defined Network and OpenFlow: From Concept to Implementation, "IEEE Communications Surveys & Tutorials, vol. 16, no. 4, pp. 2181-2206, 2014.
- [5] A. Tavakoli, M. Casado, and S. Shenker. Applying nox to the datacenter. HotSDN, pages 1–6, 2009.
- [6] M. Moshref, M. Yu, A. Sharma, and R. Govindan. Scalable rule management for data centers. USENIX Conference, pages 157–170, 2013.
- [7] A. R. Curtis, J. C. Mogul, J. Tourrilhes, P. Yalagandula, P. Sharma, and S. Banerjee. Devoflow: Scaling flow management for high performance networks. ACM SIGCOMM Comput. Commun. Rev., pages 254-265, 2011.
- [8] David Erickson. The beacon openflow controller. ACM SIGCOMM Workshop on HotSDN, pages 13–18, 2013.









Reference

- [9] R. Sherwood, M. Chan, A. Covington, G. Gibb, M. Flajslik, N. Handigol, T. Y. Huang, P. Kazemian, M. Kobayashi, J. Naous, S. Seetharaman, D. Underhill, T. Yabe, K. K. Yap, Y. Yiakoumis, H. Zeng, G. Appenzeller, R. Johari, N. McKeown, and G. Parulkar. Carving research slices out of your production networks with openflow. SIGCOMM Comput. Commun. Rev., 40(1):129–130, 2010.
- [10] T. Koponen, M. Casado, N. Gude, J. Stribling, L. Poutievski, M. Zhu, R. Ramanathan, Y. Iwata, H. Inoue, T. Hama, and S. Shenker. Onix: A distributed control platform for large-scale production networks. USENIX Conference, pages 1-6, 2010.
- [11] M. Yu, J. Rexford, M. J. Freedman, and J. Wang. Scalable flowbased networking with difane. ACM SIGCOMM, pages 351-362, 2010.
- [12] A. Markopoulo, G. Iannaccone, S. Bhattacharyya, C.N. Chuah, Y. Ganjali, and C. Diot, "Characterization of Failures in an Operational IP Backbone Network," IEEE/ACM Transactions on Networking, 2008.
- [13] M. Reitblatt, N. Foster, J. Rexford, C. Schlesinger, D. Walker, "Abstractions for network update," ACMSIGCOMM, 2012.
- [14] M. A. Fares, S. Radhakrishnan, B. Raghavan, N. Huang, and A. Vahdat, "Hedera: dynamic flow scheduling for data center networks," In Proceedings of the 7th USENIX conference on Networked systems design and implementation (NSDI), pp. 1-12, 2010.
- [15] S. Hong, et al. "Poisoning Network Visibility in Software-Defined Networks: New Attacks and Countermeasures." in NDSS, 2015.