

# Discovery of exact equations for integer sequences

Boštjan Gec

mentor: prof. dr. Ljupčo Todorovski

27. september 2023

# Introduction

## Equation discovery for integer sequences with probabilistic grammars

- Equation discovery
- Probabilistic grammars
- Integer sequences

# Experimental Evaluation (*linrec*)

---

**Algorithm 1** For experimental evaluation of SINDy for *linrec* case

---

**Input:** Matrix  $M = [X|\mathbf{y}]$  of observations  $X = [\mathbf{a}_{n-1}|\dots|\mathbf{a}_{n-19}]$  and target  $\mathbf{y} = \mathbf{a}_n$

**Output:** Equation  $a_n = \sum_{i=1}^{19} c_i a_{n-i}$  or Failed

```
1: function SINDy's linrec(M)
2:   for  $p = 1, 2, \dots, 19$  do
3:     Add  $col_p(X)$  to  $M$  (i.e.  $X = [X|M_p]$ )
4:     if SINDy_grid( $M, d_{max} = 1$ ) is not Failed then
5:       return SINDy_grid( $M, d_{max} = 1$ )
6:     end if
7:   end for
8:   return Failed
9: end function
```

---



# Experimental Evaluation (*linrec*)

---

**Algorithm 2** For experimental evaluation of Diofantos for *linrec* case

---

**Input:** Matrix  $M = [X|y]$  of observations  $X = [a_{n-1}|\dots|a_{n-19}]$  and target  $y = a_n$

**Output:** Equation  $a_n = \sum_{i=1}^{19} c_i a_{n-i}$  or Failed

```
1: function Diofantos's linrec(M)
2:   for  $p = 1, 2, \dots, 19$  do
3:     Add  $col_p(X)$  to  $M$  (i.e.  $X = [X|M_p]$ )
4:     if Diofantos( $M, d_{max} = 1$ ) is not Failed then
5:       return Diofantos( $M, d_{max} = 1$ )
6:     end if
7:   end for
8:   return Failed
9: end function
```

---

# Experimental Evaluation (*linrec*)

---

**Algorithm 3** For experimental evaluation of SINDy for *linrec* case

---

**Input:** Matrix  $M = [X|\mathbf{y}]$  of observations  $X = [\mathbf{a}_{n-1}|\dots|\mathbf{a}_{n-19}]$  and target  $\mathbf{y} = \mathbf{a}_n$

**Output:** Equation  $a_n = \sum_{i=1}^{19} c_i a_{n-i}$  or Failed

```
1: function SINDy's linrec(M)
2:   for  $p = 1, 2, \dots, 19$  do
3:     Add  $col_p(X)$  to  $M$  (i.e.  $X = [X|M_p]$ )
4:     if SINDy_grid( $M, d_{max} = 1$ ) is not Failed then
5:       return SINDy_grid( $M, d_{max} = 1$ )
6:     end if
7:   end for
8:   return Failed
9: end function
```

---

# Experimental Evaluation (*core*)

---

**Algorithm 4** For experimental evaluation of Diofantos for *core* case

---

**Input:** Matrix  $M = [X|y]$  of observations  $X = [n|a_{n-1}|\dots|a_{n-10}]$   
and target  $y = a_n$

**Output:** Equation  $a_n = f(n, a_{n-1}, \dots, a_{n-10})$  or Failed

```
1: function Diofantos's core(M)
2:    $M = [y]$ 
3:   for  $p = 1, 2, \dots, 10$  do
4:     Add  $col_p(X)$  to  $M$  (i.e.  $X = [X|M_p]$ )
5:     for  $d_{max} = 1, 2, 3$  do
6:       if Diofantos( $M, d_{max}$ ) is not Failed then
7:         return Diofantos( $M, d_{max}$ )
8:       end if
9:     end for
10:  end for
11:  return Failed
12: end function
```

# Experimental Evaluation (*core*) with SINDy

---

**Algorithm 5** For experimental comparison of SINDy for *core* case

---

**Input:** Matrix  $M = [X|\mathbf{a}_n]$  of observations  $X = [\mathbf{n}|\mathbf{a}_{n-1}|\dots|\mathbf{a}_{n-10}]$

**Output:** Equation  $a_n = f(n, a_{n-1}, \dots, a_{n-10})$  or Failed

```
1: function SINDy's core(M)
2:    $M = [\mathbf{n}|\mathbf{y}]$ 
3:   for  $p = 1, 2, \dots, 10$  do
4:     Remove column  $\mathbf{n}$  and add column  $\mathbf{a}_{n-p}$  to  $M$ 
5:     if SINDy_grid( $M, d_{max}$ ) is not Failed then
6:       return SINDy_grid( $M, d_{max} = 1$ )
7:     end if
8:     Add column of observations corresponding to  $n$  to  $M$ 
9:     if SINDy_grid( $M, d_{max}$ ) is not Failed then
10:      return SINDy_grid( $M, d_{max} = 1$ )
11:    end if
12:  end for
13:  return Failed
```