CAM1 Connector
Sch-QWA60_40 Pin GPIO.SchDoc



Reset SW
Sch-QWA60_Reset_SW.SchDoc



HDMI
Sch-QWA60_HDMI.SchDoc



LAN
Sch-QWA60_LAN.SchDoc



Unuse
Sch-QWA60_Unuse.SchDoc



WiFi BT ON OF
Sch-QWA60_WiFi_BT_ON_OFF.SchDoc



LEDs
Sch-QWA60_LEDs.SchDoc



USB Hub
Sch-QWA60_USB_Hub.SchDoc



USB
Sch-QWA60_USB_Port.SchDoc



Power
Sch-QWA60_Power.SchDoc



Title	***QWA38 -Top Level***		*Q-Wave Systems Co.,Ltd* *65/2 Moo 1 Beung* *Sriracha Chonburi* *Thailand*
Size: A4	Number: 1	Revision:	
Date: 7/22/2021	Time: 8:11:55 PM	Sheet 1 of 9	
File: C:_HW_Product\QWA60-CatsPi-Backflip\Top_Level_QWA60.SchDoc			

Q-WAVE SYSTEMS

CM4D

CAM0



The CM4 supports two camera ports; CAM0 (2 lanes) and CAM1 (4 lanes).

Camera sensors supported by the official Raspberry Pi firmware are; the OmniVision OV5647, Sony IMX219 and Sony
IMX477, no security device is required on Compute Module devices to use these camera sensors.

Raspberry Pi Compute Module 4

CM4E

CAM1



The CM4 supports two camera ports; CAM0 (2 lanes) and CAM1 (4 lanes).

Camera sensors supported by the official Raspberry Pi firmware are; the OmniVision OV5647, Sony IMX219 and Sony
IMX477, no security device is required on Compute Module devices to use these camera sensors.

Raspberry Pi Compute Module 4

CM4F

DSI0,DSI1



The CM4 supports two display ports; DISP0 (2 lanes) and DISP1 (4 lanes). Each lane supports a maximum of data rate per lane of 1Gbit/s.

Raspberry Pi Compute Module 4

CM4I

PCIe2x1



The CM4 has an internal PCIe 2.0 x1 host controller

Raspberry Pi Compute Module 4

CM4J

When SD_VDD_override is high, this signal is used to force 1.8v signalling on the SDIO interface. Typically this is used with eMMC memory

SD Card (Lite Version Only)



The SD_PWR_ON signal is used to enable an external power switch to turn on power to the SDCARD

Raspberry Pi Compute Module 4

Optional NF

CM4O

EEPROM Protect



Leaving floating NB internally pulled up to CM4_3.3V via 100K (VIL <0.8V) but can be grounded to prevent writing to the on board EEPROM which stores the bootcode

Raspberry Pi Compute Module 4

Title	*QWA38-CAM*		*Q-Wave Systems Co.,Ltd* *65/2 Moo 1 Beung* *Sriracha Chonburi* *Thailand*
Size: A4	Number:2	Revision:	
Date: 7/22/2021	Time: 8:11:55 PM	Sheet 2 of 9	
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_Unuse.SchDoc			

Q-WAVE SYSTEMS

Main CPU - Power Design

3.3V 2A

R1 range = 50k-200k
Vout= ((R1/R2)+1)x0.6



Click here : PCB Layout guildline p15 https://th.mouser.com/datasheet/2/277/MPM3820_r1.21-469212.pdf

PWR 5V micro USB Type C



5V FAN



CM4B



CM4C



CM4Q

3.3V +/-2.5% Power Output max 300mA per pin for a total of 600mA. This will be powered down during power off or GLOBAL_EN being set low



1.8V +/-2.5% Power Output max 300mA per pin for a total of 600mA. This will be powered down during power off or GLOBAL_EN being set low

Raspberry Pi Compute Module 4

Title	*QWA38-Power*		*Q-Wave Systems Co.,Ltd*
Size: A4	Number:2	Revision:	*65/2 Moo 1 Beung*
Date: 7/22/2021	Time: 8:11:55 PM	Sheet 2 of 6	*Sriracha Chonburi*
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_Power.SchDoc			*Thailand*

Q-WAVE SYSTEMS















Title	*QWA38-CAM*		*Q-Wave Systems Co.,Ltd*
Size: A4	Number:2	Revision:	*65/2 Moo 1 Beung*
Date: 7/22/2021	Time: 8:11:56 PM	Sheet 2 of 9	*Sriracha Chonburi*
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_40 Pin GPIO.SchDoc			*Thailand*

Q-WAVE SYSTEMS



Title	*QWA38 I2C Cypto Chip*		*Q-Wave Systems Co.,Ltd 65/2 Moo 1 Beung Sriracha Chonburi Thailand*
Size: A4	Number:4	Revision:	
Date: 7/22/2021	Time: 8:11:56 PM	Sheet 4 of 9	
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_WiFi_BT_ON_OFF.SchDoc			

Q-WAVE SYSTEMS



GLOBAL_EN (Input)
Drive low to power off CM4. Internally pulled up with a 100K to +5V

nRPI_BOOT (Input)
During boot if this pin is low booting from eMMC will be stopped and booting will be transferred to rpi boot which is via

nEXTRST (Output)
Driven low during reset
Driven high (CM4_3.3V) once CM4 CPU has started to boot

RUN_PG

Bidirectional pin. Internally pulled up to +3.3V via 10K

>Input
Can be driven low (via a 220R resistor) to Reset the CM4 CPU.

Ouput >
Output a high signals Power Good and CPU running.

Analog IP0,IP1
Analog input of the MAX7704. Typically connected to CC pin of Type C power connector
Raspberry Pi Compute Module 4

Title	***QWA38 I2C Cypto Chip***		*Q-Wave Systems Co.,Ltd* *65/2 Moo 1 Beung* *Sriracha Chonburi* *Thailand*
Size: A4	Number:4	Revision:	
Date: 7/22/2021	Time: 8:11:56 PM	Sheet4 of 9	
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_Reset_SW.SchDoc			

CM4G
CEC is also supported, an internal 27K pullup resistor is included in the CM4.



HDMI0_HOTPLUG
Input HDMI1 Hotplug Internally pulled down with a 100K. 5V tolerant.

HDMI0_SDA,SCL
Bidir HDMI1 SDA Internally pulled up with a 1.8K. 5V tolerant

Raspberry Pi Compute Module 4

CM4H



HDMI1_HOTPLUG
Input HDMI1 Hotplug Internally pulled down with a 100K. 5V tolerant.

HDMI1_SDA,SCL
Bidir HDMI1 SDA Internally pulled up with a 1.8K. 5V tolerant

Raspberry Pi Compute Module 4



Current Limit 200mA



Title	QWA38- HDMI		
Size: A4	Number:9	Revision:*	
Date: 7/22/2021	Time: 8:11:56 PM	Sheet 9 of 9	
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_HDMI.SchDoc			

Q-Wave Systems Co.,Ltd
65/2 Moo 1 Beung
Sriracha Chonburi
Thailand

Q-WAVE SYSTEMS

1Gbps RJ45 Connector



Title	*QWA38 -LAN*	*Q-Wave Systems Co.,Ltd 65/2 Moo 1 Beung Sriracha Chonburi Thailand*
Size: A4	Number:*	Revision:*
Date: 7/22/2021	Time: 8:11:56 PM	Sheet * of *
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_LAN.SchDoc		



Title *			*Q-Wave Systems Co.,Ltd* *65/2 Moo 1 Beung* *Sriracha Chonburi* *Thailand*
Size: A4	Number:*	Revision:*	
Date: 7/22/2021	Time: 8:11:56 PM	Sheet * of *	
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_LEDs.SchDoc			



DIFF90

Title	*QWA38 -LAN*		*Q-Wave Systems Co.,Ltd 65/2 Moo 1 Beung Sriracha Chonburi Thailand*
Size: A4	Number:*	Revision:*	
Date: 7/22/2021	Time: 8:11:56 PM	Sheet * of *	
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_USB_Hub.SchDoc			

Q-WAVE SYSTEMS









Title	*QWA38 USB Hub*		*Q-Wave Systems Co.,Ltd*
Size: A4	Number:*	Revision:*	*65/2 Moo 1 Beung*
Date: 7/22/2021	Time: 8:11:56 PM	Sheet * of *	*Sriracha Chonburi*
File: C:_HW_Product\QWA60-CatsPi-Backflip\Sch-QWA60_USB_Port.SchDoc			*Thailand*

Q-WAVE SYSTEMS