

Ultra Fast High PSRR

Low Noise CMOS Voltage Regulator

CE6205 Series

■ INTRODUCTION

The CE6205 series are a group of positive voltage regulators manufactured by CMOS technologies with high ripple rejection, ultra low noise, low power consumption and low dropout voltage, which can prolong battery life in portable electronics. The CE6205 series work with low-ESR ceramic capacitors, reducing the amount of board space necessary for power applications. The CE6205 series consume less than 0.1 μ A in shutdown mode and have fast turn-on time less than 50 μ S. The series are very suitable for the battery-powered equipments, such as RF applications and other systems requiring a quiet voltage source.


■ APPLICATIONS

- Cellular and Smart Phones
- Laptop, Palmtops and PDA
- Digital Still and Video Cameras

■ FEATURES

- Low Output Noise: 40 μ V_{RMS} (10Hz~100kHz)
- Low Dropout Voltage: 50mV@100mA
- Low Quiescent Current: 50 μ A
- High Ripple Rejection: 80dB@10kHz
- Excellent Line and Load Transient Response
- Operating Voltage Range: 1.8V~6.0V
- Output Voltage Range: 1.05V ~ 5.0V
- High Accuracy: $\pm 2\%$ (Typ.)
- Built-in Current Limiter, Short-Circuit Protection
- TTL- Logic-Controlled Shutdown Input
- Portable Audio Video Equipments
- Radio control systems
- Battery-Powered Equipments

■ BLOCK DIAGRAM




■ ORDER INFORMATION

CE6205①②③④


DESIGNATOR	SYMBOL	DESCRIPTION
①	A	Standard
	B	High Active, pull-down resistor R4 built in, with C _{OUT} discharge resistor
	C	High Active, No pull-down resistor, No C _{OUT} discharge resistor
②③	Integer	Output Voltage e.g. 1.8V=②:1, ③:8
④	M/MA/MC/MY	Package:SOT-23-3
	M/MF/ML	Package:SOT-23-5
	P/PT	Package:SOT-89-3/5
	F	Package:DFN1×1-4

PIN CONFIGURATION

SOT-23-3




SOT-23-5




DFN1×1-4(Top View)



SOT-89-3



SOT-89-5



CE6205AXX (SOT-23-3)

PIN NUMBER				SYMBOL	FUNCTION
M	MA	MC	MY		
1	2	3	3	V _{SS}	Ground
2	1	2	1	V _{OUT}	Output
3	3	1	2	V _{IN}	Power Input Pin

CE6205BXXM/ CE6205AXXMF/ CE6205BXXML (SOT-23-5)

PIN NUMBER			SYMBOL	FUNCTION
M	MF	ML		
1	1	5	V _{IN}	Power Input Pin
2	2	2	V _{SS}	Ground
3	—	1	CE	Chip Enable Pin
4	3/4	3	NC	No Connection
5	5	4	V _{OUT}	Output Pin

CE6205BXXF (DFN1×1-4)

PIN NUMBER	SYMBOL	FUNCTION
F		
1	V _{OUT}	Output Pin
2	V _{SS}	Ground
3	CE	Chip Enable Pin
4	V _{IN}	Power Input Pin
EP	Thermal PAD	Ground


CE6205AXX (SOT-89-3)

PIN NUMBER		SYMBOL	FUNCTION
P	PT		
1	2	V _{SS}	Ground
3	1	V _{OUT}	Output
2	3	V _{IN}	Power Input Pin

CE6205BXXP (SOT-89-5)

PIN NUMBER	SYMBOL	FUNCTION
P		
1	V_{OUT}	Output Pin
2	V_{SS}	Ground
3	NC	No Connection
4	CE	Chip Enable Pin
5	V_{IN}	Power Input Pin

■ TYPICAL APPLICATION

■ ABSOLUTE MAXIMUM RATINGS⁽¹⁾(Unless otherwise specified, $T_A=25^{\circ}\text{C}$)

PARAMETER		SYMBOL	RATINGS	UNITS
Input Voltage ⁽²⁾		V_{IN}	-0.3~ 7	V
Output Voltage ⁽²⁾		V_{OUT}	- 0.3~ $V_{IN}+0.3$	V
Output Current		I_{OUT}	700	mA
Power Dissipation	SOT-23	P_D	250	mW
	DFN1×1-4		400	mW
	SOT-89		600	mW
Operating free air temperature range		T_A	-40~85	$^{\circ}\text{C}$
Operating Junction Temperature Range		T_j	-40~125	$^{\circ}\text{C}$
Storage Temperature		T_{stg}	-40~125	$^{\circ}\text{C}$
Lead Temperature(Soldering, 10 sec)		T_{solder}	260	$^{\circ}\text{C}$
ESD rating ⁽³⁾		Human Body Model - (HBM)	4	kV
		Machine Model- (MM)	200	V

(1) Stresses beyond those listed under absolute maximum ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under recommended operating conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

(2) All voltages are with respect to network ground terminal.

(3) ESD testing is performed according to the respective JEDEC standard. The human body model is a 100 pF capacitor discharged through a 1.5kΩ resistor into each pin. The machine model is a 200pF capacitor discharged directly into each pin.

■ ELECTRICAL CHARACTERISTICS

CE6205 Series

(V_{IN}=V_{OUT}+1V, C_{IN}=C_{OUT}=1μF, T_A=25°C, unless otherwise specified)

PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP. ⁽⁴⁾	MAX.	UNITS
Output Voltage	V _{OUT(E)} ⁽⁵⁾	I _{OUT} =1mA	V _{OUT} ⁽⁶⁾ *0.98	V _{OUT} ⁽⁶⁾	V _{OUT} ⁽⁶⁾ *1.02	V
Supply Current	I _{SS}	I _{OUT} =0		50	100	μA
Standby Current	I _{STBY}	CE = V _{SS}		0.1	1	μA
Output Current	I _{OUT}	—	500			mA
Dropout Voltage	V _{DO} ⁽⁷⁾	I _{OUT} =100mA V _{OUT} ≥3.3V		50		mV
Load Regulation	ΔV _{OUT}	V _{IN} = V _{OUT} +1V, 1mA≤I _{OUT} ≤100mA		1		mV
Line Regulation	$\frac{\Delta V_{OUT}}{V_{OUT} \times \Delta V_{IN}}$	I _{OUT} =10mA V _{OUT} +1V≤V _{IN} ≤6V		0.01	0.2	%/V
Output Voltage Temperature Characteristics	$\frac{\Delta V_{OUT}}{\Delta T \times V_{OUT}}$	I _{OUT} =10mA -40≤T≤+85		30		ppm
Short Current	I _{Short}	V _{OUT} =V _{SS}		50		mA
Input Voltage	V _{IN}	—	1.8		6.0	V
Power Supply Rejection Rate	100Hz	PSRR	I _{OUT} =50mA	75		dB
	1kHz			80		
	10kHz			80		
CE "High" Voltage	V _{CE} "H"		1.5		V _{IN}	V
CE "Low" Voltage	V _{CE} "L"				0.3	V
C _{OUT} Auto-Discharge Resistance	R _{DISCHRG}	V _{IN} =5V, V _{OUT} =3.0V, V _{CE} =V _{SS}		60		Ω

(4) Typical numbers are at 25°C and represent the most likely norm.







(5) V_{OUT(E)} : Effective Output Voltage (i.e. The output voltage when V_{IN} = (V_{OUT} +1.0V) and maintain a certain I_{OUT} Value).(6) V_{OUT} : Specified Output Voltage.(7) V_{DO} : The Difference Of Output Voltage And Input Voltage When Input Voltage Is Decreased Gradually Till Output Voltage Equals To 98% Of V_{OUT} (E).

■ RECOMMENDED OPERATING CONDITIONS


PARAMETER	MIN.	NOM.	MAX.	UNITS
Supply voltage at V _{IN}	1.8		6	V
Operating junction temperature range, T _J	0		125	°C
Operating free air temperature range, T _A	0		85	°C

■ TYPICAL PERFORMANCE CHARACTERISTICS

($V_{CE}=V_{IN}=V_{OUT}+1V$, $C_{IN}=C_{OUT}=1\mu F$, $T_A=25^\circ C$, unless otherwise specified)



■ TYPICAL PERFORMANCE CHARACTERISTICS



C_{OUT} Auto-Discharge Function


CE6205B series can discharge the electric charge in the output capacitor (C_{OUT}), when a low signal to the CE pin, which enables a whole IC circuit turn off, is inputted via the N-channel transistor located between the V_{OUT} pin and the V_{SS} pin (cf. BLOCK DIAGRAM). The C_{OUT} auto-discharge resistance value is set at 60Ω (V_{OUT}=3.0V @ V_{IN}=5.0V at typical). The discharge time of the output capacitor (C_{OUT}) is set by the C_{OUT} auto-discharge resistance (R) and the output capacitor (C_{OUT}). By setting time constant of a C_{OUT} auto-discharge resistance value [R_{DISCHRG}] and an output capacitor value (C_{OUT}) as τ ($\tau = C \times R_{DISCHRG}$), the output voltage after discharge via the N-channel transistor is calculated by the following formulas.

$$V = V_{OUT(E)} \times e^{-t/\tau}, \text{ or } t = \tau \ln (V / V_{OUT(E)})$$

(V : Output voltage after discharge, V_{OUT(E)} : Output voltage, t: Discharge time, τ : C_{OUT} auto-discharge resistance R_{DISCHRG}×Output capacitor (C_{OUT}) value C)


■ PACKAGING INFORMATION

● SOT23-3 PACKAGE OUTLINE DIMENSIONS




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

• SOT23-5 PACKAGE OUTLINE DIMENSIONS




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

• SOT89-3 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF		0.061 REF	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP		0.060 TYP	
e1	3.000 TYP		0.118 TYP	
L	0.900	1.200	0.035	0.047

• SOT89-5 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.360	0.560	0.014	0.022
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.400	1.800	0.055	0.071
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP		0.060 TYP	
e1	2.900	3.100	0.114	0.122
L	0.900	1.100	0.035	0.043

• DFN1*1-4 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		
	Min.	Nom.	Max.
A	0.340	0.370	0.400
A1	0.000	0.020	0.050
A3	0.100REF		
b	0.170	0.220	0.270
D	0.950	1.000	1.050
E	0.950	1.000	1.050
D2	0.430	0.480	0.530
E2	0.430	0.480	0.530
L	0.200	0.250	0.300
e	-	0.650	-
K	0.150	-	-

© Nanjing Chipower Electronics Inc.

Chipower cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Chipower product. No circuit patent license, copyrights or other intellectual property rights are implied. Chipower reserves the right to make changes to their products or specifications without notice. Customers are advised to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete.