

```
In [65]: import numpy as np
from sklearn.datasets import make_classification
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.ensemble import RandomForestClassifier
from xgboost import XGBClassifier
from sklearn.metrics import classification_report
import warnings
warnings.filterwarnings('ignore')
```

```
In [66]: x,y=make_classification(n_samples=1000,n_features=10,n_informative=2,n_redundant
np.unique(y,return_counts=True))
```

```
Out[66]: (array([0, 1]), array([900, 100]))
```

```
In [67]: x_train,x_test,y_train,y_test=train_test_split(X,y,test_size=0.3,stratify=y,rand
```

```
In [68]: print(X_train.shape)
print(y_train.shape)
```

```
(1226, 10)
(700,)
```

```
In [69]: print(x_test.shape)
print(y_test.shape)
```

```
(300, 10)
(300,)
```

Experiment 1: Train Logistic Regression Classifier

```
In [70]: log_reg=LogisticRegression(C=1, solver='liblinear')
log_reg.fit(x_train,y_train)
y_pred_log_reg=log_reg.predict(x_test)
print(classification_report(y_test,y_pred_log_reg))
```

| | precision | recall | f1-score | support |
|--------------|-----------|--------|----------|---------|
| 0 | 0.95 | 0.96 | 0.95 | 270 |
| 1 | 0.60 | 0.50 | 0.55 | 30 |
| accuracy | | | 0.92 | 300 |
| macro avg | 0.77 | 0.73 | 0.75 | 300 |
| weighted avg | 0.91 | 0.92 | 0.91 | 300 |

```
In [71]: rf_clf=RandomForestClassifier(n_estimators=30,max_depth=3)
rf_clf.fit(x_train,y_train)
y_pred_rf=rf_clf.predict(x_test)
print(classification_report(y_test,y_pred_rf))
```

| | precision | recall | f1-score | support |
|--------------|-----------|--------|----------|---------|
| 0 | 0.96 | 1.00 | 0.98 | 270 |
| 1 | 0.95 | 0.67 | 0.78 | 30 |
| accuracy | | | 0.96 | 300 |
| macro avg | 0.96 | 0.83 | 0.88 | 300 |
| weighted avg | 0.96 | 0.96 | 0.96 | 300 |

Experiment 3: Train XGBoost

```
In [72]: xgb_clf=XGBClassifier(use_label_encoder=False, eval_metric='logloss')
xgb_clf.fit(x_train,y_train)
y_pred_xgb=xgb_clf.predict(x_test)
print(classification_report(y_test,y_pred_xgb))
```

| | precision | recall | f1-score | support |
|--------------|-----------|--------|----------|---------|
| 0 | 0.98 | 1.00 | 0.99 | 270 |
| 1 | 0.96 | 0.80 | 0.87 | 30 |
| accuracy | | | 0.98 | 300 |
| macro avg | 0.97 | 0.90 | 0.93 | 300 |
| weighted avg | 0.98 | 0.98 | 0.98 | 300 |

Experiment 4: Handle class imbalance using SMOTETomek and then Train XGBoost

```
In [73]: from imblearn.combine import SMOTETomek

smt=SMOTETomek(random_state=0)
x_train_res,y_train_res=smt.fit_resample(x_train,y_train)

np.unique(y_train_res,return_counts=True)
```

Out[73]: (array([0, 1]), array([613, 613]))

```
In [74]: xgb_clf=XGBClassifier(use_label_encoder=False, eval_metric='logloss')
xgb_clf.fit(x_train_res,y_train_res)
y_pred_xgb=xgb_clf.predict(x_test)
print(classification_report(y_test,y_pred_xgb))
```

| | precision | recall | f1-score | support |
|--------------|-----------|--------|----------|---------|
| 0 | 0.98 | 0.97 | 0.98 | 270 |
| 1 | 0.76 | 0.83 | 0.79 | 30 |
| accuracy | | | 0.96 | 300 |
| macro avg | 0.87 | 0.90 | 0.88 | 300 |
| weighted avg | 0.96 | 0.96 | 0.96 | 300 |

Track Experiments Using MLFlow

```
In [75]: models=[
    (
        "Logistic Regression",
        LogisticRegression(C=1, solver='liblinear'),
        (x_train,y_train),
        (x_test,y_test)
    ),
    (
        "Random Forest",
        RandomForestClassifier(n_estimators=30,max_depth=3),
        (x_train,y_train),
        (x_test,y_test)
    ),
    (
        "XGBClassifier",
        XGBClassifier(use_label_encoder=False,eval_metric='logloss'),
        (x_train,y_train),
        (x_test,y_test)
    ),
    (
        "XGBClassifier With SMOTE",
        XGBClassifier(use_label_encoder=False,eval_metric='logloss'),
        (x_train_res,y_train_res),
        (x_test,y_test)
    )
]
```

```
In [76]: reports=[]

for model_name, model,train_set,test_set in models:
    x_train=train_set[0]
    y_train=train_set[1]
    x_test=test_set[0]
    y_test=test_set[1]

    model.fit(x_train,y_train)
    y_pred=model.predict(x_test)
    report=classification_report(y_test,y_pred,output_dict=True)
    reports.append(report)
```

```

-----
XGBoostError                                Traceback (most recent call last)
Cell In[76], line 9
      6 x_test=test_set[0]
      7 y_test=test_set[1]
----> 9 model.fit(x_train,y_train)
      10 y_pred=model.predict(x_test)
      11 report=classification_report(y_test,y_pred,output_dict=True)

File D:\New folder\Lib\site-packages\xgboost\core.py:729, in require_keyword_arg
s.<locals>.throw_if.<locals>.inner_f(*args, **kwargs)
      727 for k, arg in zip(sig.parameters, args):
      728     kwargs[k] = arg
--> 729 return func(**kwargs)

File D:\New folder\Lib\site-packages\xgboost\sklearn.py:1664, in XGBClassifier.fi
t(self, X, y, sample_weight, base_margin, eval_set, verbose, xgb_model, sample_w
eight_eval_set, base_margin_eval_set, feature_weights)
      1659     params["num_class"] = self.n_classes_
      1661 model, metric, params, feature_weights = self._configure_fit(
      1662     xgb_model, params, feature_weights
      1663 )
-> 1664 train_dmatrix, evals = _wrap_evaluation_matrices(
      1665     missing=self.missing,
      1666     X=X,
      1667     y=y,
      1668     group=None,
      1669     qid=None,
      1670     sample_weight=sample_weight,
      1671     base_margin=base_margin,
      1672     feature_weights=feature_weights,
      1673     eval_set=eval_set,
      1674     sample_weight_eval_set=sample_weight_eval_set,
      1675     base_margin_eval_set=base_margin_eval_set,
      1676     eval_group=None,
      1677     eval_qid=None,
      1678     create_dmatrix=self._create_dmatrix,
      1679     enable_categorical=self.enable_categorical,
      1680     feature_types=self.feature_types,
      1681 )
      1683 self._Booster = train(
      1684     params,
      1685     train_dmatrix,
      (...)
      1694     callbacks=self.callbacks,
      1695 )
      1697 if not callable(self.objective):

File D:\New folder\Lib\site-packages\xgboost\sklearn.py:628, in _wrap_evaluation_
matrices(missing, X, y, group, qid, sample_weight, base_margin, feature_weights,
eval_set, sample_weight_eval_set, base_margin_eval_set, eval_group, eval_qid, cre
ate_dmatrix, enable_categorical, feature_types)
      607 def _wrap_evaluation_matrices(
      608     *,
      609     missing: float,
      (...)
      624     feature_types: Optional[FeatureTypes],
      625 ) -> Tuple[Any, List[Tuple[Any, str]]]:
      626     """Convert array_like evaluation matrices into DMatrix. Perform vali
      dation on the

```

```

627         way."""
--> 628     train_dmatrix = create_dmatrix(
629         data=X,
630         label=y,
631         group=group,
632         qid=qid,
633         weight=sample_weight,
634         base_margin=base_margin,
635         feature_weights=feature_weights,
636         missing=missing,
637         enable_categorical=enable_categorical,
638         feature_types=feature_types,
639         ref=None,
640     )
642     n_validation = 0 if eval_set is None else len(eval_set)
644     def validate_or_none(meta: Optional[Sequence], name: str) -> Sequence:
e:

File D:\New folder\Lib\site-packages\xgboost\sklearn.py:1137, in XGBModel._create_dmatrix(self, ref, **kwargs)
    1135 if _can_use_qdm(self.tree_method, self.device) and self.booster != "gbliner":
    1136     try:
-> 1137         return QuantileDMatrix(
    1138             **kwargs, ref=ref, nthread=self.n_jobs, max_bin=self.max_bin
    1139         )
    1140     except TypeError: # `QuantileDMatrix` supports lesser types than DMatrix
    1141         pass

File D:\New folder\Lib\site-packages\xgboost\core.py:729, in require_keyword_args.<locals>.throw_if.<locals>.inner_f(*args, **kwargs)
    727 for k, arg in zip(sig.parameters, args):
    728     kwargs[k] = arg
--> 729 return func(**kwargs)

File D:\New folder\Lib\site-packages\xgboost\core.py:1614, in QuantileDMatrix.__init__(self, data, label, weight, base_margin, missing, silent, feature_names, feature_types, nthread, max_bin, ref, group, qid, label_lower_bound, label_upper_bound, feature_weights, enable_categorical, max_quantile_batches, data_split_mode)
    1594 if any(
    1595     info is not None
    1596     for info in (
    1597         (...)
    1607     )
    1608 ):
    1609     raise ValueError(
    1610         "If data iterator is used as input, data like label should be
    1611         "specified as batch argument."
    1612     )
-> 1614 self._init(
    1615     data,
    1616     ref=ref,
    1617     label=label,
    1618     weight=weight,
    1619     base_margin=base_margin,
    1620     group=group,
    1621     qid=qid,
    1622     label_lower_bound=label_lower_bound,

```

```

1623     label_upper_bound=label_upper_bound,
1624     feature_weights=feature_weights,
1625     feature_names=feature_names,
1626     feature_types=feature_types,
1627     enable_categorical=enable_categorical,
1628     max_quantile_blocks=max_quantile_batches,
1629 )

```

File D:\New folder\Lib\site-packages\xgboost\core.py:1678, in QuantileDMatrix._in
it(self, data, ref, enable_categorical, max_quantile_blocks, **meta)

```

1663 config = make_jcargs(
1664     nthread=self.nthread,
1665     missing=self.missing,
1666     max_bin=self.max_bin,
1667     max_quantile_blocks=max_quantile_blocks,
1668 )
1669 ret = _LIB.XGQuantileDMatrixCreateFromCallback(
1670     None,
1671     it.proxy.handle,
1672     (...)
1673     ctypes.byref(handle),
1674 )
-> 1678 it.reraise()
1679 # delay check_call to throw intermediate exception first
1680 _check_call(ret)

```

File D:\New folder\Lib\site-packages\xgboost\core.py:572, in DataIter.reraise(self)

```

570 exc = self._exception
571 self._exception = None
--> 572 raise exc

```

File D:\New folder\Lib\site-packages\xgboost\core.py:553, in DataIter._handle_exception(self, fn, dft_ret)

```

550     return dft_ret
552 try:
--> 553     return fn()
554 except Exception as e: # pylint: disable=broad-except
555     # Defer the exception in order to return 0 and stop the iteration.
556     # Exception inside a ctype callback function has no effect except
557     # for printing to stderr (doesn't stop the execution).
558     tb = sys.exc_info()[2]

```

File D:\New folder\Lib\site-packages\xgboost\core.py:640, in DataIter._next_wrapper.<locals>.<lambda>()

```

638     self._temporary_data = None
639 # pylint: disable=not-callable
--> 640 return self._handle_exception(lambda: int(self.next(input_data)), 0)

```

File D:\New folder\Lib\site-packages\xgboost\data.py:1654, in SingleBatchInternalIter.next(self, input_data)

```

1652     return False
1653 self.it += 1
-> 1654 input_data(**self.kwargs)
1655 return True

```

File D:\New folder\Lib\site-packages\xgboost\core.py:729, in require_keyword_args.<locals>.<throw_if>.<locals>.<inner_f>(*args, **kwargs)

```

727 for k, arg in zip(sig.parameters, args):
728     kwargs[k] = arg

```

```
--> 729 return func(**kwargs)
```

File D:\New folder\Lib\site-packages\xgboost\core.py:629, in DataIter._next_wrapper.<locals>.input_data(data, feature_names, feature_types, **kwargs)

```
627 self._temporary_data = (new, cat_codes, feature_names, feature_types)
628 dispatch_proxy_set_data(self.proxy, new, cat_codes)
--> 629 self.proxy.set_info(
630     feature_names=feature_names,
631     feature_types=feature_types,
632     **kwargs,
633 )
634 self._data_ref = ref
```

File D:\New folder\Lib\site-packages\xgboost\core.py:729, in require_keyword_arg_s.<locals>.throw_if.<locals>.inner_f(*args, **kwargs)

```
727 for k, arg in zip(sig.parameters, args):
728     kwargs[k] = arg
--> 729 return func(**kwargs)
```

File D:\New folder\Lib\site-packages\xgboost\core.py:961, in DMatrix.set_info(self, label, weight, base_margin, group, qid, label_lower_bound, label_upper_bound, feature_names, feature_types, feature_weights)

```
958 from .data import dispatch_meta_backend
960 if label is not None:
--> 961     self.set_label(label)
962 if weight is not None:
963     self.set_weight(weight)
```

File D:\New folder\Lib\site-packages\xgboost\core.py:1099, in DMatrix.set_label(self, label)

```
1090 """Set label of dmatrix
1091
1092 Parameters
1093 (...)
1094     The label information to be set into DMatrix
1095 """
1096
1097 from .data import dispatch_meta_backend
-> 1099 dispatch_meta_backend(self, label, "label", "float")
```

File D:\New folder\Lib\site-packages\xgboost\data.py:1586, in dispatch_meta_backend(matrix, data, name, dtype)

```
1584 return
1585 if _is_np_array_like(data):
-> 1586     _meta_from_numpy(data, name, dtype, handle)
1587 return
1588 if _is_arrow(data):
```

File D:\New folder\Lib\site-packages\xgboost\data.py:1533, in _meta_from_numpy(data, field, dtype, handle)

```
1531 raise ValueError("Masked array is not supported.")
1532 interface_str = array_interface(data)
-> 1533 check_call(_LIB.XGDMatrixSetInfoFromInterface(handle, c_str(field), interface_str))
```

File D:\New folder\Lib\site-packages\xgboost\core.py:310, in _check_call(ret)

```
299 """Check the return value of C API call
300
301 This function will raise exception when error occurs.
302 (...)
303     return value from API calls
```

```

308 """
309 if ret != 0:
--> 310     raise XGBoostError(py_str(_LIB.XGBGetLastError()))

```

XGBoostError: [12:38:35] C:\actions-runner_work\xgboost\xgboost\src\data\data.c c:542: Check failed: this->labels.Size() % this->num_row_ == 0 (700 vs. 0) : Incorrect size for labels: (700,1) v.s. 1226

In [77]: `import mlflow`

```

In [80]: mlflow.set_experiment("imbalanced_classification")
mlflow.set_tracking_uri("http://localhost:5000")

for i, element in enumerate(models):
    model_name=element[0]
    model=element[1]
    report=reports[i]

    with mlflow.start_run(run_name=model_name):
        mlflow.log_param("model",model_name)
        mlflow.log_metric('accuracy',report['accuracy'])
        mlflow.log_metric('recall_class_1',report['1']['recall'])
        mlflow.log_metric('recall_class_0',report['0']['recall'])
        mlflow.log_metric('f1_score_macro',report['macro avg']['f1-score'])


        if "XGB" in model_name:
            mlflow.xgboost.log_model(model,"model")
        else:
            mlflow.sklearn.log_model(model,"model")

```

2025/09/28 12:51:05 WARNING mlflow.models.model: `artifact_path` is deprecated. Please use `name` instead.


2025/09/28 12:51:49 WARNING mlflow.models.model: Model logged without a signature and input example. Please set `input_example` parameter when logging the model to auto infer the model signature.


 View run Logistic Regression at: <http://localhost:5000/#/experiments/148083648889951264/runs/5c8b51c16b854ee68e60ccc7847c1487>

 View experiment at: <http://localhost:5000/#/experiments/148083648889951264>

2025/09/28 12:51:50 WARNING mlflow.models.model: `artifact_path` is deprecated. Please use `name` instead.


2025/09/28 12:51:59 WARNING mlflow.models.model: Model logged without a signature and input example. Please set `input_example` parameter when logging the model to auto infer the model signature.


 View run Random Forest at: <http://localhost:5000/#/experiments/148083648889951264/runs/4c1eb18618a1473f990140e0f8a143e9>

 View experiment at: <http://localhost:5000/#/experiments/148083648889951264>

2025/09/28 12:52:00 WARNING mlflow.models.model: `artifact_path` is deprecated. Please use `name` instead.

2025/09/28 12:52:09 WARNING mlflow.models.model: Model logged without a signature and input example. Please set `input_example` parameter when logging the model to auto infer the model signature.

 View run XGBClassifier at: <http://localhost:5000/#/experiments/148083648889951264/runs/ce37a9789c7c4525b3df180a2e8c512e>

 View experiment at: <http://localhost:5000/#/experiments/148083648889951264>


```
-----  
IndexError                                Traceback (most recent call last)  
Cell In[80], line 7  
      5 model_name=element[0]  
      6 model=element[1]  
----> 7 report=reports[i]  
      9 with mlflow.start_run(run_name=model_name):  
     10     mlflow.log_param("model",model_name)  
  
IndexError: list index out of range
```

In []: