

# GATE NM-54 2022

EE23BTECH11011- Batchu Ishitha\*

Q: A system with two degrees of freedom, as shown in the figure, has masses  $m_1 = 200\text{kg}$  and  $m_2 = 100\text{kg}$  and stiffness coefficients  $k_1 = k_2 = 200\text{N/m}$ . Then the lowest natural frequency of the system is \_\_\_\_\_ rad/s (rounded off to one decimal place).




Fig. 0.

GATE NM 2022

**Solution:**




Fig. 0.

Variable	Description	Value
$m_1$	Mass of block 1	$200\text{kg}$
$m_2$	Mass of block 2	$100\text{kg}$
$k_1$	Stiffness coefficient of spring1	$200\text{N/m}$
$k_2$	Stiffness coefficient of spring2	$200\text{N/m}$
$x_i(t)$	Displacement of $i^{\text{th}}$ block	$x_i(0) = 0$
$\dot{x}_i(t)$	Velocity of $i^{\text{th}}$ block	$\dot{x}_i(0) = 0$
$\ddot{x}_i(t)$	Acceleration of $i^{\text{th}}$ block	$\ddot{x}_i(0) = 0$

TABLE 0  
INPUT PARAMETERS

Applying Laplace transform for (1) and (2)

$$m_2 s^2 X_2(s) + k_2 (X_2(s) - X_1(s)) = 0 \quad (3)$$

$$m_1 s^2 X_1(s) - k_2 (X_2(s) - X_1(s)) + k_1 X_1(s) = 0 \quad (4)$$

Equating Transfer function from (3) and (4)

$$\frac{m_2 s^2 + k_2}{k_2} = \frac{k_2}{m_1 s^2 + k_1 + k_2} \quad (5)$$

$$\frac{100s^2 + 200}{200} = \frac{200}{200s^2 + 200 + 200} \quad (6)$$

$$\Rightarrow (s^2 + 2)^2 = 2 \quad (7)$$

Substituting  $s$  as  $j\omega$  in (7)

$$(2 - \omega^2)^2 = 2 \quad (8)$$

$$\omega = \sqrt{2 - \sqrt{2}} \quad (9)$$

$$\Rightarrow \omega = 0.766\text{rad/sec} \quad (10)$$

$$m_2 \ddot{x}_2(t) + k_2 (x_2(t) - x_1(t)) = 0 \quad (1)$$

$$m_1 \ddot{x}_1(t) - k_2 (x_2(t) - x_1(t)) + k_1 x_1(t) = 0 \quad (2)$$