## 1

## **GATE CH-23 44**

## EE23BTECH11011- Batchu Ishitha\*

Q: A cascade control strategy is shown in the figure below. The transfer function between the output (y) and the secondary disturbance  $(d_2)$  is defined as

$$G_{d2}(s) = \frac{y(s)}{d_2(s)}$$

Which one of the following is the CORRECT expression for the transfer function  $G_{d2}(s)$ ?




Fig. 0.

A. 
$$\frac{1}{(11s+21)(0.1s+1)}$$

B. 
$$\frac{1}{(s+1)(0.1s+1)}$$

C. 
$$\frac{(s+1)}{(s+2)(0.1s+1)}$$

D. 
$$\frac{(s+1)}{(s+1)(0.1s+1)}$$

## Solution:

Variable	Description	Value
y(s)	output	none
$d_2(s)$	Secondary disturbance	none
$G_{d2}(s)$	Transfer function between $y(s)$ and $d_2(s)$	$\frac{y(s)}{d_2(s)}$

TABLE 4
INPUT PARAMETERS

$$\left[ \left( y_{sp} - y \right) (1) - a \right] 10 + d_2(s) \frac{1}{0.1s + 1} = a \tag{1}$$

$$a\left(\frac{1}{s+1}\right) + d_1(s)\frac{1}{(2s+1)} = y \tag{2}$$

From (1)

$$(y_{sp} - y) 10 - 10a + d_2(s) \frac{1}{0.1s + 1} = a$$
(3)

$$(y_{sp} - y)10 + \frac{d_2(s)}{0.1s + 1} = 11a \tag{4}$$

$$\left(y_{sp} - y\right) \frac{10}{11} + \frac{d_2(s)}{11(0.1s + 1)} = a \tag{5}$$

Substituting (5) in (2)

$$\left[ \left( y_{sp} - y \right) \frac{10}{11} + \frac{d_2(s)}{11 \left( 0.1s + 1 \right)} \right] \frac{1}{(s+1)} + d_1(s) \frac{1}{(2s+1)} = y \tag{6}$$

$$\left(y_{sp} - y\right) \frac{10}{11} \frac{1}{(s+1)} + \frac{d_2(s)}{11(0.1s+1)(s+1)} + d_1(s) \frac{1}{(2s+1)} = y \tag{7}$$

$$(0-y)\frac{10}{11}\frac{1}{(s+1)} + \frac{d_2(s)}{11(0.1s+1)(s+1)} = y$$
(8)

$$\frac{d_2(s)}{11(0.1s+1)(s+1)} = y + \frac{10}{11}y \frac{1}{s+1}$$
(9)

$$\frac{d_2(s)}{11(0.1s+1)(s+1)} = y(s)\left(1 + \frac{10}{11}\frac{1}{(s+1)}\right) \tag{10}$$

$$\frac{d_2(s)}{11(0.1s+1)(s+1)} = y(s) \left(\frac{11(s+1)+10}{11(s+1)}\right) \tag{11}$$

$$\frac{d_2s}{(0.1s+1)} = y(s) [11s+11+10] \tag{12}$$

$$\frac{d_2s}{(0.1s+1)} = y(s) [11s+21] \tag{13}$$

$$\frac{y(s)}{d_2s} = \frac{1}{(0.1s+1)(11s+21)} \tag{14}$$

$$\implies G_{d2}(s) = \frac{1}{(0.1s+1)(11s+21)} \tag{15}$$