

Review Questions

The answers to the chapter review questions can be found in the Appendix.

1. What is output by the following code? (Choose all that apply.)

```
1: public class Fish {  
2:     public static void main(String[] args) {  
3:         int numFish = 4;  
4:         String fishType = "tuna";  
5:         String anotherFish = numFish + 1;  
6:         System.out.println(anotherFish + " " + fishType);  
7:         System.out.println(numFish + " " + 1);  
8:     } }
```

- A. 4 1
- B. 5
- C. 5 tuna
- D. 5tuna
- E. 51tuna

F. The code does not compile.

2. Which of these array declarations are not legal? (Choose all that apply.)

- A. `int[][] scores = new int[5][];`
- B. `Object[][][] cubbies = new Object[3][0][5];`
- C. `String beans[] = new beans[6];`
- D. `java.util.Date[] dates[] = new java.util.Date[2][];`
- E. `int[][] types = new int[];`
- F. `int[][] java = new int[][];`

3. Note that March 13, 2022 is the weekend when we spring forward, and November 6, 2022 is when we fall back for daylight saving time. Which of the following can fill in the blank without the code throwing an exception? (Choose all that apply.)

```
var zone = ZoneId.of("US/Eastern");  
var date = _____;  
var time = LocalTime.of(2, 15);  
var z = ZonedDateTime.of(date, time, zone);
```

- A. `LocalDate.of(2022, 3, 13)`
- B. `LocalDate.of(2022, 3, 40)`
- C. `LocalDate.of(2022, 11, 6)`

D. `LocalDate.of(2022, 11, 7)`

E. `LocalDate.of(2023, 2, 29)`

F. `LocalDate.of(2022, MonthEnum.MARCH, 13);`

4. Which of the following are output by this code? (Choose all that apply.)

```
3: var s = "Hello";
4: var t = new String(s);
5: if ("Hello".equals(s)) System.out.println("one");
6: if (t == s) System.out.println("two");
7: if (t.intern() == s) System.out.println("three");
8: if ("Hello" == s) System.out.println("four");
9: if ("Hello".intern() == t) System.out.println("five");
```

A. one

B. two

C. three

D. four

E. five

F. The code does not compile.

G. None of the above

5. What is the result of the following code?

```
7: var sb = new StringBuilder();
8: sb.append("aaa").insert(1, "bb").insert(4, "ccc");
9: System.out.println(sb);
```

A. abbaaccc

B. abbaccca

C. bbaaaccc

D. bbaaccca

E. An empty line

F. The code does not compile.

6. How many of these lines contain a compiler error? (Choose all that apply.)

```
23: double one = Math.pow(1, 2);
24: int two = Math.round(1.0);
25: float three = Math.random();
26: var doubles = new double[] {one, two, three};
```

A. 0

B. 1

C. 2

D. 3

E. 4

7. Which of these statements is true of the two values? (Choose all that apply.)

2022-08-28T05:00 GMT-04:00

2022-08-28T09:00 GMT-06:00

A. The first date/time is earlier.

B. The second date/time is earlier.

C. Both date/times are the same.

D. The date/times are two hours apart.

E. The date/times are six hours apart.

F. The date/times are 10 hours apart.

8. Which of the following return 5 when run independently? (Choose all that apply.)

```
var string = "12345";
```

```
var builder = new StringBuilder("12345");
```

A. builder.charAt(4)

B. builder.replace(2, 4, "6").charAt(3)

C. builder.replace(2, 5, "6").charAt(2)

D. string.charAt(5)

E. string.length

F. string.replace("123", "1").charAt(2)

G. None of the above

9. Which of the following are true about arrays? (Choose all that apply.)

A. The first element is index 0.

B. The first element is index 1.

C. Arrays are fixed size.

D. Arrays are immutable.

E. Calling equals() on two different arrays containing the same primitive values always returns true.

F. Calling equals() on two different arrays containing the same primitive values always returns false.

G. Calling equals() on two different arrays containing the same primitive values can return true or false.

10. How many of these lines contain a compiler error? (Choose all that apply.)

```
23: int one = Math.min(5, 3);  
24: long two = Math.round(5.5);  
25: double three = Math.floor(6.6);  
26: var doubles = new double[] {one, two, three};
```

- A.** 0
- B.** 1
- C.** 2
- D.** 3
- E.** 4

11. What is the output of the following code?

```
var date = LocalDate.of(2022, 4, 3);  
date.plusDays(2);  
date.plusHours(3);  
System.out.println(date.getYear() + " " + date.getMonth()  
    + " " + date.getDayOfMonth());
```

- A.** 2022 MARCH 4
- B.** 2022 MARCH 6
- C.** 2022 APRIL 3
- D.** 2022 APRIL 5
- E.** The code does not compile.
- F.** A runtime exception is thrown.

12. What is output by the following code? (Choose all that apply.)

```
var numbers = "012345678".indent(1);  
numbers = numbers.stripLeading();  
System.out.println(numbers.substring(1, 3));  
System.out.println(numbers.substring(7, 7));  
System.out.print(numbers.substring(7));
```

- A.** 12
- B.** 123
- C.** 7
- D.** 78
- E.** A blank line
- F.** The code does not compile.
- G.** An exception is thrown.

13. What is the result of the following code?

```
public class Lion {  
    public void roar(String roar1, StringBuilder roar2) {  
        roar1.concat("!!!");  
        roar2.append("!!!");  
    }  
    public static void main(String[] args) {  
        var roar1 = "roar";  
        var roar2 = new StringBuilder("roar");  
        new Lion().roar(roar1, roar2);  
        System.out.println(roar1 + " " + roar2);  
    } }  
}
```

- A. roar roar
- B. roar roar!!!
- C. roar!!! roar
- D. roar!!! roar!!!
- E. An exception is thrown.
- F. The code does not compile.

14. Given the following, which can correctly fill in the blank? (Choose all that apply.)

```
var date = LocalDate.now();  
var time = LocalTime.now();  
var dateTime = LocalDateTime.now();  
var zoneId = ZoneId.systemDefault();  
var zonedDateTime = ZonedDateTime.of(dateTime, zoneId);  
Instant instant = _____;
```

- A. Instant.now()
- B. new Instant()
- C. date.toInstant()
- D. dateTime.toInstant()
- E. time.toInstant()
- F. zonedDateTime.toInstant()

15. What is the output of the following? (Choose all that apply.)

```
var arr = new String[] { "PIG", "pig", "123"};  
Arrays.sort(arr);  
System.out.println(Arrays.toString(arr));  
System.out.println(Arrays.binarySearch(arr, "Pippa"));
```

- A. [pig, PIG, 123]
- B. [PIG, pig, 123]
- C. [123, PIG, pig]
- D. [123, pig, PIG]
- E. -3
- F. -2
- G. The results of `binarySearch()` are undefined in this example.

16. What is included in the output of the following code? (Choose all that apply.)

```
var base = "ewe\nsheep\\t";  
int length = base.length();  
int indent = base.indent(2).length();  
int translate = base.translateEscapes().length();  
  
var formatted = "%s %s %s".formatted(length, indent, translate);  
System.out.format(formatted);
```

- A. 10
- B. 11
- C. 12
- D. 13
- E. 14
- F. 15
- G. 16

17. Which of these statements are true? (Choose all that apply.)

```
var letters = new StringBuilder("ABCDEFGH");
```

- A. `letters.substring(1, 2)` returns a single-character `String`.
- B. `letters.substring(2, 2)` returns a single-character `String`.
- C. `letters.substring(6, 5)` returns a single-character `String`.
- D. `letters.substring(6, 6)` returns a single-character `String`.
- E. `letters.substring(1, 2)` throws an exception.
- F. `letters.substring(2, 2)` throws an exception.
- G. `letters.substring(6, 5)` throws an exception.
- H. `letters.substring(6, 6)` throws an exception.

18. What is the result of the following code? (Choose all that apply.)

```
13: String s1 = ""  
14:   purr"";
```

```
15: String s2 = "";
16:
17: s1.toUpperCase();
18: s1.trim();
19: s1.substring(1, 3);
20: s1 += "two";
21:
22: s2 += 2;
23: s2 += 'c';
24: s2 += false;
25:
26: if ( s2 == "2cfalse") System.out.println("==");
27: if ( s2.equals("2cfalse")) System.out.println("equals");
28: System.out.println(s1.length());
```

- A. 2
- B. 4
- C. 7
- D. 10
- E. ==
- F. equals
- G. An exception is thrown.
- H. The code does not compile.

19. Which of the following fill in the blank to print a positive integer? (Choose all that apply.)

```
String[] s1 = { "Camel", "Peacock", "Llama"};
String[] s2 = { "Camel", "Llama", "Peacock"};
String[] s3 = { "Camel"};
String[] s4 = { "Camel", null};
System.out.println(Arrays._____);
```

- A. compare(s1, s2)
- B. mismatch(s1, s2)
- C. compare(s3, s4)
- D. mismatch (s3, s4)
- E. compare(s4, s4)
- F. mismatch (s4, s4)

- 20.** Note that March 13, 2022 is the weekend that clocks spring ahead for daylight saving time. What is the output of the following? (Choose all that apply.)

```
var date = LocalDate.of(2022, Month.MARCH, 13);
var time = LocalTime.of(1, 30);
var zone = ZoneId.of("US/Eastern");
var dateTime1 = ZonedDateTime.of(date, time, zone);
var dateTime2 = dateTime1.plus(1, ChronoUnit.HOURS);

long diff = ChronoUnit.HOURS.between(dateTime1, dateTime2);
int hour = dateTime2.getHour();
boolean offset = dateTime1.getOffset()
    == dateTime2.getOffset();
System.out.println("diff = " + diff);
System.out.println("hour = " + hour);
System.out.println("offset = " + offset);
```

- A. diff = 1**
- B. diff = 2
- C. hour = 2
- D. hour = 3**
- E. offset = true
- F. The code does not compile.
- G. A runtime exception is thrown.

- 21.** Which of the following can fill in the blank to print `avaJ`? (Choose all that apply.)

```
3: var puzzle = new StringBuilder("Java");
4: puzzle._____;
5: System.out.println(puzzle);
```

- A. reverse()**
- B. `append("vaJ$").substring(0, 4)`
- C. `append("vaJ$").delete(0, 3).deleteCharAt(puzzle.length() - 1)`**
- D. `append("vaJ$").delete(0, 3).deleteCharAt(puzzle.length())`
- E. None of the above

- 22.** What is the output of the following code?

```
var date = LocalDate.of(2022, Month.APRIL, 30);
date.plusDays(2);
date.plusYears(3);
System.out.println(date.getYear() + " " + date.getMonth()
    + " " + date.getDayOfMonth());
```


- A.** 2022 APRIL 30
- B.** 2022 MAY 2
- C.** 2025 APRIL 2
- D.** 2025 APRIL 30
- E.** 2025 MAY 2
- F.** The code does not compile.
- G.** A runtime exception is thrown.

Respuestas del cuestionario semana 3 tema 4	
Pregunta	Comentario
1	No compila porque numFish + 1 da un int y se quiere guardar en un String.
2	Usa un nombre de variable como tipo y E/F no tienen tamaño en la primera dimensión.
3	Son fechas válidas. Las otras tienen errores de fecha o compilación.
4	Se imprimen one, three y four por cómo funcionan los Strings y el método intern().
5	El resultado final del StringBuilder es abbaccca.
6	Hay 2 errores. Math.round() devuelve long y Math.random() devuelve double.
7	La primera fecha es más temprana y hay 6 horas de diferencia.
8	Todas regresan el carácter '5'.
9	Los arreglos empiezan en 0, tienen tamaño fijo y equals() compara referencias.
10	Todo compila correctamente.
11	LocalDate no tiene el método plusHours().
12	La salida es 12, una línea vacía y 78.
13	Se imprime roar roar!!! porque StringBuilder sí cambia su contenido.
14	Instant.now() y zonedDateTime.toInstant() son válidos.
15	El arreglo queda [123, PIG, pig] y binarySearch devuelve -3.
16	Los valores calculados son 10, 11 y 16.
17	substring(1,2) devuelve un carácter y substring(6,5) lanza excepción.
18	Se imprime equals y luego 7.
19	Son las opciones que generan un entero positivo.
20	La diferencia es 1 hora y la hora final es 3 por el cambio de horario.
21	Ambas producen avaJ.
22	Se imprime 2022 APRIL 30 porque LocalDate es immutable.

Review Questions

The answers to the chapter review questions can be found in the Appendix.

1. Which statements about the `final` modifier are correct? (Choose all that apply.)

- A. Instance and static variables can be marked `final`.
- B. A variable is effectively final only if it is marked `final`.
- C. An object that is marked `final` cannot be modified.
- D. Local variables cannot be declared with type `var` and the `final` modifier.
- E. A primitive that is marked `final` cannot be modified.

2. Which of the following can fill in the blank in this code to make it compile? (Choose all that apply.)

```
public class Ant {  
    _____ void method() {}  
}
```

- A. `default`
- B. `final`
- C. `private`
- D. `Public`
- E. `String`
- F. `zzz:`

3. Which of the following methods compile? (Choose all that apply.)

- A. `final static void rain() {}`
- B. `public final int void snow() {}`
- C. `private void int hail() {}`
- D. `static final void sleet() {}`
- E. `void final ice() {}`
- F. `void public slush() {}`

4. Which of the following can fill in the blank and allow the code to compile? (Choose all that apply.)

```
final _____ song = 6;
```

- A. `int`
- B. `Integer`
- C. `long`
- D. `Long`
- E. `double`
- F. `Double`

5. Which of the following methods compile? (Choose all that apply.)

- A. `public void january() { return; }`
- B. `public int february() { return null;}`
- C. `public void march() {}`
- D. `public int april() { return 9;}`
- E. `public int may() { return 9.0;}`
- F. `public int june() { return;}`

6. Which of the following methods compile? (Choose all that apply.)

- A. `public void violin(int... nums) {}`
- B. `public void viola(String values, int... nums) {}`
- C. `public void cello(int... nums, String values) {}`
- D. `public void bass(String... values, int... nums) {}`
- E. `public void flute(String[] values, ...int nums) {}`
- F. `public void oboe(String[] values, int[] nums) {}`

7. Given the following method, which of the method calls return 2? (Choose all that apply.)

```
public int juggle(boolean b, boolean... b2) {  
    return b2.length;  
}
```

- A. `juggle();`
- B. `juggle(true);`
- C. `juggle(true, true);`
- D. `juggle(true, true, true);`
- E. `juggle(true, {true, true});`
- F. `juggle(true, new boolean[2]);`

8. Which of the following statements is correct?

- A. Package access is more lenient than protected access.
- B. A public class that has private fields and package methods is not visible to classes outside the package.
- C. You can use access modifiers so only some of the classes in a package see a particular package class.
- D. You can use access modifiers to allow access to all methods and not any instance variables.
- E. You can use access modifiers to restrict access to all classes that begin with the word Test.

9. Given the following class definitions, which lines in the `main()` method generate a compiler error? (Choose all that apply.)

// Classroom.java

```
package my.school;

public class Classroom {
    private int roomNumber;
    protected static String teacherName;
    static int globalKey = 54321;
    public static int floor = 3;
    Classroom(int r, String t) {
        roomNumber = r;
        teacherName = t; } }
```

// School.java

```
1: package my.city;
2: import my.school.*;
3: public class School {
4:     public static void main(String[] args) {
5:         System.out.println(Classroom.globalKey);
6:         Classroom room = new Classroom(101, "Mrs. Anderson");
7:         System.out.println(room.roomNumber);
8:         System.out.println(Classroom.floor);
9:         System.out.println(Classroom.teacherName); } }
```

A. None: the code compiles fine.

B. Line 5

C. Line 6

D. Line 7

E. Line 8

F. Line 9

10. What is the output of executing the Chimp program?

// Rope.java

```
1: package rope;
2: public class Rope {
3:     public static int LENGTH = 5;
4:     static {
5:         LENGTH = 10;
6:     }
7:     public static void swing() {
```

```
8:      System.out.print("swing ");
9:  } }
```

// Chimp.java

```
1: import rope.*;
2: import static rope.Rope.*;
3: public class Chimp {
4:     public static void main(String[] args) {
5:         Rope.swing();
6:         new Rope().swing();
7:         System.out.println(LENGTH);
8:     } }
```

- A. swing swing 5
 - B. swing swing 10**
 - C. Compiler error on line 2 of Chimp
 - D. Compiler error on line 5 of Chimp
 - E. Compiler error on line 6 of Chimp
 - F. Compiler error on line 7 of Chimp
11. Which statements are true of the following code? (Choose all that apply.)

```
1: public class Rope {
2:     public static void swing() {
3:         System.out.print("swing");
4:     }
5:     public void climb() {
6:         System.out.println("climb");
7:     }
8:     public static void play() {
9:         swing();
10:        climb();
11:    }
12:    public static void main(String[] args) {
13:        Rope rope = new Rope();
14:        rope.play();
15:        Rope rope2 = null;
16:        System.out.print("-");
17:        rope2.play();
18:    } }
```

- A. The code compiles as is.
- B. There is exactly one compiler error in the code.
- C. There are exactly two compiler errors in the code.
- D. If the line(s) with compiler errors are removed, the output is swing-climb.
- E. If the line(s) with compiler errors are removed, the output is swing-swing.
- F. If the line(s) with compile errors are removed, the code throws a NullPointerException.

12. How many variables in the following method are effectively final?

```
10: public void feed() {  
11:     int monkey = 0;  
12:     if(monkey > 0) {  
13:         var giraffe = monkey++;  
14:         String name;  
15:         name = "geoffrey";  
16:     }  
17:     String name = "milly";  
18:     var food = 10;  
19:     while(monkey <= 10) {  
20:         food = 0;  
21:     }  
22:     name = null;  
23: }
```

- A. 1
- B. 2
- C. 3
- D. 4
- E. 5
- F. None of the above. The code does not compile.

13. What is the output of the following code?

```
// RopeSwing.java  
import rope.*;  
import static rope.Rope.*;  
public class RopeSwing {  
    private static Rope rope1 = new Rope();  
    private static Rope rope2 = new Rope();  
    {  
        System.out.println(rope1.length);  
    }  
}
```

```
public static void main(String[] args) {  
    rope1.length = 2;  
    rope2.length = 8;  
    System.out.println(rope1.length);  
}  
}
```

// Rope.java

```
package rope;  
public class Rope {  
    public static int length = 0;  
}
```

- A. 02
- B. 08
- C. 2
- D. 8**
- E. The code does not compile.
- F. An exception is thrown.

14. How many lines in the following code have compiler errors?

```
1: public class RopeSwing {  
2:     private static final String leftRope;  
3:     private static final String rightRope;  
4:     private static final String bench;  
5:     private static final String name = "name";  
6:     static {  
7:         leftRope = "left";  
8:         rightRope = "right";  
9:     }  
10:    static {  
11:        name = "name";  
12:        rightRope = "right";  
13:    }  
14:    public static void main(String[] args) {  
15:        bench = "bench";  
16:    }  
17: }
```

- A. 0
- B. 1

- C. 2
- D. 3
- E. 4**
- F. 5

15. Which of the following can replace line 2 to make this code compile? (Choose all that apply.)

```
1: import java.util.*;
2: // INSERT CODE HERE
3: public class Imports {
4:     public void method(ArrayList<String> list) {
5:         sort(list);
6:     }
7: }
```

- A. `import static java.util.Collections;`
- B. `import static java.util.Collections.*;`**
- C. `import static java.util.Collections.sort(ArrayList<String>);`
- D. `static import java.util.Collections;`
- E. `static import java.util.Collections.*;`
- F. `static import java.util.Collections.sort(ArrayList<String>);`

16. What is the result of the following statements?

```
1: public class Test {
2:     public void print(byte x) {
3:         System.out.print("byte-");
4:     }
5:     public void print(int x) {
6:         System.out.print("int-");
7:     }
8:     public void print(float x) {
9:         System.out.print("float-");
10:    }
11:    public void print(Object x) {
12:        System.out.print("Object-");
13:    }
14:    public static void main(String[] args) {
15:        Test t = new Test();
16:        short s = 123;
17:        t.print(s);
18:        t.print(true);
19:    }
20: }
```

```

19:         t.print(6.789);
20:     }
21: }

```

- A. byte-float-Object-
- B. int-float-Object-
- C. byte-Object-float-
- D. int-Object-float-
- E. int-Object-Object-**
- F. byte-Object-Object-

17. What is the result of the following program?

```

1: public class Squares {
2:     public static long square(int x) {
3:         var y = x * (long) x;
4:         x = -1;
5:         return y;
6:     }
7:     public static void main(String[] args) {
8:         var value = 9;
9:         var result = square(value);
10:        System.out.println(value);
11:    } }

```

- A. -1
- B. 9**
- C. 81
- D. Compiler error on line 9
- E. Compiler error on a different line

18. Which of the following are output by the following code? (Choose all that apply.)

```

public class StringBuilders {
    public static StringBuilder work(StringBuilder a,
        StringBuilder b) {
        a = new StringBuilder("a");
        b.append("b");
        return a;
    }
    public static void main(String[] args) {
        var s1 = new StringBuilder("s1");
        var s2 = new StringBuilder("s2");

```

```

    var s3 = work(s1, s2);
    System.out.println("s1 = " + s1);
    System.out.println("s2 = " + s2);
    System.out.println("s3 = " + s3);
}
}

```

- A. s1 = a
- B. s1 = s1
- C. s2 = s2
- D. s2 = s2b
- E. s3 = a
- F. The code does not compile.

19. Which of the following will compile when independently inserted in the following code? (Choose all that apply.)

```

1: public class Order3 {
2:     final String value1 = "red";
3:     static String value2 = "blue";
4:     String value3 = "yellow";
5:     {
6:         // CODE SNIPPET 1
7:     }
8:     static {
9:         // CODE SNIPPET 2
10:    } }

```

- A. Insert at line 6: value1 = "green";
- B. Insert at line 6: value2 = "purple";
- C. Insert at line 6: value3 = "orange";
- D. Insert at line 9: value1 = "magenta";
- E. Insert at line 9: value2 = "cyan";
- F. Insert at line 9: value3 = "turquoise";

20. Which of the following are true about the following code? (Choose all that apply.)

```

public class Run {
    static void execute() {
        System.out.print("1-");
    }
    static void execute(int num) {
        System.out.print("2-");
    }
}

```

```

static void execute(Integer num) {
    System.out.print("3-");
}
static void execute(Object num) {
    System.out.print("4-");
}
static void execute(int... nums) {
    System.out.print("5-");
}
public static void main(String[] args) {
    Run.execute(100);
    Run.execute(100L);
}
}

```

- A. The code prints out 2-4-.
 - B. The code prints out 3-4-.
 - C. The code prints out 4-2-.
 - D. The code prints out 4-4-.
 - E. The code prints 3-4- if you remove the method `static void execute(int num)`.
 - F. The code prints 4-4- if you remove the method `static void execute(int num)`.
21. Which method signatures are valid overloads of the following method signature? (Choose all that apply.)
- ```
public void moo(int m, int... n)
```
- A. `public void moo(int a, int... b)`
  - B. `public int moo(char ch)`
  - C. `public void moooo(int... z)`
  - D. `private void moo(int... x)`
  - E. `public void moooo(int y)`
  - F. `public void moo(int... c, int d)`
  - G. `public void moo(int... i, int j...)`

| Respuestas del cuestionario semana 3 tema 5 |                                                                                         |
|---------------------------------------------|-----------------------------------------------------------------------------------------|
| Pregunta                                    | Comentario                                                                              |
| 1                                           | Las variables static e instance pueden ser final y un primitivo final no puede cambiar. |
| 2                                           | Final y private pueden ir antes de void y compilan.                                     |
| 3                                           | Static y final pueden intercambiar su posición.                                         |
| 4                                           | El valor 6 puede asignarse a int, Integer, long y double.                               |
| 5                                           | Los métodos void pueden usar return; y los métodos int deben devolver un entero.        |
| 6                                           | El parámetro varargs debe ser el último y solo puede existir uno.                       |
| 7                                           | En ambos casos el arreglo varargs tiene longitud 2.                                     |
| 8                                           | Se pueden tener atributos privados y métodos públicos.                                  |
| 9                                           | Las líneas 5, 6, 7 y 9 generan error por restricciones de acceso entre paquetes.        |
| 10                                          | La salida es: swing swing 10.                                                           |
| 11                                          | Hay un error de compilación y al quitarlo la salida es swing- swing.                    |
| 12                                          | Hay 2 variables efectivamente finales.                                                  |
| 13                                          | La salida es 8 porque length es static y se comparte.                                   |
| 14                                          | Existen 4 errores de compilación.                                                       |
| 15                                          | Se debe usar import static java.util.Collections.*;                                     |
| 16                                          | La salida es int- Object- Object-.                                                      |
| 17                                          | Imprime 9 porque Java pasa los valores por copia.                                       |
| 18                                          | La salida es: s1 = s1 s2 = s2b s3 = a                                                   |
| 19                                          | Son las opciones que compilan correctamente.                                            |
| 20                                          | Con el código actual imprime 2- 4-. Si se elimina execute(int), imprime 3- 4-.          |
| 21                                          | Son sobrecargas válidas porque cambian los parámetros.                                  |