

Brian Hogan

March 8, 2019

~~Hogan - How to Use R for Applied Data Science~~

```
#Step:1 Load Data-----Brian Hogan-----  
str(airquality) #153x6: "Ozone", "Solar.R", "Wind", "Temp", "Month", "Day"
```

```
## 'data.frame': 153 obs. of 6 variables:  
## $ Ozone : int 41 36 12 18 NA 28 23 19 8 NA ...  
## $ Solar.R: int 190 118 149 313 NA NA 299 99 19 194 ...  
## $ Wind : num 7.4 8 12.6 11.5 14.3 14.9 8.6 13.8 20.1 8.6 ...  
## $ Temp : int 67 72 74 62 56 66 65 59 61 69 ...  
## $ Month : int 5 5 5 5 5 5 5 5 5 5 ...  
## $ Day : int 1 2 3 4 5 6 7 8 9 10 ...
```

```
apply(apply(airquality,2,is.na),2,sum) #identify NAs
```

```
## Ozone Solar.R Wind Temp Month Day  
## 37 7 0 0 0 0
```

```
#Step 2: Clean Data-----  
# ==> wanted to use rnorm(ozone.mean(& sd) but had issue neg #s >:0(  
ozone <-airquality[,1] #substitute NAs with Ozone & Solar.R means  
f.ozone <- function(x)  
{ x[is.na(x)] <- round(mean(na.omit(airquality$Ozone)),1)  
# rnorm(100,mean(na.omit(my.airquality$Ozone)),sd(na.omit(my.airquality$Ozone)))  
return(x) }  
solar <-airquality[,2]  
f.solar <- function(x)  
{ x[is.na(x)] <- round(mean(na.omit(airquality$Solar.R)),1)  
return(x) }  
ozone <-f.ozone(ozone)  
solar <-f.solar(solar)  
wind <-round(airquality$Wind) #round wind  
hw6.data <-data.frame(ozone,solar,wind,airquality$Temp,airquality$Month,airquality$Day)  
colnames(hw6.data) <- colnames(airquality)  
remove(ozone,solar,wind)  
#Step 3.1: Understand data distributions-----  
col.names <- colnames(hw6.data)  
library(ggplot2)
```

```
## Warning: package 'ggplot2' was built under R version 3.5.2
```

```
library(reshape2)
```

```
## Warning: package 'reshape2' was built under R version 3.5.2
```


```
head(hw6.data,3)
```

```
##      Ozone Solar.R Wind Temp Month Day
## 1      41      190    7   67     5   1
## 2      36      118    8   72     5   2
## 3      12      149   13   74     5   3
```

```
ggplot(data = melt(hw6.data[,c(1:6)]), mapping = aes(x = value)) +
  facet_wrap(~variable, scales = "free") + geom_histogram(bins = 20) +
  ggtitle("Step 3: Histogram w 20 Bins to Visualize Variables")
```


```
## No id variables; using all as measure variables
```

Step 3: Histogram w 20 Bins to Visualize Variables




```
ggplot(hw6.data, aes(x=Day, y=Ozone, group=Month)) + geom_boxplot() +
  coord_flip() + ggtitle("Each Box Represents a Month where Bottom Box is May")
```

Each Box Represents a Month where Bottom Box is May



```
ggplot(hw6.data,aes(x=Day, y=Wind, group=Month))+geom_boxplot()+  
coord_flip()+ggtitle("Each Box Represents a Month where Bottom Box is May")
```


Each Box Represents a Month where Bottom Box is May



```
#Step 3.2: Explore how the data changes over time-----
list1 <- c(1:153)
Year <- rep(1973, length(list1)) #add in date as requested !
i <-1
mth.name <- 1
mth.name <-NULL
while (i<=153) { #making facet labels by MOnth
  if (hw6.data[i,"Month"]==5) {mth.name <-c(mth.name,"May")}
  if (hw6.data[i,"Month"]==6) {mth.name <-c(mth.name,"June")}
  if (hw6.data[i,"Month"]==7) {mth.name <-c(mth.name,"July")}
  if (hw6.data[i,"Month"]==8) {mth.name <-c(mth.name,"Aug")}
  if (hw6.data[i,"Month"]==9) {mth.name <-c(mth.name,"Sept")}
  i <-i+1 }
df3.2 <- data.frame(hw6.data,Year,mth.name)
yr.m.day <- paste(df3.2$Year,df3.2$Month, df3.2$Day, sep=".") #DATE !
df3.2 <- data.frame(hw6.data,Year,mth.name,yr.m.day)
head(df3.2)
```


| ## | Ozone | Solar.R | Wind | Temp | Month | Day | Year | mth.name | yr.m.day |
|------|-------|---------|------|------|-------|-----|------|----------|----------|
| ## 1 | 41.0 | 190.0 | 7 | 67 | 5 | 1 | 1973 | May | 1973.5.1 |
| ## 2 | 36.0 | 118.0 | 8 | 72 | 5 | 2 | 1973 | May | 1973.5.2 |
| ## 3 | 12.0 | 149.0 | 13 | 74 | 5 | 3 | 1973 | May | 1973.5.3 |
| ## 4 | 18.0 | 313.0 | 12 | 62 | 5 | 4 | 1973 | May | 1973.5.4 |
| ## 5 | 42.1 | 185.9 | 14 | 56 | 5 | 5 | 1973 | May | 1973.5.5 |
| ## 6 | 28.0 | 185.9 | 15 | 66 | 5 | 6 | 1973 | May | 1973.5.6 |

```
remove(list1,Year,mth.name, i,yr.m.day) #clean memory
ggplot(df3.2, aes(x=Day, y=Ozone))+ geom_line(color="red", size=1)+
  ggtitle("Ozone 1973: May-Sept") + facet_grid(. ~ Month)
```




```
ggplot(df3.2, aes(x=Day, y=Solar.R))+ geom_line(color="green", size=1)+
  ggtitle("Solar.R 1973: May-Sept") + facet_grid(. ~ Month)
```

Solar.R 1973: May–Sept




```
ggplot(df3.2, aes(x=Day, y=Wind))+ geom_line(color="blue", size=1)+  
ggtitle("Wind 1973: May-Sept")+ facet_grid(. ~ Month)
```

Wind 1973: May–Sept




```
ggplot(df3.2, aes(x=Day, y=Temp))+ geom_line(color="black", size=1)+  
  ggtitle("Temp 1973: May–Sept")+ facet_grid(. ~ Month)
```

Temp 1973: May–Sept



```
#3.2.2-----Multiline graph-----
ggplot(df3.2, aes(x=value)) +
  geom_line( aes(y=Ozone, x=Day, color="red")) +      #col=Ozone
  geom_line( aes(y=Solar.R, x=Day, color="blue")) +
  geom_line( aes(y=Wind, x=Day, color="black")) +
  geom_line( aes(y=Temp, x=Day, color="green")) +
  facet_grid(. ~ Month) + ylab("Values") + xlab("Day") +
  ggtitle("1973 Weather May-Sept") +
  scale_color_manual(values = c("black","blue","red","green" ),
  labels=c("Wind","Solar","Temp","Ozone")) + labs(color="Factors") +
  ggtitle("Felt was an Effective y-scale Given Colors for Factors Comparison")
```


Felt was an Effective y-scale Given Colors for Factors Comparison




```
#Step 4 Heatmap---using normalization approach between 0-1 as didnt' want negative scale
Ozone.s <- (df3.2[,1]-min(df3.2$Ozone)) / (max(df3.2$Ozone)-min(df3.2$Ozone))
Solar.s <- (df3.2[,2]-min(df3.2$Solar.R)) / (max(df3.2$Solar.R)-min(df3.2$Solar.R))
Wind.s <- (df3.2[,3]-min(df3.2$Wind)) / (max(df3.2$Wind)-min(df3.2$Wind))
Temp.s <- (df3.2[,4]-min(df3.2$Temp)) / (max(df3.2$Temp)-min(df3.2$Temp))
df4 <-data.frame(df3.2,Ozone.s,Solar.s,Wind.s,Temp.s)
df4 <-df4[-1:-4]
remove(Ozone.s,Solar.s,Wind.s,Temp.s)
summary(df4[c(-1:-5)])
```

| ## | Ozone.s | Solar.s | Wind.s | Temp.s |
|-------------|---------|----------------|----------------|----------------|
| ## Min. | :0.0000 | Min. :0.0000 | Min. :0.0000 | Min. :0.0000 |
| ## 1st Qu.: | :0.1198 | 1st Qu.:0.3456 | 1st Qu.:0.2632 | 1st Qu.:0.3902 |
| ## Median | :0.2461 | Median :0.5719 | Median :0.4211 | Median :0.5610 |
| ## Mean | :0.2462 | Mean :0.5472 | Mean :0.4221 | Mean :0.5337 |
| ## 3rd Qu.: | :0.2695 | 3rd Qu.:0.7615 | 3rd Qu.:0.5263 | 3rd Qu.:0.7073 |
| ## Max. | :1.0000 | Max. :1.0000 | Max. :1.0000 | Max. :1.0000 |

```
#Comparison to learn if need to transform data to interpret better in heatmap
ggplot(data = melt(df4[,c(5:9)]), mapping = aes(x = value)) + geom_histogram(bins=20)+
  facet_wrap(~variable, scales = "free") +
  ggtitle("One Would Expect Ozone & Wind to Lean to 0,
  Temp Mid to Hot(1), and Solar Uniform")
```

```
## Using yr.m.day as id variables
```

One Would Expect Ozone & Wind to Lean to 0,
Temp Mid to Hot(1), and Solar Uniform



```
#install.packages("tidyr")      #CLASS SLACK HELP was INVALUABLE !
library("tidyr")
```

```
## Warning: package 'tidyr' was built under R version 3.5.2
```

```
##
## Attaching package: 'tidyr'
```


```
## The following object is masked from 'package:reshape2':
```

```
##
## smiths
```

```
#Abundance = grouping of all air quality factor values 0-1
#Felt Square Root Transformation did help with graph read but could vary by person
df5 <- gather(data = df4, key = Class, value= Abundance,-c(1:5))
df5$Sqrt.Abandance <- sqrt(df5$Abundance)
head(df5,2)
```


```
##   Month Day Year mth.name yr.m.day   Class Abundance Sqrt.Abandance
## 1     5   1 1973     May 1973.5.1 Ozone.s 0.2395210   0.4894088
## 2     5   2 1973     May 1973.5.2 Ozone.s 0.2095808   0.4578000
```

```
heat.reg <-ggplot(data=df5, mapping= aes(x=Day,y=Class,fill=Abundance))+
  geom_tile() + xlab(label="Day") + ylab(label="Air Quality") +
  ggtitle("1973 Air Quality Heatmap w/ Normal Abundance Heat Scale") +
  theme(axis.text.x = element_text(size=8,angle = 90, hjust = 1)) +
  facet_grid(~ mth.name, switch = "x", scales="free_x", space="free_x")
heat.reg #non transformed data
```



```
heat.sqrt <-ggplot(data=df5, mapping= aes(x=Day,y=Class,fill=Sqrt.Abandance))+
  geom_tile() + xlab(label="Day") + ylab(label="Air Quality") +
  ggtitle("1973 Air Quality Heatmap w/ Sq.Root Abundance. Example Illustrates:
    High August Temps & Low Other Air Quality Measures in August") +
  theme(axis.text.x = element_text(angle = 90, hjust = 1)) +
  facet_grid(~ mth.name, switch = "x", scales="free_x", space="free_x")
heat.sqrt #transform data to accentuate the values
```

1973 Air Quality Heatmap w/ Sq.Root Abundance. Example Illustrates:
High August Temps & Low Other Air Quality Measures in August



END HOMEWORK 6