

# User Modeling in search for People with Autism

Author: **Esha Massand**, Supervisor: **Keith Mannoek**

MSc Computer Science  
Department of Computer Science and Information Systems  
Birkbeck College, University of London

Project report submitted in partial fulfillment of the requirement for the  
MSc in Computer Science

September 2015

## Abstract

This project report presents my research and the development of a prototype web application to assist users with Autism when they search the web. The system has modeled user interactions with the search process into a user profile for this category of users, integrating insights from the core features of autism into the model. The system is integrated with an infra-red, motion controlled, user interface component to assist users with Autism during search. The project provides insights into how search can be improved for users with Autism.

This project is substantially the result of my own work, expressed in my own words, except where explicitly indicated in the text. I give my permission for it to be submitted to a Plagiarism Detection Service. This proposal may be freely copied and distributed provided the source is explicitly acknowledged.

word count (project text only) :

# Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
<b>2</b>	<b>Aims</b>	<b>5</b>
<b>3</b>	<b>Background Research</b>	<b>6</b>
<b>4</b>	<b>Project Trailer</b>	<b>6</b>
<b>5</b>	<b>Product Specification</b>	<b>8</b>
5.1	Design Patterns (for web applications) . . . . .	8
<b>6</b>	<b>Software Architecture</b>	<b>9</b>
6.1	Design Patterns . . . . .	9
6.2	Use Case Diagram . . . . .	9
6.3	High Level UML Class Diagram of the System . . . . .	10
<b>7</b>	<b>Implementation</b>	<b>10</b>
7.1	Synthesis of Search Results . . . . .	10
7.2	JSoup API . . . . .	11
7.3	Storage of information . . . . .	11
7.4	Classification of Users . . . . .	11
7.5	Bootstrap and CSS . . . . .	11
7.6	HTML pages and JavaScript . . . . .	11
7.7	Java . . . . .	11
7.8	LEAP motion detector and LEAP SDK . . . . .	11
7.9	API's and Development Tools . . . . .	11
<b>8</b>	<b>Core Feature 1: Research and Data Collection for a Combination Search Engine using Google, Yahoo and Bing.</b>	<b>11</b>
8.1	Web Scraping . . . . .	13
8.2	User Research and Testing of Core Feature 1 . . . . .	14
<b>9</b>	<b>Core Feature 2: Building a User Model of Autism.</b>	<b>14</b>
9.1	Differences in Search Queries Between Users With and Without Autistic-like traits. .	15
<b>10</b>	<b>Core Features 3 and 4: Jellibears – A Transformation Rule Engine</b>	<b>17</b>
<b>11</b>	<b>Core Feature 5: Integration with a Motion Controlled Interface.</b>	<b>18</b>
11.1	Evaluation and Review of the Leap Motion Controller. . . . .	19
<b>12</b>	<b>User Testing the System.</b>	<b>20</b>
12.1	User Verification . . . . .	20
12.1.1	The positives . . . . .	20
12.1.2	The negatives . . . . .	21
<b>13</b>	<b>Conclusions and Discussion.</b>	<b>21</b>
13.1	Signals of Quality Content . . . . .	21
13.2	Future Directions . . . . .	22

<b>14 Appendices</b>	<b>24</b>
14.1 Search Query Survey . . . . .	25
14.2 Questions on the Autism Spectrum Quotient [1] . . . . .	29

## Abbreviations

API	Application Programming Interface
AQ	Autism Quotient
ASD	Autism Spectrum Disorder
DSM	Diagnostic and Statistical Manual
GCS	Google Custom Search
HCI	Human Computer Interaction
HTTP	Hypertext Transfer Protocol
JSON	JavaScript Object Notation
IDE	Integrated Development Environment
KWIC	Key Word In Context
LEAP	LEAP Motion Controller
REST	Representational state transfer
RIFT	Oculus Rift Virtual Reality Head Mounted Display
TDD	Test Driven Development
UI	User Interface
UX	User Experience
VR	Virtual Reality

## Definitions

**Autism** Autism is amongst the most common neurodevelopmental condition and it is currently estimated that 1/68 children meet criteria for Autism Spectrum [?]. Autism is five times more common amongst boys than girls (1/42 boys, and 1/189 girls). According to the Diagnostic and Statistical Manual (2013), Autism is characterized by persistent and early deficits in reciprocal social interaction and repetitive behaviours. Individuals vary from high functioning to low functioning (along a spectrum), with behaviours emerging around 2 to 3 years of age.

## Search Engine Measures

### Precision

The field of information retrieval defines precision as the fraction of retrieved documents that are relevant to the query.

$$Precision = \frac{|(relevant\ documents) \cap (retrieved\ documents)|}{|(retrieved\ documents)|}$$

### Recall

The field of information retrieval defines recall as the fraction of relevant documents that are retrieved by the search query.

$$Recall = \frac{|(relevant\ documents) \cap (retrieved\ documents)|}{|(relevant\ documents)|}$$

# 1 Introduction

This project report presents the development and evaluation of a prototype web-browser based application to assist users with Autism when they search the web. The application is hereafter referred to as Jellibean<sup>1</sup>. Jellibean utilises gesture and hand movement data recorded using the Leap Motion Controller (LEAP).

In programmatic terms, Jellibean is designed to implement a research-guided user model in search. The development of this user model consisted of iterations of the ‘research, development, test, evaluate’ lifecycle. I conducted research to identify the preferences within search, and the differences in user queries formed by individuals with Autism, by conducting surveys and collecting and analysing search behaviour patterns from people with and without Autism. Using these data I built a set of features into search, to guide the user through forming a more complete search query. Development and evaluation included the implementation and testing of the features, and further implementation and revision of the software to enhance the search process and the precision of the search engine for the users’ intended search query.

Jellibean integrates a motion controlled user interface (UI) using the LEAP motion controller. The interface is very dynamic as opposed to static, and can hold users’ attention for longer periods of time. In the past, users with Autism have struggled to maintain their attention to sift through the large number of search results. In line with the attention difficulties individuals with Autism face, Jellibean has been designed to reduce the amount of text on the search results page, presenting only 3 results per page, instead of the default 10.

## 2 Aims

The goal of the project is to build a prototype search tool that assists users with Autism search and navigate the web. These prototype features will be tested on a group of users with Autism. The final product will be integrated within a motion-controlled environment. The prototype will be modified accordingly in line with the outcome of several stages of user research.

The core features for Jellibean to implement and test for suitability within an environment for users with autism are:

1. A combination search engine that will synthesise the search results from three engines, Google, Bing and Yahoo. The aim of this feature is to increase recall of the engine.
2. Research, develop and test iterations of a *stereotyped* user model of Autism within Search.
3. To integrate Jellibean with Google+, to enhancing the feel of a personalised search engine.
4. Jellibean will include a review and assessment of autistic-like traits or characteristics, so that users can be aware of, and save a copy of their diagnostic information.
5. Jellibean will prioritise and display the three highest precision search results for users. The overall goal of Jellibean is to increase precision of the search results.
6. Jellibean will

Are there any specific work packages that need to be done? If so, list those out here.

---

<sup>1</sup>Jellibean are a rainbow of colours, different sizes and shades, and the name represents the difference in style of processing of individuals with ASD.

### 3 Background Research

People with Autism are less context-sensitive and prefer a more detail-focused processing style [7]. This means that web-search queries are formed very differently to the typical population. Generally speaking, individuals with Autism prefer, and are more likely to engage in an item-specific, or detailed processing style, as opposed to a context-driven processing style, resulting in web-search queries that are more likely formed of single-order associations. For example, To address this issue, the current project aims to build a user model within search for individuals with Autism.

Search queries usually fall into one of three broad categories. ‘Do’ queries which characterise transactions between the user and the search engine, for example when the user wants to do something such as buy a plane ticket or listen to a song. There are also ‘Know’ type queries. These are informational queries for example, the name of a band or restaurant in London. The third broad category is ‘Go’ type queries, which are navigational in nature, for example, searching for a particular home page on the web.

There are many stages to the search process. After identifying the information need, the user must formulate a search query. The user must browse through results once the query has been entered into a search engine. The whole process can be repeated if the user is not satisfied. The stage at which the user model will have most possible impact is before results are returned to the user, that is, at the query formulation stage. It is this stage that the user model will be implemented (stage 2 on the user web-search process.)

1. Experience the need for an answer, solution, or piece of information.
2. Formulate that need in a string of words and phrases, also known as the query.
3. Enter the query into a search engine.
4. Browse through the results for a match.
5. Click on a result
6. Scan for a solution, or a link to that solution.
7. If unsatisfied, return to the search results and browse for another link or ...
8. Perform a new search with refinements to the query

The User Web-Search Process [10]

### 4 Project Trailer

1. The development of a *stereotyped* user model of Autism. The features of the model will be determined following analyses of survey responses gathered from individuals with Autism or autism-like symptomology. The survey will be administered online using a web-based survey engine [www.surveymonkey.com](http://www.surveymonkey.com) [11], and focus on identifying the differences in user search query generation for people with autism.
2. Following the findings from above, Jellibbeans will employ a parametric search feature, and suggestions to guide the user towards forming succinct and accurate search queries.
3. Jellibbeans will be integrated with Google+, to allow the user to sign in and have their profile picture and name displayed, enhancing the feel of a personalised search engine.

4. Jellibbeans will allow users to get feedback on the level of their autism-like symptomology. The Autism Quotient [1], a scientifically validated screening tool for autism spectrum disorders will feature on the Jellibean homepage, and users will be able to retrieve their score and save their responses for each question to a local file for their reference.
5. Jellibbeans will prioritise and display the three highest precision search results for users. The overall goal of Jellibbeans is to increase precision of the search results.
6. Jellibbeans reduces the amount of text on the results page by having results display on a modal (a hovering display panel on the page) which can be easily closed, and reopened to display results.
7. Due to the nature of the parametric search, and the reduction in number of search results displayed, the results from Jellibbeans are more likely to be a direct semantic relation to the search query. This makes the selection of that result by the search engine more transparent to the user.
8. Integration of the web application with a motion controlled user interface, the LEAP controller.




Figure 1: Jellibean User Flow

## 5 Product Specification

Functional and non-functional requirements and major dependencies. How I plan on tackling the problem to meet my requirements.

### 5.1 Design Patterns (for web applications)

Search engines like Google apply strong reduction techniques to navigation of the web. For example, one common way this reduction pattern is implemented is by assuming the behaviour of the current user is similar to the behaviour of other users in similar situations. This is often seen in recommendation engines, e.g., Amazon. The principle applied by Google is to make it easy for the user [5], by assuming that users form search queries similarly, and returning similar results to those users.

As we have seen in the introduction, users with Autism behave in different ways to typical users when navigating search. Users with Autism do not use the same key phrases when looking for documents with several attributes, i.e., queries that would be best formulated using several iterations of search, or multiple search parameters. This leads to an ineffective search; one that requires users to sift through results which are in large-part irrelevant, and a bad user experience. Given the research findings observed in the current study, the parametric search pattern appears to be a better choice for the user group in question.

Parametric search queries allow users to define parameters in an increasingly logical and structured way. As an example, consider the experience of searching for flights to a particular holiday destination, or for a person. This requires high cognitive load (remembering and manipulating arrival, departure, destination, timings, airlines, seat preferences etc.) so searches are often structured using fixed options (see Figure 2).


The image shows a screenshot of the Expedia 'FLIGHT DEALS' search interface. On the left, there are three radio button options: 'Hotel only', 'Flight only', and 'Flight + Hotel' (which is selected). The main search area contains several input fields: 'Leaving from' and 'Going to' (both with a location pin icon and placeholder text 'City or airport'), 'Departing' and 'Returning' (both with a calendar icon and placeholder text 'dd/mm/yyyy'), 'Rooms' (a dropdown menu showing '1'), 'Adults (18 +)' (a dropdown menu showing '2'), and 'Children (0 - 17)' (a dropdown menu showing '0'). Below these fields is a checkbox labeled 'I only need a hotel for part of my trip'. A large yellow 'Search' button is positioned below the checkbox. At the bottom left, there is a Nectar logo and text: 'Collect Nectar points every time you book PLUS don't forget our Best Price Guarantee.'

Figure 2: Expedia Parametric Search Example

For typical users, parametric search is more structured, and in some circumstances seems more natural than a free keyword search. It makes search queries easier to formulate in situations where there is a high cognitive load. We can apply this idea to web search for people with Autism, by asking them to enter criteria that can be applied to subgroups of search queries. Parametric search can assist the user with capturing the search parameters that are useful for a query it does not ultimately reduce the number of search results returned; the possibility of a large result set is most definitely true. However, when used in addition to the original search query itself, the parametric search will refine the users search results in line with their search query, ultimately leading to a higher precision for the search engine.

One of the aims of the study is to reduce the amount of textual information on the webpage presented to the user, so the solution implemented here tries to find a balance between these two aims.



## 6 Software Architecture

### 6.1 Design Patterns

### 6.2 Use Case Diagram

Feature uses and high level description of the system.




Figure 3: Jellibeans High Level UML Use Case Diagram

### 6.3 High Level UML Class Diagram of the System




Figure 4: Jellibeans High Level UML Class Diagram

## 7 Implementation

### 7.1 Synthesis of Search Results

For search results returned by Google, the Custom Search API was used in line with the Google terms of service ('screen scraping', or copying the data directly from the website is prohibited). It is a RESTful api with a single method called list. The API method used was GET, and the response data is returned as a JSON type. The response consists of (1) the actual search result, (2) metadata for search like number of results, alternative search queries, and (3) custom search engine metadata. The data model depends on [9]. For Bing and Yahoo search results, JSoup (a Java HTML parser) will be used to identify the links from the resulting query. The JSoup HTML parser was considered more efficient for retrieving search results, as it reduced the number of lines of code required to complete the task from both search engines, using a slightly different href element filter. Jsoup also has its advantages over html parsing. It contains a class representing a list of nodes, 'Elements', which implements Iterable to iterate over a list in an enhanced for loop. The resulting links are written to text file which stores the links in a text file in the projects source directory.

The system aims to deliver relevant results to the user, but what is "relevant"? Not all users or groups of users search in the same way, so it is important to consider user intention. The first part of the current project aimed to investigate the differences between search queries of people with and without Autism, and to use those findings to build a stereotyped user model (a user model that will infer characteristics about the user from their diagnostic information) for a person with autism. Users are asked to complete the Autism Quotient Questionnaire and obtain a score of autistic-like traits.

## **7.2 JSoup API**

## **7.3 Storage of information**

Google+ and storing to file on computer. Javascript to return aboutMe profile. Returning AQ score to user.

## **7.4 Classification of Users**

Classification used the AQ into high and low scorers and feeding that information back in a downloadable file/on the screen in an alert. Javascript methods

## **7.5 Bootstrap and CSS**

## **7.6 HTML pages and JavaScript**

## **7.7 Java**

Java was chosen for quick development of packages of features to test with users as I was most proficient with Java, and could quickly develop prototypes which could then be later implemented fully.

## **7.8 LEAP motion detector and LEAP SDK**

## **7.9 API's and Development Tools**

Describe the technologies used in the project, why they were chosen and what were the other options:

Tools and programming languages

# **8 Core Feature 1: Research and Data Collection for a Combination Search Engine using Google, Yahoo and Bing.**

To implement the combination search engine I used three APIs provided by Google, Bing and Yahoo, namely, the Google Custom Search API, Yahoo BOSS Java API and Bing Search API. To get started with the Google Custom Search API, I created a project called Jellibbeans in the Google Developers Console, and an OAuth 2.0 Client ID. I obtained a Consumer Key and Secret to use the API, and used these in the application code to access the Google Custom Search Engine (see Figure 5).

```

public class GoogleCustomSearchApiApplet {

    String qry = null;
    public ArrayList<String> jSoupGoogleLinks = new ArrayList<>();

    public void cse() throws IOException {

        String key = "AIzaSyCnAIDiZchNkR00TBH3NMMNt4GmRiwpdnA";// server key

        String cx = "008818185974073145685:ga_fm9k9gf0";
        URL url = new URL("https://www.googleapis.com/customsearch/v1?key="
            + key + "&cx=" + cx + "&q=" + qry + "&alt=json");
        HttpURLConnection conn = (HttpURLConnection) url.openConnection();
        conn.setRequestMethod("GET");
        conn.setRequestProperty("Accept", "application/json");
        BufferedReader br = new BufferedReader(new InputStreamReader(
            (conn.getInputStream())));

        String output;
        while ((output = br.readLine()) != null) {

            if (output.contains("\"link\": \"\"")) {
                String link = output.substring(output.indexOf("\"link\": \"\"")
                    + ("\"link\": \"\"").length(), output.indexOf("\"",));
                jSoupGoogleLinks.add(link.toString());
            }
        }
        conn.disconnect();
    }
}

```

Figure 5: Jellibean Applet Combination Search Engine

Following that I also registered my JavaScript origins within the console to access the Google+ API, and redirected URIs so that once users sign in using their Google+ login credentials they will be redirected to Jellibean (or <http://esha.mseth.co>). This was done because I wanted users to be able to sign in and access their google profile from Jellibean (see Figure 6).




Figure 6: Google Sign In Page.

Following a similar protocol for Yahoo and Bing Search APIs, I created projects in the Yahoo

Developers Network, and Microsoft Azure Marketplace, and purchased an API Consumer Keys and Secrets (needed to use the APIs).

## 8.1 Web Scraping

Web scraping was also an option, it quickly became a preferred because of integration of the three APIs and the flexibility/manipulation of the results if they were returned using the same method. However this was against terms of service set out by Google (see section 5.3 of Figure 7).

### 5. Use of the Services by you

5.1 In order to access certain Services, you may be required to provide information about yourself (such as identification or contact details) as part of the registration process for the Service, or as part of your continued use of the Services. You agree that any registration information you give to Google will always be accurate, correct and up to date.

5.2 You agree to use the Services only for purposes that are permitted by (a) the Terms and (b) any applicable law, regulation or generally accepted practices or guidelines in the relevant jurisdictions (including any laws regarding the export of data or software to and from the United States or other relevant countries).

5.3 You agree not to access (or attempt to access) any of the Services by any means other than through the interface that is provided by Google, unless you have been specifically allowed to do so in a separate agreement with Google. You specifically agree not to access (or attempt to access) any of the Services through any automated means (including use of scripts or web crawlers) and shall ensure that you comply with the instructions set out in any robots.txt file present on the Services.

5.4 You agree that you will not engage in any activity that interferes with or disrupts the Services (or the servers and networks which are connected to the Services).

5.5 Unless you have been specifically permitted to do so in a separate agreement with Google, you agree that you will not reproduce, duplicate, copy, sell, trade or resell the Services for any purpose.

5.6 You agree that you are solely responsible for (and that Google has no responsibility to you or to any third party for) any breach of your obligations under the Terms and for the consequences (including any loss or damage which Google may suffer) of any such breach.

Figure 7: Google Terms of Service

So, instead, I used the Jsoup API [6], which is a java written API for HTML. The library provides methods to conveniently extract data using DOM (Data Object Model) and CSS (Cascading Style Sheet) methods. The Jsoup HTML parser was used to scrape results only from Yahoo and Bing, and integrated these into a Java Applet that runs in Eclipse Luna IDE (see Figure 8). The top 10 links, from each search engine were presented to users and ranked such that result 1 from Google was followed by result 1 from Yahoo, and that was followed by result 1 from Bing. Then results 2 from Google, Yahoo and Bing were presented and so on, until the 30 links were produced, in ranked order from the three search engines.

```

public void jsouphtmlYahoo() {
    Document doc;
    try {
        String searchPage = "https://uk.search.yahoo.com/search?pw=";
        String tempSearch = searchPage + query;

        // need http protocol
        doc = Jsoup.connect(tempSearch).get();

        // get page title
        String title = doc.title();
        String selection = "h3.title > a";

        Elements links = doc.select(selection);
        for (Element l : links) {
            jsoupYahooLinks.add(l.toString());
        }
    } catch (IOException e) {
        e.printStackTrace();
    }
}

public void jsouphtmlBing() {
    Document doc;
    try {
        String searchPage = "https://www.bing.com/search?q=";
        String tempSearch = searchPage + query;


        // need http protocol
        doc = Jsoup.connect(tempSearch).get();

        // get page title
        String title = doc.title();
        String selection = "h2 a";

        Elements links = doc.select(selection);
        for (Element l : links) {
            jsoupBingLinks.add(l.toString());
        }
    } catch (IOException e) {
        e.printStackTrace();
    }
}

```

(a) JSoup HTML Parser.



(b) Complete query results.

Figure 8: JSoup HTML Parsers for Yahoo and Bing working with Google Custom Search API in Java Applet for testing.

## 8.2 User Research and Testing of Core Feature 1

To test the integrated combined search engine, the returned documents from 10 pre-determined search queries were presented to 10 participants who were identified as high AQ scorers. Participants were asked to comment on the search results that had been returned, and to choose three out of the links returned to follow up with, and to observe if anything was odd about the results returned. The responses from the 10 users were analysed to test core feature 1 and whether a combination search would be a good option for Jellibean Search, or whether it would introduce redundancy in the search results. Somewhat non-surprisingly (given the statistics of preferred search engines) the results revealed Bing Search was favoured the least, and Google results the most, with Yahoo falling somewhere in between. Out of the 30 responses participants indicated to follow up with, 21 were Google results, 3 were Yahoo, and 1 was Bing and 5 results overlapped between Google and Yahoo. 4 participants commented that the Bing results were distracting rather than helpful.

Given these findings from the user group, it was decided to continue using the Google results, but to drop the results from Yahoo and Bing, in line with the aim of the project as a whole to improve returned search results for users with Autism.

## 9 Core Feature 2: Building a User Model of Autism.

To identify the features of the user model to build, I ran a study to collect example search queries on a set of informational needs from 37 participants. The participants were asked to give examples of search queries they would use to identify the name of a song they had heard (given the lyrics), or the name of a breed of a dog they had seen (given a picture of the dog). There were in total 10 search queries; the study was distributed widely via SurveyMonkey.com [11] and can be seen in Appendix 14.1. Participants were also asked to complete the Autism Spectrum Quotient 50-item questionnaire see Appendix 14.2. The participants responses are analysed and reported

back to surveymonkey.

The range of scores for the AQ is 0 to 50 with high scores indicating increased likelihood of autism-like traits. A score under 21 is a low to average result (many women average around 15 and men around 17). A score of 22-25 indicates autistic tendencies slightly above the population average. A score above 26 gives a borderline indication of high functioning autism, or aspergers. A score above 30 suggests a likelihood of Asperger syndrome or autism (sensitivity of test measure = 79% [1]). For the purposes of this study, individuals with scores equal to, and above 30 were interpreted as having ‘autistic-like traits’.

Participants were divided into two groups; low AQ scorers (scores below 30), and high AQ scorers (scores equal to and above 30). There were 30 low AQ scorers and 7 high AQ scorers.

## 9.1 Differences in Search Queries Between Users With and Without Autistic-like traits.

I conducted a qualitative analysis on the search query strings from both low and high AQ scorer groups.

In both groups, Google was the preferred search engine by far, with all participants reporting that they used Google as a first choice. No one in the current sample used Yahoo or Bing. The low AQ scorer responses were analysed as a group. A baseline answer was generated using a frequency criterion of 40% i.e., if 12 out of 30 respondents or more generated the same query string given an informational need, it was included in the model below. If two responses were equally as common, both are reported in the model. Data was discarded when a response indicated that the participant would do an image search, as this was not the aim of the survey. The results from the frequency analysis are presented below.


1. You hear a song on the radio with the lyrics, Look at your children, and you want to download it. What would you type into search on your favourite search engine to find out what song it was?  
*Look at your children song.*  
*Look at your children lyrics.*
2. Youve lost touch with an old school friend (you went to St. Marys School). What key words/queries would you use to find them?  
*St. Marys School Year of X.*
3. How would you identify what this is using a search engine (pretend you dont know what it is called). What key words/queries would you use?  
*Star shaped brown plant.*
4. How would you find out the name of this famous person using a search engine? What key words/queries would you use?  
*Brown hair famous young women.*
5. How would you identify what breed this animal is using a search engine? What key words/queries would you use?  
*Small dog fluffy breed.*
6. Your friend and you cant agree on how Thandie Newton pronounces her first name. How would you resolve this using a search engine?  
*Thandie Newton pronunciation.*
7. What would you search for to identify this patterns name, and which country it originates from?  
*Repeating square maze pattern border.*

8. How would you search for delays relating to your (imminent) flight to Paris?  
*Flight number, carrier, Paris, airport, flight time.*


The following observations were made for the users in the high AQ group:

1. There were an increased number of incompletely-formed queries. In the high AQ group, participants were more likely to miss off words in the query string. This was observed even though the sample size was much smaller in the high AQ group (7 people) compared to the low AQ group (29 people)). For example, when analysing the results from query 1 above, 2 out of 7 respondents in the high AQ group did not put ‘lyrics’ or ‘song’ in the search query when searching for the lyrics “Look at your children”. When these search strings are entered into Google, the results are very different (see Figure 9). More results are returned to the incomplete query (302,000,000 compared to 32,900,000). The high AQ user group are presented with results that have a lower precision, i.e., more irrelevant information that they must sift through to find the answer to their search query.
2. Although many high AQ scorers’ formed query strings well, there was increased use of idiosyncratic words in the query strings that were formulated. This is in line with previous research that suggests that people with autism organise information in more subjective and individual ways [2]. For example, referring to the picture of the dog as ‘yorkie pooh’(not listed in frequency index), ‘aeroplane’ (frequency of 8254 words per million) instead of plane (frequency of 33900 words per million) or flight (29535 words per million) , ‘miniature’ (less than 4973 words per million) instead of small (185463 words per million). The idiosyncratic nature of the words is captured by their lower frequency of use in the English language. Search engines use term frequency to determine if a document is relevant to the users search query. If the frequency of words used to form search queries differs between low and high AQ scorers, so will the rankings of the returned search results.





(a) Incomplete query results.



(b) Complete query results.

Figure 9: High and low AQ scorers both formed search queries accurately, however there was an increased tendency to omit the word “lyrics” in the high AQ group resulting in very different search results.

- One individual of the 7 individuals in the high AQ group demonstrated ambiguous use of third-person pronouns, which is characteristic of some individuals with Autism [8]. This includes using first names. This is particularly detrimental to search engine query strings because the use of names distracts the term frequency - inverse document frequency weighting [12] of the search query and subsequently the results returned to the user.
- For questions that were ‘social’ in nature (e.g., featuring a face of a famous woman), 2 out of 7 individuals in the high AQ group indicated that these were types of queries that they would not normally be interested in, and so “wouldn’t bother asking it”. This is, of course, in line with the characteristics of Autism according to [3]. For these queries, it was more common for individuals in the high AQ group to include information in their search query string that was extraneous to the search question itself, compared to the low AQ group. For example, in query 4 above (which asked respondents to indicate how they would identify a famous person), 2 high AQ scorers included information about the woman’s earring. Inevitably this ‘dilutes’ the search query and results in reduced precision for the search engine.

## 10 Core Features 3 and 4: Jellibeans – A Transformation Rule Engine

Given the set of observations in the data reported above, the aims were to devise a set of rules that would ‘transform’ queries made by individuals in the high AQ group to those similar to the

low AQ group. The search engines already handle some of the observations from high AQ scorer queries. For example, the use of pronouns ('I' and 'You') is already taken care of with the use of stop words, which is implemented by the search engine itself. The aim of the project is to therefore address issues that result in the search query string being misleading, and returning different results to low AQ scorer search queries.

The aim for Jellibean is to return search results that are more in line with low AQ scorers. In other words, search results from high AQ queries shared greater overlap with those made by the low AQ group, even though the queries were formed differently. The rule engine is thus a concrete and operationalised framework, for a theoretically-grounded user model of autism within search.

Jellibean works to address more than one observation made during the data collection stage. As a general rule, changes will take the form of add on questions that aim to structure the individual to form a search query in a logical order so that key search terms are not dropped. The structure of the query's formation should also assist the user with less idiosyncratic search queries.

To address observation 2 and to make high AQ scorer search queries less idiosyncratic, Jellibean will prompt the user to categorise their search query into one of 4 possible types of queries, a 'DO', 'Know', 'Go' or 'Social' query. Each type of query will be associated with a colour, and this colour will be prominent on the page, to serve as a visual reminder of the task. This works to reduce the working memory load for the user, and to serve as a goal-directed cue – Two things we know are difficult for people with Autism are maintenance of information in working memory, and goal-directed tasks involving a high demand on Executive Functioning (Executive functions (also known as cognitive control and supervisory attentional system) is an umbrella term for the management (regulation, control) of cognitive processes, including working memory, reasoning, task flexibility, and problem solving as well as planning and execution [4].)

To address observation 1, Jellibean will have an intermittent 'search' term box that confirms what the user wants to return. So, if the user wants to know something like lyrics of a song, or the name of a famous person, the price of an item for sale, they would enter 'lyrics', 'name' or 'price' and this would be added to their search query (if it has not already been added by the user). This would ensure user search queries are more complete.

For observation 3, pronouns ('I' and 'You') are ignored via a stoplist which is implemented by the search engine itself. Jellibean will also identify names of people via the third person library and suggest that these are removed, replaced with another search query term, or kept if the keyword is relevant. The extra layer of checking refines the search query.

The Autism Quotient score of the user will be stored.

## **11 Core Feature 5: Integration with a Motion Controlled Interface.**

Integrating Jellibean with Motion Controller Hardware LEAP motion controller and its use for the system. Current Projects Hardware Selection Process and Important Design Issues:

1. Good timing correlates to a good meaning and User Experience.
2. The leap has options to poll frames at a constant rate (to keep timing of movement accurate) which is important.

3. Cognitive lag time. Each of our senses operates with a different lag time. Hearing has the fastest sense-to-cognition/understanding time, and surprisingly sight – the slowest. If the device interferes with the processing of the sense, it will confuse the combinatorial configuration of the senses, leading to misunderstandings in the meaning and a worse user experience.
4. Volume is important because this is a tool to be used with individuals with ASD, the device must have a low ‘volume, i.e., the sensory experience cannot be overwhelming.
5. Load, by this I mean ‘cognitive’ load is most desirable when not high. We do not want the device to be overwhelming in terms of its cognitive load.
6. Within the selection process, I did not just consider the physical design of the device, but also the way in which the device manifests actions into behaviours. That is, how does the user engage behaviourally within the environment using the device? What about the physical sensation and its path towards a behavioural or emotional response? For example, can we program there to be an activity followed by a reward to reinforce the activity.

### 11.1 Evaluation and Review of the Leap Motion Controller.

#### Advantages

1. Impressive
2. Uses infrared to embed the users (phantom) hand on the screen
3. New technology and novel to bring to laptops
4. Easy to set up
5. Has built in gestures and navigation tools
6. Can work in pretty dimly lit environments (but not all)
7. It is sophisticated (sometimes the polling frequency lets it down)
8. Picks up an impressive distance along the z axis
9. Offers a recalibration process if the controller is persistently jumpy, or there are discontinuities in the tracking data, if there are aberrations in the tracking data that occur in certain areas of the field of view, or poor tracking range. This can be done using the shiny surface such as the computer screen or mirror.

#### Disadvantages

1. Misses small hand movements
2. The range that it will detect is 150 degree angle along the y axis, this is reasonable but not always ideal when gestures/hand movements are large.
3. Some parts of the screen the hands do not reach, i.e., bottom left /right of screen are sometimes hard to reach.
4. Loses the hand, stops working/sensing the hands, even when the controller stays on.
5. Often misses frames, so the user makes larger hand movements and then overshoots (when the LEAP catches up)
6. Built-in controls are not ideal
7. Lighting works best when the hand is seen in silhouette fashion by the controller.

## 12 User Testing the System.

### 12.1 User Verification

Five high AQ scorers were called back for interviews and a focus group. During the interview, individuals were given the same user search queries as in the data collection and research phase of the study. For each transformation that was implemented, users were asked to comment on whether it enhanced or took away from the ease of their search experience, and from their satisfaction with the search results. Users were asked to comment on:

1. Whether they liked the parametric search style of Jellibbeans
2. The ‘narrowing’ the scope for irrelevant detail, with more concrete questions above the search bar
3. Why they may choose Jellibbeans over other search engines, for example, Google
4. The speed and efficiency of search with Jellibbeans
5. The search query results themselves
6. The display and layout of the results

#### 12.1.1 The positives

Users verified that the ‘Dashboard’ colour coding was helpful (see Figure 10). The colour of the chosen type of search remained on screen for its duration.




Figure 10: Colour coding on Jellibean dashboard.

The modals (floating window reminders) for each of the colour themes were useful for newer users, when they were unfamiliar with the colours. The associations for all user groups, including users with Autism, were quick to learn, these were single link visual (rather than verbal) associations.

One tester with high functioning Autism described that the direct question (i.e., ‘What do you want to do on the web?’), with suggestions (‘Shop’, ‘Watch’, ‘Listen’), was useful when he was “at a total blank”. He disclosed that often his need for perfectionism and sameness could have him staring at a blank screen until he came up with the ‘perfect’ query. However, the suggestions were helpful for him to get started, and so his experience was that the queries were completed faster than usual.

During the focus group, participants agreed that one of the major positives of Jellibbeans was that unlike Google, users did not receive back hundreds and thousands of mostly irrelevant results. Jellibbeans held their interest for longer because of the reduced number of results that users had to sift through. Testing also revealed that the parametric search style meant that they did not need to try and remember all the key words to search for, rather the cues helped them remember points they would have missed otherwise.

Another common comment was the time/reward payoff from completing a detailed search form. Users agreed that although they would spend more time formulating their search query, they were likely to save time that would usually be spent sifting through search results.

All users positively commented on the reduced number of search results presented (top 3). The amount of textual information that was presented back on the results page is significantly reduced in Jellibbeans.

### 12.1.2 The negatives

One participant commented that the suggestions on the ‘Do’, ‘Know’, ‘Go’ and ‘Social’ pages were not user-specific. He suggested implementing something that is user-centred, or, trending, rather than static, as these may not be suited for all users. However, one of the aims of the current project was to reduce the restricted and repetitive nature of search queries for people with Autism. One future suggestion for Jellibbeans in order to achieve a balance between user-specific suggestions but not restricted interests, is to include a recommendation system that change often enough for them not to be repetitive.

One (possible) negative that was identified with Jellibbeans was that the time/reward payoff is really only apparent, over and beyond a traditional search engine, when the search query is complex, or if users are searching for something they have yet to identify, or something ambiguous. To overcome this criticism, Jellibbeans includes a ‘Search in Google’ option, so that if users know what they are searching for, they have the option to run the search outside Jellibbeans.

Describe the verification process you used in your project

Unit Testing, Static Analysis for methods in javascript etc.

Manual testing, Selenium, Cucumber etc for html.

Regression tests

## 13 Conclusions and Discussion.

Robots Apache Lucene Sandboxes JavaScript html can't access third party pages Yahoo and Bing was easier and faster to do html scraping

How does it compare to the original specification This work has successfully completed aims XXX

The final section summarizes the project as a whole

A critical evaluation by the student, emphasizing strong points and weak points

lessons learnt

design decisions which, looking back, would be made differently ways in which the project could be improved or extended etc.

recommendations for the project

You can also describe possible future work in the area of your project

### 13.1 Signals of Quality Content

I will test and evaluate the system. Testing will involve assessing the reliability and robustness of Jellibbeans; the ease of its interaction; boundary conditions; ease of use; does it fulfil the aims of

the project. Evaluation of the system will include comparisons to existing search engines; assessing how this idea can be implemented to tailor an existing systems; assessing how well the system does compared to existing systems on a set of criteria that are only relevant to the user group in question (a collective measure of user happiness). Evaluation will also include quantitative metrics such as Recall, Precision, and False Negative/Positive rates.

Apache Solr

### **13.2 Future Directions**

Future directions for the current project would be to develop an API or library for word frequencies in the written English language. These frequency data could have been used to suggest words that were more frequent in the written language for people with Autism, who tend to use idiosyncratic language. This would suggest alternatives for the user.

Alternatively, to use a thesaurus in the current project would be a useful addition.

Maybe google which has access to current trending searches would be able to have the ‘floating’ modals to reflect the trends but the current version of Jellibears is a working example of what could be achieved but with searches that are generally common, rather than trending.

colour blindness considerations - accessibility for people with Autism

## References

- [1] Baron-Cohen, Wheelright, Skinner, Martin, Clubley (2001). The Autism-Spectrum Quotient (AQ): evidence from Asperger Syndrome/high-functioning autism, males and females, scientists and mathematicians. *Journal of Autism and Developmental Disorders*, 31, 5-17.
- [2] Bowler, D. M., Gaigg, S. B., Gardiner, J. M. (2008). Subjective organisation in the free recall learning of adults with Asperger's syndrome. *Journal of Autism and Developmental Disorders*, 38(1), pp. 104-113. doi: 10.1007/s10803-007-0366-4
- [3] Developmental Disabilities Monitoring Network Surveillance (2010) *Centers for Disease Control and Prevention (CDC). Prevalence of autism spectrum disorders: Autism and Developmental Disabilities Monitoring Network, United States. MMWR Surveill Summ.2009; 58, 10:120*
- [4] Executive Function, <https://en.wikipedia.org/wiki/Executivefunctions>, Retrieved 27 August 2015.
- [5] Google Privacy and Terms, <http://www.google.com/policies/technologies/>, Retrieved 27 August 2015.
- [6] JSoup Java API, <http://jsoup.org/>, Retrieved 27 August 2015.
- [7] Laurent Mottron, Jacob A. Burack, Johannes E. A. Stauder, Philippe Robaey (1999) Perceptual Processing among High-functioning Persons with Autism. *Journal of Child Psychology and Psychiatry* 40, (2), 203-211. doi:10.1111/1469-7610.00433.
- [8] Novogrodsky, R. (2013). Subject-pronoun use of Children with Autism Spectrum Disorders (ASD). *Clinical Linguistics and Phonetics*, 27(2), 85-93.
- [9] OpenSearch, <http://www.opensearch.org/Specifications/OpenSearch/1.1>, Retrieved 30 July 2015.
- [10] Fishkin (2015) <https://moz.com/beginners-guide-to-seo/how-people-interact-with-search-engines>, Retrieved 3 August 2015.
- [11] SurveyMonkey, <https://www.surveymonkey.com/home/>, Retrieved 5 August 2015.
- [12] Term Frequency Inverse Document Frequency Weighting, <http://nlp.stanford.edu/IR-book/html/htmledition/tf-idf-weighting-1.html>, Retrieved 9 August 2015.
- [13] Word Frequency Information, <http://www.wordfrequency.info/free.asp?s=y>, Retrieved 6 August 2015.

## 14 Appendices



## 14.1 Search Query Survey

### Search Behaviours

#### Welcome to My Survey

We are trying to understand more about how people with autism, or autistic tendencies, and people without autism search the web.

For the search queries below please indicate what search terms you would use to search the web.

There are no right or wrong answers.

Some of the searches do not have an answer but please tell us how you would go about trying to search for the answer.

If you would do many iterations of search, please indicate that below. Start with the one you are most likely to try.

Please indicate as much as you can about your search process as possible. Use as much space as you need.

There are 10 questions here and this should take approximately 20 minutes or less.

The second part asks you to complete an online questionnaire and report back the score on this sheet.

If you have any questions you can contact [e.massand@bbk.ac.uk](mailto:e.massand@bbk.ac.uk).

Next

### Search Behaviours

#### An Example Question

##### EXAMPLE QUESTION:

You saw a man reading the paper today (you don't know which paper it was), and the headline was vaguely about a new discovery about the solar system. What would you type into search on your favourite search engine to find out about the story?

##### EXAMPLE ANSWER:

I could start by searching, 'solar system and discovery and news and today'.

If that doesn't work I could search, 'today's paper and solar system', or if I don't find my answer there I could search 'news' and manually /visually sift the page for relevant info.

Prev

Next

## Search Behaviours

1.

What browser do you usually use? (Google Chrome, Internet Explorer, Safari, Firefox ...)

and

What search engine do you usually use? (Google, Bing, Yahoo ...)

Prev

Next

## Search Behaviours


2. You hear a song on the radio with the lyrics, "Look at your children", and you want to download it. What would you type into search on your favourite search engine to find out what song it was?

3. You've lost touch with an old school friend (you went to St. Mary's School). What key words/queries would you use to find them?



4.

How would you identify what this is using a search engine (pretend you don't know what it is called). What key words/queries would you use?



5.

How would you find out the name of this famous person using a search engine? What key words/queries would you use?



6. Two repeats shown

What would you search for to identify this pattern's name, and which country it originates from?



7.

How would you identify what breed this dog is using a search engine? What key words/queries would you use

8. Your friend and you can't agree on how Thandie Newton pronounces her first name. How would you resolve this using a search engine?

9. How would you search for information relating to your (imminent) flight to Paris?

10. <http://aspergerstest.net/aq-test/>

Go to the link above and report back your score on the Autism Quotient. There are 2 formats, please take 'AQ Quiz Option 1'.

Prev

Done

Figure 11: Search Query Survey on Surveymonkey.com [11]

## 14.2 Questions on the Autism Spectrum Quotient [1]

Participants are asked to read each statement very carefully and rate how strongly they agree or disagree with the statement (Strongly Disagree, Slightly Disagree, Slightly Agree, or, Strongly Agree).

I prefer to do things with others rather than on my own.  
I prefer to do things the same way over and over again.  
If I try to imagine something, I find it very easy to create a picture in my mind.  
I frequently get so strongly absorbed in one thing that I lose sight of other things.  
I often notice small sounds when others do not.  
I usually notice car number plates or similar strings of information.  
Other people frequently tell me that what Ive said is impolite, even though I think it is polite.  
When Im reading a story, I can easily imagine what the characters might look like.  
I am fascinated by dates.  
In a social group, I can easily keep track of several different peoples conversations.  
I find social situations easy.  
I tend to notice details that others do not.  
I would rather go to a library than a party.  
I find making up stories easy.  
I find myself drawn more strongly to people than to things.  
I tend to have very strong interests which I get upset about if I cant pursue.  
I enjoy social chit-chat.  
When I talk, it isnt always easy for others to get a word in edgeways.  
I am fascinated by numbers.  
When Im reading a story, I find it difficult to work out the characters intentions.  
I dont particularly enjoy reading fiction.  
I find it hard to make new friends.  
I notice patterns in things all the time.  
I would rather go to the theatre than a museum.  
It does not upset me if my daily routine is disturbed.  
I frequently find that I dont know how to keep a conversation going.  
I find it easy to read between the lines when someone is talking to me.  
I usually concentrate more on the whole picture, rather than the small details.  
I am not very good at remembering phone numbers.  
I dont usually notice small changes in a situation, or a persons appearance.  
I know how to tell if someone listening to me is getting bored.  
I find it easy to do more than one thing at once.  
When I talk on the phone, Im not sure when its my turn to speak.  
I enjoy doing things spontaneously.  
I am often the last to understand the point of a joke.  
I find it easy to work out what someone is thinking or feeling just by looking at their face.  
If there is an interruption, I can switch back to what I was doing very quickly.  
I am good at social chit-chat.  
People often tell me that I keep going on and on about the same thing.  
When I was young, I used to enjoy playing games involving pretending with other children.  
I like to collect information about categories of things (e.g. types of car, types of bird, types of train, types of plant, etc.).  
I find it difficult to imagine what it would be like to be someone else.  
I like to plan any activities I participate in carefully.  
I enjoy social occasions.

I find it difficult to work out peoples intentions.  
New situations make me anxious.  
I enjoy meeting new people.  
I am a good diplomat.  
I am not very good at remembering peoples date of birth.  
I find it very easy to play games with children that involve pretending.