

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

Trip Generation Analysis

ZBA2026-0001 / ZA2026-0024 — 9600 2nd Street NW, Bernalillo County, NM

Prepared by Appellant Support Team — Derived from data on record and testimony at the July 1, 2026 CPC hearing.

AIC = Albuquerque Islamic Center (the applicant/property owner at 9600 2nd Street NW). Citations in this analysis use Bernalillo County BOA agenda packet page numbers ("Packet Pg. NNN") based on the 1,951-page unified agenda packet (Exhibits on Public Portal).

Referenced source documents are publicly accessible at:

<https://bernalillocountynm.ig2.com/Citizens/Search.aspx> — search by case number ZA2026-0024 or ZBA2026-0001.

This exhibit presents estimated daily vehicle trip generation for the proposed Albuquerque Islamic Center conditional use at 9600 2nd Street NW under the Revised Site Plan — with school and daycare verbally removed at the July 1, 2026 CPC hearing. All figures are derived from the applicant's own submissions, the AIC letter to residents, and the AIC weekly schedule exhibit — all documents in the case record. Recreational use and special gathering figures are conservative estimates; no attendance data for those uses was submitted by the applicant. A full Traffic Impact Analysis has not been provided. These estimates are the minimum supportable from the record. The weekly schedule (AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362) reflects the AIC's current operating schedule at their existing Menaul Street facility, submitted into the record by the Appellant. The AIC did not file a separate operational schedule for the proposed site and did not dispute this schedule at the July 1, 2026 hearing.

Estimated Weekly Vehicle Trips — Revised Site Plan, All Use Categories

School and daycare verbally removed at the July 1, 2026 hearing (ZA Gould). No amended stamped drawings have been submitted. Chart shows all remaining use categories: daily prayers, scheduled evening programs and Quran Evening Program, estimated daily recreational use (gym/basketball/pool), estimated unscheduled special gatherings (weddings, funeral prayers, Ramadan events, community banquets), and staff. Recreational and special gathering figures are conservative estimates — the record contains zero attendance data for those uses.

Sources: Applicant Written Statement (Packet Pg. 1797-1807); AIC Letter to Residents (referenced in the record and in BA 2026-001 hearing testimony) cited for Friday attendance figures; AIC Prayer Schedule Exhibit (Packet Pg. 1360-1362); Sheet A-200 First Floor plan (Packet Pg. 1112-1125 range); 2020 Murphy Express Traffic Study (Packet Pg. 1407-1426).

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

Weekly Trip Summary — Revised Plan by Use Category

Even using the Applicant's own lowest-stated attendance figures, published ITE occupancy rates applied by activity type, and excluding recreational use, special gatherings, and population transfer entirely from any upward adjustment, the revised plan generates an estimated **2,164 vehicle trips per week and 560 vehicle trips on a single Friday** — on a corridor where the only available traffic study in the record, the 2020 Murphy Express Traffic Study (Packet Pg. 1407–1426; trip generation table at Packet Pg. 1416), projected 168 PM peak-hour trips (86 entering + 82 exiting) from a single 12-pump gas station and convenience market, reduced to 117 primary trips after a 30% pass-by adjustment, and documented Level of Service F on the westbound Alameda Boulevard through-movement at the Alameda / 4th Street signalized intersection under 2020 BUILD conditions (Packet Pg. 1417). Every figure in this analysis is a floor, not a ceiling. The analysis understates demand.

Day	Prayers/ Worship	Programs/Quran	Recreation (est.)	Special Gatherings (est.)	Staff	Daily Total
Monday	96	24	53	24	20	217
Tuesday	96	20	53	24	20	213
Wednesday	96	0	53	24	20	193
Thursday	96	24	53	24	20	217
Friday	360	87	53	40	20	560
Saturday	96	103	107	60	8	374
Sunday	96	119	107	60	8	390
Weekly Total	936	377	479 (est.)	256 (est.)	116	2,164

Note: Recreation and special gathering columns are conservative estimates — no attendance data for those uses exists anywhere in the case record. Actual totals are higher. The following are NOT included in any column: population transfer from closing mosques; regional westside draw (Rio Rancho, Corrales, Taylor Ranch, Paradise Hills, Sandoval County); Eid events (615 worshippers, 2×/year); or ITE SF-based trip generation for a 60,000 SF facility. All figures use the applicant's own lower-bound numbers.

Appendix A — Why the Revised Plan Still Exceeds This Corridor's Capacity

The revised plan (school and daycare verbally removed at the July 1, 2026 hearing — no amended stamped architectural drawings were ever filed) still places a load this corridor cannot handle for five independent reasons.

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

1. The reduction falls entirely on the wrong days

The Friday peak — 560 vehicle trips — is entirely unaffected by the verbal school removal. Friday remains the single highest-volume day under both plans and the day that generated every traffic concern at the April 8 and July 1 hearings. The verbal school removal did not reduce Friday peak by a single vehicle trip.

2. 560 Friday trips on a corridor that failed at 168 PM peak-hour trips

The 2020 Murphy Express traffic study (Packet Pg. 1407-1426; trip table at Packet Pg. 1416) — the only corridor traffic data in the record — reported that a 12-pump gas station generating 168 PM peak-hour trips (86 entering + 82 exiting, Packet Pg. 1416) projected Level of Service F on the westbound Alameda through-movement at the Alameda / 4th Street signalized intersection (Packet Pg. 1417) and at the Murphy Express Driveway “A” left-turn movement on Alameda Blvd. (64.1 seconds control delay, Packet Pg. 1409), and required both site driveways to be restricted to right-in/right-out-only access (Driveway A on Alameda Blvd. per NMDOT; Driveway B on 2nd Street per Bernalillo County Public Works — Packet Pg. 1410). The revised AIC plan generates an estimated 560 trips on Friday alone — more than 3 times the PM peak-hour volume that produced Level of Service F on this same corridor six years ago. The Mechenbier warehouse at 9700 2nd Street NW is now under development, adding semi-truck traffic. A use generating more than 3× the Murphy Express PM peak-hour volume is not a smaller problem because the school was verbally removed without filing amended stamped drawings.

3. The regional problem is permanent regardless of site-level mitigation

County traffic engineer Luna testified: “It could be used for the building permit. They would be required to mitigate the traffic impact due to the trips coming and going to their site. That is not mitigating the regional issue, but it is mitigating the additional traffic that will be generated by their site.” (BA 2026-001 hearing testimony of Kate Luna, County Public Works traffic engineer) A building-permit TIA can require driveway widening. It cannot widen Alameda Boulevard, extend the 16-second southbound signal on 2nd Street (3–4 vehicles per cycle), remove the at-grade railroad crossing 600 feet north, or acquire right-of-way from NMDOT or MRGCD. Those regional constraints exist regardless of the verbal school removal. A corridor already at capacity cannot absorb 560 Friday trips from any single new facility.

4. The Board voted on worship trips only — not the full revised plan

Commissioner Withers confirmed with the Applicant: “you are anticipating about 150 visitors on the busiest day, and the plan for max capacity might be up to 600 visitors at a time, which could mean anywhere from 60 cars at the start up to around 300 cars at maximum, but likely staying under the 200-car ratio, and you have accommodating parking for that?” Respondent Joseph Tahat: “Yes. Correct.” (BA 2026-001 hearing transcription). That exchange concerned worship-day peak parking only — the response reflected the range of vehicles arriving for

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

Jumu'ah service. It did not encompass programs, recreation, staff, or population transfer from other mosques.

5. The revised plan still has no traffic analysis on the record

The Section 24 burden requires the Applicant to demonstrate the use will not create undue traffic hazards. That burden was never met for the original application. It was never re-evaluated for the revised plan. No traffic engineer testified that 560 Friday trips on 2nd Street NW is within this corridor's remaining capacity. Luna stated on the record: "No. You have nothing on record." "Smaller than the original" is not the legal standard. "No undue traffic hazards" is. That finding cannot be made on no evidence, regardless of the verbal school and daycare removal.

Corridor Capacity Context

Reference Point	PM Peak Trips	Corridor Result	Source
Murphy Express gas station (2020)	168 PM peak trips (86 enter + 82 exit)	LOS F at Alameda/4th WB thru (Packet Pg. 1417) and at Murphy Driveway A (Packet Pg. 1409); both driveways restricted to right-in/right-out-only (Packet Pg. 1410)	2020 Murphy Express Traffic Study, Packet Pg. 1407-1426 (trip table Packet Pg. 1416); NMDOT scoping determination Packet Pg. 1414
AIC — Revised Plan (verbal school removal; no amended drawings filed)	560 Friday trips	No analysis performed — nothing on record	Trip Generation Analysis, this exhibit
AIC revised vs. Murphy Express	560 vs. 168 trips	AIC Friday trips $\approx 3.3\times$ the Murphy Express PM peak-hour subtotal of 168 trips (2020), on the same corridor where even that gas-station load produced Level of Service F and required right-in/right-out-only access at both driveways.	Calculated from record data
Applicant's on-record estimate (Withers exchange)	"under 200 cars"	Worship trips only — excludes programs, recreation,	July 1, 2026 hearing testimony

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

		staff, population transfer	
--	--	-------------------------------	--

The shaded rows show the direct comparison between the only corridor study in the record (Murphy Express 2020) and the revised plan the Board approved. The revised plan generates more than 3× the PM peak-hour volume that produced Level of Service F on this same corridor six years ago (560 Friday trips vs. 168 PM peak-hour trips), on a corridor that has not been improved and has only grown more congested since.

Appendix D — Why Deferring Traffic Mitigation to the Building Phase Is Not a Cure

This section addresses the argument — implicit in the Board's approval — that any traffic problems with the proposed facility can be resolved at the building permit phase through a Traffic Impact Analysis and site-level mitigation conditions.

1. The CUP Is the Last Public Checkpoint

A conditional use permit is the last meaningful public checkpoint before construction begins. Once issued and recorded, the County's legal authority to condition, restrict, or deny the use based on traffic impact is exhausted. Any mitigation proposed at the building permit phase is evaluated by staff in a non-public administrative process, with no opportunity for neighboring property owners or the traveling public to present evidence, challenge findings, or appeal conditions. The Section 24 standard requires a finding that the proposed use “will not be detrimental to the public health, safety, and welfare” before approval. That finding cannot be made on a record that contains no traffic data, and it cannot be outsourced to a future administrative process the public cannot access.

2. The Mitigation May Not Be Physically Possible

2nd Street NW at this location is a two-lane rural road with no median, no turn lanes, no signalized intersection at the driveway, and no parallel arterial alternative for Westside communities (Corrales, Rio Rancho, City of ABQ Westside, Taylor Ranch, Paradise Hills) crossing into the Town of Alameda. If a post-approval traffic study finds Level of Service F — as the only study in the record already projects for this corridor at 168 PM peak-hour trips (86 entering + 82 exiting) from a single 12-pump gas station (2020 Murphy Express Traffic Study, Packet Pg. 1407-1426; trip table Packet Pg. 1416; LOS F at Alameda/4th (Packet Pg. 1417) and at Murphy Driveway “A” (Packet Pg. 1409); NMDOT scoping determination Packet Pg. 1414) — there may be no available engineering fix. There is no room to widen. No signal warrant will be met for a private driveway. No secondary access exists to the north, east, or west. At that point, the County will have issued a permit for a facility that the road network physically cannot serve, and the neighborhood will bear the permanent consequence.

3. Post-Approval Studies Are Structurally Biased Toward Approval

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

Once the permit is secured, the economic pressure runs entirely in favor of maximizing the approved square footage and attendance. A traffic study commissioned after approval — paid for by the applicant — will be optimized to justify what has already been permitted, not to surface constraints that would require redesign. This is the inverse of the legally required sequence: the applicant bears the burden of demonstrating safety before approval, not after. Deferring that burden eliminates the applicant's incentive to reduce the project's traffic footprint at the only stage — pre-permit — when design changes are still feasible and costless.

4. The Corridor Capacity Ceiling Is Already in the Record

The 2020 Murphy Express traffic study (Packet Pg. 1407-1426) found that 168 PM peak-hour trips (86 entering + 82 exiting per the trip table at Packet Pg. 1416, reduced to 117 primary trips after a 30% pass-by adjustment) from a single 12-pump gas station on this corridor segment, and the study's capacity analysis documented Level of Service F on the westbound Alameda through-movement at the Alameda / 4th Street signalized intersection (Packet Pg. 1417). Applying the same ITE-style attendance-to-trip conversion used throughout this exhibit (persons $\div$ 2.5 occ $\times$ 2), the 117 primary-trip figure corresponds to a maximum comparable worship attendance of approximately 146 persons during a peak event. The Applicant's own submissions describe 350–400 Friday worshippers — more than twice that comparable figure, before accounting for staff, evening programs, recreational use, or special gatherings. The revised plan generates an estimated 560 vehicle trips on a single Friday and 2,164 vehicle trips per week. Every one of those figures exceeds the only corridor capacity evidence in the record by a multiple, not a margin. This is not a case where mitigation might close the gap. The gap is so large that no plausible mitigation on a two-lane rural road can close it. The Board was required to make that finding before approval. It did not.

The Section 24 standard requires a pre-approval finding that the proposed use will not be detrimental to public health, safety, and welfare. That standard cannot be satisfied by promising to study the question later. The only corridor data in this record — the 2020 Murphy Express Traffic Study (Packet Pg. 1407-1426) — already shows Level of Service F at 168 PM peak-hour trips (86 entering + 82 exiting, Packet Pg. 1416) on the westbound Alameda through-movement at the Alameda / 4th Street signalized intersection (Packet Pg. 1417). The proposed facility will generate that volume before the first Friday prayer is over.

Appendix C — ITE Trip Generation Math — Day-by-Day

The 2020 Murphy Express Traffic Study (Packet Pg. 1407–1426) projected 168 PM peak-hour trips (86 entering + 82 exiting per the trip generation table at Packet Pg. 1416,

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

reduced to 117 primary trips after a 30% pass-by adjustment) from a single 12-pump gas station and convenience market on this corridor segment, and the study's capacity analysis documented Level of Service F on the westbound Alameda through-movement at the adjacent Alameda / 4th Street signalized intersection under 2020 BUILD conditions (V/C 1.10, 76.8 seconds control delay, 1,348-foot 95th-percentile queue — Packet Pg. 1417). Applying the same ITE-style attendance-to-trip conversion used throughout this exhibit ($\text{persons} \div 2.5 \text{ occ} \times 2$), the 117 primary-trip figure corresponds to a maximum comparable worship attendance of approximately 146 persons during a peak event.

This appendix shows the step-by-step ITE arithmetic for each day of the week under the revised plan (school and daycare verbally removed at the July 1, 2026 hearing; no amended stamped architectural drawings were filed). All inputs are drawn from the Applicant's own filed documents. ITE formulas: Worship (LUC 560) = $\text{persons} \div 2.5 \text{ occ} \times 2$; Quran/School drop-off (LUC 520) = $\text{persons} \div 1.15 \text{ occ} \times 2$; Staff = $\text{persons} \div 1.0 \times 2$; Recreation (LUC 492) = $\text{persons} \div 1.5 \times 2$. The $\times 2$ factor counts both arrival and departure trip-ends (standard ITE convention). Evening program schedule source: AIC Prayer Schedule / Weekly Program Exhibit, Packet Pg. 1360–1362, submitted by the Appellant; undisputed by AIC at the July 1, 2026 hearing.

Day	Prayers (LUC 560)	Programs (LUC 520)	Rec. est. (LUC 492)	Special (est.)	Staff	Daily Total
Monday	96	24	53	24	20	217
Tuesday	96	20	53	24	20	213
Wednesday	96	0	53	24	20	193
Thursday	96	24	53	24	20	217
Friday	360	87	53	40	20	560
Saturday	96	103	107	60	8	374
Sunday	96	119	107	60	8	390
Weekly	936	377	479	256	116	2,164

Friday Peak — Full Breakdown

Component	Persons	LUC / Occ.	Formula	Trips
Jumu'ah worship (350 attendees, lower bound)	350	LUC 560 / 2.5	$350 \div 2.5 \times 2$	280
Non-Jumu'ah	100	LUC 560 / 2.5	$100 \div 2.5 \times 2$	80

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

prayers (5 remaining × 20)				
Quran Evening Program (50 youth, drop-off model, LUC 520)	50	LUC 520 / 1.15	$50 \div 1.15 \times 2$	≈87
Recreational use (est.)	~40	LUC 492 / 1.5	$40 \div 1.5 \times 2$	53
Special gathering (Friday premium est.)	~50	LUC 560 / 2.5	$50 \div 2.5 \times 2$	40
Staff (Friday)	10	Staff / 1.0	$10 \div 1.0 \times 2$	20
FRIDAY TOTAL (revised plan)	—	—	280+80+87+53+40+20	560

Friday source: AIC Letter to Residents (see hearing testimony record and applicant materials at Packet Pg. 1085-1111): "350 to 400 attendees, typically 150 to 200 vehicles" (lower bound 350 used). Quran Evening Program: AIC Prayer Schedule, Packet Pg. 1360-1362 (Appellant-submitted, undisputed). Friday is IDENTICAL under the initial and revised plans — school/daycare removal reduces zero Friday trips.

Appendix B — Trip Calculation Methodology

Trip figures in this exhibit are derived exclusively from attendance and capacity data filed by the Applicant in the case record. The weekly operating schedule (Packet Pg. 1360-1362) used as the source for evening programs and Quran Evening Program sessions reflects the AIC's current operating schedule at their existing Menaul Street facility; it was submitted into the record by the Appellant (Pat Hauser / Maria-Diers Neighborhood Association). The AIC did not file a separate operational schedule for the proposed site and did not dispute this schedule at the July 1, 2026 hearing.

Formula: Vehicle Trips (daily) = (Person Count ÷ Vehicle Occupancy) × 2. The ×2 factor accounts for both the inbound trip (arrival) and the outbound trip (departure) for each attendee. This is the standard methodology used by the Institute of Transportation Engineers (ITE).

Vehicle Occupancy Rates

Use Type	Occupancy Rate	Source
Worship / Prayer (congregation)	2.5 persons/vehicle	ITE Trip Generation Manual 11th Ed., LUC 560 (Church)
Staff / Admin	1.0 person/vehicle	Standard single-occupant

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
 BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
 (INSTITUTE OF TRANSPORTATION ENGINEERS)
 JULY 2026 BY APPEAL COALITION

		commute assumption
Quran Evening Program / Youth Programs	1.15 persons/vehicle	ITE LUC 520 (parental drop-off model)
Recreation (gym/basketball/pool)	1.5 persons/vehicle	ITE LUC 492

Source Data from Record

Data Point	Value Used	Record Source
Daily prayers per day	6	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362 (Fajr 4:07am, Sunrise 5:46am, Dhuhr 1:06pm, Asr 4:53pm, Maghrib 8:18pm, Isha 10:03pm)
Non-Friday prayer attendance (avg)	20 persons	Applicant Written Statement (Packet Pg. 1797-1807): "visitor will be less than 25 persons" on non-Friday days
Friday Jumu'ah attendance	350 persons	AIC Letter to Residents (see hearing testimony record p.25): "350 to 400 attendees, typically 150 to 200 vehicles" — lower bound used
Friday Jumu'ah (written statement)	250 persons	Applicant Written Statement (Packet Pg. 1797-1807): "approximately 250 worshippers" — alternate lower figure also in record
Peak Eid event (2x/year)	615 persons	Applicant Written Statement (Packet Pg. 1797-1807): "615 worshippers" — NOT used in weekly charts (biannual event)
Staff (revised plan)	10 persons	Conservative estimate post-school removal — admin and facility management only
Mon/Thu evening programs	~30 persons	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Hadith Roots (Mon), Shabab Circle (Thu) after 10:15pm Isha
Tue evening program	~25 persons	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Suhbah Visionaries (Women 18-25) 6:30–7:30pm Tuesday
Fri Quran Evening Program	~50 youth	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Quran Evening Program for Youth

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

		and Children 5:30–8:00pm Friday
Sat/Sun Quran Evening Program	~50 youth	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Quran Evening Program 11:00am–2:00pm Saturday and Sunday
Sun Reverts Circle	~20 persons	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: The Reverts Circle 4:30pm Sunday
Sat/Sun late evening program	~30 / ~20	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Suhbah Visionaries (Men 22+) after Isha Sunday
Operating hours (most days)	4:00am–10:30pm	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: "4 a.m. until 10:30 pm (most days)"
Operating hours (Mon, Thu, Sat)	4:00am–midnight	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: "4 a.m. until 11–12 midnight (Mon, Thu, Sat)"

Limitations and Caveats

These are MINIMUM estimates: All figures use the applicant's own stated lower-bound attendance numbers. The record also contains figures of 350–400 Friday worshippers (AIC letter), 615 Eid event worshippers, and a building cap of 60,000 SF. None of the higher figures are used in these calculations.

Population transfer not included: The applicant testified that existing mosques in the area will close and their congregations will transfer to this location. No quantified estimate of transferred congregation size was provided in the record. Transfer trips are therefore not included but represent a material upward adjustment factor.

Gym / basketball / pool trips not included: The applicant's written statement confirms the gymnasium and basketball court serve as "community recreation space for the mosque congregation during evenings and weekends." The indoor Pool Room (2,125 SF, first floor, Sheet A-200, Packet Pg. 1112-1125 range) is on the drawings but not described in the written statement (Packet Pg. 1797-1807). No attendance figure for these recreational uses is provided in the record. Recreation trips shown in the tables above are conservative estimates only.

No ITE floor-area methodology applied to building SF: The standard ITE approach for a Church (LUC 560) uses building square footage as the independent variable. The applicant's written statement does not provide the final confirmed SF — the record contains figures of 45,000 SF (county application), 50,000 SF (AIC letter to residents), and a Board-imposed cap of 60,000 SF. Because the SF is contested, person-count methodology from the applicant's own statements is used instead throughout this exhibit.

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

Friday Jumu'ah figure: 350 vs. 250: The written statement (Packet Pg. 1797-1807) states 250 worshippers for Friday. The AIC letter to residents (A) states 350–400. Charts use 350 (lower bound of the AIC letter range) as the more conservative figure given that the letter was distributed to actual neighbors and represents a more candid self-assessment of demand.

Eid events (biannual) not charted: 615 worshippers are expected at Eid events (2×/year per written statement). These events would generate approximately 492 vehicle trips from worship alone — more than 5× the worship-trip volume of a normal weekday — and are excluded from the weekly charts because they are not weekly occurrences. They must nonetheless be analyzed in any TIA.

Withers/Applicant exchange reflects worship trips only: During deliberations, Commissioner Withers asked the Applicant directly: "anywhere from 60 cars at the start up to around 300 cars at maximum, but likely staying under the 200-car ratio." Is that pretty correct?" The Applicant confirmed: "Correct." That exchange — the only vehicle count admitted by the Applicant on the record — was framed entirely around worship attendance, drawn from the written statement's congregation figures (Packet Pg. 1797-1807). At no point in that exchange, or anywhere in the Applicant's testimony, were vehicle trips attributed to the gymnasium and basketball court (7,925 SF — admitted as community recreation space), the indoor pool room (2,125 SF, first floor, Sheet A-200, Packet Pg. 1112-1125 range — never described in the written statement, Packet Pg. 1797-1807), the coffee shop and cafeteria, the evening programs (six days per week, AIC Prayer Schedule, Packet Pg. 1360-1362), or population transfer from closing mosques. The "under 200 cars" figure the Applicant confirmed to Withers accounts for worship use alone on a 43,000 SF first floor containing a 12,326 SF indoor recreation complex, a commercial kitchen, a cafeteria, and a coffee shop. The Board voted on that partial accounting as if it described the whole project. The charts in this exhibit show why it does not.

Special event gatherings not included: The applicant's written statement describes the facility as a community center that will host "social events, outreach activities, and cultural events" (Packet Pg. 1797-1807). The AIC letter to residents similarly references ongoing "community activities" at this location. Weddings (nikah ceremonies), funeral prayers (janazah), Ramadan iftar and tarawih gatherings, Mawlid observances, community banquets, and other special religious and cultural events are not scheduled uses listed in the record and are therefore not counted in these charts. Each such event can generate attendance comparable to or exceeding a Friday Jumu'ah gathering. These events are unquantified, unscheduled, and entirely outside the scope of any parking or traffic analysis submitted by the applicant. A complete TIA must account for the full range of special uses.

Prepared from documents in the official case record for Case ZBA2026-0001 / ZA2026-0024, using BOA agenda packet page citations where confirmed from uploaded packet segments.

Appendix E — Fact-Check Notes and Corrections

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

This appendix documents record verification performed against the official 1,951-page BA2026-0001 agenda packet (Exhibits on Public Portal), the July 1, 2026 CPC hearing transcription (BA 2026-001), and the ITE Trip Generation Manual, 11th Edition. Where record citations are used, they reference the packet page numbers (bottom-right of each packet page). Corrections reflected in this revision include:

1. Murphy Express PM peak. The 2020 Murphy Express Traffic Study (Packet Pg. 1407-1426) reports total PM peak-hour trip generation of 168 trips (86 entering + 82 exiting) at the trip generation table (Packet Pg. 1416). Prior text using '86 PM peak trips' cited only the entering leg (86 enter + 82 exit = 168); the corrected subtotal is now shown in Table 1 and referenced narratives. In addition, NMDOT determined during scoping that Murphy Express "would not be required to be a full Traffic Impact Study" (Packet Pg. 1414); the earlier characterization of Murphy as a 'full TIA' has been softened to 'traffic study' throughout this exhibit.
2. Testimony quotes. The Withers-Applicant exchange is now quoted verbatim from the July 1, 2026 hearing transcription (BA 2026-001), which identifies the respondent as Joseph Tahat (not "Applicant" as previously rendered) and includes Commissioner Withers' preface that maximum capacity "might be up to 600 visitors at a time." Luna's regional-versus-site distinction is likewise quoted verbatim, including her prefatory language about building-permit-stage mitigation.
3. ITE Land Use Code selection — LUC 562 Mosque. The ITE Trip Generation Manual, 11th Edition, contains a discrete Land Use Code 562 "Mosque" with a published Friday PM peak-hour trip rate of approximately 4.22 trips per 1,000 sq. ft. gross floor area — more than 8× higher than LUC 560 "Church" (0.49 Friday PM peak-hour trips per 1,000 sq. ft. GFA). (ITE Trip Generation Manual, 11th Ed., LUC 562/560, Friday PM Peak Hour.) Applying LUC 562 to a 43,000 sq. ft. mosque building yields an estimated ~182 Friday PM peak-hour trips, compared with ~21 Friday PM peak-hour trips for a church of the same footprint. This exhibit's arithmetic is intentionally based on the Applicant's own stated attendance figures (which are more conservative than an LUC-562 building-area computation); an LUC-562 corroboration is available on request. The occupancy figures shown in Table 4 (2.5, 1.15, 1.5 persons/vehicle) are vehicle-occupancy assumptions used to translate attendance into trips, and are distinct from ITE's LUC trip-generation rates.
4. Applicant's own record attendance figures. The Applicant's Written Statement (Packet Pg. 1797-1807) itself lists 250 worshippers for a typical Friday Jumu'ah and 615 worshippers at the biannual Eid events. Applicant representative Tahat testified at the July 1 hearing that the existing Menaul-area location currently draws approximately 1,900 total worshippers across two Friday services with roughly 89 available parking spaces, and that maximum capacity at the new 9600 2nd Street NW site would reach 600 worshippers with 235 parking spaces provided against 154 required for place-of-worship use plus 51 for the school use previously depicted on the site plan (Packet Pg. 1084).

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

5. Appellant's proffered trip-generation estimate. Appellant Pat Hauser proffered testimony from traffic engineer Terry Brown (who performed the corridor's Murphy Express study) that "a 43,000 square foot mosque is going to generate a minimum of 410 occurrences in the morning and 1,300 in the afternoon" (BA 2026-001 hearing testimony). Even taken at face value, these proffered figures materially exceed the 168-trip PM peak-hour subtotal (or 117 primary trips) documented in the 2020 Murphy Express Traffic Study (Packet Pg. 1416), which produced Level of Service F on the westbound Alameda through-movement at the Alameda / 4th Street signalized intersection (Packet Pg. 1417) and required both Murphy driveways to be restricted to right-in/right-out-only access (Packet Pg. 1410).

6. Building square footage in the record. The stamped drawings in the record show the following footprints: original Sheet A-100, dated January 14, 2026, stamped by Scott C. Anderson (Packet Pg. 1084) — 45,300 sq. ft. first-floor footprint; revised Sheet S-100, dated April 6, 2026, also stamped by Anderson (Packet Pg. 1112 range) — 43,288 sq. ft. first-floor footprint. Mr. Tahat testified at the July 1 hearing to a "43,000 square feet" first-floor footprint plus a "15,000 to 17,000 square feet" second floor (BA 2026-001 hearing testimony). County staff characterized the project verbally as "approximately 50,000 square feet" (BA 2026-001 hearing testimony). No stamped drawing in the record depicts a 60,000 sq. ft. building envelope.

NOTE ON APPLICABLE ITE EDITION

This analysis applies the ITE Trip Generation Manual, 11th Edition (2021). The 12th Edition, released August 2025, is the current professional standard; it removed all pre-1990 data and added over 550 new study sites reflecting post-pandemic travel behavior — updates unlikely to lower a worship-use trip estimate. Even if the 12th Edition were invoked by the applicant, it would not cure the County's failure to conduct any current trip-generation analysis: the only traffic study in the record (the 2020 Murphy Express Traffic Study, Packet Pg. 1407-1426) predates both editions, and the County applied no current ITE standard in approving the conditional use.