

EXHIBIT 15

Trip-Generation Calculation Charts

ZBA2026-0001 / ZA2026-0024 — 9600 2nd Street NW, Bernalillo County, NM

The underlying ITE calculation tables and record source-data charts that follow are excerpted from the Trip Generation Analysis (Exhibit 14) and consolidated here for ready reference. They include:

- Weekly Trip Summary — revised plan by use category (2,164 weekly / 560 Friday).
- Corridor Capacity Context — Murphy Express 2020 PM peak (168 trips) vs. revised plan.
- Step-by-step ITE arithmetic by day (LUC 560 Worship, LUC 520 Programs, LUC 492 Recreation).
- Vehicle-occupancy assumptions and record source-data charts.

The full narrative analysis, methodology, and Packet Pg. citations remain in Exhibit 14. Figures here are excerpted verbatim; page footers reflect their original location in Exhibit 14.

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

Weekly Trip Summary — Revised Plan by Use Category

Even using the Applicant's own lowest-stated attendance figures, published ITE occupancy rates applied by activity type, and excluding recreational use, special gatherings, and population transfer entirely from any upward adjustment, the revised plan generates an estimated **2,164 vehicle trips per week and 560 vehicle trips on a single Friday** — on a corridor where the only available traffic study in the record, the 2020 Murphy Express Traffic Study (Packet Pg. 1407–1426; trip generation table at Packet Pg. 1416), projected 168 PM peak-hour trips (86 entering + 82 exiting) from a single 12-pump gas station and convenience market, reduced to 117 primary trips after a 30% pass-by adjustment, and documented Level of Service F on the westbound Alameda Boulevard through-movement at the Alameda / 4th Street signalized intersection under 2020 BUILD conditions (Packet Pg. 1417). Every figure in this analysis is a floor, not a ceiling. The analysis understates demand.

Day	Prayers/ Worship	Programs/Quran	Recreation (est.)	Special Gatherings (est.)	Staff	Daily Total
Monday	96	24	53	24	20	217
Tuesday	96	20	53	24	20	213
Wednesday	96	0	53	24	20	193
Thursday	96	24	53	24	20	217
Friday	360	87	53	40	20	560
Saturday	96	103	107	60	8	374
Sunday	96	119	107	60	8	390
Weekly Total	936	377	479 (est.)	256 (est.)	116	2,164

Note: Recreation and special gathering columns are conservative estimates — no attendance data for those uses exists anywhere in the case record. Actual totals are higher. The following are NOT included in any column: population transfer from closing mosques; regional westside draw (Rio Rancho, Corrales, Taylor Ranch, Paradise Hills, Sandoval County); Eid events (615 worshippers, 2×/year); or ITE SF-based trip generation for a 60,000 SF facility. All figures use the applicant's own lower-bound numbers.

Appendix A — Why the Revised Plan Still Exceeds This Corridor's Capacity

The revised plan (school and daycare verbally removed at the July 1, 2026 hearing — no amended stamped architectural drawings were ever filed) still places a load this corridor cannot handle for five independent reasons.

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

Jumu'ah service. It did not encompass programs, recreation, staff, or population transfer from other mosques.

5. The revised plan still has no traffic analysis on the record

The Section 24 burden requires the Applicant to demonstrate the use will not create undue traffic hazards. That burden was never met for the original application. It was never re-evaluated for the revised plan. No traffic engineer testified that 560 Friday trips on 2nd Street NW is within this corridor's remaining capacity. Luna stated on the record: "No. You have nothing on record." "Smaller than the original" is not the legal standard. "No undue traffic hazards" is. That finding cannot be made on no evidence, regardless of the verbal school and daycare removal.

Corridor Capacity Context

Reference Point	PM Peak Trips	Corridor Result	Source
Murphy Express gas station (2020)	168 PM peak trips (86 enter + 82 exit)	LOS F at Alameda/4th WB thru (Packet Pg. 1417) and at Murphy Driveway A (Packet Pg. 1409); both driveways restricted to right-in/right-out-only (Packet Pg. 1410)	2020 Murphy Express Traffic Study, Packet Pg. 1407-1426 (trip table Packet Pg. 1416); NMDOT scoping determination Packet Pg. 1414
AIC — Revised Plan (verbal school removal; no amended drawings filed)	560 Friday trips	No analysis performed — nothing on record	Trip Generation Analysis, this exhibit
AIC revised vs. Murphy Express	560 vs. 168 trips	AIC Friday trips $\approx 3.3\times$ the Murphy Express PM peak-hour subtotal of 168 trips (2020), on the same corridor where even that gas-station load produced Level of Service F and required right-in/right-out-only access at both driveways.	Calculated from record data
Applicant's on-record estimate (Withers exchange)	"under 200 cars"	Worship trips only — excludes programs, recreation,	July 1, 2026 hearing testimony

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

		staff, population transfer	
--	--	-------------------------------	--

The shaded rows show the direct comparison between the only corridor study in the record (Murphy Express 2020) and the revised plan the Board approved. The revised plan generates more than 3× the PM peak-hour volume that produced Level of Service F on this same corridor six years ago (560 Friday trips vs. 168 PM peak-hour trips), on a corridor that has not been improved and has only grown more congested since.

Appendix D — Why Deferring Traffic Mitigation to the Building Phase Is Not a Cure

This section addresses the argument — implicit in the Board's approval — that any traffic problems with the proposed facility can be resolved at the building permit phase through a Traffic Impact Analysis and site-level mitigation conditions.

1. The CUP Is the Last Public Checkpoint

A conditional use permit is the last meaningful public checkpoint before construction begins. Once issued and recorded, the County's legal authority to condition, restrict, or deny the use based on traffic impact is exhausted. Any mitigation proposed at the building permit phase is evaluated by staff in a non-public administrative process, with no opportunity for neighboring property owners or the traveling public to present evidence, challenge findings, or appeal conditions. The Section 24 standard requires a finding that the proposed use “will not be detrimental to the public health, safety, and welfare” before approval. That finding cannot be made on a record that contains no traffic data, and it cannot be outsourced to a future administrative process the public cannot access.

2. The Mitigation May Not Be Physically Possible

2nd Street NW at this location is a two-lane rural road with no median, no turn lanes, no signalized intersection at the driveway, and no parallel arterial alternative for Westside communities (Corrales, Rio Rancho, City of ABQ Westside, Taylor Ranch, Paradise Hills) crossing into the Town of Alameda. If a post-approval traffic study finds Level of Service F — as the only study in the record already projects for this corridor at 168 PM peak-hour trips (86 entering + 82 exiting) from a single 12-pump gas station (2020 Murphy Express Traffic Study, Packet Pg. 1407-1426; trip table Packet Pg. 1416; LOS F at Alameda/4th (Packet Pg. 1417) and at Murphy Driveway “A” (Packet Pg. 1409); NMDOT scoping determination Packet Pg. 1414) — there may be no available engineering fix. There is no room to widen. No signal warrant will be met for a private driveway. No secondary access exists to the north, east, or west. At that point, the County will have issued a permit for a facility that the road network physically cannot serve, and the neighborhood will bear the permanent consequence.

3. Post-Approval Studies Are Structurally Biased Toward Approval

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

reduced to 117 primary trips after a 30% pass-by adjustment) from a single 12-pump gas station and convenience market on this corridor segment, and the study's capacity analysis documented Level of Service F on the westbound Alameda through-movement at the adjacent Alameda / 4th Street signalized intersection under 2020 BUILD conditions (V/C 1.10, 76.8 seconds control delay, 1,348-foot 95th-percentile queue — Packet Pg. 1417). Applying the same ITE-style attendance-to-trip conversion used throughout this exhibit ($\text{persons} \div 2.5 \text{ occ} \times 2$), the 117 primary-trip figure corresponds to a maximum comparable worship attendance of approximately 146 persons during a peak event.

This appendix shows the step-by-step ITE arithmetic for each day of the week under the revised plan (school and daycare verbally removed at the July 1, 2026 hearing; no amended stamped architectural drawings were filed). All inputs are drawn from the Applicant's own filed documents. ITE formulas: Worship (LUC 560) = $\text{persons} \div 2.5 \text{ occ} \times 2$; Quran/School drop-off (LUC 520) = $\text{persons} \div 1.15 \text{ occ} \times 2$; Staff = $\text{persons} \div 1.0 \times 2$; Recreation (LUC 492) = $\text{persons} \div 1.5 \times 2$. The $\times 2$ factor counts both arrival and departure trip-ends (standard ITE convention). Evening program schedule source: AIC Prayer Schedule / Weekly Program Exhibit, Packet Pg. 1360–1362, submitted by the Appellant; undisputed by AIC at the July 1, 2026 hearing.

Day	Prayers (LUC 560)	Programs (LUC 520)	Rec. est. (LUC 492)	Special (est.)	Staff	Daily Total
Monday	96	24	53	24	20	217
Tuesday	96	20	53	24	20	213
Wednesday	96	0	53	24	20	193
Thursday	96	24	53	24	20	217
Friday	360	87	53	40	20	560
Saturday	96	103	107	60	8	374
Sunday	96	119	107	60	8	390
Weekly	936	377	479	256	116	2,164

Friday Peak — Full Breakdown

Component	Persons	LUC / Occ.	Formula	Trips
Jumu'ah worship (350 attendees, lower bound)	350	LUC 560 / 2.5	$350 \div 2.5 \times 2$	280
Non-Jumu'ah	100	LUC 560 / 2.5	$100 \div 2.5 \times 2$	80

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

prayers (5 remaining × 20)				
Quran Evening Program (50 youth, drop-off model, LUC 520)	50	LUC 520 / 1.15	$50 \div 1.15 \times 2$	≈87
Recreational use (est.)	~40	LUC 492 / 1.5	$40 \div 1.5 \times 2$	53
Special gathering (Friday premium est.)	~50	LUC 560 / 2.5	$50 \div 2.5 \times 2$	40
Staff (Friday)	10	Staff / 1.0	$10 \div 1.0 \times 2$	20
FRIDAY TOTAL (revised plan)	—	—	280+80+87+53+40+20	560

Friday source: AIC Letter to Residents (see hearing testimony record and applicant materials at Packet Pg. 1085-1111): "350 to 400 attendees, typically 150 to 200 vehicles" (lower bound 350 used). Quran Evening Program: AIC Prayer Schedule, Packet Pg. 1360-1362 (Appellant-submitted, undisputed). Friday is IDENTICAL under the initial and revised plans — school/daycare removal reduces zero Friday trips.

Appendix B — Trip Calculation Methodology

Trip figures in this exhibit are derived exclusively from attendance and capacity data filed by the Applicant in the case record. The weekly operating schedule (Packet Pg. 1360-1362) used as the source for evening programs and Quran Evening Program sessions reflects the AIC's current operating schedule at their existing Menaul Street facility; it was submitted into the record by the Appellant (Pat Hauser / Maria-Diers Neighborhood Association). The AIC did not file a separate operational schedule for the proposed site and did not dispute this schedule at the July 1, 2026 hearing.

Formula: Vehicle Trips (daily) = (Person Count ÷ Vehicle Occupancy) × 2. The ×2 factor accounts for both the inbound trip (arrival) and the outbound trip (departure) for each attendee. This is the standard methodology used by the Institute of Transportation Engineers (ITE).

Vehicle Occupancy Rates

Use Type	Occupancy Rate	Source
Worship / Prayer (congregation)	2.5 persons/vehicle	ITE Trip Generation Manual 11th Ed., LUC 560 (Church)
Staff / Admin	1.0 person/vehicle	Standard single-occupant

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
 BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
 (INSTITUTE OF TRANSPORTATION ENGINEERS)
 JULY 2026 BY APPEAL COALITION

		commute assumption
Quran Evening Program / Youth Programs	1.15 persons/vehicle	ITE LUC 520 (parental drop-off model)
Recreation (gym/basketball/pool)	1.5 persons/vehicle	ITE LUC 492

Source Data from Record

Data Point	Value Used	Record Source
Daily prayers per day	6	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362 (Fajr 4:07am, Sunrise 5:46am, Dhuhr 1:06pm, Asr 4:53pm, Maghrib 8:18pm, Isha 10:03pm)
Non-Friday prayer attendance (avg)	20 persons	Applicant Written Statement (Packet Pg. 1797-1807): "visitor will be less than 25 persons" on non-Friday days
Friday Jumu'ah attendance	350 persons	AIC Letter to Residents (see hearing testimony record p.25): "350 to 400 attendees, typically 150 to 200 vehicles" — lower bound used
Friday Jumu'ah (written statement)	250 persons	Applicant Written Statement (Packet Pg. 1797-1807): "approximately 250 worshippers" — alternate lower figure also in record
Peak Eid event (2x/year)	615 persons	Applicant Written Statement (Packet Pg. 1797-1807): "615 worshippers" — NOT used in weekly charts (biannual event)
Staff (revised plan)	10 persons	Conservative estimate post-school removal — admin and facility management only
Mon/Thu evening programs	~30 persons	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Hadith Roots (Mon), Shabab Circle (Thu) after 10:15pm Isha
Tue evening program	~25 persons	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Suhbah Visionaries (Women 18-25) 6:30–7:30pm Tuesday
Fri Quran Evening Program	~50 youth	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Quran Evening Program for Youth

TRIP GENERATION ANALYSIS OF 9600 2ND STREET NW 87114
BUILT ON THE ITE TRIP GENERATION MANUAL, 11TH EDITION
(INSTITUTE OF TRANSPORTATION ENGINEERS)
JULY 2026 BY APPEAL COALITION

		and Children 5:30–8:00pm Friday
Sat/Sun Quran Evening Program	~50 youth	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Quran Evening Program 11:00am–2:00pm Saturday and Sunday
Sun Reverts Circle	~20 persons	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: The Reverts Circle 4:30pm Sunday
Sat/Sun late evening program	~30 / ~20	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: Suhbah Visionaries (Men 22+) after Isha Sunday
Operating hours (most days)	4:00am–10:30pm	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: "4 a.m. until 10:30 pm (most days)"
Operating hours (Mon, Thu, Sat)	4:00am–midnight	AIC Prayer Schedule Exhibit, Packet Pg. 1360-1362: "4 a.m. until 11–12 midnight (Mon, Thu, Sat)"

Limitations and Caveats

These are MINIMUM estimates: All figures use the applicant's own stated lower-bound attendance numbers. The record also contains figures of 350–400 Friday worshippers (AIC letter), 615 Eid event worshippers, and a building cap of 60,000 SF. None of the higher figures are used in these calculations.

Population transfer not included: The applicant testified that existing mosques in the area will close and their congregations will transfer to this location. No quantified estimate of transferred congregation size was provided in the record. Transfer trips are therefore not included but represent a material upward adjustment factor.

Gym / basketball / pool trips not included: The applicant's written statement confirms the gymnasium and basketball court serve as "community recreation space for the mosque congregation during evenings and weekends." The indoor Pool Room (2,125 SF, first floor, Sheet A-200, Packet Pg. 1112-1125 range) is on the drawings but not described in the written statement (Packet Pg. 1797-1807). No attendance figure for these recreational uses is provided in the record. Recreation trips shown in the tables above are conservative estimates only.

No ITE floor-area methodology applied to building SF: The standard ITE approach for a Church (LUC 560) uses building square footage as the independent variable. The applicant's written statement does not provide the final confirmed SF — the record contains figures of 45,000 SF (county application), 50,000 SF (AIC letter to residents), and a Board-imposed cap of 60,000 SF. Because the SF is contested, person-count methodology from the applicant's own statements is used instead throughout this exhibit.