

<u>Unit 2 Nonlinear Classification</u>, <u>Linear regression, Collaborative</u>

Course > Filtering (2 weeks)

3. Support Vector Machine

> Project 2: Digit recognition (Part 1) >

Audit Access Expires May 11, 2020

You lose all access to this course, including your progress, on May 11, 2020. Upgrade by Apr 1, 2020 to get unlimited access to the course as long as it exists on the site. **Upgrade now**

3. Support Vector Machine

Bob thinks it is clearly not a regression problem, but a classification problem. He thinks that we can change it into a binary classification and use the support vector machine we learned in Lecture 4 to solve the problem. In order to do so, he suggests that we can build an one vs. rest model for every digit. For example, classifying the digits into two classes: 0 and not 0.

Bob wrote a function run_svm_one_vs_rest_on_MNIST where he changed the labels of digits 1-9 to 1 and keeps the label 0 for digit 0. He also found that sklearn package contains an SVM model that you can use directly. He gave you the link to this model and hopes you can tell him how to use that.

You will be working in the file part1/svm.py in this problem

Important: For this problem, you will need to use the <u>scikit-learn</u> library. If you don't have it, install it using pip install sklearn

One vs. Rest SVM

5.0/5.0 points (graded)

Use the sklearn package and build the SVM model on your local machine. Use random_state = 0, C=0.1 and default values for other parameters.

Available Functions: You have access to the sklearn's implementation of the linear SVM as LinearSVC; No need to import anything.

```
1 def one_vs_rest_svm(train_x, train_y, test_x):
 2
3
      Trains a linear SVM for binary classifciation
 4
 5
      Args:
 6
          train x - (n, d) NumPy array (n datapoints each with d features
7
          train y - (n, ) NumPy array containing the labels (0 or 1) for
8
          test x - (m, d) NumPy array (m datapoints each with d features)
 9
      Returns:
10
           pred test y - (m,) NumPy array containing the labels (0 or 1) f
11
12
      clf = LinearSVC(random state=0, C=0.1, tol=1e-5)
13
      clf.fit(train_x, train_y)
14
15
      return clf.predict(test x)
```

Press ESC then TAB or click outside of the code editor to exit

Correct

```
def one_vs_rest_svm(train_x, train_y, test_x):
    """
    Trains a linear SVM for binary classifciation

Args:
        train_x - (n, d) NumPy array (n datapoints each with d features)
        train_y - (n, ) NumPy array containing the labels (0 or 1) for each tratest_x - (m, d) NumPy array (m datapoints each with d features)
    Returns:
        pred_test_y - (m,) NumPy array containing the labels (0 or 1) for each """

clf = LinearSVC(C=0.1, random_state=0)
    clf.fit(train_x, train_y)
    pred_test_y = clf.predict(test_x)
    return pred_test_y
```

Test results

See full output

CORRECT

See full output

Submit

You have used 1 of 25 attempts

1 Answers are displayed within the problem

Binary classification error

5.0/5.0 points (graded)

Report the test error by running run_svm_one_vs_rest_on_MNIST.

✓ Answer: 0.00749999999999951

Submit

You have used 2 of 20 attempts

1 Answers are displayed within the problem

Implement C-SVM

5.0/5.0 points (graded)

Play with the C parameter of SVM, what statement is true about the C parameter?

(Choose all that apply.)

- Larger C gives larger tolerance of violation.
- ✓ Larger C gives smaller tolerance of violation.
- Larger C gives a larger-margin separating hyperplane.
- Larger C gives a smaller-margin separating hyperplane.



Solution:

C represents the tolerance of error. A larger C means we are punishing more on the classification error, thus being less tolerant to misclassifications. Therefore, we will get a smaller margin hyperplane.

Submit

You have used 1 of 2 attempts

1 Answers are displayed within the problem

Multiclass SVM

5.0/5.0 points (graded)

In fact, sklearn already implements a multiclass SVM with a one-vs-rest strategy. Use LinearSVC to build a multiclass SVM model

Available Functions: You have access to the sklearn's implementation of the linear SVM as LinearSVC; No need to import anything.

```
def multi_class_svm(train_x, train_y, test_x):
    """
    Trains a linear SVM for multiclass classifciation using a one-vs-re
    Args:
        train_x - (n, d) NumPy array (n datapoints each with d features
        train_y - (n, ) NumPy array containing the labels (int) for each
```

```
8
          test_x - (m, d) NumPy array (m datapoints each with d features)
9
      Returns:
          pred test y - (m,) NumPy array containing the labels (int) for
10
11
12
      clf = LinearSVC(random state=0, C=0.1, tol=1e-5)
13
      clf.fit(train x, train y)
14
```

Press ESC then TAB or click outside of the code editor to exit

Correct

```
def multi class svm(train x, train y, test x):
    Trains a linear SVM for multiclass classification using a one-vs-rest strate
   Args:
       train_x - (n, d) NumPy array (n datapoints each with d features)
       train_y - (n, ) NumPy array containing the labels (int) for each traini
       test x - (m, d) NumPy array (m datapoints each with d features)
    Returns:
        pred test y - (m,) NumPy array containing the labels (int) for each tes
    clf = LinearSVC(C=0.1, random state=0)
    clf.fit(train_x, train_y)
    pred_test_y = clf.predict(test_x)
    return pred test y
```

Test results

See full output **CORRECT** See full output

Solution:

As you see, we are using the same code for both SVM functions. Indeed, the default argument for multi class in LinearSVC is ovr.

Submit

You have used 1 of 25 attempts

• Answers are displayed within the problem

Multiclass SVM error

5.0/5.0 points (graded)

Report the overall test error by running run_multiclass_svm_on_MNIST .

✓ Answer: 0.0818999999999997

Submit

You have used 1 of 20 attempts

1 Answers are displayed within the problem

Discussion

Hide Discussion

Topic: Unit 2 Nonlinear Classification, Linear regression, Collaborative Filtering (2 weeks):Project 2: Digit recognition (Part 1) / 3. Support Vector Machine

Add a Post

Show all posts by recent activity

Binary classification error question

"compute test error sym" Are we to fill out this function by our self to answer the question? 3 new_6

Pinned

Is there even any difference between first and second problem?

The wording of the task is a bit confusing, is it just a trick question in the end? Not sure how t...

[Staff] What is the tolerance of violation?

I have never seen this term " tolerance of violation" before. If the tolerance of violation is sma...

https://courses.edx.org/courses/course-v1:MITx+...

? [staff] question about C. Error submitting Hi Staff, After understanding C behaves as the inverse of lambda, I changed my selection. Here	6 <u>Ho</u>
"np" is not defined for multi_class_svm function. For "multi_class_svm" function I get an error saying "NameError: name 'np' is not defined".	4 <u> I t</u>
Muticalss SVM I read bob shred documentation. I am appling 'grammer_singer' multi class and a one vs re	5 <u>est</u>
Processing Dear staff I have write function one vs rest svm and submit but is showing processing I	2 <u>ch</u>
? It's taking too long to grade the One vs. Rest SVM prediction I'm getting the following message: "The grading process is still running. Reload the page to	2 <u>se</u>
? [Staff] Multiclass SVM error Staff - please could you check why I am getting this wrong even though my previous answer	5 er i
? [STAFF] Test error correct - Code window will not grade. Hi The code is resulting in the correct test error, but the window is taking forever to grade.	1 <u>Be</u>
Convergence Warning "" /usr/local/lib/python3.7/dist-packages/sklearn/svm/_base.py:947: ConvergenceWarning	5 g:
 Link to the scikit SVM model documentation "He gave you the link to this model and hopes you can tell him how to > use that." I assu 	m 4

Learn About Verified Certificates

© All Rights Reserved