

<u>Unit 2 Nonlinear Classification</u>, <u>Linear regression, Collaborative</u>

<u>Course</u> > <u>Filtering (2 weeks)</u>
5. Collaborative Filtering with Matrix
Factorization

> Lecture 7. Recommender Systems >

## **Audit Access Expires May 11, 2020**

You lose all access to this course, including your progress, on May 11, 2020. Upgrade by Mar 25, 2020 to get unlimited access to the course as long as it exists on the site. **Upgrade now** 

## 5. Collaborative Filtering with Matrix Factorization Collaborative Filtering with Matrix Factorization





Video

Download video file

**Transcripts** 

<u>Download SubRip (.srt) file</u> Download Text (.txt) file

## Matrix Factorization Practice

1/1 point (graded)

We now use **collaborative filtering** to solve the movie recommender system problem.

As we saw in the previous problem, we ended up with an unsatisfactory and trivial solution of  $\boldsymbol{X}$  by minimizing the objective alone:

$$J\left(X
ight) = \sum_{a,i \in D} rac{\left(Y_{ai} - X_{ai}
ight)^2}{2} + rac{\lambda}{2} \sum_{(a,i)} X_{ai}^2.$$

In the collaborative filtering approach, we impose an additional constraint on X:

$$X = UV^T$$

for some n imes d matrix U and d imes m matrix  $V^T$  . The number d is the  ${\bf rank}$  of the matrix X .

Suppose

$$X = egin{bmatrix} 3 & 6 & 3 \ 2 & 4 & 2 \ 1 & 2 & 1 \end{bmatrix},$$

then what is the minimum possible d?

$$d=oxed{1}$$
 Answer: 1

**Solution:** 

X can be decomposed as

$$X = egin{bmatrix} 3 \ 2 \ 1 \end{bmatrix} egin{bmatrix} 1 & 2 & 1 \end{bmatrix}$$

**Remark:** Note that imposing that a n by m matrix X has rank  $k < \min(m, n)$  means that some of its rows (*resp.* columns) are linearly dependent on other rows (*resp.* columns).

Submit

You have used 1 of 3 attempts

**1** Answers are displayed within the problem

## Intuition on the Vector Factors

1/1 point (graded)

Assume we have a 3 by 2 matrix X i.e. we have 3 users and 2 movies. Also, X is given by

$$X = egin{bmatrix} ext{User 1's rating on movie 1} & ext{User 1's rating on movie 2} \ ext{User 2's rating on movie 1} & ext{User 2's rating on movie 2} \ ext{User 3's rating on movie 1} & ext{User 3's rating on movie 2} \end{bmatrix} = UV^T$$

for some 3 imes d matrix U and d imes 2 matrix  $V^T$  .

Now which of the following is true about U and  $V^T$ ? (Choose all those apply. )

- ightharpoonup The first row of U represents information on user 1's rating tendency
- $lue{}$  The first row of U represents information on movie 1
- lacksquare The first column of  $V^T$  represents information on movie 1

5. Collaborative Filtering with Matrix Factorization... https://courses.edx.org/courses/course-v1:MITx+... **Solution:**  ${\it U}$  encodes information about the users, and  ${\it V}$  about the movies. You have used 1 of 3 attempts Submit **1** Answers are displayed within the problem Discussion **Hide Discussion Topic:** Unit 2 Nonlinear Classification, Linear regression, Collaborative Filtering (2 weeks):Lecture 7. Recommender Systems / 5. Collaborative Filtering with Matrix Factorization Add a Post Show all posts by recent activity Is the wording in "Matrix Factorization Practice" correct? 2

**Learn About Verified Certificates** 

Can someone expand on this fact that was briefly mentioned in the lecture? At time 3:24 Thanks!

<u>n+m-1 parameters?</u>

© All Rights Reserved

1