Contact side end

21

Angle A=90°

Fold under -180°

DETAIL A
SCALE 1 : 2

Do not fold

Do not fold

Fold over 180°

1610

A

Fold 2# -90°
angle A=90°

322

170

Fold 1# 180°
angle A=45°

Reinforcement side Start

Contact side Start

Reinforcement side Start

SCALE 1:10

FFC1.00D20/1610x21x4.0-4.0-08.0-08.0xxxx PUNCHED FCI-SFW BLACK TAPE

1	Flat Flexible Cable	1610 x 21mm	-	Polyester
Quant.	Material	Max dimensions	Heat treatment	Coating

General dimensional tolerances by DIN 7168-M	General geometrical tolerances by DIN 7168	Minimum surface roughness Ra=6.3	Attached files:	sldprt, step	
			Created on: 26/04/2017		Printed on: 26/04/2017

	Reference number A3BCN3DSigma-M09C00.0P08A		**Project:** BCN3D SigmaX	
			System: Wiring	
			Assembly: -	
Scale 1:5	**Designed** Mikel Ucero	**Drawn** Mikel Ucero	**Part:** FCC Hotend 1	
Sheet / Total 1/1	**Checked** Eric Pallarés	**Aproved** Eric Pallarés	**Drawing version** V1.0	**Contact** Eric Pallarés 93.401.71.71
Sheet format A4	Views	Cuts & Sections	Dimensioning	Tolerances	Printing box

FUNDACIÓ cim BARCELONATECH