

# Advanced Programming (I00032) 2016

## Generics by overloading

### Assignment 3

## Goals of this exercise

In this exercise you learn how to implement and use the kind-indexed version of generic programming as well as native generic programming in Clean.

## 1 Kind-Index Generic Serialization

In the last exercise you implemented generic serialization. In the lecture we showed that the approach of exercise 2 fails when we need a kind different from `*`. The solution is to use kind-indexed generics as introduced in the lecture. Implement the class `serialize` based on the new version of generics. On blackboard you find a file `serialize3Start.icl` that contains all boilerplate definitions and some tests to check your implementation.

Your solution should ideally

1. avoid all generic information in the serialized form (the list of strings);
2. use only brackets for a constructor with arguments;
3. pass all tests.

The output of the test looks better if the program is compiled with `Basic Values Only` for Console in `Project Options`.... You can set this option in dialogue in the `Project` menu.

### 1.1 Tailor-made Serialization

It is possible to deviated from the generic route for specific types. For instance we can serialize the expression `(7,True)` as `["(", "7", ",", "True", ")"]`. Implement this for all 2-tuples while using the ordinary generic serialization for other types.

## 2 Serialization using Clean's Native Generics

Use the native generic from Clean to implement the class `serialize` defined as

```
class serialize a | read{[*]}, write{[*]} a
```

Use the same requirements and tailor-made version for tuples as above.

Do not forget to import `StdGeneric` and use the `Everything` environment. This environment will pass the required flag `-generics` to the compiler.

### 3 Generic Apply

On Blackboard you will find a file with the generic map function, `gMap`, used in the lecture. Use this to

1. apply the factorial function `fac` to all elements of tree `t`;
2. turn each integer `i` in list `l` to a tuple `(i,fac i)`;
3. apply the factorial function to all integers in `(l,t)`.

### Deadline

The deadline for this exercise is September 20 2016, 13:30h (just before the next lecture). Add the output of your programs as a comment.