

DvD: An R/Cytoscape pipeline for drug repurposing using public repositories of gene expression data

Clare Pacini¹, Francesco Iorio^{1,2}, Emanuel Gonçalves¹, Murat Iskar³, Thomas Klabunde⁴, Peer Bork³ and Julio Saez-Rodriguez^{1,*}

¹European Bioinformatics Institute (EMBL-EBI), Wellcome Trust Genome Campus, Cambridge, UK CB10 1SD,

²Wellcome Trust Sanger Institute, Wellcome Trust Genome Campus, Cambridge, UK, CB10 1HH, ³Structural and Computational Biology Unit, European Molecular Biology Laboratory, Meyerhofstrasse 1, 69117 Heidelberg, Germany and ⁴Sanofi-Aventis Deutschland GmbH, Frankfurt am Main, Germany

Associate Editor: Martin Bishop

ABSTRACT

Summary: Drug versus Disease (DvD) provides a pipeline, available through R or Cytoscape, for the comparison of drug and disease gene expression profiles from public microarray repositories. Negatively correlated profiles can be used to generate hypotheses of drug-repurposing, whereas positively correlated profiles may be used to infer side effects of drugs. DvD allows users to compare drug and disease signatures with dynamic access to databases Array Express, Gene Expression Omnibus and data from the Connectivity Map.

Availability and implementation: R package (submitted to Bioconductor) under GPL 3 and Cytoscape plug-in freely available for download at www.ebi.ac.uk/saezrodriguez/DvD/.

Contact: saezrodriguez@ebi.ac.uk

Supplementary information: Supplementary data are available at *Bioinformatics* online.

Received on August 3, 2012; revised on October 12, 2012; accepted on October 31, 2012

1 INTRODUCTION

Multiple methods based on matching gene expression signatures have been proposed to identify anti-correlated drug and disease profiles (Hu *et al.*, 2009; Sirota *et al.*, 2011). The central paradigm is that a drug compound, which shows the opposite effect on gene expression to the observed for a disease could be used to treat that particular disease. These methods have resulted in hypotheses of differential uses (repurposing) for existing compounds that have been validated experimentally. This highlights the potential power of mining existing safe compounds for repurposing, which does not require the expensive and extensive initial design and clinical phases of drug discovery. It is expected that analysing new and existing data from public repositories such as Array Express (www.ebi.ac.uk/arrayexpress/), Gene Expression Omnibus (GEO) (www.ncbi.nlm.nih.gov/geo/) and the Connectivity Map (CMap) (www.broadinstitute.org/cmap/) using these methods will become increasingly popular in computational drug discovery (Iorio *et al.*, 2012).

Motivated by this, we have developed Drug versus Disease (DvD), an R package to ‘match’ drug and disease profiles.


This is done by making use of gene set enrichment analysis (Subramanian *et al.*, 2005) and visualizing the final results in networks containing clusters of similar drugs and diseases. DvD differs from existing web servers and databases (such as ProfileChaser, MARQ and SPIED, see Supplementary Material) in that it can dynamically access both Array Express and GEO to generate input profiles. With DvD, users can automatically compare input profiles to reference drug data from CMap and disease profiles curated from GEO. This reference data has associated networks where, unlike similar tools, drugs or diseases exerting similar effects on transcription are grouped into clusters. DvD is flexible, offering customizable and default data options for the input profiles and the reference data. The Cytoscape (www.cytoscape.org/) plug-in provides a user interface to the full DvD pipeline, as well as a visualization platform for the results. In the final networks, drug or disease nodes are linked to the DrugBank (www.drugbank.ca/) and Medical Subject Headings (MeSH) (www.ncbi.nlm.nih.gov/mesh/) web browsers, respectively.

2 ANALYSIS PIPELINE

The DvD pipeline provides a number of processing options to generate genome-wide expression profiles from microarray experiments (see Fig. 1A). Options to import data from local directories and Array Express or GEO are supported (Davis *et al.*, 2007; Kauffmann *et al.*, 2009). Data are normalized using either rma or mas5 (Irizarry *et al.*, 2003). DvD will automatically annotate, filter and combine probes to HUGO genes for the Affymetrix platforms HG-U133A, HG-U133A-2 and HG-U133-Plus2 using BiomaRt (Durinck *et al.*, 2009). Annotation files can be passed to DvD to process data from other platforms. Probes mapping to multiple gene identifiers are removed. Multiple probes mapping to the same gene can be converted using the average or maximal intensities, median polish or by selecting the probe with the highest variance across all arrays.

DvD expects as input either a drug or disease profile. Using this, and the experimental design factors from the Array Express and GEO databases, DvD identifies a main factor for the experiment. In this way, unlike existing methods, DvD is able to calculate differential expression (Smyth *et al.*, 2004) between levels of the main factor, stratified by a second factor (see

*To whom correspondence should be addressed.



Supplementary Material). Given a ranked list of differential expression, either from DvD or by providing preprocessed data, DvD defines gene sets. These can be a fixed number chosen *a priori* or determined by the number of significantly differentially expressed genes. Enrichment scores are then calculated using either the Kolomgorov–Smirnov-based statistic (Iorio *et al.*, 2010; Subramanian *et al.*, 2005) or the weighted signed statistic (Zhang *et al.*, 2008) by querying the reference dataset with these gene sets. Significance of enrichment scores is determined by comparison with an empirical null distribution. Scores can be corrected for multiple hypothesis testing using either Benjamini–Hochberg correction or *q*-value method. Profiles producing significant scores are finally assigned to clusters using single or average linkage. In the latter case, the average score for a cluster is defined as either the mean or the median distance to each profile in the cluster.

Two associated data packages, `cMap2data` and `DrugVsDiseasedata` provide default reference ranked expression profiles and clusters. The `cMap2data` is based on the CMap version 2 dataset, which contains 6100 hybridizations of 1309

2.2 Cytoscape plug-in

3 RESULTS

ACKNOWLEDGEMENTS

Funding: C.P. was funded by Sanofi-Aventis and F.I. by the EMBL-EBI/Sanger ESPOD program.

REFERENCES

- Bolton, E. *et al.* (2000) H2-antagonists in the treatment of colon and breast cancer. *Semin. Cancer Biol.*, **10**, 3–10.
- Davis, S. *et al.* (2007) GEOquery: a bridge between the gene expression omnibus (GEO) and BioConductor. *Bioinformatics*, **14**, 1846–1847.
- Durinck, S. *et al.* (2009) Mapping identifiers for the integration of genomic datasets with the R/Bioconductor package biomaRt. *Nat. Protoc.*, **4**, 1184–1191.
- Hu, G. and Agarwal, P. (2009) Human disease-drug network based on genomic expression profiles. *PLoS One*, **4**, e6536.
- Iorio, F. *et al.* (2010) Discovery of drug mode of action and drug repositioning from transcriptional responses. *Proc. Natl Acad. Sci. USA*, **107**, 14621–14626.
- Iorio, F. *et al.* (2012) Transcriptional data: a new gateway to drug repositioning? *Drug Discov Today*, [Epub ahead of print, doi: 10.1016/j.drudis.2012.07.014, August 7, 2012].
- Irizarry, R. *et al.* (2003) Summaries of affymetrix genechip probe level data. *Nucleic Acids Res.*, **31**, e15.
- Kauffmann, A. *et al.* (2009) Importing array express datasets into R/Bioconductor. *Bioinformatics*, **25**, 2092–2094.
- Saad, F. (2009) The role of testosterone in type 2 diabetes and metabolic syndrome in men. *Arg. Bras. Endocrinol. Metabol.*, **53**, 901–907.
- Sirota, M. *et al.* (2011) Discovery and preclinical validation of drug indications using compendia of public gene expression data. *Sci. Trans. Med.*, **3**, 96ra77.
- Smyth, G.K. *et al.* (2004) Linear models and empirical Bayes method for assessing differential expression in microarray experiments. *Stat. Appl. Genet. Mol. Biol.*, **3**, Article 3.
- Subramanian, A. *et al.* (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc. Natl Acad. Sci. USA*, **102**, 15545–15550.
- Zhang, S. *et al.* (2008) A simple and robust method for connecting small-molecule drugs using gene-expression signatures. *BMC Bioinformatics*, **9**, 258.