

Bash scripting pseudocode

lab 12.

q1 int [] print number
 { i = number
 for i = 0 to 10
 { print i
 }
 }

q2 int [] print Even Number
 { for i = 0 to 50
 { if i % 2 == 0
 { print i
 }
 }
 }
 else
 Return Print odd
 }

q3. int number
 { i = input number
 n = 1
 until n > 16
 { print n * i
 n = n + 1
 }

Q4 ^{at} int[] arr & print int[] nums

{ for i = 0 to n-1

{ print A_i

}

for i = 0 to n-1

{ ~~print~~

A_i = A_i * 2

}

} Print A_i

Q5

num1 = input number
num2 = input no 2
q = quotient

r = remainder

if (num2 == 0)

{ Print "Division by 0 is not allowed"

}

else

{ q = $\frac{\text{num1}}{\text{num2}}$

r = num1 % num2

Print quotient upto two decimal place (scale = 2)

} Print r

}

Q8. { if $a > b$
 { Print a is greater than b
 }
 else
 { Print b is greater than a
 }
 }

Q9. check if Directory exists
 { if (Directory exists)
 { ~~Print~~ all the files in Directory
 }
 else
 { # Create a new Directory
 Print Directory created
 }
 }

18th
August

a) function check file()

```
{  
    if (file exists)
```

```
    { print "File exists"
```

```
    elif (file is readable)
```

```
    { print "Readable"
```

```
    elif (file is writable)
```

```
    { print "writable"
```

```
    }
```

```
else
```

```
    print "file does not exist"
```

```
}
```

Q3 1) List contents of the current Directory

2) Sort files in Reverse order (High to low)

3) Store the 1st file as the largest file from sorted list

3) Print name of the largest file along with size

15 AUG

Q1 { w = word to be found()
f = filename Cn that file()

~~if (file exists)~~

~~{~~

for file f

{ if word exists/appears

{ print that line
}

else

{ print "word not found"

}

}

}

Q2 { int multiplication table (int number N)

for i ≤ 20

{

val = n x i

print "n x i = val"

}

}

ex

{

u = usage

if u > 80%

{ Print "WARNING"

}

else

Print "SAFE"