

Q.1] Print numbers from 0 to 10.

- 1) ^{Initialize $n = 0$ & then} Give a condition that check Give a condition. That for $i = 0$ to 10 if i .
- 2] if i is greater than 10 or equal to 10 then print the number. = n .
- 3] Increment the number till it reaches 10. $n = n + 1$ & print the new number everytime.

Q.2] print the even numbers 0 - 50.



count = 0.
if For (given target).

if no. number (enter) $\rightarrow$ Start loop from 0 to 10 (i)

$n \% 2 = 0$ $\left\{ \begin{array}{l} \text{yes} \rightarrow \text{even.} \\ \text{No} \rightarrow \text{odd.} \end{array} \right.$

echo "Enter a number"

read n

for ((i = 0; i <= n; i++))

{

if [$i \% 2 -eq 0$]; then

{

echo "Number i is even"

}

else {

echo "Number is odd"

}

- 0.3) 1) Take user input (n)
- 2) Start a loop & put a condition until it is ^{then} ~~not~~ > 15.
- 3) If the no goes above 15 loop will stop or it will keep running.
- 4) Start loop from 1 to 15.
- 5) print the number $x i = \$(n \times i)$

echo "enter a num"

read n

~~for~~ i = 1

until (i - gt 15)

do

{ echo " \$ x \$i = \$(n x i) "

}

done

0.4) read -ra numbers < num.txt

- 1) read the file name (as it is)
- 2) to store the file input into array
- 3) This is the variable in which we have to save
- 4) num.txt → This is the file which has numbers.

Steps:- 1) Take the length

2) from $i = 0$ to $l-1$ ~~is~~, $i++$

3) For every i print $A[i] \times BA[i]$ gives double.

read -n 10 numbers < num.txt

A = \$ { numbers (*) }

l = \$ { numbers { () } }

for ((i=0 ; i<=\${l} ; i++))

do

echo " \$ { l members [i] + numbers[i] } "

done.

5) 1) take 2 numbers as arguments using
\$1 \$2 → in a \$ variable.

2) put conditions.

3) If ~~\$1~~ \$2: -eg \$0 → yes → can't divide by 0
→ no → quotient → a/b
remainder → a%b.

↓

Scale to 2.

for.

56) 1) Take 2 numbers using argument & store in
variable a \$b.

2) If it is 'a' is greater than b using if
→ yes → A is greater
→ no → B is greater.

- Q.7) 1) Create a function dir exists.
2) Take input from user for directory.
3) using - e check your directory name.
4) to check if the directory exists or not.
5) if yes → directory exists → list to list
no → does not exist.
6) Then mkdir new file name.

Q.8) int checkdir (dir name)
{
 if (directory does not exist)
 {
 create directory.
 print "directory created"
 }
 else
 {
 print list of all files in dir
 }
}