

Q.1] Print numbers from 0 to 10.

- 1) ^{Initialize $n = 0$ & then} Give a condition that check Give a condition. That for $i = 0$ to 10 if i .
- 2] if i is greater than 10 or equal to 10 then print the number. = n .
- 3] Increment the number till it reaches 10. $n = n + 1$ & print the new number everytime.

Q.2] print the even numbers 0 - 50.



count = 0.

if ~~For~~ (given target).

if no. number (enter) $\rightarrow$ Start loop from 0 to 10 (i)

$n \% 2 = 0$ $\left\{ \begin{array}{l} \text{yes} \rightarrow \text{even.} \\ \text{no} \rightarrow \text{odd.} \end{array} \right.$

echo "Enter a number"

read n

for ((i = 0; i <= n; i++))

{

if [$i \% 2 -eq 0$]; then

{

echo "Number i is even"

}

else {

{

echo "Number is odd"

}

- 0.3) 1) Take user input (n)
- 2) Start a loop & put a condition until it is ^{then} ~~not~~ > 15.
- 3) If the no goes above 15 loop will stop or it will keep running.
- 4) Start loop from 1 to 15.
- 5) print the number $x i = \$(n \times i)$

echo " enter a num"

read n

~~for~~ i = 1

until (i - gt 15)

do

{

echo " \$ x \$i = \$(n x i) "

}

done

0.4) read -ra numbers < num.txt

- 1) read the file name (as it is)
- 2) to store the file input into array
- 3) This is the variable in which we have to save
- 4) num.txt → This is the file which has numbers.

Steps:- 1) Take the length

2) from $i = 0$ to $l-1$ ~~is~~, $i++$

3) For every i print $A[i] \times BA[i]$ gives double.

read -n \$n numbers < num.txt

A = \$(numbers (*))

l = \$(numbers { () })

for ((i=0 ; i<=\${l} ; i++))

do

echo " \$(l members [i] + numbers[i]) "

done.

5) 1) take 2 numbers as arguments using
\$1 \$2 → in a \$ variable.

2) put conditions.

3) If ~~\$1~~ \$2: -eg \$0 → yes → can't divide by 0
→ no → quotient → a/b
remainder → a%b.

↓

Scale to 2.

for.

56) 1) Take 2 numbers using argument & store in
variable a \$b.

2) If it is 'a' is greater than b using if
→ yes → A is greater
→ no → B is greater.

- Q.7) 1) Create a function dir exists.
2) Take input from user for directory.
3) using - e check your directory name.
4) to check if the directory exists or not.
5) if yes → directory exists → list to list
no → does not exist.
6) Then mkdir new file name.

Q.8) int checkdir (dir name)
{
 if (directory does not exist)
 {
 create directory.
 print "directory created"
 }
 else
 {
 print list of all files in dir
 }
}

(5) (1) Take a number from the user.
is enter a number.

(2) Read the number.

(3) Then for $i = 1$ to 20.

(4) print number $\times i$ inside a loop.

(5) ~~Read~~ number.

(6)

③

- ① first go into the cd.
- ② Then list the contents - ls.
- ③ then pipe the (ls -s & head -n) target.
- ④ then echo the file name & size is

④ ① enter the word.

- ② head word
- ③ echo enter the filename & then head filename.
- ④ Now using grep we can search for file & word by doing \$word & \$file.

- ① enter a filename
- ② read file
- ③ check if the file exists. 2 is readable or writable 7 ~~too~~
- ④ else file does exist ~~or~~ but the file is not readable or writable
- ⑤ And if it does not exist then echo "file does not exist"

- ② ① ~~to~~ Take a file input from the user.
- ② Then read the filename.
- ③ for counting the characters

do wc -m

2 similar like wc -l

low lines

wc -w
 → words