



WhiteboxTools User Manual

John B. Lindsay, University of Guelph

Contents

1. Introduction	11
2. Installation	12
3. Interacting With <i>WhiteboxTools</i> From the Command Prompt	13
4. Interacting With <i>WhiteboxTools</i> Using Python Scripting	14
5. WhiteboxTools Runner	18
6. Available Tools	19
6.1 Data Tools	20
6.1.1 ConvertNodataToZero	20
6.1.2 ConvertRasterFormat	20
6.1.3 NewRasterFromBase	21
6.1.4 PrintGeoTiffTags	21
6.1.5 SetNodataValue	22
6.2 GIS Analysis	22
6.2.1 AggregateRaster	22
6.2.2 Centroid	23
6.2.3 Clump	23
6.2.4 CreatePlane	24
6.2.5 RadiusOfGyration	24
6.2.6 RasterCellAssignment	25
6.3 GIS Analysis => Distance Tools	25
6.3.1 BufferRaster	25
6.3.2 CostAllocation	26
6.3.3 CostDistance	26
6.3.4 CostPathway	27
6.3.5 EuclideanAllocation	27
6.3.6 EuclideanDistance	27
6.4 GIS Analysis => Overlay Tools	28
6.4.1 AverageOverlay	28
6.4.2 HighestPosition	28
6.4.3 LowestPosition	29
6.4.4 MaxAbsoluteOverlay	29
6.4.5 MaxOverlay	30
6.4.6 MinAbsoluteOverlay	30
6.4.7 MinOverlay	30
6.4.8 PercentEqualTo	31

6.4.9 PercentGreaterThan	31
6.4.10 PercentLessThan	32
6.4.11 PickFromList	32
6.4.12 WeightedSum	33
6.5 GIS Analysis => Patch Shape Tools	33
6.5.1 EdgeProportion	33
6.5.2 FindPatchOrClassEdgeCells	34
6.6 GIS Analysis => Reclass Tools	34
6.6.1 Reclass	34
6.6.2 ReclassEqualInterval	35
6.6.3 ReclassFromFile	35
6.7 Geomorphometric Analysis	36
6.7.1 Aspect	36
6.7.2 DevFromMeanElev	36
6.7.3 DiffFromMeanElev	37
6.7.4 DirectionalRelief	37
6.7.5 DownslopeIndex	38
6.7.6 ElevAbovePit	38
6.7.7 ElevPercentile	38
6.7.8 ElevRelativeToMinMax	39
6.7.9 ElevRelativeToWatershedMinMax	39
6.7.10 FeaturePreservingDenoise	40
6.7.11 FetchAnalysis	40
6.7.12 FillMissingData	41
6.7.13 FindRidges	41
6.7.14 Hillshade	42
6.7.15 HorizonAngle	42
6.7.16 HypsometricAnalysis	42
6.7.17 MaxAnisotropyDev	43
6.7.18 MaxBranchLength	43
6.7.19 MaxDownslopeElevChange	44
6.7.20 MaxElevDevSignature	44
6.7.21 MaxElevationDeviation	45
6.7.22 MinDownslopeElevChange	45
6.7.23 MultiscaleRoughness	46
6.7.24 MultiscaleRoughnessSignature	46
6.7.25 MultiscaleTopographicPositionImage	47
6.7.26 NumDownslopeNeighbours	47
6.7.27 NumUpslopeNeighbours	48
6.7.28 PennockLandformClass	48
6.7.29 PercentElevRange	49
6.7.30 PlanCurvature	49
6.7.31 Profile	50
6.7.32 ProfileCurvature	50
6.7.33 RelativeAspect	51

6.7.34 RelativeStreamPowerIndex	51
6.7.35 RelativeTopographicPosition	51
6.7.36 RemoveOffTerrainObjects	52
6.7.37 RuggednessIndex	52
6.7.38 SedimentTransportIndex	53
6.7.39 Slope	53
6.7.40 SlopeVsElevationPlot	54
6.7.41 TangentialCurvature	54
6.7.42 TotalCurvature	55
6.7.43 Viewshed	55
6.7.44 WetnessIndex	56
6.8 Hydrological Analysis	56
6.8.1 AverageFlowpathSlope	56
6.8.2 AverageUpslopeFlowpathLength	57
6.8.3 Basins	57
6.8.4 BreachDepressions	57
6.8.5 BreachSingleCellPits	58
6.8.6 D8FlowAccumulation	58
6.8.7 D8MassFlux	59
6.8.8 D8Pointer	59
6.8.9 DInfFlowAccumulation	60
6.8.10 DInfMassFlux	60
6.8.11 DInfPointer	61
6.8.12 DepthInSink	61
6.8.13 DownslopeDistanceToStream	62
6.8.14 DownslopeFlowpathLength	62
6.8.15 ElevationAboveStream	63
6.8.16 FD8FlowAccumulation	63
6.8.17 FD8Pointer	64
6.8.18 FillDepressions	64
6.8.19 FillSingleCellPits	65
6.8.20 FindNoFlowCells	65
6.8.21 FindParallelFlow	66
6.8.22 FloodOrder	66
6.8.23 FlowAccumulationFullWorkflow	67
6.8.24 FlowLengthDiff	67
6.8.25 Hillslopes	68
6.8.26 Isobasins	68
6.8.27 JensonSnapPourPoints	69
6.8.28 MaxUpslopeFlowpathLength	69
6.8.29 NumInflowingNeighbours	70
6.8.30 Rho8Pointer	70
6.8.31 Sink	70
6.8.32 SnapPourPoints	71
6.8.33 StrahlerOrderBasins	71

6.8.34 Subbasins	72
6.8.35 TraceDownslopeFlowpaths	72
6.8.36 Watershed	73
6.9 Image Processing Tools	73
6.9.1 Closing	73
6.9.2 CreateColourComposite	74
6.9.3 FlipImage	74
6.9.4 IntegrallImage	75
6.9.5 KMeansClustering	75
6.9.6 LineThinning	76
6.9.7 ModifiedKMeansClustering	76
6.9.8 Mosaic	77
6.9.9 NormalizedDifferenceVegetationIndex	77
6.9.10 Opening	78
6.9.11 RemoveSpurs	79
6.9.12 Resample	79
6.9.13 RgbToIhs	79
6.9.14 SplitColourComposite	80
6.9.15 ThickenRasterLine	81
6.9.16 TophatTransform	81
6.9.17 WriteFunctionMemoryInsertion	81
6.10 Image Processing Tools => Filters	82
6.10.1 AdaptiveFilter	82
6.10.2 BilateralFilter	82
6.10.3 ConservativeSmoothingFilter	83
6.10.4 DiffOfGaussianFilter	83
6.10.5 DiversityFilter	84
6.10.6 EmbossFilter	84
6.10.7 GaussianFilter	85
6.10.8 HighPassFilter	85
6.10.9 KNearestMeanFilter	86
6.10.10 LaplacianFilter	86
6.10.11 LaplacianOfGaussianFilter	87
6.10.12 LeeFilter	87
6.10.13 LineDetectionFilter	88
6.10.14 MajorityFilter	88
6.10.15 MaximumFilter	89
6.10.16 MeanFilter	89
6.10.17 MedianFilter	90
6.10.18 MinimumFilter	90
6.10.19 OlympicFilter	91
6.10.20 PercentileFilter	91
6.10.21 PrewittFilter	92
6.10.22 RangeFilter	92
6.10.23 RobertsCrossFilter	92

6.10.24 ScharrFilter	93
6.10.25 SobelFilter	93
6.10.26 StandardDeviationFilter	94
6.10.27 TotalFilter	94
6.11 Image Processing Tools => Image Enhancement	95
6.11.1 BalanceContrastEnhancement	95
6.11.2 DirectDecorrelationStretch	95
6.11.3 GammaCorrection	96
6.11.4 HistogramEqualization	96
6.11.5 HistogramMatching	96
6.11.6 HistogramMatchingTwoImages	97
6.11.7 MinMaxContrastStretch	97
6.11.8 PanchromaticSharpening	98
6.11.9 PercentageContrastStretch	99
6.11.10 SigmoidalContrastStretch	99
6.11.11 StandardDeviationContrastStretch	100
6.12 LiDAR Tools	100
6.12.1 BlockMaximum	100
6.12.2 BlockMinimum	101
6.12.3 FilterLidarScanAngles	101
6.12.4 FindFlightlineEdgePoints	102
6.12.5 FlightlineOverlap	102
6.12.6 LasToAscii	103
6.12.7 LidarColourize	103
6.12.8 LidarElevationSlice	103
6.12.9 LidarGroundPointFilter	104
6.12.10 LidarHillshade	105
6.12.11 LidarHistogram	105
6.12.12 LidarIdwInterpolation	106
6.12.13 LidarInfo	106
6.12.14 LidarJoin	107
6.12.15 LidarKappaIndex	107
6.12.16 LidarNearestNeighbourGridding	108
6.12.17 LidarPointDensity	108
6.12.18 LidarPointStats	109
6.12.19 LidarRemoveDuplicates	110
6.12.20 LidarRemoveOutliers	110
6.12.21 LidarSegmentation	111
6.12.22 LidarSegmentationBasedFilter	111
6.12.23 LidarTile	112
6.12.24 LidarTophatTransform	112
6.12.25 NormalVectors	113
6.13 Math and Stats Tools	113
6.13.1 AbsoluteValue	113
6.13.2 Add	113

6.13.3 And	114
6.13.4 Anova	114
6.13.5 ArcCos	115
6.13.6 ArcSin	115
6.13.7 ArcTan	116
6.13.8 Atan2	116
6.13.9 Ceil	116
6.13.10 Cos	117
6.13.11 Cosh	117
6.13.12 CrispnessIndex	118
6.13.13 CrossTabulation	118
6.13.14 CumulativeDistribution	119
6.13.15 Decrement	119
6.13.16 Divide	119
6.13.17 EqualTo	120
6.13.18 Exp	120
6.13.19 Exp2	121
6.13.20 ExtractRasterStatistics	121
6.13.21 Floor	122
6.13.22 GreaterThan	122
6.13.23 ImageAutocorrelation	123
6.13.24 ImageCorrelation	123
6.13.25 ImageRegression	123
6.13.26 Increment	124
6.13.27 IntegerDivision	124
6.13.28 IsNoData	125
6.13.29 KSTestForNormality	125
6.13.30 KappaIndex	126
6.13.31 LessThan	126
6.13.32 Ln	127
6.13.33 Log10	127
6.13.34 Log2	127
6.13.35 Max	128
6.13.36 Min	128
6.13.37 Modulo	129
6.13.38 Multiply	129
6.13.39 Negate	130
6.13.40 Not	130
6.13.41 NotEqualTo	130
6.13.42 Or	131
6.13.43 Power	131
6.13.44 Quantiles	132
6.13.45 RandomField	132
6.13.46 RandomSample	133
6.13.47 RasterHistogram	133

6.13.48 RasterSummaryStats	133
6.13.49 Reciprocal	134
6.13.50 RescaleValueRange	134
6.13.51 RootMeanSquareError	135
6.13.52 Round	135
6.13.53 Sin	136
6.13.54 Sinh	136
6.13.55 Square	136
6.13.56 SquareRoot	137
6.13.57 Subtract	137
6.13.58 Tan	138
6.13.59 Tanh	138
6.13.60 ToDegrees	139
6.13.61 ToRadians	139
6.13.62 Truncate	139
6.13.63 TurningBandsSimulation	140
6.13.64 Xor	140
6.13.65 ZScores	141
6.14 Stream Network Analysis	141
6.14.1 DistanceToOutlet	141
6.14.2 ExtractStreams	142
6.14.3 ExtractValleys	142
6.14.4 FarthestChannelHead	143
6.14.5 FindMainStem	143
6.14.6 HackStreamOrder	144
6.14.7 HortonStreamOrder	145
6.14.8 LengthOfUpstreamChannels	145
6.14.9 LongProfile	146
6.14.10 LongProfileFromPoints	146
6.14.11 RemoveShortStreams	147
6.14.12 ShreveStreamMagnitude	147
6.14.13 StrahlerStreamOrder	148
6.14.14 StreamLinkClass	148
6.14.15 StreamLinkIdIdentifier	149
6.14.16 StreamLinkLength	149
6.14.17 StreamLinkSlope	150
6.14.18 StreamSlopeContinuous	151
6.14.19 TopologicalStreamOrder	151
6.14.20 TributaryIdentifier	152
7. Supported Data Formats	152
8. Contributing	153
9. Reporting Bugs	153
10. Known Issues and Limitations	154
11. License	154
12. Frequently Asked Questions	155

12.1 Do I need Whitebox GAT to use WhiteboxTools?	155
12.2 How do I request a tool be added?	155
12.3 Can WhiteboxTools be incorporated into other software and open-source GIS projects?	155
12.4 What platforms does WhiteboxTools support?	155
12.5 What are the system requirements?	156
12.6 Are pre-compiled executables of WhiteboxTools available?	156
12.7 Why is WhiteboxTools programmed in Rust?	156
12.8 Do I need Rust installed on my computer to run WhiteboxTools?	157
12.9 How does WhiteboxTools' design philosophy differ?	157


WhiteboxTools Version 0.4

Dr. John B. Lindsay © March 2, 2018

Geomorphometry and Hydrogeomatics Research Group

University of Guelph

Guelph, Canada



Geomorphometry & Hydrogeomatics Research Group

1. Introduction

WhiteboxTools is an advanced geospatial data analysis engine developed by Prof. John Lindsay ([webpage](#); [jblindsay](#)) at the [University of Guelph's Geomorphometry and Hydrogeomatics Research Group](#) (GHRG). The project began in January 2017 and quickly evolved in terms of its analytical capabilities. *WhiteboxTools* can be used to perform common geographical information systems (GIS) analysis operations, such as cost-distance analysis, distance buffering, and raster reclassification. Remote sensing and image processing tasks include image enhancement (e.g. panchromatic sharpening, contrast adjustments), image mosaicing, numerous filtering operations, simple classification (k-means clustering), and common image transformations. *WhiteboxTools* also contains advanced tooling for spatial hydrological analysis (e.g. flow-accumulation, watershed delineation, stream network analysis, sink removal), terrain analysis (e.g. common terrain indices such as slope, curvatures, wetness index, hillshading; hypsometric analysis; multi-scale topographic position analysis), and LiDAR data processing. LiDAR point clouds can be interrogated (LidarInfo, LidarHistogram), segmented, tiled and joined, analyzed for outliers, interpolated to rasters (DEMs, intensity images), and ground-points can be classified or filtered. *WhiteboxTools* is not a cartographic or spatial data visualization package; instead it is meant to serve as an analytical backend for other data visualization software, mainly GIS.

In this manual, **WhiteboxTools** refers to the standalone geospatial analysis library, a collection of tools contained within a compiled binary executable command-line program and the associated Python scripts that are distributed alongside the binary file (e.g. *whitebox_tools.py* and *wb_runner.py*). **Whitebox Geospatial Analysis Tools** and **Whitebox GAT** refer to the GIS software, which includes a user-interface (front-end), point-and-click tool interfaces, and cartographic data visualization capabilities.

Although *WhiteboxTools* is intended to serve as a source of plugin tools for the [Whitebox Geospatial Analysis Tools \(GAT\)](#) open-source GIS project, the tools contained in the library are stand-alone and can run outside of the larger *Whitebox GAT* project. See [Interacting With WhiteboxTools* From the Command Prompt*](#) for further details. There have been a large number of requests to call *Whitebox GAT* tools and functionality from outside of the *Whitebox GAT* user-interface (e.g. from Python automation scripts). *WhiteboxTools* is intended to meet these usage requirements. The current version of *Whitebox GAT* contains many equivalent tools to those found in the *WhiteboxTools* library, although they are developed using the Java programming language. A future version of *Whitebox GAT* will replace these previous tools with the new *WhiteboxTools* backend. This transition will occur over the next several releases. Eventually most of the approximately 450 tools contained within *Whitebox GAT* [will be ported](#) to *WhiteboxTools*. In addition to separating the processing capabilities and the user-interface (and thereby reducing the reliance on Java), this migration should significantly improve processing efficiency. This is because [Rust](#), the programming language used to develop *WhiteboxTools*, is generally [faster than the equivalent Java code](#) and because many of the *WhiteboxTools* functions are designed to process data in parallel wherever possible. In contrast, the older Java codebase included largely single-threaded applications.

In addition to *Whitebox GAT*, the *WhiteboxTools* project is related to other GHRG software projects including, the [GoSpatial](#) project, which has similar goals but is designed using the Go programming language instead of Rust. *WhiteboxTools* has however superseded the *GoSpatial* project, having subsumed all of its

functionality. *GoSpatial* users should now transition to *WhiteboxTools*.

2. Installation

WhiteboxTools is a stand-alone executable command-line program with no actual installation. Pre-compiled binaries can be downloaded from the [Geomorphometry and Hydrogeomatics Research Group](#) software web site for various supported operating systems. It is likely that *WhiteboxTools* will work on a wider variety of operating systems and architectures. If you do not find your operating system/architecture in the list of available *WhiteboxTool* binaries, then compilation from source code will be necessary. *WhiteboxTools* can be compiled from the source code with the following steps:

1. Install the Rust compiler; Rustup is recommended for this purpose. Further instruction can be found at this [link](#).
2. Download the *Whitebox GAT* [source code](#). Note: *WhiteboxTools* is currently housed as a sub-repository of the main *Whitebox GAT* repo. To download the code, click the green Clone or download button on the GitHub repository site.
3. Decompress the zipped download file.
4. Open a terminal (command prompt) window and change the working directory to the `whitebox_tools` sub-folder, which is contained within the decompressed downloaded *Whitebox GAT* folder:

```
>> cd /path/to/folder/whitebox_tools/
```

5. Finally, use the rust package manager Cargo, which will be installed alongside Rust, to compile the executable:

```
>> cargo build --release
```

Depending on your system, the compilation may take several minutes. When completed, the compiled binary executable file will be contained within the `whitebox_tools/target/release/` folder. Type `./whitebox_tools --help` at the command prompt (after changing the directory to the containing folder) for information on how to run the executable from the terminal.

The '>>' is shorthand used in this document to denote the command prompt and is not intended to be typed.

Be sure to follow the instructions for installing Rust carefully. In particular, if you are installing on Microsoft Windows, you must have a linker installed prior to installing the Rust compiler (*rustc*). The Rust webpage recommends either the **MS Visual C++ 2015 Build Tools** or the GNU equivalent and offers details for each installation approach. You should also consider using **RustUp** to install the Rust compiler.

3. Interacting With *WhiteboxTools* From the Command Prompt

WhiteboxTools is a command-line program and can be run either by calling it from a terminal application with appropriate commands and arguments, or, more conveniently, by calling it from a script. The following commands are recognized by the *WhiteboxTools* library:

Command	Description
--cd, --wd	Changes the working directory; used in conjunction with --run flag.
-h, --help	Prints help information.
-l, --license	Prints the whitebox-tools license.
--listtools	Lists all available tools, with tool descriptions. Keywords may also be used, --listtools slope.
-r, --run	Runs a tool; used in conjunction with --cd flag; -r="LidarInfo".
--toolbox	Prints the toolbox associated with a tool; --toolbox=Slope.
--toolhelp	Prints the help associated with a tool; --toolhelp="LidarInfo".
--toolparameters	Prints the parameters (in json form) for a specific tool; e.g. --toolparameters="FeaturePreservingDenoise".
-v	Verbose mode. Without this flag, tool outputs will not be printed.
--viewcode	Opens the source code of a tool in a web browser; --viewcode="LidarInfo".
--version	Prints the version information.

Generally, the Unix convention is that single-letter arguments (options) use a single hyphen (e.g. -h) while word-arguments (longer, more descriptive argument names) use double hyphens (e.g. --help). The same rule is used for passing arguments to tools as well. Use the *--toolhelp* argument to print information about a specific tool (e.g. --toolhelp=Clump).

Tool names can be specified either using the snake_case or CamelCase convention (e.g. *lidar_info* or *LidarInfo*).

The following is an example of calling the *WhiteboxTools* binary executable file directly from the command prompt:

```
>>./whitebox_tools --wd='/Users/johnlindsay/Documents/data/' ^
--run=DevFromMeanElev --input='DEM clipped.dep' ^
--output='DEV raster.dep' -v
```

Notice the quotation marks (single or double) used around directories and filenames, and string tool arguments in general. Use the '-v' flag (run in verbose mode) to force the tool print output to the command prompt. Please note that the whitebox_tools executable file must have permission to be executed; on some systems, this may require setting special permissions. Also, the above example uses the forward slash character (/), the directory path separator used on unix based systems. On Windows, users should use the back slash character (\) instead. Also, it is sometimes necessary to break (^) commands across mul-

tuple lines, as above, in order to better fit with the documents format. Actual command prompts should be contained to a single line.

4. Interacting With *WhiteboxTools* Using Python Scripting

By combining the *WhiteboxTools* library with the a high-level scripting language, such as Python, users are capable of creating powerful stand-alone geospatial applications and workflow automation scripts. In fact, *WhiteboxTools* functionality can be called from many different programming languages. However, given the prevalent use of the Python language in the geospatial field, the library is distributed with several resources specifically aimed at Python scripting. This section focuses on how Python programming can be used to interact with the *WhiteboxTools* library.

Note that all of the following material assumes the user system is configured with Python 3. The code snippets below are not guaranteed to work with older versions of the language.

Interacting with *WhiteboxTools* from Python scripts is easy. To begin, each script must start by importing the *WhiteboxTools* class, contained with the *whitebox_tools.py* script; a new *WhiteboxTools* object can then be created:

```
from whitebox_tools import WhiteboxTools

wbt = WhiteboxTools()
```

The *WhiteboxTools* class expects to find the *WhiteboxTools* executable file (*whitebox_tools.exe* on Windows and *whitebox_tools* on other platforms) within the same directory as the *whitebox_tools.py* script. If the binary file is located in a separate directory, you will need to set the executable directory as follows:

```
wbt.set_whitebox_dir('/local/path/to/whitebox/binary/')
# Or alternatively...
wbt.exe_path = '/local/path/to/whitebox/binary/'
```

Individual tools can be called using the convenience methods provided in the *WhiteboxTools* class:

```
# This line performs a 5 x 5 mean filter on 'inFile.tif':
wbt.mean_filter('/file/path/inFile.tif', '/file/path/outFile.tif', 5, 5)
```

Each tool has a cooresponding convenience method. Tools can also be called using the *run_tool()* method, specifying the tool name and a list of tool arguments. Each of the tool-specific convenience

methods collect their arguments into a properly formatted list and then ultimately call the `run_tools()` method. Notice that while internally *whitebox_tools.exe* uses CamelCase (e.g. MeanFilter) to denote tool names, the Python interface of *whitebox_tools.py* uses snake_case (e.g. mean_filter), according to Python style conventions. The only exceptions are tools with names that clash with Python keywords (e.g. `And()`, `Not()`, and `Or()`).

The return value can be used to check for errors during operation:

```
if wbt.ruggedness_index('/path/DEM.flt', '/path/ruggedness.flt') != 0:
    # Non-zero returns indicate an error.
    print('ERROR running ruggedness_index')
```

If, like me, your data files tend to be burried deeply in layers of sub-directories, specifying complete file names as input parameters can be tedious. In this case, the best option is setting the working directory before calling tools:

```
from whitebox_tools import WhiteboxTools

wbt = WhiteboxTools()
wbt.work_dir = "/path/to/data/" # Sets the Whitebox working directory

# Because the working directory has been set, file arguments can be
# specified simply using file names, without paths.
wbt.d_inf_flow_accumulation("DEM.dep", "output.dep", log=True)
```

An advanced text editor, such as VS Code or Atom, can provide hints and autocompletion for available tool convenience methods and their parameters, including default values.

Sometimes, however, it can be useful to print a complete list of available tools:

```
print(wbt.list_tools()) # List all tools in WhiteboxTools
```

The `list_tools()` method also takes an optional keywords list to search for tools:

```
# Lists tools with 'lidar' or 'LAS' in tool name or description.
print(wbt.list_tools(['lidar', 'LAS']))
```

To retrieve more detailed information for a specific tool, use the `tool_help()` method:

```
print(wbt.tool_help("elev_percentile"))
```

```
19 f arc_sin
20 f arc_tan
21 f aspect
22 f atan2
23 f average_flowpath_slope
24 f average_overlay
25 f average_upslope_flowpath_length
26 f balance_contrast_enhancement
27 f basins
28 f bilateral_filter
29
30 bilateral_filter(self, input, output, sigma_dist=0.75, sigma_int=1.0,
31 callback=default_callback)
32
33 A bilateral filter is an edge-preserving smoothing filter introduced by Tomasi and Manduchi (1998).
34
35 Keyword arguments:
36
37 input -- Input raster file.
38 output -- Output raster file.
39 sigma_dist -- Standard deviation in distance in pixels.
40 sigma_int -- Standard deviation in intensity in pixels.
41 callback -- Custom function for handling tool text outputs.
42 wbt.
```

Autocompletion in Atom text editor makes calling *WhiteboxTools* functions easier.

`tool_help()` prints tool details including a description, tool parameters (and their flags), and example usage at the command line prompt. The above statement prints this report:

ElevPercentile

Description:

Calculates the elevation percentile raster from a DEM.

Toolbox: Geomorphometric Analysis

Parameters:

Flag	Description
-i, --input, --dem	Input raster DEM file.
-o, --output	Output raster file.
--filterx	Size of the filter kernel in the x-direction.
--filtery	Size of the filter kernel in the y-direction.
--sig_digits	Number of significant digits.

Example usage:

```
>>./whitebox_tools -r=ElevPercentile -v --wd="/path/to/data/" --dem=DEM.dep
>>-o=output.dep --filterx=25
```

Tools will frequently print text to the standard output during their execution, including warnings, progress updates and other notifications. Sometimes, when users run many tools in complex workflows and in batch mode, these output messages can be undesirable. Most tools will have their outputs suppressed by setting the *verbose* mode to *False* as follows:

```
wbt.set_verbose_mode(False)
# Or, alternatively...
wbt.verbose = False
```

Alternatively, it may be helpful to capture the text output of a tool for custom processing. This is achieved by specifying a custom *callback* function to the tool's run method:

```
# This callback function suppresses printing progress updates,
# which always use the '%' character. The callback function
# approach is flexible and allows for any level of complex
# interaction with tool outputs.
def my_callback(value):
    if not "%" in value:
        print(value)

wbt.slope('DEM.tif', 'slope_raster.tif', callback=my_callback)
```

Callback functions can also serve as a means of cancelling operations:

```
def my_callback(value):
    if user_selected_cancel_btn: # Assumes a 'Cancel' button on a GUI
        print('Cancelling operation...')
        wbt.cancel_op = True
    else:
        print(value)

wbt.breach_depressions('DEM.flt', 'DEM_breached.flt', callback=my_callback)
```

The *whitebox_tools.py* script provides several other functions for interacting with the *WhiteboxTools* library, including:

```
# Print the WhiteboxTools help...a listing of available commands
print(wbt.help())

# Print the WhiteboxTools license
print(wbt.license())

# Print the WhiteboxTools version
print("Version information: {}".format(wbt.version()))

# Get the toolbox associated with a tool
tb = wbt.toolbox('lidar_info')

# Retrieve a JSON object of a tool's parameters.
tp = tool_parameters('raster_histogram')


# Opens a browser and navigates to a tool's source code in the
# WhiteboxTools GitHub repository
view_code('watershed')
```

For a working example of how to call functions and run tools from Python, see the *whitebox_example.py* Python script, which is distributed with the *WhiteboxTools* library.

5. WhiteboxTools Runner

There is a Python script contained within the *WhiteboxTools* directory called '*wb_runner.py*'. This script is intended to provide a very basic user-interface, *WhiteboxTools Runner*, for running the tools contained

within the *WhiteboxTools* library. The user-interface uses Python's TkInter GUI library and is cross-platform. The user interface is currently experimental and is under heavy testing. Please report any issues that you experience in using it.



The *WhiteboxTools Runner* user-interface

The *WhiteboxTools Runner* does not rely on the *Whitebox GAT* user interface at all and can therefore be used independent of the larger project. The script must be run from a directory that also contains the '*whitebox_tools.py*' Python script and the '*whitebox_tools*' executable file. There are plans to link tool help documentation in *WhiteboxTools Runner* and to incorporate toolbox information, rather than one large listing of available tools.

6. Available Tools

Eventually most of *Whitebox GAT*'s approximately 400 tools [will be ported](#) to *WhiteboxTools*, although this is an immense task. Support for vector data (Shapefile/GeoJSON) reading/writing and a topological analysis library (like the Java Topology Suite) will need to be added in order to port the tools involving vector spatial data. Opportunities to parallelize algorithms will be sought during porting. All new plugin tools will be added to *Whitebox GAT* using this library of functions.

The library currently contains the following 279 tools, which are each grouped based on their main function into one of the following categories: *Data Tools*, *Geomorphometric Analysis* (i.e. digital terrain analysis), *GIS Analysis*, *Hydrological Analysis*, *Image Analysis*, *LiDAR Analysis*, *Mathematical and Statistical Analysis*, and *Stream Network Analysis*. To retrieve detailed information about a tool's input arguments and example usage, either use the `--toolhelp` command from the terminal, or the `tool_help('tool_name')` function from the `whitebox_tools.py` script. The following is a complete listing of available tools, with brief descriptions, tool parameter, and example usage.

6.1 Data Tools

6.1.1 ConvertNodataToZero

Converts nodata values in a raster to zero.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ConvertNodataToZero -v ^
--wd="/path/to/data/" --input=in.dep -o=NewRaster.dep
```

Python function name: `convert_nodata_to_zero`

6.1.2 ConvertRasterFormat

Converts raster data from one format to another.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ConvertRasterFormat -v ^
--wd="/path/to/data/" --input=DEM.dep -o=output.dep
```

Python function name: convert_raster_format

6.1.3 NewRasterFromBase

Creates a new raster using a base image.

Parameters:

Flag	Description
-i, --base	Input base raster file
-o, --output	Output raster file
--value	Constant value to fill raster with; either 'nodata' or numeric value
--data_type	Output raster data type; options include 'double' (64-bit), 'float' (32-bit), and 'integer' (signed 16-bit) (default is 'float')

Command-line Interface:

```
>> ./whitebox_tools -r=NewRasterFromBase -v ^
--wd="/path/to/data/" --base=base.dep -o=NewRaster.dep ^
--value=0.0 --data_type=integer
>> ./whitebox_tools ^
-r=NewRasterFromBase -v --wd="/path/to/data/" --base=base.dep ^
-o=NewRaster.dep --value=nodata
```

Python function name: new_raster_from_base

6.1.4 PrintGeoTiffTags

Prints the tags within a GeoTIFF.

Parameters:

Flag	Description
-i, --input	Input GeoTIFF file

Command-line Interface:

```
>> ./whitebox_tools -r=PrintGeoTiffTags -v ^
--wd="/path/to/data/" --input=DEM.tiff
```

Python function name: print_geo_tiff_tags

6.1.5 SetNoDataValue

Assign a specified value in an input image to the NoData value.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--back_value	Background value to set to nodata

Command-line Interface:

```
>>./whitebox_tools -r=SetNoDataValue -v --wd="/path/to/data/" ^
-i=in.dep -o=newRaster.dep --back_value=1.0
```

Python function name: set_nodata_value

6.2 GIS Analysis

6.2.1 AggregateRaster

Aggregates a raster to a lower resolution.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--agg_factor	Aggregation factor, in pixels
--type	Statistic used to fill output pixels

Command-line Interface:

```
>>./whitebox_tools -r=AggregateRaster -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep ^
--output_text
```

Python function name: aggregate_raster

6.2.2 Centroid

Calculates the centroid, or average location, of raster polygon objects.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--text_output	Optional text output

Command-line Interface:

```
>>./whitebox_tools -r=Centroid -v --wd="/path/to/data/" ^
-i=polygons.dep -o=output.dep
>>./whitebox_tools -r=Centroid ^
-v --wd="/path/to/data/" -i=polygons.dep -o=output.dep ^
--text_output
```

Python function name: centroid

6.2.3 Clump

Groups cells that form physically discrete areas, assigning them unique identifiers.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--diag	Flag indicating whether diagonal connections should be considered
--zero_back	Flag indicating whether zero values should be treated as a background

Command-line Interface:

```
>>./whitebox_tools -r=Clump -v --wd="/path/to/data/" ^
-i=input.dep -o=output.dep --diag
```

Python function name: clump

6.2.4 CreatePlane

Creates a raster image based on the equation for a simple plane.

Parameters:

Flag	Description
--base	Input base raster file
-o, --output	Output raster file
--gradient	Slope gradient in degrees (-85.0 to 85.0)
--aspect	Aspect (direction) in degrees clockwise from north (0.0-360.0)
--constant	Constant value

Command-line Interface:

```
>>./whitebox_tools -r=CreatePlane -v --wd="/path/to/data/" ^
--base=base.dep -o=NewRaster.dep --gradient=15.0 ^
--aspect=315.0
```

Python function name: create_plane

6.2.5 RadiusOfGyration

Calculates the distance of cells from their polygon's centroid.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--text_output	Optional text output

Command-line Interface:

```
>>./whitebox_tools -r=RadiusOfGyration -v ^
--wd="/path/to/data/" -i=polygons.dep -o=output.dep ^
--text_output
```

Python function name: radius_of_gyration

6.2.6 RasterCellAssignment

Assign row or column number to cells.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
-a, --assign	Which variable would you like to assign to grid cells? Options include 'column', 'row', 'x', and 'y'

Command-line Interface:

```
>> ./whitebox_tools -r=RasterCellAssignment -v ^
--wd="/path/to/data/" -i='input.dep' -o=output.dep ^
--assign='column'
```

Python function name: raster_cell_assignment

6.3 GIS Analysis => Distance Tools

6.3.1 BufferRaster

Maps a distance-based buffer around each non-background (non-zero/non-nodata) grid cell in an input image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--size	Buffer size
--gridcells	Optional flag to indicate that the 'size' threshold should be measured in grid cells instead of the default map units

Command-line Interface:

```
>> ./whitebox_tools -r=BufferRaster -v --wd="/path/to/data/" ^
-i=DEM.dep -o=output.dep
```

Python function name: buffer_raster

6.3.2 CostAllocation

Identifies the source cell to which each grid cell is connected by a least-cost pathway in a cost-distance analysis.

Parameters:

Flag	Description
--source	Input source raster file
--backlink	Input backlink raster file generated by the cost-distance tool
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=CostAllocation -v --wd="/path/to/data/" ^
--source='source.dep' --backlink='backlink.dep' ^
-o='output.dep'
```

Python function name: cost_allocation

6.3.3 CostDistance

Performs cost-distance accumulation on a cost surface and a group of source cells.

Parameters:

Flag	Description
--source	Input source raster file
--cost	Input cost (friction) raster file
--out_accum	Output cost accumulation raster file
--out_backlink	Output backlink raster file

Command-line Interface:

```
>>./whitebox_tools -r=CostDistance -v --wd="/path/to/data/" ^
--source=src.dep --cost=cost.dep --out_accum=accum.dep ^
--out_backlink=backlink.dep
```

Python function name: cost_distance

6.3.4 CostPathway

Performs cost-distance pathway analysis using a series of destination grid cells.

Parameters:

Flag	Description
--destination	Input destination raster file
--backlink	Input backlink raster file generated by the cost-distance tool
-o, --output	Output cost pathway raster file
--zero_background	Flag indicating whether zero values should be treated as a background

Command-line Interface:

```
>>./whitebox_tools -r=CostPathway -v --wd="/path/to/data/" ^
--destination=dst.dep --backlink=backlink.dep ^
--output=cost_path.dep
```

Python function name: cost_pathway

6.3.5 EuclideanAllocation

Assigns grid cells in the output raster the value of the nearest target cell in the input image, measured by the Shih and Wu (2004) Euclidean distance transform.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=EuclideanAllocation -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep
```

Python function name: euclidean_allocation

6.3.6 EuclideanDistance

Calculates the Shih and Wu (2004) Euclidean distance transform.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=EuclideanDistance -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep
```

Python function name: euclidean_distance

6.4 GIS Analysis => Overlay Tools

6.4.1 AverageOverlay

Calculates the average for each grid cell from a group of raster images.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=AverageOverlay -v --wd='/path/to/data/' ^
-i='image1.dep;image2.dep;image3.dep' -o=output.dep
```

Python function name: average_overlay

6.4.2 HighestPosition

Identifies the stack position of the maximum value within a raster stack on a cell-by-cell basis.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=HighestPosition -v ^
--wd='/path/to/data/' -i='image1.dep;image2.dep;image3.dep' ^
-o=output.dep
```

Python function name: highest_position

6.4.3 LowestPosition

Identifies the stack position of the minimum value within a raster stack on a cell-by-cell basis.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=LowestPosition -v --wd='/path/to/data/' ^
-i='image1.dep;image2.dep;image3.dep' -o=output.dep
```

Python function name: lowest_position

6.4.4 MaxAbsoluteOverlay

Evaluates the maximum absolute value for each grid cell from a stack of input rasters.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=MaxAbsoluteOverlay -v ^
--wd='/path/to/data/' -i='image1.dep;image2.dep;image3.dep' ^
-o=output.dep
```

Python function name: max_absolute_overlay

6.4.5 MaxOverlay

Evaluates the maximum value for each grid cell from a stack of input rasters.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=MaxOverlay -v --wd='/path/to/data/' ^
-i='image1.dep;image2.dep;image3.dep' -o=output.dep
```

Python function name: max_overlay

6.4.6 MinAbsoluteOverlay

Evaluates the minimum absolute value for each grid cell from a stack of input rasters.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=MinAbsoluteOverlay -v ^
--wd='/path/to/data/' -i='image1.dep;image2.dep;image3.dep' ^
-o=output.dep
```

Python function name: min_absolute_overlay

6.4.7 MinOverlay

Evaluates the minimum value for each grid cell from a stack of input rasters.

Parameters:

Flag	Description
-i, --inputs	Input raster files

Flag	Description
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=MinOverlay -v --wd='/path/to/data/' ^
-i='image1.dep;image2.dep;image3.dep' -o=output.dep
```

Python function name: min_overlay

6.4.8 PercentEqualTo

Calculates the percentage of a raster stack that have cell values equal to an input on a cell-by-cell basis.

Parameters:

Flag	Description
-i, --inputs	Input raster files
--comparison	Input comparison raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=PercentEqualTo -v --wd='/path/to/data/' ^
-i='image1.dep;image2.dep;image3.dep' --comparison='comp.dep' ^
-o='output.dep'
```

Python function name: percent_equal_to

6.4.9 PercentGreaterThan

Calculates the percentage of a raster stack that have cell values greater than an input on a cell-by-cell basis.

Parameters:

Flag	Description
-i, --inputs	Input raster files
--comparison	Input comparison raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=PercentGreaterThan -v ^
--wd='/path/to/data/' -i='image1.dep;image2.dep;image3.dep' ^
--comparison='comp.dep' -o='output.dep'
```

Python function name: percent_greater_than

6.4.10 PercentLessThan

Calculates the percentage of a raster stack that have cell values less than an input on a cell-by-cell basis.

Parameters:

Flag	Description
-i, --inputs	Input raster files
--comparison	Input comparison raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=PercentLessThan -v ^
--wd='/path/to/data/' -i='image1.dep;image2.dep;image3.dep' ^
--comparison='comp.dep' -o='output.dep'
```

Python function name: percent_less_than

6.4.11 PickFromList

Outputs the value from a raster stack specified by a position raster.

Parameters:

Flag	Description
-i, --inputs	Input raster files
--pos_input	Input position raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=PickFromList -v --wd='/path/to/data/' ^
--pos_input=position.dep -i='image1.dep;image2.dep;image3.dep' ^
-o=output.dep
```


Python function name: pick_from_list

6.4.12 WeightedSum

Performs a weighted-sum overlay on multiple input raster images.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output raster file
-w, --weights	Weight values, contained in quotes and separated by commas or semicolons

Command-line Interface:

```
>>./whitebox_tools -r=WeightedSum -v --wd='/path/to/data/' ^
-i='image1.dep;image2.dep;image3.dep' -o=output.dep ^
--weights='0.3;0.2;0.5'
```

Python function name: weighted_sum

6.5 GIS Analysis => Patch Shape Tools

6.5.1 EdgeProportion

Calculate the proportion of cells in a raster polygon that are edge cells.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--output_text	flag indicating whether a text report should also be output

Command-line Interface:

```
>>./whitebox_tools -r=EdgeProportion -v --wd="/path/to/data/" ^
-i=input.dep -o=output.dep --output_text
```

Python function name: edge_proportion

6.5.2 FindPatchOrClassEdgeCells

Finds all cells located on the edge of patch or class features.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>> ./whitebox_tools -r=FindPatchOrClassEdgeCells -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep
```

Python function name: find_patch_or_class_edge_cells

6.6 GIS Analysis => Reclass Tools

6.6.1 Reclass

Reclassifies the values in a raster image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--reclass_vals	Reclassification triplet values (new value; from value; to less than), e.g. '0.0;0.0;1.0;1.0;1.0;2.0'
--assign_mode	Optional Boolean flag indicating whether to operate in assign mode, reclass_vals values are interpreted as new value; old value pairs

Command-line Interface:

```
>> ./whitebox_tools -r=Reclass -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep ^
--reclass_vals='0.0;0.0;1.0;1.0;1.0;2.0'
>> ./whitebox_tools ^
-r=Reclass -v --wd="/path/to/data/" -i='input.dep' ^
-o=output.dep --reclass_vals='10;1;20;2;30;3;40;4' ^
--assign_mode
```

Python function name: reclass

6.6.2 ReclassEqualInterval

Reclassifies the values in a raster image based on equal-ranges.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--interval	Class interval size
--start_val	Optional starting value (default is input minimum value)
--end_val	Optional ending value (default is input maximum value)

Command-line Interface:

```
>>./whitebox_tools -r=ReclassEqualInterval -v ^
--wd="/path/to/data/" -i='input.dep' -o=output.dep ^
--interval=10.0 --start_val=0.0
```

Python function name: reclass_equal_interval

6.6.3 ReclassFromFile

Reclassifies the values in a raster image using reclass ranges in a text file.

Parameters:

Flag	Description
-i, --input	Input raster file
--reclass_file	Input text file containing reclass ranges
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ReclassFromFile -v ^
--wd="/path/to/data/" -i='input.dep' ^
--reclass_file='reclass.txt' -o=output.dep
```

Python function name: reclass_from_file

6.7 Geomorphometric Analysis

6.7.1 Aspect

Calculates an aspect raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=Aspect -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep
```

Python function name: aspect

6.7.2 DevFromMeanElev

Calculates deviation from mean elevation.

Parameters:

Flag	Description
-i, --input, --dem	Input raster DEM file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=DevFromMeanElev -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--filter=25
```

Python function name: dev_from_mean_elev

6.7.3 DiffFromMeanElev

Calculates difference from mean elevation (equivalent to a high-pass filter).

Parameters:

Flag	Description
-i, --input, --dem	Input raster DEM file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=DiffFromMeanElev -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--filter=25
```

Python function name: diff_from_mean_elev

6.7.4 DirectionalRelief

Calculates relief for cells in an input DEM for a specified direction.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--azimuth	Wind azimuth in degrees
--max_dist	Optional maximum search distance (unspecified if none; in xy units)

Command-line Interface:

```
>>./whitebox_tools -r=DirectionalRelief -v ^
--wd="/path/to/data/" -i='input.dep' -o=output.dep ^
--azimuth=315.0
```

Python function name: directional_relief

6.7.5 DownslopeIndex

Calculates the Hjerdt et al. (2004) downslope index.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--drop	Vertical drop value (default is 2.0)
--out_type	Output type, options include 'tangent', 'degrees', 'radians', 'distance' (default is 'tangent')

Command-line Interface:

```
>>./whitebox_tools -r=DownslopeIndex -v --wd="/path/to/data/" ^
--dem=pointer.dep -o=dsi.dep --drop=5.0 --out_type=distance
```

Python function name: downslope_index

6.7.6 ElevAbovePit

Calculate the elevation of each grid cell above the nearest downstream pit cell or grid edge cell.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ElevAbovePit -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep
```

Python function name: elev_above_pit

6.7.7 ElevPercentile

Calculates the elevation percentile raster from a DEM.

Parameters:

Flag	Description
-i, --input, --dem	Input raster DEM file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction
--sig_digits	Number of significant digits

Command-line Interface:

```
>>./whitebox_tools -r=ElevPercentile -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep --filter=25
```

Python function name: elev_percentile

6.7.8 ElevRelativeToMinMax

Calculates the elevation of a location relative to the minimum and maximum elevations in a DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ElevRelativeToMinMax -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep
```

Python function name: elev_relative_to_min_max

6.7.9 ElevRelativeToWatershedMinMax

Calculates the elevation of a location relative to the minimum and maximum elevations in a watershed.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
--watersheds	Input raster watersheds file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ElevRelativeToWatershedMinMax -v ^
--wd="/path/to/data/" --dem=DEM.dep --watersheds=watershed.dep ^
-o=output.dep
```

Python function name: elev_relative_to_watershed_min_max

6.7.10 FeaturePreservingDenoise

Reduces short-scale variation in an input DEM using a modified Sun et al. (2007) algorithm.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--filter	Size of the filter kernel
--norm_diff	Maximum difference in normal vectors, in degrees
--num_iter	Number of iterations
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=FeaturePreservingDenoise -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep
```

Python function name: feature_preserving_denoise

6.7.11 FetchAnalysis

Performs an analysis of fetch or upwind distance to an obstacle.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--azimuth	Wind azimuth in degrees in degrees
--hgt_inc	Height increment value

Command-line Interface:


```
>>./whitebox_tools -r=FetchAnalysis -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep --azimuth=315.0
```

Python function name: fetch_analysis

6.7.12 FillMissingData

Fills nodata holes in a DEM.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filter	Filter size (cells)

Command-line Interface:

```
>>./whitebox_tools -r=FillMissingData -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep --filter=25
```

Python function name: fill_missing_data

6.7.13 FindRidges

Identifies potential ridge and peak grid cells.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--line_thin	Optional flag indicating whether post-processing line-thinning should be performed

Command-line Interface:

```
>>./whitebox_tools -r=FindRidges -v --wd="/path/to/data/" ^
--dem=pointer.dep -o=out.dep --line_thin
```

Python function name: find_ridges

6.7.14 Hillshade

Calculates a hillshade raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--azimuth	Illumination source azimuth in degrees
--altitude	Illumination source altitude in degrees
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=Hillshade -v --wd="/path/to/data/" ^
-i=DEM.dep -o=output.dep --azimuth=315.0 --altitude=30.0
```

Python function name: hillshade

6.7.15 HorizonAngle

Calculates horizon angle (maximum upwind slope) for each grid cell in an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--azimuth	Wind azimuth in degrees
--max_dist	Optional maximum search distance (unspecified if none; in xy units)

Command-line Interface:

```
>>./whitebox_tools -r=HorizonAngle -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep --azimuth=315.0
```

Python function name: horizon_angle

6.7.16 HypsometricAnalysis

Calculates a hypsometric curve for one or more DEMs.

Parameters:

Flag	Description
-i, --inputs	Input DEM files
--watershed	Input watershed files (optional)
-o, --output	Output HTML file (default name will be based on input file if unspecified)

Command-line Interface:

```
>>./whitebox_tools -r=HypsometricAnalysis -v ^
--wd="/path/to/data/" -i="DEM1.tif;DEM2.tif" ^
--watershed="ws1.tif;ws2.tif" -o=outfile.html
```

Python function name: `hypsometric_analysis`

6.7.17 MaxAnisotropyDev

Calculates the maximum anisotropy (directionality) in elevation deviation over a range of spatial scales.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
--out_mag	Output raster DEVmax magnitude file
--out_scale	Output raster DEVmax scale file
--min_scale	Minimum search neighbourhood radius in grid cells
--max_scale	Maximum search neighbourhood radius in grid cells
--step	Step size as any positive non-zero integer

Command-line Interface:

```
>>./whitebox_tools -r=MaxAnisotropyDev -v ^
--wd="/path/to/data/" --dem=DEM.dep --out_mag=DEVmax_mag.dep ^
--out_scale=DEVmax_scale.dep --min_scale=1 --max_scale=1000 ^
--step=5
```

Python function name: `max_anisotropy_dev`

6.7.18 MaxBranchLength

Lindsay and Seibert's (2013) branch length index is used to map drainage divides or ridge lines.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--log	Optional flag to request the output be log-transformed

Command-line Interface:

```
>>./whitebox_tools -r=MaxBranchLength -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep
```

Python function name: max_branch_length

6.7.19 MaxDownslopeElevChange

Calculates the maximum downslope change in elevation between a grid cell and its eight downslope neighbors.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=MaxDownslopeElevChange -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=out.dep
```

Python function name: max_downslope_elev_change

6.7.20 MaxElevDevSignature

Calculates the maximum elevation deviation over a range of spatial scales and for a set of points.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
--points	Input vector points file
-o, --output	Output HTML file

Flag	Description
--min_scale	Minimum search neighbourhood radius in grid cells
--max_scale	Maximum search neighbourhood radius in grid cells
--step	Step size as any positive non-zero integer

Command-line Interface:

```
>>./whitebox_tools -r=MaxElevDevSignature -v ^
--wd="/path/to/data/" --dem=DEM.dep --points=sites.shp ^
--output=topo_position.html --min_scale=1 --max_scale=1000 ^
--step=5
```

Python function name: max_elev_dev_signature

6.7.21 MaxElevationDeviation

Calculates the maximum elevation deviation over a range of spatial scales.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
--out_mag	Output raster DEVmax magnitude file
--out_scale	Output raster DEVmax scale file
--min_scale	Minimum search neighbourhood radius in grid cells
--max_scale	Maximum search neighbourhood radius in grid cells
--step	Step size as any positive non-zero integer

Command-line Interface:

```
>>./whitebox_tools -r=MaxElevationDeviation -v ^
--wd="/path/to/data/" --dem=DEM.dep --out_mag=DEVmax_mag.dep ^
--out_scale=DEVmax_scale.dep --min_scale=1 --max_scale=1000 ^
--step=5
```

Python function name: max_elevation_deviation

6.7.22 MinDownslopeElevChange

Calculates the minimum downslope change in elevation between a grid cell and its eight downslope neighbors.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=MinDownslopeElevChange -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=out.dep
```

Python function name: min_downslope_elev_change

6.7.23 MultiscaleRoughness

Calculates surface roughness over a range of spatial scales.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
--out_mag	Output raster roughness magnitude file
--out_scale	Output raster roughness scale file
--min_scale	Minimum search neighbourhood radius in grid cells
--max_scale	Maximum search neighbourhood radius in grid cells
--step	Step size as any positive non-zero integer

Command-line Interface:

```
>>./whitebox_tools -r=MultiscaleRoughness -v ^
--wd="/path/to/data/" --dem=DEM.dep --out_mag=roughness_mag.dep ^
--out_scale=roughness_scale.dep --min_scale=1 --max_scale=1000 ^
--step=5
```

Python function name: multiscale_roughness

6.7.24 MultiscaleRoughnessSignature

Calculates the surface roughness for points over a range of spatial scales.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
--points	Input vector points file
-o, --output	Output HTML file
--min_scale	Minimum search neighbourhood radius in grid cells
--max_scale	Maximum search neighbourhood radius in grid cells
--step	Step size as any positive non-zero integer

Command-line Interface:

```
>>./whitebox_tools -r=MultiscaleRoughnessSignature -v ^
--wd="/path/to/data/" --dem=DEM.dep --points=sites.shp ^
--output=roughness.html --min_scale=1 --max_scale=1000 ^
--step=5
```

Python function name: multiscale_roughness_signature

6.7.25 MultiscaleTopographicPositionImage

Creates a multiscale topographic position image from three DEVmax rasters of differing spatial scale ranges.

Parameters:

Flag	Description
--local	Input local-scale topographic position (DEVmax) raster file
--meso	Input meso-scale topographic position (DEVmax) raster file
--broad	Input broad-scale topographic position (DEVmax) raster file
-o, --output	Output raster file
--lightness	Image lightness value (default is 1.2)

Command-line Interface:

```
>>./whitebox_tools -r=MultiscaleTopographicPositionImage -v ^
--wd="/path/to/data/" --local=DEV_local.dep --meso=DEV_meso.dep ^
--broad=DEV_broad.dep -o=output.dep --lightness=1.5
```

Python function name: multiscale_topographic_position_image

6.7.26 NumDownslopeNeighbours

Calculates the number of downslope neighbours to each grid cell in a DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=NumDownslopeNeighbours -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep
```

Python function name: num_downslope_neighbours

6.7.27 NumUpslopeNeighbours

Calculates the number of upslope neighbours to each grid cell in a DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=NumUpslopeNeighbours -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep
```

Python function name: num_upslope_neighbours

6.7.28 PennockLandformClass

Classifies hillslope zones based on slope, profile curvature, and plan curvature.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--slope	Slope threshold value, in degrees (default is 3.0)
--prof	Profile curvature threshold value (default is 0.1)
--plan	Plan curvature threshold value (default is 0.0)

Flag	Description
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=PennockLandformClass -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep --slope=3.0 ^
--prof=0.1 --plan=0.0
```

Python function name: pennock_landform_class

6.7.29 PercentElevRange

Calculates percent of elevation range from a DEM.

Parameters:

Flag	Description
-i, --input, --dem	Input raster DEM file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=PercentElevRange -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep --filter=25
```

Python function name: percent_elev_range

6.7.30 PlanCurvature

Calculates a plan (contour) curvature raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=PlanCurvature -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep
```

Python function name: plan_curvature

6.7.31 Profile

Plots profiles from digital surface models.

Parameters:

Flag	Description
--lines	Input vector line file
--surface	Input raster surface file
-o, --output	Output HTML file

Command-line Interface:

```
>>./whitebox_tools -r=Profile -v --wd="/path/to/data/" ^
--lines=profile.shp --surface=dem.dep -o=profile.html
```

Python function name: profile

6.7.32 ProfileCurvature

Calculates a profile curvature raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=ProfileCurvature -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep
```

Python function name: profile_curvature

6.7.33 RelativeAspect

Calculates relative aspect (relative to a user-specified direction) from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--azimuth	Illumination source azimuth
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=RelativeAspect -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep --azimuth=180.0
```

Python function name: relative_aspect

6.7.34 RelativeStreamPowerIndex

Calculates the relative stream power index.

Parameters:

Flag	Description
--sca	Input raster specific contributing area (SCA) file
--slope	Input raster slope file
-o, --output	Output raster file
--exponent	SCA exponent value

Command-line Interface:

```
>>./whitebox_tools -r=RelativeStreamPowerIndex -v ^
--wd="/path/to/data/" --sca='flow_accum.dep' ^
--slope='slope.dep' -o=output.dep --exponent=1.1
```

Python function name: relative_stream_power_index

6.7.35 RelativeTopographicPosition

Calculates the relative topographic position index from a DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=RelativeTopographicPosition -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--filter=25
```

Python function name: relative_topographic_position

6.7.36 RemoveOffTerrainObjects

Removes off-terrain objects from a raster digital elevation model (DEM).

Parameters:

Flag	Description
-i, --input, --dem	Input raster DEM file
-o, --output	Output raster file
--filter	Filter size (cells)
--slope	Slope threshold value

Command-line Interface:

```
>>./whitebox_tools -r=RemoveOffTerrainObjects -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=bare_earth_DEM.dep ^
--filter=25 --slope=10.0
```

Python function name: remove_off_terrain_objects

6.7.37 RuggednessIndex

Calculates the Riley et al.'s (1999) terrain ruggedness index from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=RuggednessIndex -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep
```

Python function name: ruggedness_index

6.7.38 SedimentTransportIndex

Calculates the sediment transport index.

Parameters:

Flag	Description
--sca	Input raster specific contributing area (SCA) file
--slope	Input raster slope file
-o, --output	Output raster file
--sca_exponent	SCA exponent value
--slope_exponent	Slope exponent value

Command-line Interface:

```
>>./whitebox_tools -r=SedimentTransportIndex -v ^
--wd="/path/to/data/" --sca='flow_accum.dep' ^
--slope='slope.dep' -o=output.dep --sca_exponent=0.5 ^
--slope_exponent=1.0
```

Python function name: sediment_transport_index

6.7.39 Slope

Calculates a slope raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file

Flag	Description
-o, --output	Output raster file
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=Slope -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep
```

Python function name: slope

6.7.40 SlopeVsElevationPlot

Creates a slope vs. elevation plot for one or more DEMs.

Parameters:

Flag	Description
-i, --inputs	Input DEM files
--watershed	Input watershed files (optional)
-o, --output	Output HTML file (default name will be based on input file if unspecified)

Command-line Interface:

```
>>./whitebox_tools -r=SlopeVsElevationPlot -v ^
--wd="/path/to/data/" -i="DEM1.tif;DEM2.tif" ^
--watershed="ws1.tif;ws2.tif" -o=outfile.html
```

Python function name: slope_vs_elevation_plot

6.7.41 TangentialCurvature

Calculates a tangential curvature raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=TangentialCurvature -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep
```

Python function name: tangential_curvature

6.7.42 TotalCurvature

Calculates a total curvature raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--zfactor	Optional multiplier for when the vertical and horizontal units are not the same

Command-line Interface:

```
>>./whitebox_tools -r=TotalCurvature -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep
```

Python function name: total_curvature

6.7.43 Viewshed

Identifies the viewshed for a point or set of points.

Parameters:

Flag	Description
--dem	Input raster DEM file
--stations	Input viewing station raster file
-o, --output	Output raster file
--height	Viewing station height, in z units

Command-line Interface:

```
>>./whitebox_tools -r=Viewshed -v --wd="/path/to/data/" ^
--dem='dem.dep' --stations='stations.dep' -o=output.dep ^
--height=10.0
```

Python function name: viewshed

6.7.44 WetnessIndex

Calculates the topographic wetness index, $\ln(A / \tan(\text{slope}))$.

Parameters:

Flag	Description
--sca	Input raster specific contributing area (SCA) file
--slope	Input raster slope file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=WetnessIndex -v --wd="/path/to/data/" ^
--sca='flow_accum.dep' --slope='slope.dep' -o=output.dep
```

Python function name: wetness_index

6.8 Hydrological Analysis

6.8.1 AverageFlowpathSlope

Measures the average slope gradient from each grid cell to all upslope divide cells.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=AverageFlowpathSlope -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep
```

Python function name: average_flowpath_slope

6.8.2 AverageUpslopeFlowpathLength

Measures the average length of all upslope flowpaths draining each grid cell.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=AverageUpslopeFlowpathLength -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep
```

Python function name: average_upslope_flowpath_length

6.8.3 Basins

Identifies drainage basins that drain to the DEM edge.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=Basins -v --wd="/path/to/data/" ^
--d8_pntr='d8pntr.dep' -o='output.dep'
```

Python function name: basins

6.8.4 BreachDepressions

Breaches all of the depressions in a DEM using Lindsay's (2016) algorithm. This should be preferred over depression filling in most cases.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--max_depth	Optional maximum breach depth (default is Inf)
--max_length	Optional maximum breach channel length (in grid cells; default is Inf)

Command-line Interface:

```
>>./whitebox_tools -r=BreachDepressions -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep
```

Python function name: breach_depressions

6.8.5 BreachSingleCellPits

Removes single-cell pits from an input DEM by breaching.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=BreachSingleCellPits -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep
```

Python function name: breach_single_cell_pits

6.8.6 D8FlowAccumulation

Calculates a D8 flow accumulation raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--out_type	Output type; one of 'cells', 'specific contributing area' (default), and 'catchment area'
--log	Optional flag to request the output be log-transformed

Flag	Description
--clip	Optional flag to request clipping the display max by 1%

Command-line Interface:

```
>>./whitebox_tools -r=D8FlowAccumulation -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--out_type='cells'
>>./whitebox_tools -r=D8FlowAccumulation -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--out_type='specific catchment area' --log --clip
```

Python function name: d8_flow_accumulation

6.8.7 D8MassFlux

Performs a D8 mass flux calculation.

Parameters:

Flag	Description
--dem	Input raster DEM file
--loading	Input loading raster file
--efficiency	Input efficiency raster file
--absorption	Input absorption raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=D8MassFlux -v --wd="/path/to/data/" ^
--dem=DEM.dep --loading=load.dep --efficiency=eff.dep ^
--absorption=abs.dep -o=output.dep
```

Python function name: d8_mass_flux

6.8.8 D8Pointer

Calculates a D8 flow pointer raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=D8Pointer -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep
```

Python function name: d8_pointer

6.8.9 DInfFlowAccumulation

Calculates a D-infinity flow accumulation raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--out_type	Output type; one of 'cells', 'sca' (default), and 'ca'
--threshold	Optional convergence threshold parameter, in grid cells; default is infinity
--log	Optional flag to request the output be log-transformed
--clip	Optional flag to request clipping the display max by 1%

Command-line Interface:

```
>>./whitebox_tools -r=DInfFlowAccumulation -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--out_type=sca
>>./whitebox_tools -r=DInfFlowAccumulation -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--out_type=sca --threshold=10000 --log --clip
```

Python function name: d_inf_flow_accumulation

6.8.10 DInfMassFlux

Performs a D-infinity mass flux calculation.

Parameters:

Flag	Description
--dem	Input raster DEM file
--loading	Input loading raster file
--efficiency	Input efficiency raster file
--absorption	Input absorption raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=DInfMassFlux -v --wd="/path/to/data/" ^
--dem=DEM.dep --loading=load.dep --efficiency=eff.dep ^
--absorption=abs.dep -o=output.dep
```

Python function name: d_inf_mass_flux

6.8.11 DInfPointer

Calculates a D-infinity flow pointer (flow direction) raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=DInfPointer -v --wd="/path/to/data/" ^
--dem=DEM.dep
```

Python function name: d_inf_pointer

6.8.12 DepthInSink

Measures the depth of sinks (depressions) in a DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--zero_background	Flag indicating whether the background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=DepthInSink -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep --zero_background
```

Python function name: depth_in_sink

6.8.13 DownslopeDistanceToStream

Measures distance to the nearest downslope stream cell.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
--streams	Input raster streams file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=DownslopeDistanceToStream -v ^
--wd="/path/to/data/" --dem='dem.dep' --streams='streams.dep' ^
-o='output.dep'
```

Python function name: downslope_distance_to_stream

6.8.14 DownslopeFlowpathLength

Calculates the downslope flowpath length from each cell to basin outlet.

Parameters:

Flag	Description
--d8_pntr	Input D8 pointer raster file
--watersheds	Optional input watershed raster file
--weights	Optional input weights raster file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=DownslopeFlowpathLength -v ^
--wd="/path/to/data/" --d8_pntr=pointer.dep ^
```

```
-o=flowpath_len.dep
>>./whitebox_tools ^
-r=DownslopeFlowpathLength -v --wd="/path/to/data/" ^
--d8_pntr=pointer.flt --watersheds=basin.flt ^
--weights=weights.flt -o=flowpath_len.flt --esri_pntr
```

Python function name: downslope_flowpath_length

6.8.15 ElevationAboveStream

Calculates the elevation of cells above the nearest downslope stream cell.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
--streams	Input raster streams file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ElevationAboveStream -v ^
--wd="/path/to/data/" --dem='dem.dep' --streams='streams.dep' ^
-o='output.dep'
```

Python function name: elevation_above_stream

6.8.16 FD8FlowAccumulation

Calculates an FD8 flow accumulation raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--out_type	Output type; one of 'cells', 'specific contributing area' (default), and 'catchment area'
--exponent	Optional exponent parameter; default is 1.1
--threshold	Optional convergence threshold parameter, in grid cells; default is infinity
--log	Optional flag to request the output be log-transformed
--clip	Optional flag to request clipping the display max by 1%

Command-line Interface:

```
>>./whitebox_tools -r=FD8FlowAccumulation -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--out_type='cells'
>>./whitebox_tools -r=FD8FlowAccumulation -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--out_type='catchment area' --exponent=1.5 --threshold=10000 ^
--log --clip
```

Python function name: fd8_flow_accumulation

6.8.17 FD8Pointer

Calculates an FD8 flow pointer raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=FD8Pointer -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep
```

Python function name: fd8_pointer

6.8.18 FillDepressions

Fills all of the depressions in a DEM. Depression breaching should be preferred in most cases.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--fix_flats	Optional flag indicating whether flat areas should have a small gradient applied

Command-line Interface:

```
>>./whitebox_tools -r=FillDepressions -v ^
```



```
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep ^
--fix_flats
```

Python function name: fill_depressions

6.8.19 FillSingleCellPits

Raises pit cells to the elevation of their lowest neighbour.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=FillSingleCellPits -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=NewRaster.dep
```

Python function name: fill_single_cell_pits

6.8.20 FindNoFlowCells

Finds grid cells with no downslope neighbours.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=FindNoFlowCells -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=NewRaster.dep
```

Python function name: find_no_flow_cells

6.8.21 FindParallelFlow

Finds areas of parallel flow in D8 flow direction rasters.

Parameters:

Flag	Description
--d8_pntr	Input D8 pointer raster file
--streams	Input raster streams file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=FindParallelFlow -v ^
--wd="/path/to/data/" --d8_pntr=pointer.dep ^
-o=out.dep
>>./whitebox_tools -r=FindParallelFlow -v ^
--wd="/path/to/data/" --d8_pntr=pointer.dep -o=out.dep ^
--streams='streams.dep'
```

Python function name: find_parallel_flow

6.8.22 FloodOrder

Assigns each DEM grid cell its order in the sequence of inundations that are encountered during a search starting from the edges, moving inward at increasing elevations.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=FloodOrder -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep
```

Python function name: flood_order

6.8.23 FlowAccumulationFullWorkflow

Resolves all of the depressions in a DEM, outputting a breached DEM, an aspect-aligned non-divergent flow pointer, a flow accumulation raster.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
--out_dem	Output raster DEM file
--out_pntr	Output raster flow pointer file
--out_accum	Output raster flow accumulation file
--out_type	Output type; one of 'cells', 'sca' (default), and 'ca'
--log	Optional flag to request the output be log-transformed
--clip	Optional flag to request clipping the display max by 1%
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=FlowAccumulationFullWorkflow -v ^
--wd="/path/to/data/" --dem='DEM.dep' ^
--out_dem='DEM_filled.dep' --out_pntr='pointer.dep' ^
--out_accum='accum.dep' --out_type=sca --log --clip
```

Python function name: flow_accumulation_full_workflow

6.8.24 FlowLengthDiff

Calculates the local maximum absolute difference in downslope flowpath length, useful in mapping drainage divides and ridges.

Parameters:

Flag	Description
--d8_pntr	Input D8 pointer raster file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=FlowLengthDiff -v --wd="/path/to/data/" ^
--d8_pntr=pointer.dep -o=output.dep
```

Python function name: flow_length_diff

6.8.25 Hillslopes

Identifies the individual hillslopes draining to each link in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=Hillslopes -v --wd="/path/to/data/" ^
--d8_pntr='d8pntr.dep' --streams='streams.dep' ^
-o='output.dep'
```

Python function name: hillslopes

6.8.26 Isobasins

Divides a landscape into nearly equal sized drainage basins (i.e. watersheds).

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--size	Target basin size, in grid cells

Command-line Interface:

```
>>./whitebox_tools -r=Isobasins -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep --size=1000
```

Python function name: isobasins

6.8.27 JensenSnapPourPoints

Moves outlet points used to specify points of interest in a watershedding operation to the nearest stream cell.

Parameters:

Flag	Description
--pour_pts	Input raster pour points (outlet) file
--streams	Input raster streams file
-o, --output	Output raster file
--snap_dist	Maximum snap distance in map units

Command-line Interface:

```
>>./whitebox_tools -r=JensenSnapPourPoints -v ^
--wd="/path/to/data/" --pour_pts='pour_pts.dep' ^
--streams='streams.dep' -o='output.dep' --snap_dist=15.0
```

Python function name: jenson_snap_pour_points

6.8.28 MaxUpslopeFlowpathLength

Measures the maximum length of all upslope flowpaths draining each grid cell.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=MaxUpslopeFlowpathLength -v ^
--wd="/path/to/data/" -i=DEM.dep ^
-o=output.dep
>>./whitebox_tools -r=MaxUpslopeFlowpathLength -v ^
--wd="/path/to/data/" --dem=DEM.dep -o=output.dep --log ^
--clip
```

Python function name: max_upslope_flowpath_length

6.8.29 NumInflowingNeighbours

Computes the number of inflowing neighbours to each cell in an input DEM based on the D8 algorithm.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=NumInflowingNeighbours -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep
```

Python function name: num_inflowing_neighbours

6.8.30 Rho8Pointer

Calculates a stochastic Rho8 flow pointer raster from an input DEM.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=Rho8Pointer -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep
```

Python function name: rho8_pointer

6.8.31 Sink

Identifies the depressions in a DEM, giving each feature a unique identifier.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file

Flag	Description
-o, --output	Output raster file
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=Sink -v --wd="/path/to/data/" ^
--dem=DEM.dep -o=output.dep --zero_background
```

Python function name: sink

6.8.32 SnapPourPoints

Moves outlet points used to specify points of interest in a watershedding operation to the cell with the highest flow accumulation in its neighbourhood.

Parameters:

Flag	Description
--pour_pts	Input raster pour points (outlet) file
--flow_accum	Input raster D8 flow accumulation file
-o, --output	Output raster file
--snap_dist	Maximum snap distance in map units

Command-line Interface:

```
>>./whitebox_tools -r=SnapPourPoints -v --wd="/path/to/data/" ^
--pour_pts='pour_pts.dep' --flow_accum='d8accum.dep' ^
-o='output.dep' --snap_dist=15.0
```

Python function name: snap_pour_points

6.8.33 StrahlerOrderBasins

Identifies Strahler-order basins from an input stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file

Flag	Description
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=StrahlerOrderBasins -v ^
--wd="/path/to/data/" --d8_pntr='d8pntr.dep' ^
--streams='streams.dep' -o='output.dep'
```

Python function name: strahler_order_basins

6.8.34 Subbasins

Identifies the catchments, or sub-basin, draining to each link in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input D8 pointer raster file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=Subbasins -v --wd="/path/to/data/" ^
--d8_pntr='d8pntr.dep' --streams='streams.dep' ^
-o='output.dep'
```

Python function name: subbasins

6.8.35 TraceDownslopeFlowpaths

Traces downslope flowpaths from one or more target sites (i.e. seed points).

Parameters:

Flag	Description
--seed_pts	Input raster seed points file
--d8_pntr	Input D8 pointer raster file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Flag	Description
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=TraceDownslopeFlowpaths -v ^
--wd="/path/to/data/" --seed_pts=seeds.dep ^
--flow_dir=flow_directions.dep --output=flow_paths.dep
```

Python function name: trace_downslope_flowpaths

6.8.36 Watershed

Identifies the watershed, or drainage basin, draining to a set of target cells.

Parameters:

Flag	Description
--d8_pntr	Input D8 pointer raster file
--pour_pts	Input vector pour points (outlet) file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=Watershed -v --wd="/path/to/data/" ^
--d8_pntr='d8pntr.dep' --pour_pts='pour_pts.dep' ^
-o='output.dep'
```

Python function name: watershed

6.9 Image Processing Tools

6.9.1 Closing

A closing is a mathematical morphology operating involving an erosion (min filter) of a dilation (max filter) set.

Parameters:

Flag	Description
-i, --input	Input raster file

Flag	Description
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=Closing -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=25
```

Python function name: closing

6.9.2 CreateColourComposite

Creates a colour-composite image from three bands of multispectral imagery.

Parameters:

Flag	Description
--red	Input red band image file
--green	Input green band image file
--blue	Input blue band image file
--opacity	Input opacity band image file (optional)
-o, --output	Output colour composite file
--enhance	Optional flag indicating whether a balance contrast enhancement is performed

Command-line Interface:

```
>>./whitebox_tools -r=CreateColourComposite -v ^
--wd="/path/to/data/" --red=band3.dep --green=band2.dep ^
--blue=band1.dep -o=output.dep
>>./whitebox_tools ^
-r=CreateColourComposite -v --wd="/path/to/data/" ^
--red=band3.dep --green=band2.dep --blue=band1.dep ^
--opacity=a.dep -o=output.dep
```

Python function name: create_colour_composite

6.9.3 FlipImage

Reflects an image in the vertical or horizontal axis.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--direction	Direction of reflection; options include 'v' (vertical), 'h' (horizontal), and 'b' (both)

Command-line Interface:

```
>>./whitebox_tools -r=FlipImage -v --wd="/path/to/data/" ^
--input=in.dep -o=out.dep --direction=h
```

Python function name: flip_image

6.9.4 IntegrallImage

Transforms an input image (summed area table) into its integral image equivalent.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=IntegralImage -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep
```

Python function name: integral_image

6.9.5 KMeansClustering

Performs a k-means clustering operation on a multi-spectral dataset.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output raster file
--out_html	Output HTML report file

Flag	Description
--classes	Number of classes
--max_iterations	Maximum number of iterations
--class_change	Minimum percent of cells changed between iterations before completion
--initialize	How to initialize cluster centres?
--min_class_size	Minimum class size, in pixels

Command-line Interface:

```
>> ./whitebox_tools -r=KMeansClustering -v ^
--wd='/path/to/data/' -i='image1.tif;image2.tif;image3.tif' ^
-o=output.tif --out_html=report.html --classes=15 ^
--max_iterations=25 --class_change=1.5 --initialize='random' ^
--min_class_size=500
```

Python function name: k_means_clustering

6.9.6 LineThinning

Performs line thinning a on Boolean raster image; intended to be used with the RemoveSpurs tool.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>> ./whitebox_tools -r=LineThinning -v --wd="/path/to/data/" ^
--input=DEM.dep -o=output.dep
```

Python function name: line_thinning

6.9.7 ModifiedKMeansClustering

Performs a modified k-means clustering operation on a multi-spectral dataset.

Parameters:

Flag	Description
-i, --inputs	Input raster files

Flag	Description
-o, --output	Output raster file
--out_html	Output HTML report file
--start_clusters	Initial number of clusters
--merger_dist	Cluster merger distance
--max_iterations	Maximum number of iterations
--class_change	Minimum percent of cells changed between iterations before completion

Command-line Interface:

```
>>./whitebox_tools -r=ModifiedKMeansClustering -v ^
--wd='/path/to/data/' -i='image1.tif;image2.tif;image3.tif' ^
-o=output.tif --out_html=report.html --start_clusters=100 ^
--merger_dist=30.0 --max_iterations=25 --class_change=1.5
```

Python function name: modified_k_means_clustering

6.9.8 Mosaic

Mosaics two or more images together.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output raster file
--method	Resampling method

Command-line Interface:

```
>>./whitebox_tools -r=Mosaic -v --wd='/path/to/data/' ^
-i='image1.dep;image2.dep;image3.dep' -o=dest.dep ^
--method='cc
```

Python function name: mosaic

6.9.9 NormalizedDifferenceVegetationIndex

Calculates the normalized difference vegetation index (NDVI) from near-infrared and red imagery.

Parameters:

Flag	Description
--nir	Input near-infrared band image
--red	Input red band image
-o, --output	Output raster file
--clip	Optional amount to clip the distribution tails by, in percent
--osavi	Optional flag indicating whether the optimized soil-adjusted veg index (OSAVI) should be used

Command-line Interface:

```
>>./whitebox_tools -r=NormalizedDifferenceVegetationIndex -v ^
--wd="/path/to/data/" --nir=band4.dep --red=band3.dep ^
-o=output.dep
>>./whitebox_tools ^
-r=NormalizedDifferenceVegetationIndex -v --wd="/path/to/data/" ^
--nir=band4.dep --red=band3.dep -o=output.dep --clip=1.0 ^
--osavi
```

Python function name: normalized_difference_vegetation_index

6.9.10 Opening

An opening is a mathematical morphology operating involving a dilation (max filter) of an erosion (min filter) set.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=Opening -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=25
```

Python function name: opening

6.9.11 RemoveSpurs

Removes the spurs (pruning operation) from a Boolean line image.; intended to be used on the output of the LineThinning tool.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--iterations	Maximum number of iterations

Command-line Interface:

```
>>./whitebox_tools -r=RemoveSpurs -v --wd="/path/to/data/" ^
--input=DEM.dep -o=output.dep --iterations=10
```

Python function name: remove_spurs

6.9.12 Resample

Resamples one or more input images into a destination image.

Parameters:

Flag	Description
-i, --inputs	Input raster files
--destination	Destination raster file
--method	Resampling method

Command-line Interface:

```
>>./whitebox_tools -r=Resample -v --wd='/path/to/data/' ^
-i='image1.dep;image2.dep;image3.dep' --destination=dest.dep ^
--method='cc'
```

Python function name: resample

6.9.13 RgbToIhs

Converts red, green, and blue (RGB) images into intensity, hue, and saturation (IHS) images.

Parameters:

Flag	Description
--red	Input red band image file. Optionally specified if colour-composite not specified
--green	Input green band image file. Optionally specified if colour-composite not specified
--blue	Input blue band image file. Optionally specified if colour-composite not specified
--composite	Input colour-composite image file. Only used if individual bands are not specified
--intensity	Output intensity raster file
--hue	Output hue raster file
--saturation	Output saturation raster file

Command-line Interface:

```
>>./whitebox_tools -r=RgbToIhs -v --wd="/path/to/data/" ^
--red=band3.dep --green=band2.dep --blue=band1.dep ^
--intensity=intensity.dep --hue=hue.dep ^
--saturation=saturation.dep
>>./whitebox_tools -r=RgbToIhs -v ^
--wd="/path/to/data/" --composite=image.dep ^
--intensity=intensity.dep --hue=hue.dep ^
--saturation=saturation.dep
```

Python function name: `rgb_to_ihs`

6.9.14 SplitColourComposite

This tool splits an RGB colour composite image into separate multispectral images.

Parameters:

Flag	Description
-i, --input	Input colour composite image file
-o, --output	Output raster file (suffixes of '_r', '_g', and '_b' will be appended)

Command-line Interface:

```
>>./whitebox_tools -r=SplitColourComposite -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep
```

Python function name: `split_colour_composite`

6.9.15 ThickenRasterLine

Thickens single-cell wide lines within a raster image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ThickenRasterLine -v ^
--wd="/path/to/data/" --input=DEM.dep -o=output.dep
```

Python function name: thicken_raster_line

6.9.16 TophatTransform

Performs either a white or black top-hat transform on an input image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction
--variant	Optional variant value. Options include 'white' and 'black'

Command-line Interface:

```
>>./whitebox_tools -r=TophatTransform -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --filter=25
```

Python function name: tophat_transform

6.9.17 WriteFunctionMemoryInsertion

Performs a write function memory insertion for single-band multi-date change detection.

Parameters:

Flag	Description
--i1, --input1	Input raster file associated with the first date
--i2, --input2	Input raster file associated with the second date
--i3, --input3	Optional input raster file associated with the third date
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=WriteFunctionMemoryInsertion -v ^
--wd="/path/to/data/" -i1=input1.dep -i2=input2.dep ^
-o=output.dep
```

Python function name: write_function_memory_insertion

6.10 Image Processing Tools => Filters

6.10.1 AdaptiveFilter

Performs an adaptive filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction
--threshold	Difference from mean threshold, in standard deviations

Command-line Interface:

```
>>./whitebox_tools -r=AdaptiveFilter -v --wd="/path/to/data/" ^
-i=DEM.dep -o=output.dep --filter=25 --threshold = 2.0
```

Python function name: adaptive_filter

6.10.2 BilateralFilter

A bilateral filter is an edge-preserving smoothing filter introduced by Tomasi and Manduchi (1998).

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--sigma_dist	Standard deviation in distance in pixels
--sigma_int	Standard deviation in intensity in pixels

Command-line Interface:

```
>>./whitebox_tools -r=BilateralFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep ^
--sigma_dist=2.5 --sigma_int=4.0
```

Python function name: bilateral_filter

6.10.3 ConservativeSmoothingFilter

Performs a conservative-smoothing filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=ConservativeSmoothingFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --filter=25
```

Python function name: conservative_smoothing_filter

6.10.4 DiffOfGaussianFilter

Performs a Difference of Gaussian (DoG) filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Flag	Description
--sigma1	Standard deviation distance in pixels
--sigma2	Standard deviation distance in pixels

Command-line Interface:

```
>>./whitebox_tools -r=DiffOfGaussianFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --sigma1=2.0 ^
--sigma2=4.0
```

Python function name: diff_of_gaussian_filter

6.10.5 DiversityFilter

Assigns each cell in the output grid the number of different values in a moving window centred on each grid cell in the input raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=DiversityFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --filter=25
```

Python function name: diversity_filter

6.10.6 EmbossFilter

Performs an emboss filter on an image, similar to a hillshade operation.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--direction	Direction of reflection; options include 'n', 's', 'e', 'w', 'ne', 'se', 'nw',

Flag	Description
	'sw'
--clip	Optional amount to clip the distribution tails by, in percent

Command-line Interface:

```
>>./whitebox_tools -r=EmbossFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --direction='s' --clip=1.0
```

Python function name: emboss_filter

6.10.7 GaussianFilter

Performs a Gaussian filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--sigma	Standard deviation distance in pixels

Command-line Interface:

```
>>./whitebox_tools -r=GaussianFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --sigma=2.0
```

Python function name: gaussian_filter

6.10.8 HighPassFilter

Performs a high-pass filter on an input image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=HighPassFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=25
```

Python function name: high_pass_filter

6.10.9 KNearestMeanFilter

A k-nearest mean filter is a type of edge-preserving smoothing filter.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction
-k	k-value in pixels; this is the number of nearest-valued neighbours to use

Command-line Interface:

```
>>./whitebox_tools -r=KNearestMeanFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --filter=9 ^
-k=5
>>./whitebox_tools -r=KNearestMeanFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --filtery=7 ^
--filterx=9 -k=5
```

Python function name: k_nearest_mean_filter

6.10.10 LaplacianFilter

Performs a Laplacian filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--variant	Optional variant value. Options include 3x3(1), 3x3(2), 3x3(3), 3x3(4), 5x5(1), and 5x5(2) (default is 3x3(1))
--clip	Optional amount to clip the distribution tails by, in percent

Command-line Interface:

```
>>./whitebox_tools -r=LaplacianFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep ^
--variant='3x3(1)' --clip=1.0
```

Python function name: laplacian_filter

6.10.11 LaplacianOfGaussianFilter

Performs a Laplacian-of-Gaussian (LoG) filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--sigma	Standard deviation in pixels

Command-line Interface:

```
>>./whitebox_tools -r=LaplacianOfGaussianFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --sigma=2.0
```

Python function name: laplacian_of_gaussian_filter

6.10.12 LeeFilter

Performs a Lee (Sigma) smoothing filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction
--sigma	Sigma value should be related to the standard deviation of the distribution of image speckle noise
-m	M-threshold value the minimum allowable number of pixels within the intensity range

Command-line Interface:

```
>>./whitebox_tools -r=LeeFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=9 --sigma=10.0 ^
-m=5
>>./whitebox_tools -r=LeeFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=7 --filter=9 ^
--sigma=10.0 -m=5
```

Python function name: lee_filter

6.10.13 LineDetectionFilter

Performs a line-detection filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--variant	Optional variant value. Options include 'v' (vertical), 'h' (horizontal), '45', and '135' (default is 'v')
--absvals	Optional flag indicating whether outputs should be absolute values
--clip	Optional amount to clip the distribution tails by, in percent

Command-line Interface:

```
>>./whitebox_tools -r=LineDetectionFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --variant=h ^
--clip=1.0
```

Python function name: line_detection_filter

6.10.14 MajorityFilter

Assigns each cell in the output grid the most frequently occurring value (mode) in a moving window centred on each grid cell in the input raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Flag	Description
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=MajorityFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=25
```

Python function name: majority_filter

6.10.15 MaximumFilter

Assigns each cell in the output grid the maximum value in a moving window centred on each grid cell in the input raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=MaximumFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=25
```

Python function name: maximum_filter

6.10.16 MeanFilter

Performs a mean filter (low-pass filter) on an input image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=MeanFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filterx=25 --filtery=25
```

Python function name: mean_filter

6.10.17 MedianFilter

Performs a median filter on an input image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction
--sig_digits	Number of significant digits

Command-line Interface:

```
>>./whitebox_tools -r=MedianFilter -v --wd="/path/to/data/" ^
-i=input.dep -o=output.dep --filter=25
```

Python function name: median_filter

6.10.18 MinimumFilter

Assigns each cell in the output grid the minimum value in a moving window centred on each grid cell in the input raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=MinimumFilter -v --wd="/path/to/data/" ^
```

```
-i=image.dep -o=output.dep --filter=25
```

Python function name: minimum_filter

6.10.19 OlympicFilter

Performs an olympic smoothing filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=OlympicFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=25
```

Python function name: olympic_filter

6.10.20 PercentileFilter

Performs a percentile filter on an input image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction
--sig_digits	Number of significant digits

Command-line Interface:

```
>>./whitebox_tools -r=PercentileFilter -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep --filter=25
```

Python function name: percentile_filter

6.10.21 PrewittFilter

Performs a Prewitt edge-detection filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--clip	Optional amount to clip the distribution tails by, in percent

Command-line Interface:

```
>>./whitebox_tools -r=PrewittFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --clip=1.0
```

Python function name: prewitt_filter

6.10.22 RangeFilter

Assigns each cell in the output grid the range of values in a moving window centred on each grid cell in the input raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=RangeFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=25
```

Python function name: range_filter

6.10.23 RobertsCrossFilter

Performs a Robert's cross edge-detection filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--clip	Optional amount to clip the distribution tails by, in percent

Command-line Interface:

```
>>./whitebox_tools -r=RobertsCrossFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --clip=1.0
```

Python function name: roberts_cross_filter

6.10.24 ScharrFilter

Performs a Scharr edge-detection filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--clip	Optional amount to clip the distribution tails by, in percent

Command-line Interface:

```
>>./whitebox_tools -r=ScharrFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --clip=1.0
```

Python function name: scharr_filter

6.10.25 SobelFilter

Performs a Sobel edge-detection filter on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--variant	Optional variant value. Options include 3x3 and 5x5 (default is 3x3)
--clip	Optional amount to clip the distribution tails by, in percent (default is 0.0)

Command-line Interface:

```
>>./whitebox_tools -r=SobelFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --variant=5x5 --clip=1.0
```

Python function name: sobel_filter

6.10.26 StandardDeviationFilter

Assigns each cell in the output grid the standard deviation of values in a moving window centred on each grid cell in the input raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=StandardDeviationFilter -v ^
--wd="/path/to/data/" -i=image.dep -o=output.dep --filter=25
```

Python function name: standard_deviation_filter

6.10.27 TotalFilter

Performs a total filter on an input image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--filterx	Size of the filter kernel in the x-direction
--filtery	Size of the filter kernel in the y-direction

Command-line Interface:

```
>>./whitebox_tools -r=TotalFilter -v --wd="/path/to/data/" ^
-i=image.dep -o=output.dep --filter=25
```

Python function name: total_filter

6.11 Image Processing Tools => Image Enhancement

6.11.1 BalanceContrastEnhancement

Performs a balance contrast enhancement on a colour-composite image of multispectral data.

Parameters:

Flag	Description
-i, --input	Input colour composite image file
-o, --output	Output raster file
--band_mean	Band mean value

Command-line Interface:

```
>>./whitebox_tools -r=BalanceContrastEnhancement -v ^
--wd="/path/to/data/" --input=image.dep -o=output.dep ^
--band_mean=120
```

Python function name: balance_contrast_enhancement

6.11.2 DirectDecorrelationStretch

Performs a direct decorrelation stretch enhancement on a colour-composite image of multispectral data.

Parameters:

Flag	Description
-i, --input	Input colour composite image file
-o, --output	Output raster file
-k	Achromatic factor (k) ranges between 0 (no effect) and 1 (full saturation stretch), although typical values range from 0.3 to 0.7
--clip	Optional percent to clip the upper tail by during the stretch

Command-line Interface:

```
>>./whitebox_tools -r=DirectDecorrelationStretch -v ^
--wd="/path/to/data/" --input=image.dep -o=output.dep -k=0.4
```

Python function name: direct_decorrelation_stretch

6.11.3 GammaCorrection

Performs a sigmoidal contrast stretch on input images.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--gamma	Gamma value

Command-line Interface:

```
>>./whitebox_tools -r=GammaCorrection -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep --gamma=0.5
```

Python function name: gamma_correction

6.11.4 HistogramEqualization

Performs a histogram equalization contrast enhancement on an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--num_tones	Number of tones in the output image

Command-line Interface:

```
>>./whitebox_tools -r=HistogramEqualization -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep ^
--num_tones=1024
```

Python function name: histogram_equalization

6.11.5 HistogramMatching

Alters the statistical distribution of a raster image matching it to a specified PDF.

Parameters:

Flag	Description
-i, --input	Input raster file
--histo_file	Input reference probability distribution function (pdf) text file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=HistogramMatching -v ^
--wd="/path/to/data/" -i=input1.dep --histo_file=histo.txt ^
-o=output.dep
```

Python function name: histogram_matching

6.11.6 HistogramMatchingTwoImages

This tool alters the cumulative distribution function of a raster image to that of another image.

Parameters:

Flag	Description
--i1, --input1	Input raster file to modify
--i2, --input2	Input reference raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=HistogramMatchingTwoImages -v ^
--wd="/path/to/data/" --i1=input1.dep --i2=input2.dep ^
-o=output.dep
```

Python function name: histogram_matching_two_images

6.11.7 MinMaxContrastStretch

Performs a min-max contrast stretch on an input greytone image.

Parameters:

Flag	Description
-i, --input	Input raster file

Flag	Description
-o, --output	Output raster file
--min_val	Lower tail clip value
--max_val	Upper tail clip value
--num_tones	Number of tones in the output image

Command-line Interface:

```
>>./whitebox_tools -r=MinMaxContrastStretch -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep ^
--min_val=45.0 --max_val=200.0 --num_tones=1024
```

Python function name: min_max_contrast_stretch

6.11.8 PanchromaticSharpening

Increases the spatial resolution of image data by combining multispectral bands with panchromatic data.

Parameters:

Flag	Description
--red	Input red band image file. Optionally specified if colour-composite not specified
--green	Input green band image file. Optionally specified if colour-composite not specified
--blue	Input blue band image file. Optionally specified if colour-composite not specified
--composite	Input colour-composite image file. Only used if individual bands are not specified
--pan	Input panchromatic band file
-o, --output	Output colour composite file
--method	Options include 'brovey' (default) and 'ihs'

Command-line Interface:

```
>>./whitebox_tools -r=PanchromaticSharpening -v ^
--wd="/path/to/data/" --red=red.dep --green=green.dep ^
--blue=blue.dep --pan=pan.dep --output=pan_sharp.dep ^
--method='brovey'
>>./whitebox_tools -r=PanchromaticSharpening ^
-v --wd="/path/to/data/" --composite=image.dep --pan=pan.dep ^
--output=pan_sharp.dep --method='ihs'
```

Python function name: panchromatic_sharpening

6.11.9 PercentageContrastStretch

Performs a percentage linear contrast stretch on input images.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--clip	Optional amount to clip the distribution tails by, in percent
--tail	Specified which tails to clip; options include 'upper', 'lower', and 'both' (default is 'both')
--num_tones	Number of tones in the output image

Command-line Interface:

```
>>./whitebox_tools -r=PercentageContrastStretch -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep --clip=2.0 ^
--tail='both' --num_tones=1024
```

Python function name: percentage_contrast_stretch

6.11.10 SigmoidalContrastStretch

Performs a sigmoidal contrast stretch on input images.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--cutoff	Cutoff value between 0.0 and 0.95
--gain	Gain value
--num_tones	Number of tones in the output image

Command-line Interface:

```
>>./whitebox_tools -r=SigmoidalContrastStretch -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep --cutoff=0.1 ^
--gain=2.0 --num_tones=1024
```

Python function name: sigmoidal_contrast_stretch

6.11.11 StandardDeviationContrastStretch

Performs a standard-deviation contrast stretch on input images.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--clip, --stdev	Standard deviation clip value
--num_tones	Number of tones in the output image

Command-line Interface:

```
>> ./whitebox_tools -r=StandardDeviationContrastStretch -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep --stdev=2.0 ^
--num_tones=1024
```

Python function name: standard_deviation_contrast_stretch

6.12 LiDAR Tools

6.12.1 BlockMaximum

Creates a block-maximum raster from an input LAS file.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output file
--resolution	Output raster's grid resolution

Command-line Interface:

```
>> ./whitebox_tools -r=BlockMaximum -v --wd="/path/to/data/" ^
-i=file.las -o=outfile.dep --resolution=2.0"
./whitebox_tools ^
-r=BlockMaximum -v --wd="/path/to/data/" -i=file.las ^
-o=outfile.dep --resolution=5.0 --palette=light_quant.plt
```

Python function name: block_maximum

6.12.2 BlockMinimum

Creates a block-minimum raster from an input LAS file.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output file
--resolution	Output raster's grid resolution

Command-line Interface:

```
>>./whitebox_tools -r=BlockMinimum -v --wd="/path/to/data/" ^
-i=file.las -o=outfile.dep --resolution=2.0"
./whitebox_tools ^
-r=BlockMinimum -v --wd="/path/to/data/" -i=file.las ^
-o=outfile.dep --resolution=5.0 --palette=light_quant.plt
```

Python function name: block_minimum

6.12.3 FilterLidarScanAngles

Removes points in a LAS file with scan angles greater than a threshold.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output LiDAR file
--threshold	Scan angle threshold

Command-line Interface:

```
>>./whitebox_tools -r=FilterLidarScanAngles -v ^
--wd="/path/to/data/" -i="input.las" -o="output.las" ^
--threshold=10.0
```

Python function name: filter_lidar_scan_angles

6.12.4 FindFlightlineEdgePoints

Identifies points along a flightline's edge in a LAS file.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output file

Command-line Interface:

```
>>./whitebox_tools -r=FindFlightlineEdgePoints -v ^
--wd="/path/to/data/" -i="input.las" -o="output.las"
```

Python function name: find_flightline_edge_points

6.12.5 FlightlineOverlap

Reads a LiDAR (LAS) point file and outputs a raster containing the number of overlapping flight lines in each grid cell.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output file
--resolution	Output raster's grid resolution

Command-line Interface:

```
>>./whitebox_tools -r=FlightlineOverlap -v ^
--wd="/path/to/data/" -i=file.las -o=outfile.dep ^
--resolution=2.0"
./whitebox_tools -r=FlightlineOverlap -v ^
--wd="/path/to/data/" -i=file.las -o=outfile.dep ^
--resolution=5.0 --palette=light_quant.plt
```

Python function name: flightline_overlap

6.12.6 LasToAscii

Converts one or more LAS files into ASCII text files.

Parameters:

Flag	Description
-i, --inputs	Input LiDAR files

Command-line Interface:

```
>>./whitebox_tools -r=LasToAscii -v --wd="/path/to/data/" ^
-i="file1.las, file2.las, file3.las" -o=outfile.las"
```

Python function name: las_to_ascii

6.12.7 LidarColourize

Adds the red-green-blue colour fields of a LiDAR (LAS) file based on an input image.

Parameters:

Flag	Description
--in_lidar	Input LiDAR file
--in_image	Input colour image file
-o, --output	Output LiDAR file

Command-line Interface:

```
>>./whitebox_tools -r=LidarColourize -v --wd="/path/to/data/" ^
--in_lidar="input.las" --in_image="image.dep" ^
-o="output.las"
```

Python function name: lidar_colourize

6.12.8 LidarElevationSlice

Outputs all of the points within a LiDAR (LAS) point file that lie between a specified elevation range.

Parameters:

Flag	Description
-i, --input	Input LiDAR file

Flag	Description
-o, --output	Output LiDAR file
--minz	Minimum elevation value (optional)
--maxz	Maximum elevation value (optional)
--class	Optional boolean flag indicating whether points outside the range should be retained in output but reclassified
--inclassval	Optional parameter specifying the class value assigned to points within the slice
--outclassval	Optional parameter specifying the class value assigned to points within the slice

Command-line Interface:

```
>>./whitebox_tools -r=LidarElevationSlice -v ^
--wd="/path/to/data/" -i="input.las" -o="output.las" ^
--minz=100.0 --maxz=250.0
>>./whitebox_tools ^
-r=LidarElevationSlice -v -i="/path/to/data/input.las" ^
-o="/path/to/data/output.las" --minz=100.0 --maxz=250.0 ^
--class
>>./whitebox_tools -r=LidarElevationSlice -v ^
-i="/path/to/data/input.las" -o="/path/to/data/output.las" ^
--minz=100.0 --maxz=250.0 --inclassval=1 --outclassval=0
```

Python function name: lidar_elevation_slice

6.12.9 LidarGroundPointFilter

Identifies ground points within LiDAR dataset using a slope-based method.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output LiDAR file
--radius	Search Radius
--slope_threshold	Maximum inter-point slope to be considered an off-terrain point
--height_threshold	Inter-point height difference to be considered an off-terrain point

Command-line Interface:

```
>>./whitebox_tools -r=LidarGroundPointFilter -v ^
--wd="/path/to/data/" -i="input.las" -o="output.las" ^
```


--radius=10.0

Python function name: lidar_ground_point_filter

6.12.10 LidarHillshade

Calculates a hillshade value for points within a LAS file and stores these data in the RGB field.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output file
--azimuth	Illumination source azimuth in degrees
--altitude	Illumination source altitude in degrees
--radius	Search Radius

Command-line Interface:

```
>>./whitebox_tools -r=LidarHillshade -v --wd="/path/to/data/" ^
-i="input.las" -o="output.las" --radius=10.0
>>./whitebox_tools ^
-r=LidarHillshade -v --wd="/path/to/data/" -i="input.las" ^
-o="output.las" --azimuth=180.0 --altitude=20.0 --radius=1.0
```

Python function name: lidar_hillshade

6.12.11 LidarHistogram

Creates a histogram from LiDAR data.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output HTML file (default name will be based on input file if unspecified)
--parameter	Parameter; options are 'elevation' (default), 'intensity', 'scan angle', 'class
--clip	Amount to clip distribution tails (in percent)

Command-line Interface:

```
>>./whitebox_tools -r=LidarHistogram -v --wd="/path/to/data/" ^
```

```
-i="file1.tif, file2.tif, file3.tif" -o=outfile.htm ^
--contiguity=Bishops1
```

Python function name: lidar_histogram

6.12.12 LidarIdwInterpolation

Interpolates LAS files using an inverse-distance weighted (IDW) scheme.

Parameters:

Flag	Description
-i, --input	Input LiDAR file (including extension)
-o, --output	Output raster file (including extension)
--parameter	Interpolation parameter; options are 'elevation' (default), 'intensity', 'class', 'scan angle', 'user data'
--returns	Point return types to include; options are 'all' (default), 'last', 'first'
--resolution	Output raster's grid resolution
--weight	IDW weight value
--radius	Search Radius
--exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, --exclude_cls='3,4,5,6,7,18'
--minz	Optional minimum elevation for inclusion in interpolation
--maxz	Optional maximum elevation for inclusion in interpolation

Command-line Interface:

```
>>./whitebox_tools -r=LidarIdwInterpolation -v ^
--wd="/path/to/data/" -i=file.las -o=outfile.dep ^
--resolution=2.0 --radius=5.0"
./whitebox_tools ^
-r=LidarIdwInterpolation --wd="/path/to/data/" -i=file.las ^
-o=outfile.dep --resolution=5.0 --weight=2.0 --radius=2.0 ^
--exclude_cls='3,4,5,6,7,18' --palette=light_quant.plt
```

Python function name: lidar_idw_interpolation

6.12.13 LidarInfo

Prints information about a LiDAR (LAS) dataset, including header, point return frequency, and classification data and information about the variable length records (VLRs) and geokeys.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output HTML file for regression summary report
--vlr	Flag indicating whether or not to print the variable length records (VLRs)
--geokeys	Flag indicating whether or not to print the geokeys

Command-line Interface:

```
>>./whitebox_tools -r=LidarInfo -v --wd="/path/to/data/" ^
-i=file.las --vlr --geokeys"
./whitebox_tools -r=LidarInfo ^
--wd="/path/to/data/" -i=file.las
```

Python function name: lidar_info

6.12.14 LidarJoin

Joins multiple LiDAR (LAS) files into a single LAS file.

Parameters:

Flag	Description
-i, --inputs	Input LiDAR files
-o, --output	Output LiDAR file

Command-line Interface:

```
>>./whitebox_tools -r=LidarJoin -v --wd="/path/to/data/" ^
-i="file1.las, file2.las, file3.las" -o=outfile.las"
```

Python function name: lidar_join

6.12.15 LidarKappaIndex

Performs a kappa index of agreement (KIA) analysis on the classifications of two LAS files.

Parameters:

Flag	Description
--i1, --input1	Input LiDAR classification file
--i2, --input2	Input LiDAR reference file
-o, --output	Output HTML file

Command-line Interface:

```
>>./whitebox_tools -r=LidarKappaIndex -v ^
--wd="/path/to/data/" --i1=class.tif --i2=reference.tif ^
-o=kia.html
```

Python function name: lidar_kappa_index

6.12.16 LidarNearestNeighbourGridding

Grids LAS files using nearest-neighbour scheme.

Parameters:

Flag	Description
-i, --input	Input LiDAR file (including extension)
-o, --output	Output raster file (including extension)
--parameter	Interpolation parameter; options are 'elevation' (default), 'intensity', 'class', 'scan angle', 'user data'
--returns	Point return types to include; options are 'all' (default), 'last', 'first'
--resolution	Output raster's grid resolution
--radius	Search Radius
--exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, -exclude_cls='3,4,5,6,7,18'
--minz	Optional minimum elevation for inclusion in interpolation
--maxz	Optional maximum elevation for inclusion in interpolation

Command-line Interface:

```
>>./whitebox_tools -r=LidarNearestNeighbourGridding -v ^
--wd="/path/to/data/" -i=file.las -o=outfile.dep ^
--resolution=2.0 --radius=5.0"
./whitebox_tools ^
-r=LidarNearestNeighbourGridding --wd="/path/to/data/" ^
-i=file.las -o=outfile.dep --resolution=5.0 --radius=2.0 ^
--exclude_cls='3,4,5,6,7,18' --palette=light_quant.plt
```

Python function name: lidar_nearest_neighbour_gridding

6.12.17 LidarPointDensity

Calculates the spatial pattern of point density for a LiDAR data set.

Parameters:

Flag	Description
-i, --input	Input LiDAR file (including extension)
-o, --output	Output raster file (including extension)
--returns	Point return types to include; options are 'all' (default), 'last', 'first'
--resolution	Output raster's grid resolution
--radius	Search Radius
--exclude_cls	Optional exclude classes from interpolation; Valid class values range from 0 to 18, based on LAS specifications. Example, -exclude_cls='3,4,5,6,7,18'
--minz	Optional minimum elevation for inclusion in interpolation
--maxz	Optional maximum elevation for inclusion in interpolation

Command-line Interface:

```
>>./whitebox_tools -r=LidarPointDensity -v ^
--wd="/path/to/data/" -i=file.las -o=outfile.dep ^
--resolution=2.0 --radius=5.0"
./whitebox_tools ^
-r=LidarPointDensity -v --wd="/path/to/data/" -i=file.las ^
-o=outfile.dep --resolution=5.0 --radius=2.0 ^
--exclude_cls='3,4,5,6,7,18' --palette=light_quant.plt
```

Python function name: lidar_point_density

6.12.18 LidarPointStats

Creates several rasters summarizing the distribution of LAS point data.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
--resolution	Output raster's grid resolution
--num_points	Flag indicating whether or not to output the number of points raster
--num_pulses	Flag indicating whether or not to output the number of pulses raster
--z_range	Flag indicating whether or not to output the elevation range raster
--intensity_range	Flag indicating whether or not to output the intensity range raster
--predom_class	Flag indicating whether or not to output the predominant classification raster

Command-line Interface:

```
>>./whitebox_tools -r=LidarPointStats -v ^
```

```
--wd="/path/to/data/" -i=file.las --resolution=1.0 ^
--num_points
```

Python function name: lidar_point_stats

6.12.19 LidarRemoveDuplicates

Removes duplicate points from a LiDAR data set.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output LiDAR file
--include_z	Include z-values in point comparison?

Command-line Interface:

```
>>./whitebox_tools -r=LidarRemoveDuplicates -v ^
--wd="/path/to/data/" -i="input.las" -o="output.las"
```

Python function name: lidar_remove_duplicates

6.12.20 LidarRemoveOutliers

Removes outliers (high and low points) in a LiDAR point cloud.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output LiDAR file
--radius	Search Radius
--elev_diff	Max. elevation difference

Command-line Interface:

```
>>./whitebox_tools -r=LidarRemoveOutliers -v ^
--wd="/path/to/data/" -i="input.las" -o="output.las" ^
--radius=10.0 --elev_diff=25.0
```

Python function name: lidar_remove_outliers

6.12.21 LidarSegmentation

Segments a LiDAR point cloud based on normal vectors.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output file
--dist, --radius	Search Radius
--norm_diff	Maximum difference in normal vectors, in degrees
--maxzdiff	Maximum difference in elevation (z units) between neighbouring points of the same segment

Command-line Interface:

```
>>./whitebox_tools -r=LidarSegmentation -v ^
--wd="/path/to/data/" -i="input.las" -o="output.las" ^
--radius=10.0 --norm_diff=2.5 --maxzdiff=0.75
```

Python function name: lidar_segmentation

6.12.22 LidarSegmentationBasedFilter

Identifies ground points within LiDAR point clouds using a segmentation based approach.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output file
--dist, --radius	Search Radius
--norm_diff	Maximum difference in normal vectors, in degrees
--maxzdiff	Maximum difference in elevation (z units) between neighbouring points of the same segment
--classify	Classify points as ground (2) or off-ground (1)

Command-line Interface:

```
>>./whitebox_tools -r=LidarSegmentationBasedFilter -v ^
--wd="/path/to/data/" -i="input.las" -o="output.las" ^
--radius=10.0 --norm_diff=2.5 --maxzdiff=0.75 --classify
```

Python function name: lidar_segmentation_based_filter

6.12.23 LidarTile

Tiles a LiDAR LAS file into multiple LAS files.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
--width_x	Width of tiles in the X dimension; default 1000.0
--width_y	Width of tiles in the Y dimension
--origin_x	Origin point X coordinate for tile grid
--origin_y	Origin point Y coordinate for tile grid
--min_points	Minimum number of points contained in a tile for it to be saved

Command-line Interface:

```
>>./whitebox_tools -r=LidarTile -v -i=/path/to/data/input.las ^
--width_x=1000.0 --width_y=2500.0 --min_points=100
```

Python function name: lidar_tile

6.12.24 LidarTophatTransform

Performs a white top-hat transform on a Lidar dataset; as an estimate of height above ground, this is useful for modelling the vegetation canopy.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output LiDAR file
--radius	Search Radius

Command-line Interface:

```
>>./whitebox_tools -r=LidarTophatTransform -v ^
--wd="/path/to/data/" -i="input.las" -o="output.las" ^
--radius=10.0
```

Python function name: lidar_tophat_transform

6.12.25 NormalVectors

Calculates normal vectors for points within a LAS file and stores these data (XYZ vector components) in the RGB field.

Parameters:

Flag	Description
-i, --input	Input LiDAR file
-o, --output	Output LiDAR file
--radius	Search Radius

Command-line Interface:

```
>>./whitebox_tools -r=NormalVectors -v --wd="/path/to/data/" ^
-i="input.las" -o="output.las" --radius=10.0
```

Python function name: normal_vectors

6.13 Math and Stats Tools

6.13.1 AbsoluteValue

Calculates the absolute value of every cell in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=AbsoluteValue -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: absolute_value

6.13.2 Add

Performs an addition operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Add -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: add

6.13.3 And

Performs a logical AND operator on two Boolean raster images.

Parameters:

Flag	Description
--input1	Input raster file
--input2	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=And -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: And

6.13.4 Anova

Performs an analysis of variance (ANOVA) test on a raster dataset.

Parameters:

Flag	Description
-i, --input	Input raster file
--features	Feature definition (or class) raster
-o, --output	Output HTML file

Command-line Interface:

```
>>./whitebox_tools -r=Anova -v --wd="/path/to/data/" ^
-i=data.tif --features=classes.tif -o=anova.html
```

Python function name: anova

6.13.5 ArcCos

Returns the inverse cosine (arccos) of each values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ArcCos -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: arc_cos

6.13.6 ArcSin

Returns the inverse sine (arcsin) of each values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ArcSin -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: arc_sin

6.13.7 ArcTan

Returns the inverse tangent (arctan) of each values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ArcTan -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: arc_tan

6.13.8 Atan2

Returns the 2-argument inverse tangent (atan2).

Parameters:

Flag	Description
--input_y	Input y raster file or constant value (rise)
--input_x	Input x raster file or constant value (run)
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Atan2 -v --wd="/path/to/data/" ^
--input_y='in1.dep' --input_x='in2.dep' -o=output.dep
```

Python function name: atan2

6.13.9 Ceil

Returns the smallest (closest to negative infinity) value that is greater than or equal to the values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Ceil -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: ceil

6.13.10 Cos

Returns the cosine (cos) of each values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Cos -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: cos

6.13.11 Cosh

Returns the hyperbolic cosine (cosh) of each values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Cosh -v --wd="/path/to/data/" ^
```

```
-i='input.dep' -o=output.dep
```

Python function name: cosh

6.13.12 CrispnessIndex

Calculates the Crispness Index, which is used to quantify how crisp (or conversely how fuzzy) a probability image is.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Optional output html file (default name will be based on input file if unspecified)

Command-line Interface:

```
>>./whitebox_tools -r=CrispnessIndex -v --wd="/path/to/data/" ^
-i=input.dep
>>./whitebox_tools -r=CrispnessIndex -v ^
--wd="/path/to/data/" -o=crispness.html
```

Python function name: crispness_index

6.13.13 CrossTabulation

Performs a cross-tabulation on two categorical images.

Parameters:

Flag	Description
--i1, --input1	Input raster file 1
--i2, --input2	Input raster file 1
-o, --output	Output HTML file (default name will be based on input file if unspecified)

Command-line Interface:

```
>>./whitebox_tools -r=CrossTabulation -v ^
--wd="/path/to/data/" --i1="file1.tif" --i2="file2.tif" ^
-o=outfile.html
```

Python function name: cross_tabulation

6.13.14 CumulativeDistribution

Converts a raster image to its cumulative distribution function.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=CumulativeDistribution -v ^
--wd="/path/to/data/" -i=DEM.dep -o=output.dep
```

Python function name: cumulative_distribution

6.13.15 Decrement

Decreases the values of each grid cell in an input raster by 1.0.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Decrement -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: decrement

6.13.16 Divide

Performs a division operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Divide -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: divide

6.13.17 EqualTo

Performs a equal-to comparison operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=EqualTo -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: equal_to

6.13.18 Exp

Returns the exponential (base e) of values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:


```
>>./whitebox_tools -r=Exp -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: exp

6.13.19 Exp2

Returns the exponential (base 2) of values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Exp2 -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: exp2

6.13.20 ExtractRasterStatistics

Extracts descriptive statistics for a group of patches in a raster.

Parameters:

Flag	Description
-i, --input	Input data raster file
--features	Input feature definition raster file
-o, --output	Output raster file
--stat	Statistic to extract
--out_table	Output HTML Table file

Command-line Interface:

```
>>./whitebox_tools -r=ExtractRasterStatistics -v ^
--wd="/path/to/data/" -i='input.dep' --features='groups.dep' ^
-o='output.dep' --stat='minimum'
>>./whitebox_tools ^
-r=ExtractRasterStatistics -v --wd="/path/to/data/" ^
```

```
-i='input.dep' --features='groups.dep' ^
--out_table='output.html'
```

Python function name: extract_raster_statistics

6.13.21 Floor

Returns the largest (closest to positive infinity) value that is less than or equal to the values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Floor -v --wd="/path/to/data/" ^
-i='input.dep' -o='output.dep'
```

Python function name: floor

6.13.22 GreaterThan

Performs a greater-than comparison operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file
--incl_equals	Perform a greater-than-or-equal-to operation

Command-line Interface:

```
>>./whitebox_tools -r=GreaterThan -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep ^
--incl_equals
```

Python function name: greater_than

6.13.23 ImageAutocorrelation

Performs Moran's I analysis on two or more input images.

Parameters:

Flag	Description
-i, --inputs	Input raster files
--contiguity	Contiguity type
-o, --output	Output HTML file (default name will be based on input file if unspecified)

Command-line Interface:

```
>>./whitebox_tools -r=ImageAutocorrelation -v ^
--wd="/path/to/data/" -i="file1.tif, file2.tif, file3.tif" ^
-o=outfile.html --contiguity=Bishops
```

Python function name: image_autocorrelation

6.13.24 ImageCorrelation

Performs image correlation on two or more input images.

Parameters:

Flag	Description
-i, --inputs	Input raster files
-o, --output	Output HTML file (default name will be based on input file if unspecified)

Command-line Interface:

```
>>./whitebox_tools -r=ImageCorrelation -v ^
--wd="/path/to/data/" -i="file1.tif, file2.tif, file3.tif" ^
-o=outfile.html
```

Python function name: image_correlation

6.13.25 ImageRegression

Performs image regression analysis on two input images.

Parameters:

Flag	Description
--i1, --input1	Input raster file (independent variable, X)
--i2, --input2	Input raster file (dependent variable, Y)
-o, --output	Output HTML file for regression summary report
--out_residuals	Output raster regression residual file
--standardize	Optional flag indicating whether to standardize the residuals map

Command-line Interface:

```
>>./whitebox_tools -r=ImageRegression -v ^
--wd="/path/to/data/" --i1='file1.tif' --i2='file2.tif' ^
-o='outfile.html' --out_residuals='residuals.tif' ^
--standardize
```

Python function name: image_regression

6.13.26 Increment

Increases the values of each grid cell in an input raster by 1.0.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Increment -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: increment

6.13.27 IntegerDivision

Performs an integer division operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value

Flag	Description
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=IntegerDivision -v ^
--wd="/path/to/data/" --input1='in1.dep' --input2='in2.dep' ^
-o=output.dep
```

Python function name: integer_division

6.13.28 IsNoData

Identifies NoData valued pixels in an image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=IsNoData -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: is_no_data

6.13.29 KSTestForNormality

Evaluates whether the values in a raster are normally distributed.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output HTML file
--num_samples	Number of samples. Leave blank to use whole image

Command-line Interface:

```
>>./whitebox_tools -r=KSTestForNormality -v ^
--wd="/path/to/data/" -i=input.dep -o=output.html ^
--num_samples=1000
>>./whitebox_tools -r=KSTestForNormality -v ^
--wd="/path/to/data/" -i=input.dep -o=output.html
```

Python function name: ks_test_for_normality

6.13.30 KappaIndex

Performs a kappa index of agreement (KIA) analysis on two categorical raster files.

Parameters:

Flag	Description
--i1, --input1	Input classification raster file
--i2, --input2	Input reference raster file
-o, --output	Output HTML file

Command-line Interface:

```
>>./whitebox_tools -r=KappaIndex -v --wd="/path/to/data/" ^
--i1=class.tif --i2=reference.tif -o=kia.html
```

Python function name: kappa_index

6.13.31 LessThan

Performs a less-than comparison operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file
--incl_equals	Perform a less-than-or-equal-to operation

Command-line Interface:

```
>>./whitebox_tools -r=LessThan -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep ^
```

--incl_equals

Python function name: less_than

6.13.32 Ln

Returns the natural logarithm of values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Ln -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: ln

6.13.33 Log10

Returns the base-10 logarithm of values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Log10 -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: log10

6.13.34 Log2

Returns the base-2 logarithm of values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Log2 -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: log2

6.13.35 Max

Performs a MAX operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Max -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: max

6.13.36 Min

Performs a MIN operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Min -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: min

6.13.37 Modulo

Performs a modulo operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Modulo -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: modulo

6.13.38 Multiply

Performs a multiplication operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Multiply -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: multiply

6.13.39 Negate

Changes the sign of values in a raster or the 0-1 values of a Boolean raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Negate -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: negate

6.13.40 Not

Performs a logical NOT operator on two Boolean raster images.

Parameters:

Flag	Description
--input1	Input raster file
--input2	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Not -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: Not

6.13.41 NotEqualTo

Performs a not-equal-to comparison operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value

Flag	Description
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=NotEqualTo -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: not_equal_to

6.13.42 Or

Performs a logical OR operator on two Boolean raster images.

Parameters:

Flag	Description
--input1	Input raster file
--input2	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Or -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: Or

6.13.43 Power

Raises the values in grid cells of one rasters, or a constant value, by values in another raster or constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Power -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: power

6.13.44 Quantiles

Transforms raster values into quantiles.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--num_quantiles	Number of quantiles

Command-line Interface:

```
>>./whitebox_tools -r=Quantiles -v --wd="/path/to/data/" ^
-i=DEM.dep -o=output.dep --num_quantiles=5
```

Python function name: quantiles

6.13.45 RandomField

Creates an image containing random values.

Parameters:

Flag	Description
-i, --base	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=RandomField -v --wd="/path/to/data/" ^
--base=in.dep -o=out.dep
```

Python function name: random_field

6.13.46 RandomSample

Creates an image containing randomly located sample grid cells with unique IDs.

Parameters:

Flag	Description
-i, --base	Input raster file
-o, --output	Output raster file
--num_samples	Number of samples

Command-line Interface:

```
>>./whitebox_tools -r=RandomSample -v --wd="/path/to/data/" ^
--base=in.dep -o=out.dep --num_samples=1000
```

Python function name: random_sample

6.13.47 RasterHistogram

Creates a histogram from raster values.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output HTML file (default name will be based on input file if unspecified)

Command-line Interface:

```
>>./whitebox_tools -r=RasterHistogram -v ^
--wd="/path/to/data/" -i="file1.tif" -o=outfile.html
```

Python function name: raster_histogram

6.13.48 RasterSummaryStats

Measures a rasters average, standard deviation, num. non-nodata cells, and total.

Parameters:

Flag	Description
-i, --input	Input raster file

Command-line Interface:

```
>>./whitebox_tools -r=RasterSummaryStats -v ^
--wd="/path/to/data/" -i=DEM.dep
```

Python function name: raster_summary_stats

6.13.49 Reciprocal

Returns the reciprocal (i.e. $1/z$) of values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Reciprocal -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: reciprocal

6.13.50 RescaleValueRange

Performs a min-max contrast stretch on an input greytone image.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file
--out_min_val	New minimum value in output image
--out_max_val	New maximum value in output image
--clip_min	Optional lower tail clip value
--clip_max	Optional upper tail clip value

Command-line Interface:

```
>>./whitebox_tools -r=RescaleValueRange -v ^
--wd="/path/to/data/" -i=input.dep -o=output.dep ^
--out_min_val=0.0 --out_max_val=1.0
>>./whitebox_tools ^
-r=RescaleValueRange -v --wd="/path/to/data/" -i=input.dep ^
-o=output.dep --out_min_val=0.0 --out_max_val=1.0 ^
--clip_min=45.0 --clip_max=200.0
```

Python function name: rescale_value_range

6.13.51 RootMeanSquareError

Calculates the RMSE and other accuracy statistics.

Parameters:

Flag	Description
-i, --input	Input raster file
--base	Input base raster file used for comparison

Command-line Interface:

```
>>./whitebox_tools -r=RootMeanSquareError -v ^
--wd="/path/to/data/" -i=DEM.dep
```

Python function name: root_mean_square_error

6.13.52 Round

Rounds the values in an input raster to the nearest integer value.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Round -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: round

6.13.53 Sin

Returns the sine (sin) of each values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Sin -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: sin

6.13.54 Sinh

Returns the hyperbolic sine (sinh) of each values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Sinh -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: sinh

6.13.55 Square

Squares the values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Square -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: square

6.13.56 SquareRoot

Returns the square root of the values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=SquareRoot -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: square_root

6.13.57 Subtract

Performs a differencing operation on two rasters or a raster and a constant value.

Parameters:

Flag	Description
--input1	Input raster file or constant value
--input2	Input raster file or constant value
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Subtract -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: subtract

6.13.58 Tan

Returns the tangent (tan) of each values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Tan -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: tan

6.13.59 Tanh

Returns the hyperbolic tangent (tanh) of each values in a raster.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Tanh -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: tanh

6.13.60 ToDegrees

Converts a raster from radians to degrees.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ToDegrees -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: to_degrees

6.13.61 ToRadians

Converts a raster from degrees to radians.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ToRadians -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep
```

Python function name: to_radians

6.13.62 Truncate

Truncates the values in a raster to the desired number of decimal places.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Flag	Description
--num_decimals	Number of decimals left after truncation (default is zero)

Command-line Interface:

```
>>./whitebox_tools -r=Truncate -v --wd="/path/to/data/" ^
-i='input.dep' -o=output.dep --num_decimals=2
```

Python function name: truncate

6.13.63 TurningBandsSimulation

Creates an image containing random values based on a turning-bands simulation.

Parameters:

Flag	Description
-i, --base	Input base raster file
-o, --output	Output file
--range	The field's range, in xy-units, related to the extent of spatial autocorrelation
--iterations	The number of iterations

Command-line Interface:

```
>>./whitebox_tools -r=TurningBandsSimulation -v ^
--wd="/path/to/data/" --base=in.dep -o=out.dep --range=850.0 ^
--iterations=2500
```

Python function name: turning_bands_simulation

6.13.64 Xor

Performs a logical XOR operator on two Boolean raster images.

Parameters:

Flag	Description
--input1	Input raster file
--input2	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=Xor -v --wd="/path/to/data/" ^
--input1='in1.dep' --input2='in2.dep' -o=output.dep
```

Python function name: xor

6.13.65 ZScores

Standardizes the values in an input raster by converting to z-scores.

Parameters:

Flag	Description
-i, --input	Input raster file
-o, --output	Output raster file

Command-line Interface:

```
>>./whitebox_tools -r=ZScores -v --wd="/path/to/data/" ^
-i=DEM.dep -o=output.dep
```

Python function name: z_scores

6.14 Stream Network Analysis

6.14.1 DistanceToOutlet

Calculates the distance of stream grid cells to the channel network outlet cell.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=DistanceToOutlet -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
```

```
-o=output.dep
>>./whitebox_tools -r=DistanceToOutlet -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: distance_to_outlet

6.14.2 ExtractStreams

Extracts stream grid cells from a flow accumulation raster.

Parameters:

Flag	Description
--flow_accum	Input raster D8 flow accumulation file
-o, --output	Output raster file
--threshold	Threshold in flow accumulation values for channelization
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=ExtractStreams -v --wd="/path/to/data/" ^
--flow_accum='d8accum.dep' -o='output.dep' --threshold=100.0 ^
--zero_background
```

Python function name: extract_streams

6.14.3 ExtractValleys

Identifies potential valley bottom grid cells based on local topography alone.

Parameters:

Flag	Description
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--variant	Options include 'lq' (lower quartile), 'JandR' (Johnston and Rosenfeld), and 'PandD' (Peucker and Douglas); default is 'lq'
--line_thin	Optional flag indicating whether post-processing line-thinning should be performed
--filter	Optional argument (only used when variant='lq') providing the filter size, in grid cells, used for lq-filtering (default is 5)

Command-line Interface:

```
>>./whitebox_tools -r=ExtractValleys -v --wd="/path/to/data/" ^
--dem=pointer.dep -o=out.dep --variant='JandR' ^
--line_thin
>>./whitebox_tools -r=ExtractValleys -v ^
--wd="/path/to/data/" --dem=pointer.dep -o=out.dep ^
--variant='lq' --filter=7 --line_thin
```

Python function name: extract_valleys

6.14.4 FarthestChannelHead

Calculates the distance to the furthest upstream channel head for each stream cell.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=FarthestChannelHead -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=FarthestChannelHead -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: farthest_channel_head

6.14.5 FindMainStem

Finds the main stem, based on stream lengths, of each stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file

Flag	Description
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=FindMainStem -v --wd="/path/to/data/" ^
--d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=FindMainStem -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: find_main_stem

6.14.6 HackStreamOrder

Assigns the Hack stream order to each tributary in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=HackStreamOrder -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=HackStreamOrder -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: hack_stream_order

6.14.7 HortonStreamOrder

Assigns the Horton stream order to each tributary in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=HortonStreamOrder -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=HortonStreamOrder -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: horton_stream_order

6.14.8 LengthOfUpstreamChannels

Calculates the total length of channels upstream.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=LengthOfUpstreamChannels -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=LengthOfUpstreamChannels -v ^
```

```
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: length_of_upstream_channels

6.14.9 LongProfile

Plots the stream longitudinal profiles for one or more rivers.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
--dem	Input raster DEM file
-o, --output	Output HTML file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=LongProfile -v --wd="/path/to/data/" ^
--d8_pntr=D8.dep --streams=streams.dep --dem=dem.dep ^
-o=output.html --esri_pntr
```

Python function name: long_profile

6.14.10 LongProfileFromPoints

Plots the longitudinal profiles from flow-paths initiating from a set of vector points.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--points	Input vector points file
--dem	Input raster DEM file
-o, --output	Output HTML file
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>>./whitebox_tools -r=LongProfileFromPoints -v ^
```

```
--wd="/path/to/data/" --d8_pntr=D8.dep --points=stream_head.shp ^
--dem=dem.dep -o=output.html --esri_pntr
```

Python function name: long_profile_from_points

6.14.11 RemoveShortStreams

Removes short first-order streams from a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--min_length	Minimum tributary length (in map units) used for network pruning
--esri_pntr	D8 pointer uses the ESRI style scheme

Command-line Interface:

```
>> ./whitebox_tools -r=RemoveShortStreams -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
```

Python function name: remove_short_streams

6.14.12 ShreveStreamMagnitude

Assigns the Shreve stream magnitude to each link in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>> ./whitebox_tools -r=ShreveStreamMagnitude -v ^
```

```
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=ShreveStreamMagnitude -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: shreve_stream_magnitude

6.14.13 StrahlerStreamOrder

Assigns the Strahler stream order to each link in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=StrahlerStreamOrder -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=StrahlerStreamOrder -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: strahler_stream_order

6.14.14 StreamLinkClass

Identifies the exterior/interior links and nodes in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme

Flag	Description
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=StreamLinkClass -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=StreamLinkClass -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: stream_link_class

6.14.15 StreamLinkIdentifier

Assigns a unique identifier to each link in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=StreamLinkIdentifier -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=StreamLinkIdentifier -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: stream_link_identifier

6.14.16 StreamLinkLength

Estimates the length of each link (or tributary) in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--linkid	Input raster streams link ID (or tributary ID) file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=StreamLinkLength -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --linkid=streamsID.dep ^
--dem=dem.dep -o=output.dep
>>./whitebox_tools ^
-r=StreamLinkLength -v --wd="/path/to/data/" --d8_pntr=D8.flt ^
--linkid=streamsID.flt --dem=dem.flt -o=output.flt --esri_pntr ^
--zero_background
```

Python function name: stream_link_length

6.14.17 StreamLinkSlope

Estimates the average slope of each link (or tributary) in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--linkid	Input raster streams link ID (or tributary ID) file
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=StreamLinkSlope -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --linkid=streamsID.dep ^
--dem=dem.dep -o=output.dep
>>./whitebox_tools ^
-r=StreamLinkSlope -v --wd="/path/to/data/" --d8_pntr=D8.flt ^
--linkid=streamsID.flt --dem=dem.flt -o=output.flt --esri_pntr ^
```

--zero_background

Python function name: stream_link_slope

6.14.18 StreamSlopeContinuous

Estimates the slope of each grid cell in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-i, --dem	Input raster DEM file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>> ./whitebox_tools -r=StreamSlopeContinuous -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --linkid=streamsID.dep ^
--dem=dem.dep -o=output.dep
>> ./whitebox_tools ^
-r=StreamSlopeContinuous -v --wd="/path/to/data/" ^
--d8_pntr=D8.flt --streams=streamsID.flt --dem=dem.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: stream_slope_continuous

6.14.19 TopologicalStreamOrder

Assigns each link in a stream network its topological order.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=TopologicalStreamOrder -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=TopologicalStreamOrder -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: topological_stream_order

6.14.20 TributaryIdentifier

Assigns a unique identifier to each tributary in a stream network.

Parameters:

Flag	Description
--d8_pntr	Input raster D8 pointer file
--streams	Input raster streams file
-o, --output	Output raster file
--esri_pntr	D8 pointer uses the ESRI style scheme
--zero_background	Flag indicating whether a background value of zero should be used

Command-line Interface:

```
>>./whitebox_tools -r=TributaryIdentifier -v ^
--wd="/path/to/data/" --d8_pntr=D8.dep --streams=streams.dep ^
-o=output.dep
>>./whitebox_tools -r=TributaryIdentifier -v ^
--wd="/path/to/data/" --d8_pntr=D8.flt --streams=streams.flt ^
-o=output.flt --esri_pntr --zero_background
```

Python function name: tributary_identifier

7. Supported Data Formats

The **WhiteboxTools** library can currently support reading/writing raster data in [Whitebox GAT](#), GeoTIFF, ESRI (ArcGIS) ASCII and binary (.flt & .hdr), GRASS GIS, Idrisi, SAGA GIS (binary and ASCII), and Surfer 7 data formats. The library is primarily tested using Whitebox raster data sets and if you encounter issues when reading/writing data in other formats, you should report the [issue](#). Please note that there are no plans to

incorporate third-party libraries, like [GDAL](#), in the project given the design goal of keeping a pure (or as close as possible) Rust codebase.

At present, there is limited ability in *WhiteboxTools* to read vector geospatial data. Support for Shapefile (and other common vector formats) will be enhanced within the library soon.

LiDAR data can be read/written in the common [LAS](#) data format. *WhiteboxTools* can read and write LAS files that have been compressed (zipped with a .zip extension) using the common DEFLATE algorithm. Note that only LAS file should be contained within a zipped archive file. The compressed LiDAR format LAZ and ESRI LiDAR format are not currently supported by the library. The following is an example of running a LiDAR tool using zipped input/output files:

```
>>./whitebox_tools -r=LidarTophatTransform -v --wd="/path/to/data/"  
-i="input.las.zip" -o="output.las.zip" --radius=10.0
```

Note that the double extensions (.las.zip) in the above command are not necessary and are only used for convenience of keeping track of LiDAR data sets (i.e. .zip extensions work too). The extra work of decoding/encoding compressed files does add additional processing time, although the Rust compression library that is used is highly efficient and usually only adds a few seconds to tool run times. Zipping LAS files frequently results 40-60% smaller binary files, making the additional processing time worthwhile for larger LAS file data sets with massive storage requirements.

8. Contributing

If you would like to contribute to the project as a developer, follow these instructions to get started:

1. Fork the larger Whitebox project (in which whitebox-tools exists) (<https://github.com/jblindsay/whitebox-geospatial-analysis-tools>)
2. Create your feature branch (git checkout -b my-new-feature)
3. Commit your changes (git commit -am 'Add some feature')
4. Push to the branch (git push origin my-new-feature)
5. Create a new Pull Request

Unless explicitly stated otherwise, any contribution intentionally submitted for inclusion in the work shall be licensed [as above](#) without any additional terms or conditions.

If you would like to contribute financial support for the project, please contact [John Lindsay](#). We also welcome contributions in the form of media exposure. If you have written an article or blog about *WhiteboxTools* please let us know about it.

9. Reporting Bugs

WhiteboxTools is distributed as is and without warranty of suitability for application. If you encounter flaws with the software (i.e. bugs) please report the issue. Providing a detailed description of the conditions

under which the bug occurred will help to identify the bug. *Use the Issues tracker on GitHub to report issues with the software and to request feature enhancements.* Please do not email Dr. Lindsay directly with bugs.

10. Known Issues and Limitations

- There is limited support for reading, writing, or analyzing vector data yet. Plans include native support for the ESRI Shapefile format and possibly GeoJSON data.
- The LAZ compressed LiDAR data format is currently unsupported although zipped LAS files (.zip) are.
- There is no support for reading waveform data contained within or associated with LAS files.
- File directories cannot contain apostrophes (', e.g. /John's data/) as they will be interpreted in the arguments array as single quoted strings.
- The Python scripts included with **WhiteboxTools** require Python 3. They will not work with Python 2, which is frequently the default Python version installed on many systems.

11. License

The **WhiteboxTools** library is distributed under the [MIT license](#), a permissive open-source (free software) license.

The MIT License (MIT)

Copyright (c) 2017-2018 John Lindsay

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

12. Frequently Asked Questions

12.1 Do I need Whitebox GAT to use WhiteboxTools?

No you do not. You can call the tools contained within *WhiteboxTools* completely independent from the *Whitebox GAT* user interface using a Remote Procedure Call (RPC) approach. In fact, you can interact with the tools using Python scripting or directly, using a terminal application (command prompt). See *Interacting With WhiteboxTools* From the Command Prompt** for further details.

12.2 How do I request a tool be added?

Eventually most of the tools in *Whitebox GAT* will be ported over to *WhiteboxTools* and all new tools will be added to this library as well. Naturally, this will take time. The order by which tools are ported is partly a function of ease of porting, existing infrastructure (i.e. raster and LiDAR tools will be ported first since their is currently no support in the library for vector I/O), and interest. If you are interested in making a tool a higher priority for porting, email [John Lindsay](#).

12.3 Can WhiteboxTools be incorporated into other software and open-source GIS projects?

WhiteboxTools was developed with the open-source GIS [Whitebox GAT](#) in mind. That said, the tools can be accessed independently and so long as you abide by the terms of the [MIT license](#), there is no reason why other software and GIS projects cannot use *WhiteboxTools* as well. In fact, this was one of the motivating factors for creating the library in the first place. Feel free to use *WhiteboxTools* as the geospatial analysis engine in your open-source software project.

12.4 What platforms does WhiteboxTools support?

WhiteboxTools is developed using the Rust programming language, which supports a [wide variety of platforms](#) including MS Windows, MacOS, and Linux operating systems and common chip architectures. Interestingly, Rust also supports mobile platforms, and *WhiteboxTools* should therefore be capable of targeting (although no testing has been completed in this regard to date). Nearly all development and testing of the software is currently carried out on MacOS and we cannot guarantee a bug-free performance on other platforms. In particular, MS Windows is the most different from the other platforms and is therefore the most likely to encounter platform-specific bugs. If you encounter bugs in the software, please consider reporting an issue using the GitHub support for issue-tracking.

12.5 What are the system requirements?

The answer to this question depends strongly on the type of analysis and data that you intend to process. However, generally we find performance to be optimal with a recommended minimum of 8-16GB of memory (RAM), a modern multi-core processor (e.g. 64-bit i5 or i7), and an solid-state-drive (SSD). It is likely that *WhiteboxTools* will have satisfactory performance on lower-spec systems if smaller datasets are being processed. Because *WhiteboxTools* reads entire raster datasets into system memory (for optimal performance, and in recognition that modern systems have increasingly larger amounts of fast RAM), this tends to be the limiting factor for the upper-end of data size successfully processed by the library. 64-bit operating systems are recommended and extensive testing has not been carried out on 32-bit OSs. See [“What platforms does WhiteboxTools support?”](#) for further details on supported platforms.

12.6 Are pre-compiled executables of WhiteboxTools available?

Pre-compiled binaries for *WhiteboxTools* can be downloaded from the [Geomorphometry and Hydrogeomatics Research Group](#) software web site for various supported operating systems. If you need binaries for other operating systems/system architectures, you will need to compile the executable from source files. See [Installation](#) for details.

12.7 Why is WhiteboxTools programmed in Rust?

I spent a long time evaluating potential programming language for future development efforts for the *Whitebox GAT* project. My most important criterion for a language was that it compile to native code, rather than target the Java virtual machine (JVM). I have been keen to move Whitebox GAT away from Java because of some of the challenges that supporting the JVM has included for many Whitebox users. The language should be fast and productive—Java is already quite fast, but if I am going to change development languages, I would like a performance boost. Furthermore, given that many, though not all, of the algorithms used for geospatial analysis scale well with concurrent (parallel) implementations, I favoured languages that offered easy and safe concurrent programming. Although many would consider C/C++ for this work, I was looking for a modern and safe language. Fortunately, we are living through a renaissance period in programming language development and there are many newer languages that fit the bill nicely. Over the past two years, I considered each of Go, Rust, D, Nim, and Crystal for Whitebox development and ultimately decided on Rust. [See [GoSpatial](#) and [lidario](#).]

Each of the languages I examined has its own advantages of disadvantages, so why Rust? It’s a combination of factors that made it a compelling option for this project. Compared with many on the list, Rust is a mature language with a vibrant user community. Like C/C++, it’s a high-performance and low-level language that allows for complete control of the system. However, Rust is also one of the safest languages, meaning that I can be confident that *WhiteboxTools* will not contain common bugs, such as memory use-after-release, memory leaks and race conditions within concurrent code. Importantly, and quite uniquely, this safety is achieved in the Rust language without the use of a garbage collector (automatic memory management). Garbage collectors can be great, but they do generally come with a certain efficiency trade-off that Rust does not have. The other main advantage of Rust’s approach to memory management is

that it allows for a level of interaction with scripting languages (e.g. Python) that is quite difficult to do in garbage collected languages. Although **WhiteboxTools** is currently set up to use an automation approach to interacting with Python code that calls it, I like the fact that I have the option to create a *WhiteboxTools* shared library.

Not everything with Rust is perfect however. It is still a very young language and there are many pieces still missing from its ecosystem. Furthermore, it is not the easiest language to learn, particularly for people who are inexperienced with programming. This may limit my ability to attract other programmers to the Whitebox project, which would be unfortunate. However, overall, Rust was the best option for this particular application.

12.8 Do I need Rust installed on my computer to run WhiteboxTools?

No, you would only need Rust installed if you were compiling the *WhiteboxTools* codebase from source files.

12.9 How does WhiteboxTools' design philosophy differ?

Whitebox GAT is frequently praised for its consistent design and ease of use. Like *Whitebox GAT*, *WhiteboxTools* follows the convention of *one tool for one function*. For example, in *WhiteboxTools* assigning the links in a stream channel network their Horton, Strahler, Shreve, or Hack stream ordering numbers requires running separate tools (i.e. *HortonStreamOrder*, *StrahlerStreamOrder*, *ShreveStreamMagnitude*, and *HackStreamOrder*). By contrast, in GRASS GIS¹ and ArcGIS single tools (i.e. the *r.stream.order* and *StreamOrder* tools respectively) can be configured to output different channel ordering schemes. The *WhiteboxTools* design is intended to simplify the user experience and to make it easier to find the right tool for a task. With more specific tool names that are reflective of their specific purposes, users are not as reliant on reading help documentation to identify the tool for the task at hand. Similarly, it is not uncommon for tools in other GIS to have multiple outputs. For example, in GRASS GIS the *r.slope.aspect* tool can be configured to output slope, aspect, profile curvature, plan curvature, and several other common terrain surface derivatives. Based on the *one tool for one function* design approach of *WhiteboxTools*, multiple outputs are indicative that a tool should be split into different, more specific tools. Are you more likely to go to a tool named *r.slope.aspect* or *TangentialCurvature* when you want to create a tangential curvature raster from a DEM? If you're new to the software and are unfamiliar with it, probably the later is more obvious. The *WhiteboxTools* design approach also has the added benefit of simplifying the documentation for tools. The one downside to this design approach, however, is that it results (or will result) in a large number of tools, often with significant overlap in function.

¹ NOTE: It's not my intent to criticize GRASS GIS, as I deeply respect the work that the GRASS developers have contributed. Rather, I am contrasting the consequences of *WhiteboxTools*' design philosophy to that of other GIS.