

# Package ‘phyloscannerR’

September 28, 2018

**Title** Phylogenetics between and within hosts at once, all along the genome

**Version** 1.6.2

**Description** An R package for the second half of phyloscanner (tree analysis).

**Depends** R (>= 3.4.0)

**Imports** ape, argparse, extraDistr, ff, GGally, ggtree, grid, gtable, kimisc, network, pegas, phangorn, phytools, prodlim, RColorBrewer, reshape2, scales, sna, tidyverse, viridis

**License** GPL

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.1.0

## R topics documented:

|  |    |
|--|----|
| draw.summary.statistics . . . . .              | 1  |
| gather.summary.statistics . . . . .            | 2  |
| multinomial.calculations . . . . .             | 3  |
| multipage.summary.statistics . . . . .         | 4  |
| pairwise.relationship.statistics . . . . .     | 4  |
| phyloscanner.analyse.trees . . . . .           | 5  |
| reconstruct.ancestral.sequences . . . . .      | 10 |
| reconstruct.host.ancestral.sequences . . . . . | 11 |
| simplified.transmission.summary . . . . .      | 11 |
| transmission.summary . . . . .                 | 12 |
| write.annotated.tree . . . . .                 | 13 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>14</b> |
|--------------|-----------|

---

draw.summary.statistics

*Graph summary statistics for a single host*

---

## Description

Graph summary statistics for a single host

**Usage**

```
draw.summary.statistics(phyloscanner.trees, sum.stats, host, verbose = F)
```

**Arguments**

|                    |  |
|--------------------|--|
| phyloscanner.trees | A list of class phyloscanner.trees                 |
| sum.stats          | The output of a call to gather.summary.statistics. |
| host               | The host to obtain graphs for.                     |
| verbose            | Verbose output                                     |

---

```
gather.summary.statistics
```

*Make a tibble of per-window host statistics*

---

**Description**

This function collects per-window statistics on hosts

**Usage**

```
## S3 method for class 'summary.statistics'
gather(ptrees,
  hosts = all.hosts.from.trees(ptrees),
  tip.regex = "^(.*)_read_([0-9]+)_count_([0-9]+)$", verbose = F)
```

**Arguments**

|           |  |
|-----------|--|
| ptrees    | A list of class phyloscanner.trees   |
| hosts     | A list of hosts to record statistics for. If not specified, every identifiable host in phyloscanner.trees  |
| tip.regex | Regular expression identifying tips from the dataset. This expects up to three capture groups, for host ID, read ID, and read count (in that order). If the latter two groups are missing then read information will not be used. The default matches input from the phyloscanner pipeline where the host ID is the BAM file name. |
| verbose   | Produce verbose output   |

**Value**

A tibble

---

multinomial.calculations

*Calculate parameters of the posterior density for pairwise host relationships*

---

## Description

Calculate parameters of the posterior density for pairwise host relationships

## Usage

```
multinomial.calculations(ptrees, close.threshold,
  tip.regex = "^(.*)_read_([0-9]+)_count_([0-9]+)$", allow.mt = F,
  min.reads = 0, min.tips = 0, distant.threshold = close.threshold,
  relationship.types = c("proximity.3.way", "any.ancestry",
    "close.x.contiguous", "close.and.contiguous",
    "close.and.contiguous.and.directed", "close.and.adjacent.and.directed",
    "close.and.contiguous.and.ancestry.cat",
    "close.and.adjacent.and.ancestry.cat", "adjacent.and.proximity.cat"),
  verbose = F)
```

## Arguments

|                   |   |
|-------------------|---|
| ptrees            | A list of class <code>phyloscanner.trees</code> produced by <code>phyloscanner.analyse.trees</code> .   |
| close.threshold   | The (potentially normalised) patristic threshold used to determine if two patients' subgraphs are "close"   |
| tip.regex         | The regular expression used to identify host IDs in tip names   |
| allow.mt          | If FALSE, directionality is only inferred between pairs of hosts where a single clade from one host is nested in one from the other; this is more conservative.   |
| min.reads         | The minimum number of reads from a host in a window needed in order for that window to count in determining relationships involving that patient  |
| min.tips          | The minimum number of tips from a host in a window needed in order for that window to count in determining relationships involving that patient   |
| distant.threshold | If present, a second distance threshold determines hosts that are "distant" from each other, with those lying between <code>close.threshold</code> and <code>dist.threshold</code> classed as "intermediate". The default is the same as <code>close.threshold</code> , so the intermediate class does not exist. |
| verbose           | Verbose output  |

## Value

A list with two items: `dwin` giving information on the genome windows for each pair of hosts, and `rplk1` giving information on phylogenetic relationships between each pair of hosts.

---

`multipage.summary.statistics`

*Draw summary statistics to file for many hosts as a multipage file*

---

### Description

Draw summary statistics to file for many hosts as a multipage file

### Usage

```
multipage.summary.statistics(ptrees, sum.stats,
  hosts = all.hosts.from.trees(phyloscanner.trees), file.name,
  height = 11.6929, width = 8.26772, verbose = F)
```

### Arguments

|                        |   |
|------------------------|---|
| <code>ptrees</code>    | A list of class <code>phyloscanner.trees</code>   |
| <code>sum.stats</code> | The output of a call to <code>gather.summary.statistics</code> .                                |
| <code>hosts</code>     | A vector of hosts to obtain graphs for. By default, all hosts detected in <code>ptrees</code> . |
| <code>file.name</code> | Output file name (expected to be a PDF)   |
| <code>height</code>    | The height of each page of the output file in inches (defaults to A4 size)                      |
| <code>width</code>     | The width of each page of the output file in inches (defaults to A4 size)                       |
| <code>verbose</code>   | Verbose output  |

---

`pairwise.relationship.statistics`

*Draw bar graphs of pairwise topological/distance relationships to file*

---

### Description

Draw bar graphs of pairwise topological/distance relationships to file

### Usage

```
pairwise.relationship.statistics(ptrees,
  hosts = combn(all.hosts.from.trees(phyloscanner.trees), 2, simplify =
  F), file.name, height = 11.6929, width = 8.26772, verbose = F)
```

### Arguments

|                        |   |
|------------------------|---|
| <code>ptrees</code>    | A list of class <code>phyloscanner.trees</code>   |
| <code>hosts</code>     | A list of pairs of hosts (as vectors) to obtain graphs for. By default, all pairs hosts detected in <code>ptrees</code> . |
| <code>file.name</code> | Output file name (expected to be a PDF)   |
| <code>height</code>    | The height of each page of the output file in inches (defaults to A4 size)  |
| <code>width</code>     | The width of each page of the output file in inches (defaults to A4 size)   |
| <code>verbose</code>   | Verbose output  |

---

phyloscanner.analyse.trees

*Perform a phyloscanner analysis on a tree or set of trees*


---

## Description

These functions perform a parsimony reconstruction and classification of pairwise host relationships.

## Usage

```

phyloscanner.analyse.trees(tree.file.directory,
  tree.file.regex = "^RAxML_bestTree.InWindow_([0-9]+_to_[0-9]+)\\.tree$",
  splits.rule = c("s", "r", "f"), sankoff.k = 0,
  sankoff.unassigned.switch.threshold = 0,
  continuation.unassigned.proximity.cost = 1000, outgroup.name = NULL,
  multifurcation.threshold = -1, guess.multifurcation.threshold = F,
  user.blacklist.directory = NULL, user.blacklist.file.regex = NULL,
  duplicate.file.directory = NULL,
  duplicate.file.regex = "^DuplicateReadCountsProcessed_InWindow_([0-9]+_to_[0-9]+).csv$",
  recombination.file.directory = NULL,
  recombination.file.regex = "^RecombinantReads_InWindow_([0-9]+_to_[0-9]+).csv$",
  alignment.file.directory = NULL, alignment.file.regex = NULL,
  tip.regex = "^(.*)_read_([0-9]+)_count_([0-9]+)$",
  file.name.regex = "^\\D*([0-9]+)_to_([0-9]+)\\D*$",
  seed = sample(1:1e+07, 1), norm.ref.file.name = NULL,
  norm.standardise.gag.pol = F, norm.constants = NULL,
  parsimony.blacklist.k = 0, raw.blacklist.threshold = 0,
  ratio.blacklist.threshold = 0, do.dual.blacklisting = F,
  max.reads.per.host = Inf, blacklist.underrepresented = F,
  use.ff = F, prune.blacklist = F, count.reads.in.parsimony = T,
  verbosity = 0, no.progress.bars = F)

phyloscanner.analyse.tree(tree.file.name, splits.rule = c("s", "r", "f"),
  sankoff.k = 0, sankoff.unassigned.switch.threshold = 0,
  continuation.unassigned.proximity.cost = 1000, outgroup.name = NULL,
  multifurcation.threshold = -1, guess.multifurcation.threshold = F,
  user.blacklist.file.name = NULL, duplicate.file.name = NULL,
  recombination.file.name = NULL, alignment.file.name = NULL,
  tip.regex = "^(.*)_read_([0-9]+)_count_([0-9]+)$",
  file.name.regex = "^\\D*([0-9]+)_to_([0-9]+)\\D*$",
  seed = sample(1:1e+07, 1), norm.ref.file.name = NULL,
  norm.standardise.gag.pol = F, norm.constants = NULL,
  parsimony.blacklist.k = 0, raw.blacklist.threshold = 0,
  ratio.blacklist.threshold = 0, do.dual.blacklisting = F,
  max.reads.per.host = Inf, blacklist.underrepresented = F,
  use.ff = F, prune.blacklist = F, count.reads.in.parsimony = T,
  verbosity = 0, no.progress.bars = F)

phyloscanner.generate.blacklist(tree.file.directory,
  tree.file.regex = "^RAxML_bestTree.InWindow_([0-9]+_to_[0-9]+)\\.tree$",

```

```

outgroup.name = NULL, multifurcation.threshold = -1,
guess.multifurcation.threshold = F, user.blacklist.directory = NULL,
user.blacklist.file.regex = NULL, duplicate.file.directory = NULL,
duplicate.file.regex = "^DuplicateReadCountsProcessed_InWindow_([0-9]+_to_[0-9]+).csv$",
alignment.file.directory = NULL, alignment.file.regex = NULL,
tip.regex = "^(.*)_read_([0-9]+)_count_([0-9]+)$",
file.name.regex = "^\\D*([0-9]+)_to_([0-9]+)\\D*$",
seed = sample(1:1e+07, 1), norm.ref.file.name = NULL,
norm.standardise.gag.pol = F, norm.constants = NULL,
parsimony.blacklist.k = 0, raw.blacklist.threshold = 0,
ratio.blacklist.threshold = 0, do.dual.blacklisting = F,
max.reads.per.host = Inf, blacklist.underrepresented = F,
count.reads.in.parsimony = F, verbosity = 0)

```

## Arguments

- tree.file.directory**  
The directory containing all input trees.
- tree.file.regex**  
A regular expression identifying every file in `tree.file.directory` that is to be included in the analysis. The first capture group, if present, gives a unique string identifying each tree. If this is `NULL` then phyloscanner will attempt to open every file in `tree.file.directory`.
- splits.rule**  
The rules by which the sets of hosts are split into groups in order to ensure that all groups can be members of connected subgraphs without causing conflicts. Options: `s`=Sankoff with optional within-host diversity penalty (slow, rigorous, recommended), `r`=Romero-Severson (quick, less rigorous with >2 hosts), `f`=Sankoff with continuation costs (experimental).
- sankoff.k**  
For `splits.rule = s` or `f` only. The  $k$  parameter in the Sankoff reconstruction, representing the within-host diversity penalty.
- sankoff.unassigned.switch.threshold**  
For `splits.rule = s` only. Threshold at which a lineage reconstructed as infecting a host will transition to the unassigned state, if it would be equally parsimonious to remain in that host.
- continuation.unassigned.proximity.cost**  
For `splits.rule = f` only. The branch length at which an node is reconstructed as unassigned if all its neighbouring nodes are a greater distance away. The default is 1000, intended to be effectively infinite, such a node will never normally receive the unassigned state.
- outgroup.name**  
The name of the tip in the phylogeny/phylogenies to be used as outgroup (if unspecified, trees will be assumed to be already rooted). This should be sufficiently distant to any sequence obtained from a host that it can be assumed that the MRCA of the entire tree was not a lineage present in any sampled individual.
- multifurcation.threshold**  
If specified, branches shorter than this in the input tree will be collapsed to form multifurcating internal nodes. This is recommended; many phylogenetics packages output binary trees with short or zero-length branches indicating multifurcations.
- guess.multifurcation.threshold**  
Whether to guess the multifurcation threshold from the branch lengths of the trees and the width of the genomic window (if that information is available). It

is recommended that trees are examined by eye to check that they do appear to have multifurcations if using this option.

`user.blacklist.directory`

An optional path for a folder containing pre-existing blacklist files. These tips are specified by the user to be excluded from the analysis.

`user.blacklist.file.regex`

A regular expression identifying every file in `user.blacklist.directory` that contains a blacklist. If a capture group is specified then its contents will uniquely identify the tree it belongs to, which must matches the IDs found by `tree.file.regex`. If these IDs cannot be identified then matching will be attempted using genome window coordinates.

`duplicate.file.directory`

An optional path for a folder containing information on duplicate reads, to be used for duplicate blacklisting. Normally this is produced by `phyloscanner_make_trees.py`.

`duplicate.file.regex`

A regular expression identifying every file in `duplicate.file.directory` that contains a duplicates file. If a capture group is specified then its contents will uniquely identify the tree it belongs to, which must matches the IDs found by `tree.file.regex`. If these IDs cannot be identified then matching will be attempted using genome window coordinates.

`recombination.file.directory`

An optional path for a folder containing results of the `phyloscanner_make_trees.py` recombination metric analysis.

`recombination.file.regex`

A regular expression identifying every file in `recombination.file.directory` that contains a recombination file. If a capture group is specified then its contents will uniquely identify the tree it belongs to, which must matches the IDs found by `tree.file.regex`. If these IDs cannot be identified then matching will be attempted using genome window coordinates.

`alignment.file.regex`

A regular expression identifying every file in `alignment.directory` that is an alignment. If a capture group is specified then its contents will uniquely identify the tree it belongs to, which must matches the IDs found by `tree.file.regex`. If these IDs cannot be identified then matching will be attempted using genome window coordinates.

`tip.regex`

Regular expression identifying tips from the dataset. This expects up to three capture groups, for host ID, read ID, and read count (in that order). If the latter two groups are missing then read information will not be used. The default matches input from the phyloscanner pipeline where the host ID is the BAM file name.

`file.name.regex`

Regular expression identifying window coordinates. Two capture groups: start and end; if the latter is missing then the first group is a single numerical identifier for the window. The default matches input from the phyloscanner pipeline.

`seed`

Random number seed; used by the downsampling process, and also ties in some parsimony reconstructions can be broken randomly.

`norm.ref.file.name`

Name of a file giving a normalisation constant for every genome position. Cannot be used simultaneously with `norm.constants`. If neither is given then no normalisation will be performed.

|   |   |
|---|---|
| <code>norm.standardise.gag.pol</code>   | Use only if <code>norm.ref.file.name</code> is given. An HIV-specific option: if true, the normalising constants are standardised so that the average on gag+pol equals 1. Otherwise they are standardised so the average on the whole genome equals 1.   |
| <code>norm.constants</code>             | Either the path of a CSV file listing the file name for each tree (column 1) and the respective normalisation constant (column 2) or a single numerical normalisation constant to be applied to every tree. Cannot be used simultaneously with <code>norm.ref.file.name</code> . If neither is given then no normalisation will be performed.   |
| <code>parsimony.blacklist.k</code>      | The $k$ parameter of the single-host Sankhoff parsimony reconstruction used to identify probable contaminants. A value of 0 is equivalent to not performing parsimony blacklisting.   |
| <code>raw.blacklist.threshold</code>    | Used to specify a read count to be used as a raw threshold for duplicate or parsimony blacklisting. Use with <code>parsimony.blacklist.k</code> or <code>duplicate.file.regex</code> or both. Parsimony blacklisting will blacklist any subgraph with a read count strictly less than this threshold. Duplicate blacklisting will blacklist any duplicate read with a count strictly less than this threshold. The default value of 0 means nothing is blacklisted.   |
| <code>ratio.blacklist.threshold</code>  | Used to specify a read count ratio (between 0 and 1) to be used as a threshold for duplicate or parsimony blacklisting. Use with <code>parsimony.blacklist.k</code> or <code>duplicate.file.regex</code> or both. Parsimony blacklisting will blacklist a subgraph if the ratio of its read count to the total read count from the same host is strictly less than this threshold. Duplicate blacklisting will blacklist a duplicate read if the ratio of its count to the count of the duplicate (from another host) is strictly less than this threshold. |
| <code>do.dual.blacklisting</code>       | Blacklist all reads from the minor subgraphs for all hosts established as dual by parsimony blacklisting (which must have been done for this to do anything).   |
| <code>max.reads.per.host</code>         | Used to turn on downsampling. If given, reads will be blacklisted such that read counts (or tip counts if no read counts are identified) from each host are equal (although see <code>blacklist.underrepresented</code> ).  |
| <code>blacklist.underrepresented</code> | If TRUE and <code>max.reads.per.host</code> is given, blacklist hosts from trees where their total tip count does not reach the maximum.  |
| <code>use.ff</code>                     | Use the <code>ff</code> package to store parsimony reconstruction matrices. Use if you run out of memory.   |
| <code>prune.blacklist</code>            | If TRUE, all blacklisted and reference tips (except the outgroup) are pruned away before starting parsimony-based reconstruction.   |
| <code>count.reads.in.parsimony</code>   | If TRUE, read counts on tips will be taken into account in parsimony reconstructions at the parents of zero-length terminal branches. Not applicable for the Romero-Severson-like reconstruction method.  |
| <code>verbosity</code>                  | The type of verbose output. 0=none, 1=minimal, 2=complete   |
| <code>no.progress.bars</code>           | Hide the progress bars from verbose output.   |



`tree.file.name` The name of a single tree file (Newick or NEXUS format).  
`user.blacklist.file.name`  
     The path of a single text file containing the user-specified list of tips to be black-listed  
`duplicate.file.name`  
     The path of a single .csv file specifying which tree tips are from duplicate reads. Normally this is produced by `phyloscanner_make_trees.py`.  
`recombination.file.name`  
     The path for a single file containing the results of the `phyloscanner_make_trees.py` recombination metric analysis.  
`alignment.directory`  
     The directory containing the alignments used to construct the phylogenies.

## Details

`phyloscanner.analyse.tree` is for a single phylogeny and `phyloscanner.analyse.trees` for a collection, while `phyloscanner.generate.blacklist` performs the blacklisting steps only.

## Value

A list of class `phyloscanner.trees`. Each element of this list is itself a list of class `phyloscanner.tree` and corresponds to a single tree, recording details of the phyloscanner reconstruction. The names of the `phyloscanner.trees` object are the tree IDs, usually derived from file suffixes. A list of class `phyloscanner.tree` may, depending on exact circumstances, have the following items:

- `id` The tree ID.
- `tree` The tree as a phylo object. This will have been rooted and have multifurcations collapsed as requested, but branch lengths are original. It may have been pruned of blacklisted tips if `prune.blacklist` was specified.
- `alignment` The alignment as a DNABin object.
- `tree.file.name` The file name from which the tree was loaded.
- `alignment.file.name` The file name for the alignment.
- `user.blacklist.file.name` The file name for the user-specified blacklist.
- `duplicate.file.name` The file name for the list of between-host duplicate tips.
- `recombination.file.name` The file name for the results of the `phyloscanner_make_trees.py` recombination metric analysis.
- `index` The index of this tree in the `phyloscanner.trees` list.
- `bl.report` A data.frame outlining the blacklisted tips in this tree and the reasons they were blacklisted.
- `window.coords` A vector giving the start and end of the genome coordinates of the window from which the tree was built (if the windowed approach was used).
- `xcoord` A single genome position to locate this tree along the genome; generally the window midpoint in the windowed approach.
- `duplicate.file.name` The file name used to determine between-host duplicate tips
- `original.tip.labels` Blacklisting may lead to the pruning of tips from the tree or their renaming. The original tip labels read from the tree file are recorded here.
- `hosts.for.tips` A vector mapping each tip onto its corresponding hosts. Blacklisted tips are given NA.

- `normalisation.constant` The normalisation constant for this tree. This will be 1 if no normalisation was requested.
- `duplicate.tips` A list whose entries are vectors of tips whose sequences are exactly alike.
- `blacklist` A vector of numbers for all tips blacklisted for whatever reason. If the blacklist was pruned away, this will be empty.
- `dual.detection.splits` A data.frame determining the multiplicity of infection for each host as determined by parsimony blacklisting.
- `duals.info` A data.frame describing the subgraphs that each tip belong to in the dual infection detection, prior to parsimony and dual blacklisting.
- `tips.for.hosts` A list giving the tips numbers corresponding to each host
- `read.counts` A vector giving the read counts for each tip. Blacklisted tips and the outgroup have NAs. All non-NAs will be 1 if the data has no read count.
- `splits.table` A data frame giving the host and subgraph containing each tip, according to the parsimony reconstruction.
- `clades.by.host` A list of lists of tips, each determining a monophyletic clade from one host.
- `clade.mrcas.by.host` A list of vectors containing the MRCA nodes of those clades.
- `classification.results` A data.frame describing the pairwise topological classification of each pair of hosts in the tree.

A `phyloscanner.trees` object has the following attributes:

- `readable.coords` TRUE if genome window coordinates could be obtained from file names.
- `match.mode` Either "ID" (tree IDs were identified using `tree.file.regex`), "coords" (tree IDs were identified from what appear to be genome window coordinates in file names) or "none" (string IDs could not be determined).
- `has.read.counts` TRUE if phyloscanner detected read counts in tip labels.
- `outgroup.name` The tip label of the outgroup.

---

```
reconstruct.ancestral.sequences
```

*Reconstruct the ancestral sequence at every node of the tree*

---

## Description

Reconstruct the ancestral sequence at every node of the tree

## Usage

```
reconstruct.ancestral.sequences(ptree, verbose = F, default = F, ...)
```

## Arguments

|                      |  |
|----------------------|--|
| <code>ptree</code>   | A list of class <code>phyloscanner.tree</code> (usually an item in a list of class <code>phyloscanner.trees</code> )                             |
| <code>verbose</code> | Verbose output   |
| <code>default</code> | If TRUE, the reconstruction is done according to the default model used in RAxML to build trees for phyloscanner. The ... below will be ignored. |
| <code>...</code>     | Further arguments to be passed to <code>pml</code> and <code>optim.pml</code>  |

**Value**

An alignment of the sequences at all nodes (in DNABin format)

---

```
reconstruct.host.ancestral.sequences
```

*Find the ancestral sequence at the MRCA of the tips from this host, or, if a dual infection was previously identified, of the MRCA of the tips making up each infection event*

---

**Description**

Find the ancestral sequence at the MRCA of the tips from this host, or, if a dual infection was previously identified, of the MRCA of the tips making up each infection event

**Usage**

```
reconstruct.host.ancestral.sequences(ptree, host, individual.duals = F,
  verbose = F)
```

**Arguments**

|                  |  |
|------------------|--|
| ptree            | A list of class <code>phyloscanner.tree</code> (usually an item in a list of class <code>phyloscanner.trees</code> ). This must have an <code>ancestral.alignment</code> element (see <i>reconstruct.ancestral.sequences</i> ) |
| host             | The host ID  |
| individual.duals | Whether to output multiple sequences for host based on the results of a previous dual infection analysis   |
| verbose          | Verbose output   |

---

```
simplified.transmission.summary
```

*Simplify and visually display the pairwise host relationships across all trees*

---

**Description**

Simplify and visually display the pairwise host relationships across all trees

**Usage**

```
simplified.transmission.summary(ptrees, transmission.summary,
  arrow.threshold, plot = F)
```

**Arguments**

|                    |  |
|--------------------|--|
| arrow.threshold    | The proportion of trees in which a pair of hosts need to show a direction of transmission for that direction to be indicated as an arrow. If both directions meet this threshold, the arrow is in the direction with the larger proportion of trees. |
| plot               | If TRUE, the returned list has an item called simp.diagram, a ggplot object plotting the simplified relationship diagram.  |
| phyloscanner.trees | A list of class phyloscanner.trees   |
| trans.summary      | The output of transmission.summary; a tibble.  |

---

|                      |   |
|----------------------|---|
| transmission.summary | <i>Summarise the pairwise host relationships across all trees</i> |
|----------------------|---|

---

**Description**

Summarise the pairwise host relationships across all trees

**Usage**

```
transmission.summary(ptrees, win.threshold = 0, dist.threshold = Inf,
  allow.mt = T, close.sib.only = F, verbose = F)
```

**Arguments**

|                    |   |
|--------------------|---|
| win.threshold      | The proportion of windows that a pair of hosts need to be related (adjacent and within dist.threshold of each other) in order for them to appear in the summary.                  |
| dist.threshold     | The patristic distance within which the subgraphs from two hosts need to be in order for them to be declared related (default is infinity, so adjacent hosts are always related). |
| allow.mt           | If FALSE, directionality is only inferred between pairs of hosts where a single clade from one host is nested in one from the other; this is more conservative.                   |
| close.sib.only     | If TRUE, then the distance threshold applies only to hosts in sibling clades. Any ancestry is automatically a relationship.   |
| verbose            | Give verbose output   |
| phyloscanner.trees | A list of class phyloscanner.trees  |

**Value**

A tibble, every line of which counts the number of pairwise relationships of a particular type between a pair of hosts

---

|                      |  |
|----------------------|--|
| write.annotated.tree | <i>Write the phylogeny with reconstructed host annotations to file</i> |
|----------------------|--|

---

**Description**

Write the phylogeny with reconstructed host annotations to file

**Usage**

```
write.annotated.tree(ptree, file.name, format = c("pdf", "nex"),  
  pdf.scale.bar.width = 0.01, pdf.w = 50, pdf.hm = 0.15,  
  verbose = F)
```

**Arguments**

|                     |   |
|---------------------|---|
| file.name           | The name of the output file   |
| format              | The format - PDF or NEXUS - in which to write the output.                                 |
| pdf.scale.bar.width | The width, in substitutions per site, of the scale bar in PDF output                      |
| pdf.w               | The width of the output PDF file, in inches   |
| pdf.hm              | The height, in inches per tip, of the output PDF file                                     |
| verbose             | Verbose output  |
| phyloscanner.tree   | A list of class phyloscanner.tree (usually an item in a list of class phyloscanner.trees) |

# Index

`draw.summary.statistics`, [1](#)

`gather.summary.statistics`, [2](#)

`multinomial.calculations`, [3](#)

`multipage.summary.statistics`, [4](#)

`pairwise.relationship.statistics`, [4](#)

`phyloscanner.analyse.tree`  
    (`phyloscanner.analyse.trees`), [5](#)

`phyloscanner.analyse.trees`, [5](#)

`phyloscanner.generate.blacklist`  
    (`phyloscanner.analyse.trees`), [5](#)

`reconstruct.ancestral.sequences`, [10](#)

`reconstruct.host.ancestral.sequences`,  
    [11](#)

`simplified.transmission.summary`, [11](#)

`transmission.summary`, [12](#)

`write.annotated.tree`, [13](#)