




Linear classifiers in higher dimensions



Ariel Shamir
Zohar Yakhini



Outline




- Linear Separability
- Linear decision boundaries
- The perceptron algorithm
- Non linear mapping of features
- Mapping to higher dimension
- Cover's Thm
- Kernels
- Dual perceptron
- Kernel perceptron
- SVMs

A hyperspace as a linear separator

Consider the decision function

$$h(\vec{x}) = \text{sgn}(\vec{x} \cdot \vec{w} - b)$$

In this figure, who is w ?
what is b ? what values does
 h take for various points?



Linear separability

Data in \mathbb{R}^d is linearly separable iff we can find a hyperplane so that:

$$y_i(\vec{x}_i \cdot \vec{w} - b) \geq 0, 1 \leq i \leq m$$

The Perceptron Learning Algorithm

- Assume the target value for classification are $t \in \{-1, +1\}$
- The perceptron seeks to find a linear separator with NO ERRORS.
- Is this always possible?

Initialize each w_i to some small random number.

Until termination do

For each \vec{x}_d in D compute

$$o_d = \text{sgn}(\vec{w} \cdot \vec{x}_d)$$

For each linear unit weight w_i , Do

$$\Delta w_i = -\eta(o_d - t_d)x_{id}$$

$$w_i = w_i + \Delta w_i$$

n+1 weights to be updated
in the normal vector

For any misclassified (at the present iteration) training instance, x , with $C(x) = +1$ we update the weights as:

$$w = w + 2\eta x$$

Rosenblatt's Perceptron Theorem


The Perceptron learning algorithm converges to a perfect classifier (no errors on the training data) iff the training data, D , is linearly separable.

- Note: we also need to control η to really guarantee convergence
(if its too big we may overshoot the perfect classifier)
- Some results on the rate of convergence were proven and can be useful in the context of ANNs (and deep learning)
- The Perceptron itself is not a practical learning approach but is an important component of many modern learning approaches.




Frank Rosenblatt
Cornell Univ, NY, US
1928-1971

What would the Perceptron do here?




Data not always linearly separable




The Perceptron and Linear Separability

In 1D: $w_1 \cdot x + w_0 > 0$ OR $C(x) = \text{sgn}(w, x)$
 $w = (w_1, w_0)$




Can We Build a 1D Perceptron for This?


- Red: $C(x) = -1$
- Blue: $C(x) = +1$




Mapping to Higher Dimension




Linear Separability in the Target Space



Data is not always linearly separable






the discriminant function

$$(x, y) \mapsto \varphi(x, y) = (1, x, y, x^2 + y^2)$$

$$w = (-1, 0, 0, 1)$$

(x, y) is BLUE iff

$$F(x, y) = \text{sgn}(w \cdot \varphi(x, y)) < 0$$




$$(x, y) \mapsto \varphi(x, y) = (x, y, -x^2 - y^2)$$

$$w = (1, 0, 0, 1)$$

Non-Linear Decision Boundaries

- Decision boundaries which separate between classes may not always be linear
- In fact, they will sometimes be very complex boundaries and therefore may sometimes require the use of highly non-linear discriminant functions




Data is not always linearly separable

London walking commuters



Lipids vs peptides (Dittwald et al)



Generalized Linear Discriminant Functions

A possible approach to generalizing the concept of linear decision functions is to consider a generalized decision function as:

$$F(\vec{x}) = w_0 + w_1 \varphi_1(\vec{x}) + w_2 \varphi_2(\vec{x}) + \dots + w_N \varphi_N(\vec{x})$$

where

$$\varphi_i(\vec{x}): \mathbb{R}^n \rightarrow \mathbb{R}, \quad 1 \leq i \leq N$$


are scalar functions of the input $\vec{x} \in \mathbb{R}^n$

(all spaces here are Euclidean)

The ambient dimension N is typically larger than n (but not necessarily)


Classification will be based on the Boolean $F(x) \geq 0$

Linear separation after mapping into a different space?



What φ_i s
can we use in
this example?

Mapping into 3D



$$F(x) = w \cdot \varphi(x) > 0 \Rightarrow \bullet$$

What are the w s?

Higher Dimension Linear Separability

Classifier: $\text{sgn}(F(\vec{x}))$, wherein

$$F(x) = \sum_{i=0}^N w_i \varphi_i(x) = \vec{w} \cdot \varphi(\vec{x})$$

consists of a vector of coefficients

$$\vec{w} = (w_0, w_1, w_2, \dots, w_N)$$

and of the mapping

$$\varphi(\vec{x}) = (\varphi_0(x), \varphi_1(x), \varphi_2(x), \dots, \varphi_N(x))^T$$

- We can assume $\varphi_0(x) = 1$
- This representation of $\varphi(x)$ implies that any decision function defined by the weight equation can be treated as linear in the N -dimensional space (*where possibly $N > n$*)
- Note that the components of $\varphi(x)$ may be non-linear in the input space, \mathbb{R}^n , e.g polynomial or exponential terms

Non-linear Mapping Idea


- Map data from low dimensional Input Space to high dimensional Mapped Space (aka Ambient Space) and hope that the data is linearly separable there:
- Example: quadratic mapping

$$\vec{x} = (x_1, x_2) \mapsto (1, x_1, x_2, x_1 \cdot x_2, x_1^2, x_2^2)$$

- The discriminant function would then be:

$$\begin{aligned} F(\vec{x}) &= \sum_{i=0}^5 w_i \varphi_i(\vec{x}) \\ &= w_0 + w_1 x_1 + w_2 x_2 + w_3 x_1 x_2 + w_4 x_1^2 + w_5 x_2^2 \end{aligned}$$

Mapping into 3D



$$x_1 x_2 = 3$$

$$(x_1, x_2) \rightarrow \varphi(x) = (1, x_1, x_2, x_1 \cdot x_2, x_1^2, x_2^2)$$

$$F(x) = w \cdot \varphi(x) > 0 \Rightarrow \bullet$$

Polynomial Discriminant Functions

- The most commonly used generalized decision function is $F(\vec{x})$ for which $\varphi_i(\vec{x})$ ($1 \leq i \leq N$) are multi-dimensional monomials.
- Examples:

$$\varphi_1(\vec{x}) = 5x_4^3$$

$$\varphi_2(\vec{x}) = 7x_4^3x_5^2$$

$$\varphi_3(\vec{x}) = -x_2x_3^2$$

The discriminant function might then look something like:

$$F(\vec{x}) = 100 + 3x_1 - \pi x_3^2x_4^2x_5^2 + x_2^7$$


Mapping to higher dimensional space, revisited – full rational varieties

But how would we engineer a map for this?

We could do this but a more principled approach is to try all quadratic forms by mapping into the full quadratic variety:

$$(x, y) \mapsto (1, \sqrt{2}x, \sqrt{2}y, \sqrt{2}xy, x^2, y^2)$$

And then apply the Perceptron in \mathbb{R}^6 .




That does not work ...
What's next?

Mapping to higher dimensional space, revisited – full rational varieties

We now map
into the full cubic variety:

$$(x, y) \mapsto (1, c_1x, c_1y, c_2xy, c_3x^2, c_3y^2, c_4x^2y, c_4xy^2, x^3, y^3)$$

And then apply the Perceptron in \mathbb{R}^{10} .



Mapping to higher dimensional space, revisited – full rational varieties


The equation of the red curves is

$$y = \frac{9}{x^2 - 9}$$

And we therefore now get a perfect classifier with

$$w = (-9, 0, \frac{-9}{c_2}, 0, 0, 0, \frac{1}{c_4}, 0, 0, 0),$$

namely $C(x, y) = \text{sgn}(x^2y - 9y - 9)$




Rational Varieties

- A full rational variety of order r in an input space of dimension n is described by all r -th degree monomials of the input variables in x :

$$\varphi_i(\vec{x}) = 1^{r_0} x_1^{r_1} x_2^{r_2} \dots x_n^{r_n}$$

$$\text{where } \sum_{j=0}^n r_j = r$$

- The number of different monomer terms in such expressions is:



What is the benefit?

- Why should we assume that in higher dimensions the classes are more likely to be linearly separable?
- What can we do if they are?

Cover's Pattern Counting Theorem (1965)

A complex pattern classification problem cast in a high dimensional space nonlinearly is increasingly more likely to be linearly separable.

Cover, T.M. , 1965

Geometrical and Statistical properties of systems of linear inequalities with applications in pattern recognition.




Thomas M Cover
US, 1938-2012
Stanford University
World leader in
Statistics and
Information Theory

Counting Dichotomies







- A dichotomy of a set S is a partition of S into two disjoint subsets.
- Assume we have k samples in a set of instances S .
- We then have 2^k possible dichotomies over these instances
- Each dichotomy defines a classification task (separate between the two classes)

Linearly separable/non-separable dichotomies in 1D



How many separable dichotomies for k points in \mathbb{R} ?

Linearly separable/non-separable dichotomies in 2D



Cover's Pattern Counting Theorem (1965)

A complex pattern classification problem cast in a high dimensional space nonlinearly is increasingly more likely to be linearly separable.

Cover, T.M. , 1965

Geometrical and Statistical properties of systems of linear inequalities with applications in pattern recognition.



Thomas M Cover
US, 1938-2012
Stanford University
World leader in
Statistics and
Information Theory

Cover's Thm: counting separable dichotomies

- How many dichotomies of a set of points S are linearly separable?
- Cover's Counting Thm: in N dimensional space the number of linearly separable dichotomies of k samples is:

$$2 \sum_{i=0}^N \binom{k-1}{i}$$


- Hence, the probability that a dichotomy, uniformly drawn at random, is linearly separable is:

$$P(k, N) = \frac{1}{2^{k-1}} \sum_{i=0}^N \binom{k-1}{i}$$

- This gets larger as N grows


(Assume that k is fixed at a number typically much larger than N)

Spuriously separable in higher dimensions ...



Proof of Cover's Counting Theorem

Fixed N , as a function of k



From Emin Orhan, NYU

Full rational varieties – what is the dimension?

Summary so far

- The Perceptron converges to a perfect linear classifier for linearly separable data.
- We can often translate non linear decision boundaries to linear ones by mapping the original instance space, in a non linear manner, into higher dimensional space – the ambient space.
We then run e.g the Perceptron in the ambient space
- We saw examples with cleverly engineered mapping and mentioned rational varieties as a general approach, to bypass the clever engineering.
- Cover's Thm: in higher dimensions, an increasingly high fraction of dichotomies of k points are linearly separable;
- Implication: linear separability in higher dimension is easier to achieve.
Caveat: it can be spurious!

