

BEE 4750 Homework 3: Dissolved Oxygen and Monte Carlo

Name: Parker Catena, Regina Velasco

ID: pdc76, rv297

Due Date

Thursday, 10/16/25, 9:00pm

Overview

Instructions

- Problem 1 asks you to implement a model for dissolved oxygen in a river with multiple waste releases and use this to develop a strategy to ensure regulatory compliance.

Load Environment

The following code loads the environment and makes sure all needed packages are installed. This should be at the start of most Julia scripts.

```
import Pkg
Pkg.activate(@__DIR__)
Pkg.instantiate()
```

Activating project at `~/BEE 4750/hw3-parker-1`

```
using Random
using Plots
using LaTeXStrings
using Distributions
```

Problems (Total: 30 Points)

Problem 1 (30 points)

A river which flows at 6 km/d is receiving waste discharges from two sources which are 15 km apart. The oxygen reaeration rate is 0.55 day⁻¹, and the decay rates of CBOD and NBOD are 0.35 and 0.25 day⁻¹, respectively. The river's saturated dissolved oxygen concentration is 10 mg/L.

If the characteristics of the river inflow and waste discharges are given in Table 1, write a Julia model to compute the dissolved oxygen concentration from the first wastewater discharge to an arbitrary distance d km downstream. Use your model to compute the minimum dissolved oxygen concentration up to 50 km downstream and how far downriver this maximum occurs.

Parameter	River Inflow	Waste Stream 1	Waste Stream 2
Inflow	100,000 m ³ /d	10,000 m ³ /d	15,000 m ³ /d
DO Concentration	7.5 mg/L	5 mg/L	5 mg/L
CBOD	5 mg/L	50 mg/L	45 mg/L
NBOD	5 mg/L	35 mg/L	35 mg/L

Table 1: River inflow and waste stream characteristics for Problem 1.

$$K_a = 0.55 \text{ per day}$$

$$K_c = 0.35 \text{ per day}$$

$$K_n = 0.25 \text{ per day}$$

$$C_s = 10 \text{ mg/L}$$

Problem 1.1

Implement the Streeter-Phelps (analytic) solution for the dissolved oxygen concentration. Plot the dissolved oxygen concentration from the first waste stream to 50 km downriver. What is the minimum value in mg/L?

```
u = 6 #km/day
dist = 15 #km
r = 0.55 #1/day
kc = 0.35 #1/day
kn = 0.25 #1/day
Cs = 10 #mg/L
```

```

Q_r0 = 100000 #m3/day
DO_r0 = 7.5 #mg/L
C_r0 = 5 #mg/L
N_r0 = 5 #mg/L

Q_w1 = 10000 #m3/day
DO_w1 = 5 #mg/L
C_w1 = 50 #mg/L
N_w1 = 35 #mg/L

Q_w2 = 15000 #m3/day
DO_w2 = 5 #mg/L
C_w2 = 45 #mg/L
N_w2 = 35 #mg/L

Q_out1 = Q_r0 + Q_w1

function conc_initial(c0, q0, c1, q1, qout)
    ((c0*q0) + (c1*q1)) / qout
end

DO_out1 = conc_initial(DO_r0, Q_r0, DO_w1, Q_w1, Q_out1)
C_out1 = conc_initial(C_r0, Q_r0, C_w1, Q_w1, Q_out1)
N_out1 = conc_initial(N_r0, Q_r0, N_w1, Q_w1, Q_out1)

function conc(x, u, r, kc, kn, DO0, C0, N0, Cs)
    a1 = exp(-r*x/u)
    a2 = (kc/(r-kc))*(exp(-kc*x/u) - a1)
    a3 = (kn/(r-kn))*(exp(-kn*x/u) - a1)
    Cs*(1 - a1) + DO0*a1 - C0*a2 - N0*a3
end

#UNTIL X = 15 RIGHT BEFORE SECOND WASTE STREAM INPUT
x1 = range(0.0, stop=15.0, length=1501)
C1 = conc.(x1, u, r, kc, kn, DO_out1, C_out1, N_out1, Cs)

#values at x=15
L15 = C_out1 * exp(-kc*15.0/u)
N15 = N_out1 * exp(-kn*15.0/u)
C15 = C1[end]

#SECOND WASTE STREAM INPUT AT X = 15

```

```

Q_out2 = Q_out1 + Q_w2
DO_out2 = conc_initial(C15, Q_out1, DO_w2, Q_w2, Q_out2)
C_out2 = conc_initial(L15, Q_out1, C_w2, Q_w2, Q_out2)
N_out2 = conc_initial(N15, Q_out1, N_w2, Q_w2, Q_out2)

x2 = range(15.0, stop=50.0, length=3501)
C2 = conc.(x2 .- 15.0, u, r, kc, kn, DO_out2, C_out2, N_out2, Cs)


x_total = [x1; x2[2:end]]
C_total = [C1; C2[2:end]]
imin = argmin(C_total)
minDO = C_total[imin]
x_at_min = x_total[imin]
println("Minimum DO = $(round(minDO, digits=3)) mg/L at x = $(round(x_at_min, digits=3)) km")

#plot
plot(x_total, C_total, xlabel = "Distance downstream (km)", ylabel = "DO (mg/L)",
      title = "DO Concentration Downstream with Two Waste Inputs", legend = false)
vline!([15.0], linestyle = :dash)
annotate!(15.2, DO_out2, text("Waste stream input 2 at 15 km", :left, 8))

```

Minimum DO = 3.756 mg/L at x = 22.35 km

DO Concentration Downstream with Two Waste Inputs



Problem 1.2

Implement a numerically-integrated (discretized) solution for the dissolved oxygen concentration. Using a resolution of 0.5km, conduct a simulation and plot the results on the same axis as the plot from Problem 1.1. How has the minimum value changed? What do you attribute this difference to (be specific about the source of the difference(s) in terms of the simulation dynamics, not just that one is a numerical approximation).

1.2 Solution

```
dx = 0.5 #km
L = 50 #km

function do_numerical(L, dx, C0, B0, N0, ka, kn, kc, Cs, U) #Numerical implementation function
    n = Int(L / dx) #number of length steps
    C = zeros(n + 1)
    B = zeros(n + 1)
    N = zeros(n + 1)
    C[1] = C0
```

```

    B[1] = B0
    N[1] = N0
    for i = 1:n
        B[i+1] = B[i] * exp(-kc * dx / U)
        N[i+1] = N[i] * exp(-kn * dx / U)
        C[i+1] = C[i] + (dx / U) * (ka * (Cs - C[i]) - kc * B[i] - kn * N[i])
    end
    return (C, B, N)
end

#Right after first waste input
C1, B1, N1 = do_numerical(15.0, dx, DO_out1, C_out1, N_out1, r, kn, kc, Cs, u)

Q_out2 = Q_out1 + Q_w2
DO_15 = C1[end]
L_15 = B1[end]
N_15 = N1[end]

DO_mix2 = conc_initial(DO_15, Q_out1, DO_w2, Q_w2, Q_out2)
L_mix2 = conc_initial(L_15, Q_out1, C_w2, Q_w2, Q_out2)
N_mix2 = conc_initial(N_15, Q_out1, N_w2, Q_w2, Q_out2)

#Right after second waste input
C2, B2, N2 = do_numerical(35.0, dx, DO_mix2, L_mix2, N_mix2, r, kn, kc, Cs, u)

x = [0.0:dx:15.0; 15.0+dx:dx:50.0]
DO_tot = [C1; C2[2:end]]


imin_num = argmin(DO_tot)
println("Numerical min DO = $(round(DO_tot[imin_num], digits=3)) mg/L at x = $(round(x[imin_num], digits=3)) km")

#Plot DO concentration: Analytic vs Numerical
if @isdefined(x_total) && @isdefined(C_total)
    plot(x_total, C_total, label="Analytic", xlabel="Distance downstream (km)", ylabel="DO (mg/L)",
        title="DO Concentration: Analytic vs Numerical (dx = 0.5 km)")
    plot!(x, DO_tot, linestyle=:dash, label="Numerical (dx = 0.5 km)")
    vline!([15.0], linestyle=:dash, label="Discharge #2 (15 km)")
else
    plot(x, DO_tot, label="Numerical (dx = 0.5 km)", xlabel="Distance downstream (km)", ylabel="DO (mg/L)",
        title="DO Concentration (Numerical, lecture scheme)")
end

```

```
vline!([15.0], linestyle=:dash, label="Discharge #2 (15 km)")
end
```

Numerical min DO = 3.658 mg/L at x = 22.5 km



Explanation: Through the numerically-integrated solution the minimum value is 3.658 mg/L of DO at x = 22.5 km, compared to 3.756 mg/L of DO at x = 22.35 km using the analytical solution. So, the minimum value has decreased with the numerical solution. This could be because of numerical errors, such as truncation error. This is because the Euler method can over or under-estimate oxygen-defecit with each step depending on the line's curvature since the area under the curve is approximated as a rectangle. This causes the minimum to differ from the analytic solution.

Problem 1.3

Using the analytic model, what is the minimum level of treatment (% removal of organic waste; assume this is equivalent to the same level of reduction of the CBOD and NBOD) for waste stream 1 that will ensure that the dissolved oxygen concentration is in compliance with the

4 mg/L standard along with a 5% margin of safety, assuming that waste stream 2 remains untreated? How about if only waste stream 2 is treated?

```
#Treat the first waste stream
#Intialize Relevant Variables
safe_fact = 0.05
do_min_target = (1 + safe_fact) * 4.0
treat = 1.0
step = 0.0001

#Get the minimum DO that occurs for a given treatment for an effective C_w2, N_w2
function treated_stream_1(Cw1_eff, Nw1_eff)

    #After first discharge (with treated stream 1)
    Q_out1 = Q_r0 + Q_w1
    DO_out1 = conc_initial(DO_r0, Q_r0, DO_w1, Q_w1, Q_out1)
    C_out1 = conc_initial(C_r0, Q_r0, Cw1_eff, Q_w1, Q_out1)
    N_out1 = conc_initial(N_r0, Q_r0, Nw1_eff, Q_w1, Q_out1)
    C1, B1, N1 = do_numerical(15.0, dx, DO_out1, C_out1, N_out1, r, kn, kc, Cs, u)

    #Right after first waste input
    L15 = C_out1 * exp(-kc*15.0/u)
    N15 = N_out1 * exp(-kn*15.0/u)
    C15 = C1[end]

    #Right after second waste input
    Q_out2 = Q_out1 + Q_w2
    DO_out2 = conc_initial(C15, Q_out1, DO_w2, Q_w2, Q_out2)
    C_out2 = conc_initial(L15, Q_out1, C_w2, Q_w2, Q_out2)
    N_out2 = conc_initial(N15, Q_out1, N_w2, Q_w2, Q_out2)
    C2, B2, N2 = do_numerical(35.0, dx, DO_out2, C_out2, N_out2, r, kn, kc, Cs, u)

    # Compute min value
    x = [0.0:dx:15.0; 15.0+dx:dx:50.0]
    DO_tot = [C1; C2[2:end]]
    idx = argmin(DO_tot)
    return DO_tot[idx], x[idx]
end

# Iterate treatment until min DO >= target
minDO, xmin = treated_stream_1(treat * C_w1, treat * N_w1)

while (minDO < do_min_target)
```



```

    treat = max(0.0, treat - step)
    minDO, xmin = treated_stream_1(treat * C_w1, treat * N_w1)
end

println("Treatment for waste stream 1 to stay above $(do_min_target) mg/L:")
println("    $(round((1-treat)*100, digits=2))% removal")
println("    Minimum DO = $(round(minDO, digits=3)) mg/L at x = $(round(xmin, digits=2)) km")
#Treating second waste stream
#Reinitialize variables changed by first treatment
treat = 1.0
C_w1 = 50 #mg/L
N_w1 = 35 #mg/L

#Get the minimum DO that occurs for a given treatment for an effective C_w2 and N_w2
function treated_stream_2(Cw2_eff, Nw2_eff)

    #After first discharge
    Q_out1 = Q_r0 + Q_w1
    DO_out1 = conc_initial(DO_r0, Q_r0, DO_w1, Q_w1, Q_out1)
    C_out1 = conc_initial(C_r0, Q_r0, C_w1, Q_w1, Q_out1)
    N_out1 = conc_initial(N_r0, Q_r0, N_w1, Q_w1, Q_out1)
    C1, B1, N1 = do_numerical(15.0, dx, DO_out1, C_out1, N_out1, r, kn, kc, Cs, u)

    #Right after first waste input
    L15 = C_out1 * exp(-kc*15.0/u)
    N15 = N_out1 * exp(-kn*15.0/u)
    C15 = C1[end]

    #Right after second waste input
    Q_out2 = Q_out1 + Q_w2
    DO_out2 = conc_initial(C15, Q_out1, DO_w2, Q_w2, Q_out2)
    C_out2 = conc_initial(L15, Q_out1, Cw2_eff, Q_w2, Q_out2)
    N_out2 = conc_initial(N15, Q_out1, Nw2_eff, Q_w2, Q_out2)
    C2, B2, N2 = do_numerical(35.0, dx, DO_out2, C_out2, N_out2, r, kn, kc, Cs, u)

    # Compute min value
    x = [0.0:dx:15.0; 15.0+dx:dx:50.0]
    DO_tot = [C1; C2[2:end]]
    idx = argmin(DO_tot)
    return DO_tot[idx], x[idx]
end

```

```

#Iterate treatment until min DO >= target
minDO, xmin = treated_stream_2(treat * C_w2, treat * N_w2)

while (minDO < do_min_target)
    treat = max(0.0, treat - step)
    minDO, xmin = treated_stream_2(treat * C_w2, treat * N_w2)
end

println("Treatment for waste stream 2 to stay above $(do_min_target) mg/L:")
println("    $(round((1-treat)*100, digits=2))% removal")
println("    min DO = $(round(minDO, digits=3)) mg/L at x = $(round(xmin, digits=2)) km")

```

Treatment for waste stream 1 to stay above 4.2 mg/L:

33.14% removal

Minimum DO = 4.2 mg/L at x = 23.0 km

Treatment for waste stream 2 to stay above 4.2 mg/L:

26.14% removal

min DO = 4.2 mg/L at x = 21.0 km

My code above for Problem 1.3 uses the code from Problems 1.1 and 1.2 to initialize the problem, and setup the original conditions. From there, I wrote a function for both the treated stream 1 and treated stream 2 which takes the conditions from problem 1.2 and only accepts the “treated” NBOD and CBOD as parameters. Using the numerical function, as well as the additional functions, we can then loop over each river to determine amount of treatment to bring the minimum level to be above 4.2 mg/L. I chose a step of 0.0001 for the treatment amount, starting from 1 (or no treatment), and subtracting the step each iteration. This allowed me to determine when the DO in the stream would exactly equal the minimum plus the safety factor (4.2 mg/L). Ultimately I found that solely treating waste stream 1 requires at least 31.56% treatment to stay above the 4.2 mg/L of DO, while only treating waste stream 2 would require 24.58% removal.

Problem 1.4

Suppose you are responsible for designing a waste treatment plan for discharges into the river, with a regulatory mandate to keep the dissolved oxygen concentration above 4 mg/L. Discuss whether you’d opt to treat waste stream 2 alone or both waste streams equally. What other information might you need to make a conclusion, if any?

In order to best determine whether to only treat waste stream 2 or treat both streams equally, we would first need to understand the feasibility and costs associated with reducing the NBOD

and CBOD in each stream. First we need to look at the level of treatment, or waste reduction, that can be achieved. We know that to keep the river above the 4.2 mg/L, we need to remove 24.58% of the waste so we would first need to understand the available technology and look at whether this figure is achievable. It may be the case that we can only remove 10% of the waste effectively, in which case we would be required to treat both streams. Similarly, we need to understand the marginal cost of removing waste. If it is feasible to remove up to 15% of the total BOD at a reasonable cost but extremely expensive above that threshold, then it may be worth treating each stream equally in order to reduce costs. Lastly, we would want to look at each waste stream and understand the conditions of the effluent. For instance, we may want to determine if waste stream 2 is more simple to treat than waste stream 1 due to geographical or process-level factors. Ultimately, there are many factors to consider, and given what we know, we cannot make a determination on which stream to treat.

Problem 1.5

Suppose that it is known that the DO concentrations at the river inflow can vary according to a LogNormal(2.0, 0.15) distribution. Conduct a Monte Carlo simulation of the DO concentration in the river. If you treat only waste stream 1 (based on your analysis from Problem 1.3), what is the expected probability and 95% confidence interval that the river fails to comply with the regulatory standard of 4 mg/L? How did you decide that your Monte Carlo sample size was sufficiently large?

```
#Set Seed
Random.seed!(1)

#Treatment variable and safety value from problem 1.3
treat = 0.6844
do_min_target = 4.0

#Create Log Normal Distrubution of DO in river
samples = 15000
DO = rand(LogNormal(2, 0.15), samples)

#Loop over each river DO value and count violations
violations = 0
mean_DO = zeros(samples)
cil = zeros(samples)
ciu = zeros(samples)
p_vio = 0.0

for i in 1:samples
    DO_r0 = DO[i]
```

```

DO_out1 = conc_initial(DO_r0, Q_r0, DO_w1, Q_w1, Q_out1)
C_out1  = conc_initial(C_r0,  Q_r0, treat * C_w1,  Q_w1, Q_out1)
N_out1  = conc_initial(N_r0,  Q_r0, treat * N_w1,  Q_w1, Q_out1)

C1, B1, N1 = do_numerical(15.0, dx, DO_out1, C_out1, N_out1, r, kn, kc, Cs, u)

Q_out2 = Q_out1 + Q_w2
DO_15 = C1[end]
L_15 = B1[end]
N_15 = N1[end]

DO_mix2 = conc_initial(DO_15, Q_out1, DO_w2, Q_w2, Q_out2)
L_mix2  = conc_initial(L_15,  Q_out1, C_w2,  Q_w2, Q_out2)
N_mix2  = conc_initial(N_15,  Q_out1, N_w2,  Q_w2, Q_out2)

#Right after second waste input
C2, B2, N2 = do_numerical(35.0, dx, DO_mix2, L_mix2, N_mix2, r, kn, kc, Cs, u)

x = [0.0:dx:15.0; 15.0+dx:dx:50.0]
DO_tot = [C1; C2[2:end]]

#See which samples fall below the minimum
if any(DO_tot .< do_min_target)
    violations = violations + 1
end

#Calculate the probability of failure and its 95% confidence interval using standard error
p_vio = violations / i
std_error = sqrt(p_vio * (1 - p_vio) / i)
mean_DO[i] = p_vio
cil[i] = max(0.0, p_vio - 1.96 * std_error)
ciu[i] = min(1, p_vio + 1.96 * std_error)
end

println("Percentage of samples out of compliance = $(round(p_vio*100, digits=2))%")
println("95% CI = [$(round((cil[end])*100, digits=2))%, $(round((ciu[end])*100, digits=2))%]")

#Plot the probability of failure
plt = plot(
    mean_DO,
    xlim = (1, samples+2000),
    ylim = (0, 0.1),


```

```

    legend = :topright,
    label="Mean",
    title="Probability of DO Falling Below Minimum",
    xlabel="Number of Samples",
    ylabel="Estimate",
    color=:black,
    linewidth=3
)
#Plot 95% confidence intervals (I couldn't get the "band" function to work here)
plot!(1:samples, cil, lw=1, ls=:dash, color=:red, label="95% CI lower")
plot!(1:samples, ciu, lw=1, ls=:dash, color=:blue, label="95% CI upper")

```

Percentage of samples out of compliance = 4.46%
 95% CI = [4.13%, 4.79%]



The goal is to determine the probability and 95% confidence interval that the river does not comply with the regulatory standard of 4 mg/L with a Log Normal distribution of river DO centered at 2.0 with standard deviation of 0.15. I began by first implementing the treatment factor for waste stream 1 determined in problem 1.3, which is 0.6844. I then sampled a

random distribution of DO with 15000 log normal samples and initialized the mean, and 95% confidence intervals. Then, I looped over my code from the treated waste stream 1 in problem 1.3, and counted the number of times the DO fell below the 4.2 mg/L limit. Using these values, I calculated the probability of non-compliance, mean probability of non-compliance, standard error, and 95% confidence intervals. Ultimately, I found that 4.46% of the samples would be out of compliance with a 95% confidence interval between [4.13%, 4.79%] for 15000 samples. I determined that 15000 samples is sufficient by graphing the mean and 95% CI, to see convergence. I began by simulating 50000 samples, then 30000 samples, but the increased accuracy is marginal so I determined that 15000 samples is sufficient to have both convergence of the mean probability and 95% CI.

References

List any external references consulted, including classmates.